



Nothing but **HEAVY DUTY.**[™]



2023

TO DEVELOP AND PRODUCE **NOTHING BUT HEAVY DUTY™** POWERTOOLS IS ONLY ONE PART OF THE **MILWAUKEE®** PROMISE.

These tools need to last day in and day out. For this reason, serviceability is incorporated into every tool produced.

All powertools leave the factory with a complete documentation package including instructions for use, listing of customer service centres and safety instructions. Milwaukee Tool has a worldwide service network.

Should a problem arise requiring assistance or support at short notice, you can rely on our service centres/agents worldwide.

The global network ensures that our customers' needs and requirements are shared to influence future product development.

Expertise and competence gained over many years ensures a fast and efficient professional repair service.



Milwaukee Tools strive to meet and surpass all international and European standards and directives for both design and safety. Constant research and development programs aim to anticipate and fulfil future market trends in all regulatory and efficiency requirements. Milwaukee Tool is, amongst others, an active member of EPTA (European Power Tool Association) and so is proudly aligned to all industry measurement standards agreed by the organization.

EXPERIENCE THE HEAVY DUTY DIFFERENCE

TOOLS BUILT TO DO THE JOB BETTER.

At Milwaukee Tool Heavy Duty is more than just a slogan. It is a promise to offer the best to professional users. Engineers at Milwaukee Tools don't just design tools.

They design tools to get the job done better, faster, reliably and safely.



WWW.MILWAUKEETOOL.CO.UK

ALL YOU HAVE TO DO TO TAKE ADVANTAGE OF OUR EXTRA GUARANTEE OFFER IS TO REGISTER ONLINE. NOTHING BUT HEAVY DUTY™

NOTHING BUT HEAVY DUTY GUARANTEE:



*From 1st April 2023 the extended guarantee for **MILWAUKEE®** power tool(s), outdoor power equipment and REDLITHIUM® batteries will only be granted if the product is new and purchased via an Authorised **MILWAUKEE®** Distributor. The same applies to the guarantee for **MILWAUKEE®** hand tool(s) as well. Rights already established before 1st April 2023 shall remain unaffected.



For full terms and conditions for each of the above mentioned guarantees, please see the link below; www.milwaukeetool.co.uk/service



MILWAUKEE® power tool(s), outdoor power equipment & batteries come with a standard 1 year guarantee. Guarantee extensions are available by visiting www.milwaukeetool.co.uk **MILWAUKEE®** power tool(s) and outdoor power equipment guarantee can be extended from 1 year to a maximum of 3 years (1 + 2). With the exception of **MX FUEL™** tools for which the guarantee can be extended from 1 year to a maximum of 2 years (1 + 1).

All **MILWAUKEE® REDLITHIUM™** batteries including **MX FUEL™** batteries come with a standard 1 year guarantee which can be extended to a maximum of 2 years (1 + 1). All guarantee extensions are subject to registering online within 30 days of the purchase date.

Every **MILWAUKEE®** tool is tested according to a comprehensive certified process before leaving the factory and

is guaranteed to be **NOTHING BUT HEAVY DUTY™** qualified. At Milwaukee Tool we take great pride in the products and services we offer to our professional customers.

The guarantee extension is only available in those countries listed on our warranty registration website. The extended guarantee offer excludes products used in the hire industry, battery chargers and accessories supplied.

MILWAUKEE® hand tool lifetime guarantee

Certain **MILWAUKEE®** hand tools come with a lifetime guarantee which means they can be replaced or repaired free of charge should they break during normal usage due to material or manufacturing fault.*

MILWAUKEE® Levels - 30 year accuracy guarantee

The following **MILWAUKEE®** levels are sold with a 30 year accuracy guarantee: **MILWAUKEE® BACKBONE™**; Compact box levels; and the Block Torpedo level.*

MILWAUKEE® Levels - 10 year accuracy guarantee

The following **MILWAUKEE®** levels are sold with a 10 year accuracy guarantee: **MILWAUKEE® Slim box level**; **REDCAST™** level; Minibox level; Billet Torpedo; and I-Beam level.*

*For full terms and conditions for each of the above mentioned guarantees, please see the link below; www.milwaukeetool.co.uk/service

ENVIRONMENT



HEALTH



SAFETY



PRODUCTIVITY



ECONOMIC VALUE



**EQUIPMENT
REDEFINED
TRADE FOCUSED
SYSTEM WIDE**

VIEW THE
FULL RANGE



**INNOVATIONS THAT
ARE TRADE FOCUSED**

**OUR NEW
MX FUEL™
EQUIPMENT**
ELIMINATES THE
HAZARDS ASSOCIATED
WITH EMISSIONS,
NOISE, VIBRATION &
THE FRUSTRATION OF
PETROL MAINTENANCE.




SAVE TIME AND MONEY

CALCULATE YOUR SAVINGS ONLINE WITH THE ONLINE COST CALCULATOR
visit WWW.MILWAUKEETOOL.CO.UK




MXF PSC | MX FUEL™ SCREED

- The MX FUEL™ Screed is the ideal solution when working on larger areas, delivering petrol like performance without petrol headaches
- Power to pull blades up to 4.9 m
- The push-button start delivers instant power, eliminating the repetitive motions of a pull start and reducing downtime, allowing you to get jobs done faster without sacrificing the power and run time you expect
- The POWERSTATE™ brushless motor delivers the power to pull 4.9 m bar at 9,000 VPM with a variable speed trigger, giving you maximum control in stiff and wet concrete
- Foldable handles for easy transport on site and in concrete
- Easy quick connect system of the blade with two bolts
- Up to 2 hrs of run time per charge with the 3.65 m blade and the MXF CP203 battery
- System attachments, blades are available separately
- Building on the strengths of the FUEL™ technology, MX FUEL™ system reaches new levels of cordless performance. Focused on petrol, corded and pneumatic performance, these tools deliver without the hazards associated with emissions, noise, vibration, tripping hazards and the frustrations of complex maintenance
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Supplied with a 9/16" wrench



	MXF PSC-0	MXF PSC-302	MXF PSCKIT-302
Vibrations [1/min]	9,000	9,000	9,000
Weight with battery pack (EPTA) (kg)	16.8 (MXF CP203)	16.8 (MXF CP203)	16.8 (MXF CP203)
Standard equipment	-	-	3 m blade
Kit included	No batteries supplied, 2 x MXF CP203 No charger supplied, No kitbox or bag supplied	Battery packs, MXF C Charger, No kitbox or bag supplied	2 x MXF CP203 Battery packs, MXF C Charger, No kitbox or bag supplied
Article number	4933479771	4933479773	4933479775
EAN code	4058546375652	4058546375676	4058546375690

SCREED ACCESSORIES



Model Variant	Catalogue product description	Length [m]	Weight (kg)	Article number
MXF PSB-1.22m	Screed blade for MX FUEL™ screed (MXF PSC) - 1.22 m	1.22	3.6	4932479776
MXF PSB-1.83m	Screed blade for MX FUEL™ screed (MXF PSC) - 1.83 m	1.83	5.5	4932479777
MXF PSB-2.44m	Screed blade for MX FUEL™ screed (MXF PSC) - 2.44 m	2.44	7.3	4932479778
MXF PSB-3.00m	Screed blade for MX FUEL™ screed (MXF PSC) - 3.0 m	3.00	9.1	4932479779
MXF PSB-3.65m	Screed blade for MX FUEL™ screed (MXF PSC) - 3.65 m	3.65	10.9	4932479780
MXF PSB-4.25m	Screed blade for MX FUEL™ screed (MXF PSC) - 4.25 m	4.25	12.8	4932479781
MXF PSB-4.87m	Screed blade for MX FUEL™ screed (MXF PSC) - 4.87 m	4.87	14.6	4932479782

MXF CVBP | MX FUEL™ BACKPACK CONCRETE VIBRATOR

- The MX FUEL™ Backpack Concrete Vibrator is the ideal solution when working on larger areas, delivering AC like performance without the hassle of laying cables or having the need for a AC socket on the jobsite
- It has the power to push up to Ø63 mm head at over 11,200 VPM for optimal consolidation, even in the stiffest concrete
- The push-button start delivers instant power, eliminating the repetitive motions of a pull start and reducing downtime, allowing you to get jobs done faster without sacrificing the power and run time you expect
- The modular design makes it easy to remove the backpack harness for walls and columns
- Modular design - with just one click from backpack to briefcase
- It can accept shafts up to 6.4 m long and heads up to Ø63 mm without sacrificing power
- Consolidates up to 40 m³ of concrete on 1x MXF XC406 battery
- The wireless remote gives you the ability to turn the machine on from up to 9 m away for more freedom when using long shafts
- System attachments, heads and shafts are available separately
- Building on the strengths of the FUEL™ technology, MX FUEL™ system reaches new levels of cordless performance. Focused on petrol, corded and pneumatic performance, these tools deliver without the hazards associated with emissions, noise, vibration, tripping hazards and the frustrations of complex maintenance



	MXF CVBP-0	MXF CVBP-602	MXF CVBPKIT-602
Vibrations [1/min]	11,200	11,200	11,200
Columns	✓	✓	✓
Footings	✓✓	✓✓	✓✓
Slabs	✓✓✓	✓✓✓	✓✓✓
Walls	✓✓	✓	✓
Weight with battery pack (EPTA) (kg)	15.7 (MXF XC406)	15.7 (MXF XC406)	15.7 (MXF XC406)
Standard equipment	Remote control	Remote control	Remote control, 2 m vibrator shaft, 38 mm vibrator head
Kit included	No batteries supplied, 2 x MXF XC406 No charger supplied, No kitbox or bag supplied	Battery packs, MXF C Charger, No kitbox or bag supplied	2 x MXF XC406 Battery packs, MXF C Charger, No kitbox or bag supplied
Article number	4933479595	4933479592	4933479594
EAN code	4058546373894	4058546373863	4058546373887

MXF CVBC | MX FUEL™ BRIEFCASE CONCRETE VIBRATOR

- Compact and slim design for increased mobility suiting stationary as well as mobile applications
- Carrying strap and handle for increased flexibility on site and easy transport
- Equipped with a ring for easy attachment of the vibrator to the scaffolding or the formwork
- The MX FUEL™ Briefcase Concrete Vibrator is the ideal solution when working on walls and columns, delivering AC like performance without the hassle of laying cables or having the need for an AC socket on the jobsite
- It has the power to push up to Ø63 mm head at over 11,200 VPM for optimal consolidation, even in the stiffest concrete
- The push-button start delivers instant power, eliminating the repetitive motions of a pull start and reducing downtime, allowing you to get jobs done faster without sacrificing the power and run time you expect
- It can accept shafts up to 6.4 m long and heads up to Ø63 mm without sacrificing power
- Consolidates up to 40 m³ of concrete on 1x MXF XC406 battery
- The wireless remote gives you the ability to turn the machine on from up to 9 m away for more freedom when using long shafts
- System attachments, heads and shafts are available separately



	MXF CVBC-0	MXF CVBC-602	MXF CVBCKIT-602
Vibrations [1/min]	11,200	11,200	11,200
Columns	✓✓✓	✓✓✓	✓✓✓
Footings	✓✓	✓✓	✓✓
Slabs	✓✓	✓	✓
Walls	✓✓✓	✓✓✓	✓✓✓
Weight with battery pack (EPTA) (kg)	10.3 (MXF XC406)	10.3 (MXF XC406)	10.3 (MXF XC406)
Standard equipment	Remote control	Remote control	Remote control, 4 m vibrator shaft, 38 mm vibrator head
Kit included	No batteries supplied, 2 x MXF XC406 No charger supplied, No kitbox or bag supplied	Battery packs, MXF C Charger, No kitbox or bag supplied	2 x MXF XC406 Battery packs, MXF C Charger, No kitbox or bag supplied
Article number	4933479607	4933479609	4933479611
EAN code	4058546374013	4058546374037	4058546374051

CHOOSE YOUR CONCRETE VIBRATOR

- *Heads and shafts are not exchangeable!
- ✓✓✓ = Perfect, ✓✓ = Good, ✓ = Acceptable, ✗ = Not recommended

	Slabs	Footings	Columns	Walls
MXF CVBP	✓✓✓	✓✓	✓	✓
MXF CVBC	✓	✓✓	✓✓✓	✓✓✓
M18 FCVN-12"	✓✓✓	✓✓✓	✗	✗
M18 FCVN-24"	✗	✓	✓✓✓	✓✓✓

CHOOSE YOUR CONCRETE VIBRATOR HEAD

- To choose the perfect head diameter you must consider the needed radius of influence as well as the distance between the rebar
- MILWAUKEE® provides a range of different sizes to give you the perfect solution for every application

	Ø (mm)	Article number	EAN code	
Concrete vibrator heads	25	4932479839	4058546376338	
	38	4932478612	4058546348052	
	50	4932478613	4058546348069	
	63	4932479840	4058546376345	

CHOOSE YOUR CONCRETE VIBRATOR WHIP

- ✓✓✓ = Perfect, ✓✓ = Good, ✓ = Acceptable, ✗ = Not recommended

	Slabs MXF CVBP	Slabs MXF CVBC	Footings MXF CVBP	Footings MXF CVBC	Columns MXF CVBP	Columns MXF CVBC	Walls MXF CVBP	Walls MXF CVBC	Article number	EAN code	
MXF CVS-2 m	✓✓✓	✓	✓✓✓	✓	✗	✗	✗	✗	4932478611	4058546348045	
MXF CVS-3 m	✓✓✓	✓	✓✓✓	✓	✓	✓	✓	✓	4932479612	4058546374068	
MXF CVS-4 m	✓	✓✓	✓	✓✓	✓✓✓	✓✓✓	✓✓✓	✓✓✓	4932478610	4058546348038	
MXF CVS-6.4 m	✗	✓✓✓	✗	✓✓✓	✗	✓✓✓	✗	✓✓✓	4932479613	4058546374075	

MXF DH2528H | MX FUEL™ 25 KG CLASS 28 MM HEX DEMOLITION HAMMER

- The industry's first cordless 28 mm Hex demolition hammer, delivering the power of petrol, corded and pneumatic
- Heavy Duty hammer provides 64 blow Joules of impact energy for toughest demolition applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- Low 5.17 m/s² vibrations for over 7 hrs (HAVS) non-stop productivity
- Fast material removal at 1300 BPM, providing maximum productivity in all applications
- Breaks up to 2 tons of concrete or a 12 m (20 cm deep and 30 cm wide) trench on 1 x MXF XC406 battery
- AC-equivalent tool life and service friendly with an integrated service indicator light alerting the user every 40 hours to add grease
- Building on the strengths of the FUEL™ technology, MX FUEL™ system reaches new levels of cordless performance. Focused on petrol, corded and pneumatic performance, these tools deliver without the hazards associated with emissions, noise, vibration, tripping hazards and the frustrations of complex maintenance
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality



	MXF DH2528H-0	MXF DH2528H-602
Tool reception	28 mm K-Hex	28 mm K-Hex
Blow energy [EPTA][J]	64	64
Full load hammer action (bpm)	1300	1300
Vibration chiseling (m/s²)	5.17	5.17
Weight with battery pack (EPTA) (kg)	29.6 (MXF XC406)	29.6 (MXF XC406)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x MXF XC406 Battery packs, MXF C Charger, No kitbox or bag supplied
Article Number	4933478985	4933464878
EAN Code	4058546362676	4058546228231

MXF DHT | BREAKER TROLLEY FOR MX FUEL™ DEMOLITION HAMMER

- Lightweight demolition hammer cart with large rubber wheels for easy transport across uneven terrain
- Integrated demolition hammer retention strap and full-metal fastening locations
- On-board spring-loaded storage locations for 4 chisels
- Battery & charger storage dock with charger cable hook for transport



	MXF DHT
Loading capacity	150
Weight (kg)	15.7
Supplied in	No kitbox or bag supplied
Article Number	4933464879
EAN Code	4058546228248

MXF DCD150 | MX FUEL™ 150 MM DIAMOND CORE DRILL

- Core with confidence by delivering AC performance with a maximum core diameter capacity of 152 mm wet & dry
- 2 speed gearing for a wide range of applications, with laser edged speed and capacity markings into the metal body
- Speed 1: up to 75 mm diameter wet & dry coring at 1600 rpm
- Speed 2: 76 to 152 mm diameter wet & dry coring 800 rpm
- Patented AUTOSTOP™ clutch provides best in class protection, preventing over rotating when losing control or in case of a stuck core
- On-board level sensor guides the user to achieve a straight and accurate finish whilst horizontal drilling
- On-board pressure gauge allows user to optimise drilling speed in order to get the best lifetime of machine and accessory
- On-board battery gauge allows the user to monitor battery capacity during entire drilling process
- Integrated water line for wet coring that is compatible with the M18™ SWITCH TANK™ interchangeable sprayer and water supply system
- 1 1/4"UNC + 1/2"G core fitting to fit most common cores, with friction plate design allowing for easy core changes
- Separately available core drill stand MXF DR255TV with 60 mm collar - 60 mm mount on the core drill fits most universal core stands



	MXF DCD150-0C	MXF DCD150-302C
No load speed (rpm)	0 - 800/ 0 - 1600	0 - 800/ 0 - 1600
Drilling capacity in concrete 1st/ 2nd gear (mm)	76 - 152/ 25 - 76	76 - 152/ 25 - 76
Tool reception	1 1/4" UNC + 1/2" G	1 1/4" UNC + 1/2" G
Weight with battery pack (EPTA) (kg)	12.4 (MXF CP203)	12.4 (MXF CP203)
Standard equipment	Trigger lock-on, side handle	Trigger lock-on, side handle
Kit included	No batteries supplied, No charger supplied, Kitbox	2 x MXF CP203 Battery packs, MXF C Charger, Kitbox
Article Number	4933478986	4933464888
EAN Code	4058546362683	4058546228330

SYSTEM ATTACHMENTS FOR MXF DCD150

	Description	Article Number	EAN Code	
Rig fixing	Fixing kit for exclusive use in concrete. Ø 16 mm drill bit is required to set the drop anchor. Kit includes stud bolt, setting tool, wing nut, washer and 5 pcs of M12 drop anchor	4932399731	4002395363827	
	Vacuum pump VP6 for fastening of the diamond drill rig on smooth and even surfaces. Suction capacity: 850 mbar. Max. vacuum pressure: 6 m³/h/ 100 l/min. Rated voltage: 220-240 V. Supplied with 5 m hose with DW7 connection	4932352094	4002395367474	
Wet coring	Watertank WT 10. 10 liters capacity, steel water tank with inside and outside polyester coating. Reliable brass pump with a max. pressure bar of 6 bar. 2.5 m hose with quick connection system fits direct to MILWAUKEE® diamond drills	4932399726	4002395363773	
	The cordless backpack base (M18 BPFPH-401) and water supply (M18 BPFP-WST) guarantees the optimal water pressure with a click of a button and provides the perfect match for every wet cutting application. 15 l capacity, up to 12 tanks with one M18™ 4.0 Ah battery pack	4933464963	4058546229085	
		4933464965	4058546229108	
	Aluminium water collection ring for wet drilling operations. For use with max. Ø 180 mm core bits. Suitable for overhead coring	4932399727	4002395363780	
	Water collection ring for wet drilling operations, for use with max. Ø 152 mm core bits. Universal use with diamond drilling tools. Suitable for floor and wall coring only	4932478073	4058546340063	
Dry coring	Drilling shroud for drilling and dry coring from Ø 25 - 152 mm. Brush insert to improve suction and extraction	4932471990	4058546298890	

MXF DR255TV | PREMIUM DIAMOND DRILLING STAND FOR MX FUEL™ DIAMOND CORE DRILL

- Height-adjustable insulated drive handle and easy to reach depth adjustment handle to facilitate one-handed operation
- Universal hinged motor clamp with 60 mm collar diameter
- Tool-free machine and watertank attachment compatible with M18™ SWITCH TANK™ 15 l water supply
- With extra long column for use with cordless MXF DCD150 diamond drilling tool, for drilling holes up to Ø 250 mm
- Can be used with vacuum pump on smooth and even surfaces
- Drill angle indication on base plate, can be variably tilted from 0° to 45°
- Adjustable sliding blocks
- Lightweight and durable aluminium design
- Concrete drop anchor fixing set (4932399731) included



	MXF DR255TV
Base size (mm)	276 x 467
Height (mm)	892
Angle capacity (°)	0 - 45
Max. drilling core bit (mm)	250
Stroke length (mm)	570
Weight (kg)	13.2
Supplied in	No kitbox or bag supplied
Article Number	4933472247
EAN Code	4058546338930

MXF COS350 | MX FUEL™ 350 MM CUT-OFF SAW

- The world's first 350 mm battery powered cut-off saw to deliver the power to cut reinforced concrete with a full 350 mm cut capacity
- Faster cuts, start to finish: 3 second push button start up eliminates the need to mix petrol and oil, and avoids petrol engine maintenance
- No petrol headaches: Can be used indoors due to zero fume emissions
- Petrol-equivalent performance with a maximum no-load speed of 5370 rpm and a full 125 mm depth of cut
- Quieter than other petrol equivalent saws, with a low engine vibration and well-balanced weight
- Keyless adjustable blade guard & on-board water line for wet cutting which is compatible with the M18™ SWITCH TANK™ interchangeable sprayer and water supply system
- Separately available cut-off saw cart MXF COSC to maintain straight cuts
- Building on the strengths of the FUEL™ technology, MX FUEL™ system reaches new levels of cordless performance. Focused on petrol, corded and pneumatic performance, these tools deliver without the hazards associated with emissions, noise, vibration, tripping hazards and the frustrations of complex maintenance



	MXF COS350-0	MXF COS350-602
No load speed (rpm)	5370	5370
Blade diameter (mm)	350	350
Bore size (mm)	20/ 25.4	20/ 25.4
Cutting depth (mm)	125	125
Weight with battery pack (EPTA) (kg)	16.7 (MXF XC406)	16.7 (MXF XC406)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x MXF XC406 Battery packs, MXF C Charger, No kitbox or bag supplied
Article Number	4933478984	4933479969
EAN Code	4058546362669	4058546377632

MXF COSC | MX FUEL™ CUT-OFF SAW CART

- Light weight 350 mm cut-off saw cart to maintain straight cuts with full 125 mm depth of cut capacity
- Height-adjustable drive handle and easy to reach depth adjustment handle to facilitate one-handed operation
- Tool-free machine and water tank attachment compatible with the M18™ SWITCH TANK™ interchangeable sprayer and water supply system
- Full mobility with on-board spare battery storage
- Easily collapsible for transport and storage
- Supplied with 11.4 l gravity feed tank



	MXF COSC
Loading capacity	69
Tank capacity (l)	10.4
Weight (kg)	26.0
Supplied in	No kitbox or bag supplied
Article Number	4933464883
EAN Code	4058546228286

MXF TL | MX FUEL™ TOWER LIGHT

- TRUEVIEW™ high definition light output with up to 27,000 lumens in AC and up to 20,000 lumens in DC mode for both task and area lighting
- Has the ability to manoeuvre the light heads in multiple orientations, allowing the user to direct light to wherever it's needed
- Low weight of 48 kg with the two big all-terrain wheels, this tower light is easy to transport across wet and uneven job site terrains with minimum effort
- Due to the motorised mast, the tower light is capable to be set up in less than 10 sec. The mast is extendable up to 3.10 meter and can withstand up to 55 km/h of wind
- To withstand the toughest conditions on the toughest job sites, the MX FUEL™ Tower Light is built with a durable, high impact polycarbonate lenses that delivers superior impact durability
- A sealed battery box ensures batteries are kept protected from the elements at all times
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. Customisation function allows for precise tool adjustment to application
- The built-in MX FUEL™ charger gives you the freedom to charge any MX FUEL™ battery in the AC mode
- IP 55 rating

TRUEVIEW™

ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE.



	MXF TL-601
System	MX FUEL™
Battery compatibility	All MX FUEL™ batteries
Bulb type	LED
Max. AC light output High/Medium/Low/Stroke (lumens)	27,000/ 14,000/ 7000/ -
Max. DC light output High/Medium/Low/Stroke (lumens)	20,000/ 10,000/ 5000/ -
Max. run time AC mode (h)	Endless
Max. run time with MXF XC406 (h)	3/ 6/ 10
Max. mast height (m)	3.1
Weight with battery pack (EPTA) (kg)	53 (MXF XC406)
Kit included [L4]	1 x MXF XC406 Battery pack, Integrated charger, No kitbox or bag supplied
Article Number 110V	4933471845
Article Number 240V	4933471846

MXF PS | MX FUEL™ POWER SUPPLY

- Building on the strengths of the FUEL™ technology, the MX FUEL™ system reaches new levels of cordless performance. Focused on petrol, corded and pneumatic performance, this generator delivers without the hazards associated with emissions, noise, vibration, tripping hazards and the frustrations of complex maintenance
- Provides 3,600 peak watts and 1,800 continuous watts output of pure sine inverter energy, powering everything from high demand 16A tools to sensitive electronics
- No emissions and quiet operation allow users to use it safely indoors
- Battery powered generator eliminates the cost of petrol, maintenance, reducing downtime and increasing jobsite productivity
- Built-in charger gives users the freedom to charge any MX FUEL™ batteries in the AC mode
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Robust roll cage design provides durability for outdoor jobsite use
- Operates with one, or two batteries for extended run time
- Product not be used in bad weather conditions



	MXF PS-602
Running Power [W]	1800
Weight with battery pack (EPTA) (kg)	28.2 (2 x MXF XC406)
Kit included	2 x MXF XC406 Battery packs, Integrated charger, No kitbox or bag supplied
Article number 110V	4933479268
Article number 240V	4933479267
EAN code 110V	4058546370626
EAN code 240V	4058546370619

MXF LSDP | MX FUEL™ LARGE SEWER DRUM MACHINE WITH POWERTREDZ™

- The MX FUEL™ large sewer drum machine with integrated POWERTREDZ™ assists one-person only to move the sewer machine in and out of the service van, up and down building stairs
- World's first battery powered large drum machine that uses MILWAUKEE® 16 mm and 20 mm inner core spirals in drains from 75 mm up to 200 mm, with the power to clear roots up to 60 m down the line
- Fully enclosed drum eliminates free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclogging drains
- Electronic foot pedal with non-slip grip and an integrated drum brake electronically slows the drum very fast for maximum end user control and safety
- MX FUEL™ drum capacity for 16 mm x 30 m long and 20 mm x 30 m long drain cleaning cables
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Building on the strengths of the FUEL™ technology, MX FUEL™ system reaches new levels of cordless performance. Focused on petrol, corded and pneumatic performance, these tools deliver without the hazards associated with emissions, noise, vibration, tripping hazards and the frustrations of complex maintenance



MXF LSDP-301	
No load speed (rpm)	200
Drain capacity (mm)	75 - 200
Spiral diameter (mm)	20
Spiral length (m)	23
Weight with battery pack (EPTA) (kg)	56.6 (MXF CP203)
Standard equipment	1 x 20 mm x 15.2 m inner core cable, 1 x 20 mm x 7.6 m inner core cable, 1 x 9 pc head attachment kit
Kit included	1 x MXF CP203 Battery pack, MXF C Charger, No kitbox or bag supplied
Article Number	4933471852
EAN Code	4058546297510



SYSTEM ATTACHMENTS FOR MXF LSDP

	Description	Fits drain cleaners MXF LSDP	Article Number	EAN Code	
Tight wind spiral SD	16 mm x 7.6 m inner core coupling end	✓	4932471701	4058546296001	
	16 mm x 15.2 m inner core coupling end	✓	4932471702	4058546296018	
	20 mm x 7.6 m inner core coupling end	✓	4932471703	4058546296025	
	20 mm x 15.2 m inner core coupling end	✓	4932471704	4058546296032	
	16 mm anchor cable coupling end	✓	4932471707	4058546296063	
	16 mm x 60 cm leader cable coupling end	✓	4932471708	4058546296070	
	20 mm x 600 mm leader cable coupling end	✓	4932471709	4058546296087	
Straight auger SD	Straight auger for 16, 20 mm cables	✓	48532830	4058546323370	
Funnel auger SD	Funnel auger for 16, 20 mm cables	✓	48532831	4058546323387	
Root cutter SD	75 mm root cutter for 16, 20 mm cables	✓	48532832	4058546323394	
	100 mm root cutter for 16, 20 mm cables	✓	48532833	4058546323400	
	150 mm root cutter for 16, 20 mm cables	✓	48532834	4058546323417	
Opening tool SD	Small opening tool for 16, 20 mm cables	✓	48532835	4058546323424	
	Medium opening tool for 16, 20 mm cables	✓	48532836	4058546323431	
Chain knocker SD	75 mm chain knocker for 16, 20 mm cables	✓	48532837	4058546323448	
	100 mm chain knocker for 16, 20 mm cables	✓	48532838	4058546323455	
Head kit SD	9 pc head kit 16, 20 mm cables	✓	48532840	4058546296131	
MX drum guide hose	Guide hose for MXFSDP	✓	4932478110	4058546340421	
Pin key	Pin key for all cables	✓	4932471717	4058546296162	

MXF XC406 | MX FUEL™ REDLITHIUM™ 6.0 AH BATTERY

- MX FUEL™ REDLITHIUM™ batteries leverage the best-performing and highest-quality lithium-ion technology
- Delivering AC power in a compact and portable battery pack, allowing users to work in areas where power cords struggle to reach
- MX FUEL™ REDLITHIUM™ batteries utilise unique design to protect against drops, vibration, water, and extreme temperatures
- Operates down to -28.0° temperature
- Most advanced electronic power management system communicates with the tool in order to deliver full power in balance with maximum durability
- Enables the user to run tools in confined spaces as well as indoors or in trenches
- Offering a new solution in comparison to petrol
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality



MXF XC406	
System	MX FUEL™
Battery pack capacity (Ah)	6.0
No. of batteries supplied	1
Charge time MXF C charger	90 min
Weight (kg)	4.8
Supplied in	No kitbox or bag supplied
Article number	4933471837



MXF CP203 | MX FUEL™ REDLITHIUM™ 3.0 AH BATTERY

- MX FUEL™ REDLITHIUM™ batteries leverage the best-performing and highest-quality lithium-ion technology
- Delivering AC power in a compact and portable battery pack, allowing users to work in areas where power cords struggle to reach
- MX FUEL™ REDLITHIUM™ batteries utilise unique designs to protect against drops, vibration, water, and extreme temperatures
- Operates down to -28.0° temperature
- Most advanced electronic power management system communicates with the tool in order to deliver full power in balance with maximum durability
- Enables the user to run tools in confined spaces as well as indoors or in trenches
- Offering a new solution in comparison to petrol



MXF CP203	
System	MX FUEL™
Battery pack capacity (Ah)	3.0
No. of batteries supplied	1
Charge time MXF C charger	55 min
Weight (kg)	2.7
Supplied in	No kitbox or bag supplied
Article Number	4933471838
EAN Code	4058546297374



MXF C | MX FUEL™ CHARGER

- Charges MXF CP203 battery pack in 55 minutes
- Charges MXF XC406 battery pack in 90 minutes
- REDLINK™ intelligence optimise the charge rate (4.5 A/h) for each battery to minimise charge time
- Internal fan optimises charge time and performance
- LED light indicates 80% state of charge under 30/ 55 minutes (CP/ XC)
- On-board carry handle



MXF C	
Charging ports	1 x MX FUEL™
Charge type	Single
Power source	AC
Carry handle	Yes
Wall mountable	Yes
Weight (kg)	2.7
Supplied in	No kitbox or bag supplied
Article Number 110V	4933472027
EAN Code	4058546324230



MXF NRG | MX FUEL™ BATTERIES AND CHARGER KIT

- 2 x MXF XC406 - MX FUEL™ REDLITHIUM™ 6.0 Ah battery
- MXF C - MX FUEL™ charger



MXF NRG-406	
System	MX FUEL™
Battery pack capacity (Ah)	6.0
No. of batteries supplied	2
Charge time MXF C charger	90 min
Supplied in	No kitbox or bag supplied
Article number	4933479160
EAN code	4058546369545



M18



UPGRADE.
OUTWORK.
OUTLAST.

IF IT'S M18 IT FITS ALL



ONE SYSTEM
OVER
255
TOOLS

PERFORMANCE DRIVEN.
TRADE FOCUSED.
SYSTEM WIDE.

ONE KEY
UNLOCKING THE DIGITAL JOBSITE



M18 FUEL

VIEW THE
FULL RANGE



VIEW M18 ON OUR
YOUTUBE CHANNEL

REDLITHIUM™
HIGH OUTPUT™
BATTERY TECHNOLOGY

REDLITHIUM™

M18 FUEL™

DRIVEN TO OUTPERFORM.™

**M18 FUEL™ NEXT GENERATION.
MORE COMPACT. UNRIVALED ACCURACY.
REDEFINED PERFORMANCE.**

M18™ Next Generation FUEL™, packs a mighty punch in a smaller package. More compact, yet more powerful, the range is perfect for those hard to reach areas, and ideal for working at height, due to the reduced size and weight, better balance and easier handling.

Put M18™ Next Generation FUEL™ to the test, and reset your expectations of 18 V tools.

NEW
MORE
COMPACT

UNRIVALED
ACCURACY

REDEFINED
PERFORMANCE



VIEW
THE

NEXT GENERATION

1

**POWERSTATE™
BRUSHLESS
MOTOR**



2

**REDLINK PLUS™
INTELLIGENCE**



3

**REDLITHIUM™
BATTERY PACKS**



H3 REDLITHIUM™
HIGH OUTPUT
BATTERY TECHNOLOGY

REDLITHIUM™



ONE-KEY™

UNLOCKING THE DIGITAL JOBSITE™



Bluetooth® LOCATION

UP TO
30 m

Scan here
for more
information



Bluetooth®

BUILD A MORE CONNECTED JOBSITE

Over 40 connected tools and counting, MILWAUKEE® is the world leader in smart solutions, dedicated to moving jobs forward.


Download ONE-KEY™ APP for free via the APP store, or Google Play Store, or simply use your browser



DIGITAL INVENTORY



TOOL TRACKING



CONNECTED TOOLS



DIGITAL INVENTORY

ONE-KEY™ lets you manage your assets from your computer, tablet, or smartphone. On the jobsite, in the office - access your inventory, wherever you go with our cloud-based solution.



THE INVENTORY DASHBOARD:

- Helps you draw quick insight
- Smart filters display essential information like recent transfers from jobsites



ITEM DETAIL:

- Seamlessly manage details
- Increase accountability across jobs with visibility of tools
- Know where the tools are assigned to



TOOL HISTORY:


- Build a digital breadcrumb trail with accessible history of when, where and how your tools have been used



SERVICE REMINDER:

- Set service reminders on your equipment and ONE-KEY™ will notify you when attention is needed

CREW MANAGEMENT




MULTI-USER

- Invite employees to your account and let them manage your equipment and inventory
- Integrated role assignments decide what they'll have access to
- Import contacts from your phone book or add new ones to a virtual address book
- Call, text, or email people right from the app

PLACES MANAGEMENT

- Manage your inventory based on where it is stored
- Quick access of all your jobs in one clean view
- Visualise what's on-hand to cut back on hoarding, or get something where it needs to be
- Audit anywhere, the quickest way to verify what you have on-hand
- Transfers, fill a shopping cart of items to send to a site, auto-generate a pick-list for accountability



TOOL TRACKING

With community Bluetooth® tracking, barcode scanning, and geo-fencing, staying on top of your tools and equipment is easy. ONE-KEY™ shows the last seen location of your connected tools. Mark one missing and our network, made up of hundreds of thousands, helps find it



BTT - Bluetooth® Tracking Tag

Versatile Bluetooth® tracker that can be attached with glue, screws rivets or straps on anything. It provides location updates (last seen date, time & location) when it comes within a 90 m range of any phone with the ONE-KEY™ App.



*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc., and any use of such marks by (TTI corporate name) is under license. Other trademarks and trade names are those of their respective owners.

CONNECTED TOOLS

- Track and lock tools, remote tool lockout makes stolen tools useless to thieves
- Dial in performance, set up your tools for the work you do
- Utilisation data, verify that tools are performing tasks to specification
- Ultimate control, maximise tool performance and accessory life
- Reporting, generate detailed reports on how your equipment is performing and send them to anyone that needs to know



REDLITHIUM™ AND REDLITHIUM™ HIGH OUTPUT™ SUPERIOR PACK CONSTRUCTION

IT LASTS LONGER, THINKS FASTER & WORKS HARDER*

BATTERY FUEL GAUGE
Displays remaining run time

PATENTED REDLINK™ INTELLIGENCE
Protects the pack in abusive situations, provides optimum performance and monitors the cells for maximum life

SHOCK RESPONSIVE SEPARATORS
Prevents pack failure from vibration or drops

SINGLE PIECE CELL CARRIER
Full enclosure protects cells and provides a strong structure delivering maximum durability

RUBBER OVERMOLD
Protects cells and pack during drops and provides maximum life

LATCH COVER
Prevents water from entering pack through the latch buttons

WATER PROTECTION BARRIER
Routes water away from the electronics and out of the battery pack

ELECTRONIC COATING
Protects the electronics from water and condensation















TEMP CONTROL CELL FRAME
Provides a strong structure and transfers energy efficiently for maximum life

REDLITHIUM™ BATTERY CELLS
Provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life



NEW GENERATION
REDLITHIUM™
HIGH OUTPUT™ BATTERIES

CHECK OUT OUR LATEST RUN TIME VIDEOS ON MILWAUKEE TOOL EUROPE youtube.

REDLITHIUM™ CELLS	<ul style="list-style-type: none">• High power cell• Fade free performance• Lasts in extreme environments 	 
REDLINK™ ELECTRONICS	<ul style="list-style-type: none">• Individual cell monitoring• Digital overload protection• System performance optimisation• M18™ system compatibility 	 
CONSTRUCTION	<ul style="list-style-type: none">• Best-in-class pack construction• Long-lasting reliability• Proven durability on the jobsite 	 
BENEFITS	<p>WORKS FASTER, LONGER, HARDER & EXTREMER*</p> <ul style="list-style-type: none">• Up to 20% more power*• Up to 2.5x more run-time*• Up to 2x longer battery life*• Works down to -20°C	 <p>MOST POWERFUL MILWAUKEE® BATTERY EVER</p> <ul style="list-style-type: none">• Up to 50% more power*• Up to 33% more run-time*• Runs up to 50% cooler*• Works down to -28°C
APPLICATION RECOMMENDATION	<p>ALL PROFESSIONAL TRADE APPLICATIONS</p>	 <p>HIGH DEMAND APPLICATIONS REQUIRING HIGH OUTPUT CURRENT</p>
RANGE		 

* Vs Standard Lithium-Ion technologies

* Vs Standard REDLITHIUM™ batteries in high current draw applications

IF IT'S M18 IT FITS

* Compared with previous MILWAUKEE® battery technology. Results dependent on voltage, tool and application.

WATER ELECTRONICS THERMAL IMPACT



GET THE RIGHT HAMMER FOR THE JOB

SDS-MAX

FOR THE MORE DEMANDING, HEAVY-DUTY APPLICATIONS, INCLUDING DRY CORING AND MEDIUM DUTY CHIPPING IN BOTH CONCRETE BLOCK AND REINFORCED CONCRETE

**M18 FUEL**

11.0 J

**ONE-KEY™**
M18 FHM-121C
Ø16–45 mm*

SDS-PLUS

FOR HEAVY DUTY APPLICATIONS, IDEAL FOR PLUMBING OR FORMWORK

**M18 FUEL**

5.0 J

ONE-KEY™
M18 ONEFHPX-552X
Ø8–32 mm*

EXCELLENT PERFORMANCE, IDEAL FOR REPETITIVE AND FAST DRILLING

**M18 FUEL**

2.5 J

ONE-KEY™
M18 ONEFHX-552X
Ø6–26 mm*

BALANCED PERFORMANCE WEIGHT RATIO. IDEAL FOR LIGHT CHISELING APPLICATIONS

**M18**

2.4 J

HD18 HX-402C
Ø6–18 mm***M18 BRUSHLESS**

2.3 J

M18 BLHX-502X
Ø6–18 mm*

FIXING HAMMERS, IDEAL FOR TIGHT SPACES AND ALL-DAY USE

**M12**

1.1 J

M12 H-402C
Ø5.5–10 mm***M12 FUEL**

0.9 J

M12 CH-602X
Ø5.5–12 mm***M18**

1.2 J

M18 BH-402C
Ø5.5–13 mm*

*Optimal drilling capacity



Scan here to view
our PPE range



Scan here to view
compatible drill bits

RED LITHIUM™

M18 FHM | M18 FUEL™ ONE-KEY™ 8 KG SDS-MAX DRILLING AND BREAKING HAMMER

- The M18 FHM is the most productive SDS-Max tool Milwaukee Tool has produced, delivering AC power with the flexibility of the cordless M18™ platform
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- AUTOSTOP™ shuts down the tool to protect the user after 45° of sharp movement in bind up situations
- Trigger lock on prevents users from having to hold trigger during long periods of chipping applications
- Large anti-vibration back handle supports two handed drilling applications whilst minimising vibration exposure
- Service light indicator illuminates when tool requires servicing
- Anti-vibration side handle for lower vibration exposure
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FHM-0C	M18 FHM-121C
Tool reception	SDS-Max	SDS-Max
Blow energy (EPTA)[J]	11.0	11.0
Full load hammer action (bpm)	0 - 2900	0 - 2900
No load speed (rpm)	0 - 380	0 - 380
Max. drilling concrete (mm)	45	45
mx. drilling tunnel bit (mm)	65	65
Max. drilling core bit (mm)	150	150
Vibration drilling (m/s²)	9.4	9.4
Vibration chiseling (m/s²)	9.4	9.4
Weight with battery pack (EPTA) (kg)	10.2 (M18 HB12)	10.2 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M18 HB12 Battery pack, M12-18 FC Charger, Kitbox
Article Number	4933464893	4933464895

M18 ONEFHPX

M18 FUEL™ HIGH PERFORMANCE 4-MODE 32 MM SDS-PLUS HAMMER WITH ONE-KEY™ AND FIXTEC™ CHUCK

- Hardest hitting cordless SDS-Plus hammer in its class. Powerful hammer mechanism delivers 5.0 J (EPTA) of impact energy at low 6.9 m/s² vibrations
- Drills up to 10 Ø18 x 100 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck
- All metal gear case - optimum seating of the gears for enhanced tool life
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility
- Compatible with M18 FPDDEXL dust extractor
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE's POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries

	M18 ONEFHPX-0X	M18 ONEFHPX-552X
Tool reception	SDS-Plus + Reduced shank 13 mm	SDS-Plus + Reduced shank 13 mm
Blow energy (EPTA)[J]	5.0	5.0
Max. percussion rate (bpm)	0 - 4600	0 - 4600
No load speed (rpm)	0 - 800	0 - 800
Max. drilling wood (mm)	30	30
Max. drilling steel (mm)	13	13
Max. drilling concrete (mm)	32	32
Vibration drilling (m/s²)	6.9	6.9
Vibration chiseling (m/s²)	7.4	7.4
Weight with battery pack (EPTA) (kg)	5.2 (M18 HB5.5)	5.2 (M18 HB5.5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 HB5.5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933478495	4933478497
EAN code	4058546346881	4058546346904



SDS-PLUS DRILL BIT SET (7 PCS)

Article Number 4932451464



M18 FPDDEXL | DEDICATED DUST EXTRACTION FOR M18 FUEL™ 32 MM SDS-PLUS HAMMERS WITH AUTOPULSE™

- Designed to collect dust efficiently with automatic operation from the tools on/ off trigger switch
- AUTOPULSE™ industry's first on-board automatic filter cleaning mechanism for an on-tool dust extractor, which increases the air flow efficiency as well as the filter life time
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns
- Translucent dust box allows user to see the current level of dust inside as well as when the dust box is full
- Dust box with vacuum port allows user to attach to large dust extractors to suction out dust from the box. Optimised to be used with AS 30 LAC 30 I dust extractor and DEK26 hose clip adapter (4931447295)
- Exchangeable nozzles to adjust to the different drilling diameters. Supplied with 2 nozzle sizes 1x up to Ø16 mm, 1x up to Ø32 mm, which can be quickly switched thanks to the quick lock mechanism
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length up to 230 mm depth
- Adjustable depth gauge with easily and precisely adjustment buttons for accurate hole depths
- Removable and switchable depth gauge, in case the user prefers the other side
- Bright LED workspace illumination



M18 FPDDEXL-0	
Max. drill bit diameter [mm]	32
Max. drilling depth [mm]	230
Max. drill bit length [mm]	260
Stroke length [mm]	203
Weight [kg]	2.0
Supplied in	No kitbox or bag supplied
Article number	4933478509
EAN code	4058546347024

M18 ONEFHX | M18 FUEL™ 4-MODE 26 MM SDS-PLUS HAMMER WITH FIXTEC™ CHUCK AND ONE-KEY™

- The fastest drilling rotary hammer in its class leading to increased productivity
- Powerful hammer mechanism delivers 2.5 J of impact energy at low 12.9 m/s² vibrations
- Drills up to 125 Ø10 x 50 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck
- All metal gear case - optimum seating of the gears for enhanced tool life
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility
- Compatible with M18 FCDDEXL or M18 FDDEXL dust extractors
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability



	M18 ONEFHX-0X	M18 ONEFHX-552X
Tool reception	SDS-Plus + Reduced shank 13 mm	SDS-Plus + Reduced shank 13 mm
Blow energy [EPTA][J]	2.5	2.5
Max. percussion rate (bpm)	0 - 4800	0 - 4800
No load speed (rpm)	0 - 1330	0 - 1330
Max. drilling wood (mm)	28	28
Max. drilling steel (mm)	13	13
Max. drilling concrete (mm)	26	26
Vibration drilling (m/s²)	12.9	12.9
Vibration chiseling (m/s²)	14.2	14.2
Weight with battery pack (EPTA) (kg)	4.5 (M18 HB5.5)	4.5 (M18 HB5.5)
Kit included	No batteries supplied, No charger supplied, HD Box	No batteries supplied, No charger supplied, Kitbox
Article number	4933478503	4933478505
EAN code	4058546346966	4058546346980

M18 FDDEXL | DEDICATED DUST EXTRACTION FOR M18 FUEL™ 26 MM SDS-PLUS HAMMERS WITH AUTOPULSE™

- Designed to collect dust efficiently with automatic operation from the tools on/ off trigger switch
- AUTOPULSE™ industry's first on-board automatic filter cleaning mechanism for an on-tool dust extractor, which increases the air flow efficiency as well as the filter life time
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns
- Translucent dust box allows user to see the current level of dust inside as well as when the dust box is full
- Dust box with vacuum port allows user to attach to large dust extractors to suction out dust from the box. Optimised to be used with AS 30 LAC 30 I dust extractor and DEK26 hose clip adapter (4931447295)
- Exchangeable nozzles to adjust to the different drilling diameters. Supplied with 2 nozzle sizes 1x up to Ø16 mm, 1x up to Ø26 mm, which can be quickly switched thanks to the quick lock mechanism
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length up to 210 mm depth
- Adjustable depth gauge with easily and precisely adjustment buttons for accurate hole depths



M18 FDDEXL-0	
Max. drill bit diameter [mm]	26
Max. drilling depth [mm]	152
Max. drill bit length [mm]	210
Stroke length [mm]	152
Weight [kg]	1.9
Supplied in	No kitbox or bag supplied
Article number	4933478508
EAN code	4058546347017

M18 FCDDEXL | COMPACT DEDICATED DUST EXTRACTION FOR M18 FUEL™ 26 MM SDS-PLUS HAMMERS

- Designed to collect dust efficiently with automatic operation from the tools on/ off trigger switch
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns
- Manual filter cleaning mechanism increases the air flow efficiency as well as the filter life time
- Exchangeable nozzles to adjust to the different drilling diameters. Supplied with 2 nozzle sizes 1x up to Ø16 mm, 1x up to Ø26 mm, which can be quickly switched thanks to the quick lock mechanism
- Adjustable depth gauge with easily and precisely adjustment buttons for accurate hole depths
- Bright LED workspace illumination
- Compatible with M18 FH, M18 FHX, M18 ONEFH and M18 ONEFHX hammers



M18 FCDDEXL-0	
Max. drill bit diameter [mm]	26
Max. drilling depth [mm]	96
Max. drill bit length [mm]	200
Stroke length [mm]	96
Weight [kg]	1.4
Supplied in	No kitbox or bag supplied
Article number	4933478507
EAN code	4058546347000

M18 CDEX | M18 FUEL™ SDS-PLUS DUST EXTRACTOR

- Designed to collect dust effectively with automatic operation from the tools on/off trigger switch
- HEPA Filter: widely regarded as the ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%
- Large dust collection box
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length 16 mm max and 90 mm depth
- Compatible with M18 CHX
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 CDEX-0	
Max. drill bit diameter [mm]	16
Max. drilling depth [mm]	90
Max. drill bit length [mm]	160
Stroke length [mm]	100
Weight without battery pack (kg)	1.6
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933447450
EAN Code	4002395006243

M18 BH | M18™ COMPACT 2-MODE SDS-PLUS HAMMER

- Superior power to weight ratio in its class 2.5 kg 1.2 J (EPTA)
- High performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility
- Low vibration value of 10.3 m/s²
- Optimised hammer drilling from 4 to 10 mm, max diameter 16 mm
- Forward & reverse switch for added versatility in fastening applications
- 43 mm neck size - compatible with M12 UDEL dust extractor
- Fuel gauge displays remaining charge
- Bright LED workspace illumination
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BH-0	M18 BH-402C
Tool reception	SDS-Plus	SDS-Plus
Blow energy [EPTA][J]	1.2	1.2
Max. percussion rate (bpm)	7000	7000
No load speed (rpm)	0 - 1300	0 - 1300
Max. drilling wood (mm)	16	16
Max. drilling steel (mm)	10	10
Max. drilling concrete (mm)	16	16
Vibration drilling (m/s²)	10.3	10.3
Weight with battery pack (EPTA) (kg)	2.5 (M18 B4)	2.5 (M18 B4)
Kit included	No batteries supplied, No charger supplied, kitbox or bag supplied	2 x M18 B4 Battery, No packs, M12-18 C Charger, Kitbox
Article Number	4933443320	4933443334
EAN Code	4002395003730	4002395003754

HD18 HX | M18™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC™ CHUCK

- High powered motor gives corded tool performance
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy
- All metal gear case: optimum seating for gears to enhance service life
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility
- Variolock and hammer stop function
- FIXTEC™ system - keyless chuck changing
- Mechanical clutch: protects tool when bit binds up
- Anti-Vibration-System delivers max. comfort by minimising vibration
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	HD18 HX-0	HD18 HX-402C
Tool reception	SDS-Plus	SDS-Plus
Blow energy [EPTA][J]	2.4	2.4
Max. percussion rate (bpm)	4200	4200
No load speed (rpm)	1400	1400
Max. drilling wood (mm)	30	30
Max. drilling steel (mm)	13	13
Max. drilling concrete (mm)	24	24
Vibration drilling (m/s²)	12.2	12.2
Vibration chiseling (m/s²)	7.4	7.4
Weight with battery pack (EPTA) (kg)	3.7 (M18 B4)	3.7 (M18 B4)
Kit included	No batteries supplied, No charger supplied, No packs, M12-18 C kitbox or bag supplied	2 x M18 B4 Battery Charger, Kitbox
Article Number	4933408320	4933441283
EAN code	4002395239689	4002395001682

M18 FCOS230 | M18 FUEL™ CUT OFF SAW

- The world's first 18V 230 mm battery powered cut off saw, delivers the power to cut reinforced concrete, whilst being 50% lighter than other petrol comparisons
- Starts up instantly, eliminates the need to mix petrol and oil, and avoids petrol engine maintenance
- Can be used indoors due to zero fume emissions
- Features RAPIDSTOP™ blade brake and load indicator light, as well as lowest vibrations at 1.81 m/s²
- 85 mm cutting depth for class leading performance
- Dual sided water supply for optimised dust management
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Compatible with the M18™ SWITCH TANK™ interchangeable sprayer and water supply system
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FCOS230-0	M18 FCOS230-121
No load speed (rpm)	6600	6600
Blade diameter (mm)	230	230
Cutting depth (mm)	85	85
Max. water supply inlet [bar/PSI]	6/ 90	6/ 90
Weight with battery pack (EPTA) (kg)	6.2 (M18 HB12)	6.2 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M18 HB12 Battery pack, M12-18 FC Charger, No kitbox or bag supplied
Article Number	4933471696	4933471698
EAN Code	4058546295950	4058546295974

M18 FPM | M18 FUEL™ PADDLE MIXER

- Thanks to the POWERSTATE™ brushless motor it has the power to mix heavy compounds, such as concrete and mortar
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Ultimate speed control: 3 different ways of controlling speed for clean and consistent mixes (8-speed setting dial, variable speed trigger and a lock on button)
- 180° adjustable handle with 16 adjustable settings for user to optimise the handle position based on preference and comfort
- M14 tool reception
- On board fuel gauge and LED light
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Kitted with 150 mm paddle extension (M14)



	M18 FPM-0X
No load speed (rpm)	0 - 550
Tool reception	M14
Max. stirrer paddle diameter [mm]	120
Max. recommended mixing capacities [kg/l]20	
Weight with battery pack (EPTA) (kg)	3.0 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box
Article Number	4933459719
EAN Code	4058546028916

M18 FCVN
M18 FUEL™ NEEDLE CONCRETE VIBRATOR

M18 FUEL



- M18 FUEL™ Needle Vibrator for consolidation of concrete with a compact design
- 1.2 m whip length execution recommended for footings or small flatwork (M18 FCVN12)
- 2.4 m whip length execution recommended for walls or columns (M18 FCVN24)
- 25 mm² head design and 12,500 VPM for an improved consolidation power
- Variable speed trigger for ideal adaption to each material and formwork size
- Hang hook, when tool not in use, to be attached to the formwork or scaffolding
- Light weight for comfortable application and easy transport on site
- Power to consolidate up to one concrete truck (8 m³) on a single M18™ 5.5 HIGH OUTPUT™ battery
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FCVN12-0	M18 FCVN12-551	M18 FCVN24-0	M18 FCVN24-551
Vibrations [1/min]	12,500	12,500	12,500	12,500
Columns	x	x	✓✓✓	✓✓✓
Footings	✓✓✓	✓✓✓	✓	✓
Slabs	✓✓✓	✓✓✓	x	x
Walls	x	x	✓✓✓	✓✓✓
Weight with battery pack (EPTA) (kg)	5.0 (M18 HB5.5)	5.0 (M18 HB5.5)	6.5 (M18 HB5.5)	6.5 (M18 HB5.5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M18 HB5.5 Battery pack, M12-18 FC Charger, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M18 HB5.5 Battery pack, M12-18 FC Charger, No kitbox or bag supplied
Article number	4933479596	4933479598	4933479599	4933479601
EAN code	4058546373900	4058546373924	4058546373931	4058546373955



GET THE RIGHT
PERCUSSION DRILL
FOR THE JOB

FUEL™

M18 FUEL

0 - 2000 rpm
0 - 32,000 bpm

ONE-KEY™

M18 ONEPD2-502X

135 Nm

M12 FUEL

0 - 1700 rpm
0 - 25,500 bpm

M12 FPD2-602X

44 Nm

M18 FUEL

0 - 2100 rpm
0 - 33,000 bpm

M18 FPD3-502X

158 Nm

M12 FUEL

0 - 1700 rpm
0 - 25,500 bpm

M12 FPDXXKIT-202X

37 Nm

M18 FPD3
M18 FUEL™ PERCUSSION DRILL

- Higher power efficiency under load with outstanding torque of 158 Nm
- Extremely compact design of 175 mm length for access into tight spaces
- AUTOSTOP™ control mode offers enhanced safety for the operator by preventing over-rotation in a bind-up
- 13 mm metal chuck for quick bit changes and bit retention
- Fastest drilling and driving applications under load
- Brighter LED workspace illumination
- Fuel gauge displays remaining charge
- All metal reversible belt clip to hang your tool quickly and easily
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- The DNA of our FUEL™ platform redefines the balance of cordless technologies, MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 FPD3-502X	
No load speed gear 1 (rpm)	0 - 500
No load speed gear 2 (rpm)	0 - 2100
Chuck capacity (mm)	13
Max. drilling wood (mm)	89
Max. drilling steel (mm)	16
Max. drilling masonry (mm)	16
Max. percussion rate (bpm)	0 - 33,000
Max. torque (Nm)	158
Weight with battery pack (EPTA) (kg)	2.2 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933479861
EAN code	4058546376550



BRUSHLESS

M18

0 - 1800 rpm
0 - 28,800 bpm

M18 BLPD2-502X

82 Nm

BRUSHED

M12

0 - 1500 rpm
0 - 22,500 bpm

M12 BPD-402C

38 Nm

M18 ONEPD2 | M18 FUEL™ ONE-KEY™ PERCUSSION DRILL

- Higher power efficiency under load - outstanding torque of 135 Nm
- Extremely compact design of 175 mm length for access into tight spaces
- Advanced heavy duty chuck providing increased bit grip
- Connect via Bluetooth® with the ONE-KEY™ app
- Customise anti-kickback control via ONE-KEY™ app
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- Configure to any application choosing optimum tool settings for repeatable precision
- Control speed, torque, start and end speeds, anti-kickback functions and LED
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 ONEPD2-502X	
No load speed gear 1 (rpm)	0 - 550
No load speed gear 2 (rpm)	0 - 2000
Chuck capacity (mm)	13
Max. drilling wood (mm)	89
Max. drilling steel (mm)	16
Max. drilling masonry (mm)	16
Max. percussion rate (bpm)	0 - 32,000
Max. torque (Nm)	135
Weight with battery pack (EPTA) (kg)	2.2 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933464528
EAN Code	4058546224738

M18 BLPD2 | M18™ BRUSHLESS PERCUSSION DRILL

- New brushless motor design delivers 40% more torque than previous model - up to 82 Nm
- Compact design (180 mm in length) provides excellent balance and control, ideal for overhead applications or work in tight spaces
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Optimised speed for faster drilling & fastening (0 - 550/ 0 - 1800 rpm)
- On board fuel gauge and LED light
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 BLPD2-502X	
No load speed gear 1 (rpm)	0 - 550
No load speed gear 2 (rpm)	0 - 1800
Chuck capacity (mm)	13
Max. drilling wood (mm)	76
Max. drilling steel (mm)	13
Max. drilling masonry (mm)	16
Max. percussion rate (bpm)	0 - 28,800
Max. torque (Nm)	82
Weight with battery pack (EPTA) (kg)	2.1 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933464518
EAN Code	4058546224639



Scan here to view
our PPE range



Scan here to view
compatible drill bits



M18 FRAD2

M18 FUEL™ SUPER HAWG® 2-SPEED
RIGHT ANGLE DRILL DRIVER GEN II

- On board fuel gauge and LED light
- POWERSTATE™ brushless motor provides constant power under load to power through 152 mm holes
- REDLINK PLUS™ electronics and REDLITHIUM™ battery pack deliver more run time and more work over pack life
- Compact design allows working in confined spaces
- Extremely long run time, up to 100 holes with a 65 mm auger bit into wood
- Mechanical clutch protects the tool in the event of a stall
- All metal gear case and 13 mm keyed chuck for high durability
- Low speed / High speed dial for different applications
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FRAD2-0	
No load speed gear 1 (rpm)	0 - 500
No load speed gear 2 (rpm)	0 - 1550
Chuck capacity (mm)	13
Max. drilling wood with auger bit (mm)	40
Max. drilling wood with selffeed bit (mm)	117
Max. drilling wood with hole saw (mm)	159
Max. drilling steel (mm)	13
Weight with battery pack (EPTA) (kg)	6.4 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471207
EAN Code	4058546288358

BIG HAWG™ MULTI MATERIAL SET (10 PC)

Article Number 4932464939



M18 CRAD2 | M18 FUEL™ RIGHT ANGLE DRILL

- Delivers corded power and speed (1500 rpm) in wood drilling applications
- All metal gear case and 13 mm keyed chuck
- Extremely long run time with a 5.5 Ah battery pack drills up to 200 holes with a 22 mm auger bit into 50 x 100 mm wood
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 CRAD2-0X	
No load speed (rpm)	0 - 1500
Chuck capacity (mm)	13
Max. drilling wood with auger bit (mm)	26
Max. drilling wood with selffeed bit (mm)	65
Max. drilling wood with hole saw (mm)	102
Max. drilling steel (mm)	12.7
Weight with battery pack (EPTA) (kg)	4.1 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box
Article Number	4933471641
EAN Code	4058546295400

C18 RAD | M18™ COMPACT RIGHT ANGLE DRILL

- Optimised performance: 1500 rpm at 20 Nm
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Perfect speed to power ratio for fast application completion
- 10 mm single sleeve ratcheting chuck provides maximum versatility and grip
- 100 mm compact head designed to fit in the tightest work areas
- Multi-position handle design allows for multiple hand positions and maximum comfort
- 10 + 1 electronic clutch enables complete control while fastening
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Built in LED light illuminates the work surface
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



C18 RAD-0	
No load speed (rpm)	0 - 1500
Chuck capacity (mm)	10
Max. torque (Nm)	20
Max. drilling wood (mm)	28
Max. drilling steel (mm)	10
Weight with battery pack (EPTA) (kg)	1.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933427189
EAN Code	4002395239085

GET THE RIGHT
IMPACT DRIVER
FOR THE JOB

ONE KEY

M18 ONEID2-502X

M18 FUEL 226 Nm

0 - 3600 rpm
0 - 4300 ipm

M18 FID3-502X

M18 FUEL 226 Nm

0 - 3900 rpm
0 - 4400 ipm

M12 FID2-602X

M12 FUEL 147 Nm

0 - 3300 rpm
0 - 4000 ipm

M18 FQID-502X

M18 FUEL 50 Nm

0 - 3000 rpm
0 - 4000 ipm

SURGE LOW NOISE
LOW VIBRATION

M12 FQID-202X

M12 FUEL 50 Nm

0 - 3200 rpm
0 - 3400 ipm

SURGE LOW NOISE
LOW VIBRATION

M18 BLID2-502X

M18

0 - 3400 rpm
0 - 4200 ipm

180 Nm

M12 BID-202C

M12 112 Nm

0 - 2500 rpm
0 - 3300 ipm

M18 BRAID-0

M18 81 Nm

0 - 2250 rpm
0 - 3400 ipm

M12 BRAID-0

M12 68 Nm

0 - 2425 rpm
0 - 3300 ipm



Scan here to view
our PPE range



Scan here to view
compatible impact bits

REDLITHIUM™



M18 FID3

M18 FUEL™ 1/4" HEX IMPACT DRIVER

- Higher power efficiency under load with outstanding torque of 226 Nm
- Faster driving speed vs. previous model, up to 3900 rpm and 4400 ipm
- Extremely compact design, total length of just 113 mm for access into tight spaces
- DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 1 for precision work
- Mode 2 helps prevent damage to fasteners and material
- Mode 3 delivers maximum performance for the toughest applications
- Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 1/4"Hex chuck for quick and easy bit change
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

	M18 FID3-0X	M18 FID3-502X
No load speed (rpm)	1750/3000/3900/0-3900	1750/3000/3900/0-3900
Impact rate (ipm)	1400/3600/4400/0-4400	1400/3600/4400/0-4400
Max. torque (Nm)	226	226
Tool reception	1/4" Hex	1/4" Hex
Weight with battery pack (EPTA) (kg)	1.7 (M18 B5)	1.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933479864	4933479866
EAN code	4058546376581	4058546376604



M18 FUEL

M18 ONEID2 | M18 FUEL™ ONE-KEY™ 1/4" HEX IMPACT DRIVER

- Higher power efficiency under load - outstanding torque of 226 Nm
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm
- Extremely compact design - total length of just 117 mm for access into tight spaces
- Connect via Bluetooth® with the ONE-KEY™ app
- ONE-KEY™ app provides inventory function for total management of your complete tool/equipment fleet
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- Configure to any application choosing optimum tool settings for repeatable precision
- Control speed, torque, start and end speeds and LED
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 ONEID2-0X	M18 ONEID2-502X
No load speed (rpm)	1900/2800/3600/0-3600	1900/2800/3600/0-3600
Impact rate (ipm)	1200/3400/4300/0-4300	1200/3400/4300/0-4300
Max. torque (Nm)	119/176/226/0-226	119/176/226/0-226
Tool reception	1/4" Hex	1/4" Hex
Max. bolt diameter	M16	M16
Weight with battery pack (EPTA) (kg)	1.7 (M18 B5)	1.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box

M18 FUEL

M18 FQID | M18 FUEL™ SURGE™ 1/4" HEX HYDRAULIC IMPACT DRIVER

- The M18 FUEL™ SURGE™ 1/4" Hex hydraulic driver is Milwaukee Tool's quietest impact driver
- FLUID-DRIVE™ hydraulic powertrain reduces metal on metal contact within the tool, delivering quieter operation, smoother performance and increased durability over a standard impact
- Delivers same performance in wood fastening as standard brushless impact drivers
- POWERSTATE™ brushless motor delivers up to 0 - 3.000 rpm with constant power output to drive screws faster
- REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Self-tapping screw mode is designed to reduce walking when starting self-tapping screws as well as reduce overdriving, breaking and stripping out screws
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 1/4" Hex chuck for quick and easy bit change



SURGE™ M18 FUEL

	M18 FQID-0	M18 FQID-502X
No load speed (rpm)	900/2100/3000/0-3000	900/2100/3000/0-3000
Impact rate (ipm)	1800/2900/4000/0-4000	1800/2900/4000/0-4000
Max. torque (Nm)	50	50
Tool reception	1/4" Hex	1/4" Hex
Max. bolt diameter	M14	M14
Weight with battery pack (EPTA) (kg)	1.7 (M18 B5)	1.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933451792	4933451791
EAN Code	4002395277650	4002395277643

M18 BLID2 | M18™ BRUSHLESS 1/4" HEX IMPACT DRIVER

- Brushless impact driver measures only 130 mm in length making it ideal for working within confined spaces
- Brushless motor technology delivers 180 Nm of torque, 3400 rpm and 4200 ipm
- 3-Mode DRIVE CONTROL allows the user to shift into three different speed and torque settings to maximise application versatility
- One-handed bit insert with retention lock, for faster, easier changing of bits
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- On board fuel gauge and LED light
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BLID2-0X	M18 BLID2-502X
No load speed (rpm)	1700/2600/0-3400	1700/2600/0-3400
Impact rate (ipm)	1500/3400/0-4200	1500/3400/0-4200
Max. torque (Nm)	180	180
Tool reception	1/4" Hex	1/4" Hex
Weight with battery pack (EPTA) (kg)	1.7 (M18 B5)	1.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933464519	4933464521
EAN Code	4058546224646	4058546224660

M18

M18 BRAID | M18™ RIGHT ANGLE IMPACT DRIVER

- Compact right angle impact driver measures 307 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gearbox and gears for superior durability and maximum torque
- Compact 53 mm head design
- Multi-handle design for multiple hand positions and maximum comfort
- 1/4" Hex chuck for quick easy one handed bit change
- 2 speed settings for wider range of applications
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BRAID-0
No load speed (rpm)	0 - 1500 / 0 - 2250
Impact rate (ipm)	0 - 2400 / 0 - 3400
Tool reception	1/4" Hex
Max. torque (Nm)	41 / 81
Weight with battery pack (EPTA) (kg)	1.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933447891
EAN Code	4002395006663

M18

M18 FSGC | M18 FUEL™ SCREW GUN WITH A COLLATED ATTACHMENT

- Brushless POWERSTATE™ motor for up to 10x longer motor life and up to 60% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- AUTO-START™ technology: When activated the power only engages when the screw gun is pushed into the material during application, delivering outstanding run time
- Quick release 1/4" Hex chuck allows for easy bit change
- Fine adjustment nose cone for setting desired countersink levels in single screw applications
- Removable collated attachment allows the user to use the gun as a stand alone screwdriver or a collaged screw gun
- Intuitive design of collated attachment to allow for easy cleaning of drywall dust
- Reinforced collated attachment to protect against dropping of tool
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge



	M18 FSGC-202X
No load speed (rpm)	0 - 4500
Wood screws to (mm)	6
Max. static stalling torque (Nm)	13
Tool reception	1/4" Hex
Weight with battery pack (EPTA) (kg)	2.0 (M18 B2)
Kit included	2 x M18 B2 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933459200
EAN Code	4002395289950

M18 FUEL

M18 FSG | M18 FUEL™ SCREW GUN

- Brushless POWERSTATE™ motor for up to 10x longer motor life and up to 60% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- AUTO-START™ technology: When activated the power only engages when the screw gun is pushed into the material during application, delivering outstanding run time
- Quick release 1/4" Hex chuck allows for easy bit change
- Fine adjustment nose cone for setting desired countersink levels in single screw applications
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Brightest LED workspace illumination
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FSG-0X
No load speed (rpm)	0 - 4500
Wood screws to (mm)	6
Max. static stalling torque (Nm)	13
Tool reception	1/4" Hex
Weight with battery pack (EPTA) (kg)	2.0 (M18 B2)
Kit included	No batteries supplied, No charger supplied, HD Box
Article Number	4933459201
EAN Code	4002395289967

M18 FUEL

GET THE RIGHT IMPACT WRENCH FOR THE JOB

SPECIALIST

SPECIALIST TOOLS DESIGNED FOR DIFFERENT APPLICATION TO GET THE JOB DONE FAST

**M18 FUEL**


ONE-KEY

**M18 ONEFHIWH716-0X**

1017 Nm

M18 FUEL

Lug Nut Mode

**M18 ONEFHIWF1D-121C**

2576 Nm

HIGH PERFORMANCE



LARGE METRIC BOLTS

M18 FUEL

ONE-KEY

**M18 ONEFHIWF34-502X**

1627 Nm

WORKING IN AND AROUND SEMI TRUCKS TO THE CONSTRUCTION SITE FOR HIGH TORQUE APPLICATIONS



EXTRA LARGE METRIC BOLTS

M18 FUEL

ONE-KEY

**M18 ONEFHIWF1-802X**

2033 Nm

PERFECT MATCH OF POWER, SIZE AND FUNCTIONALITY FOR THE MACHINERY TECHNICIAN TO MOUNTING BOLT ON A STEEL JUNCTION PLATE



MEDIUM TO LARGE METRIC BOLTS

M18 FUEL

ONE-KEY

**M18 ONEFHIWF12-502X**

1356 Nm

MID SIZE

TYRE CHANGE ON CARS TO MOUNTING LARGER BOLTS TO THE CHASSIS



SMALL TO MEDIUM METRIC BOLTS

M18 FUEL**M18 FIW2F12-502X**

339 Nm

M18 FUEL

ONE-KEY

**M18 ONEIWF12-502X**

300 Nm

M18 FUEL**M18 FMTIW2F12-502X**

745 Nm

COMPACT

ENGINE WORKS AND GETTING INTO THE HARD TO REACH SPOTS ON THE UNDERCARRIAGE



SMALL METRIC BOLTS

M12**M12 BIW12-202C**

138 Nm

M18**M18 BIW12-202C**

240 Nm

M12 FUEL**M12 FIWF12-622X**

339 Nm



Scan here to view our PPE range



Scan here to view compatible impact sockets

REDLITHIUM™

M18 ONEFHIWF1D | M18 FUEL™ ONE-KEY™ 1" HIGH TORQUE D-HANDLE IMPACT WRENCH WITH FRICTION RING AND EXTENDED ANVIL **M18 FUEL**

- The M18 FUEL™ D-Handle high torque impact wrench with a 150 mm extended anvil delivers 2576 Nm of fastening torque replacing AC, petrol or pneumatic solutions
- Delivers up to 2711 Nm of nut-busting torque that enables bolts up to M42 to be unfastened
- The 4 -Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. Customisation function allows for precise tool adjustment to application
- Lug nut mode when enabled through ONE-KEY™ will automatically shut the tool off when it comes into the range of 475 Nm - 610 Nm to prevent over-tightening of lug nuts
- Tri-LEDs deliver high definition lighting to increase workspace visibility
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 ONEFHIWF1D-121C	
No load speed (rpm)	600/ 700/ 900/ 1200
Impact rate (ipm)	750/ 930/ 1200/ 1440
Tool reception	1" square
Max. torque (Nm)	1180/ 1254/ 1966/ 2576
Nut_busting torque (Nm)	2711
Max. bolt diameter	M42
Weight with battery pack (EPTA) (kg)	12.7 (M18 HB12)
Kit included	1 x M18 HB12 Battery pack, M12-18 FC Charger, Kitbox
Article Number	4933471757
EAN Code	4058546296568

M18 ONEFHIWF1 | M18 FUEL™ ONE-KEY™ 1" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING **M18 FUEL**

- The M18 FUEL™ 1" T-handle high torque impact wrench has the power to replace AC, petrol or pneumatic solutions
- Delivering up to 2033 Nm of fastening torque at half the size and weight of AC, petrol or pneumatic solutions
- Packed with 2400 Nm of nut busting torque meaning those rusted stubborn old bolts wont stand a chance
- The 4 -Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. Customisation function allows for precise tool adjustment to application
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 ONEFHIWF1-802X	
No load speed (rpm)	0-950/ 0-1080/ 0-1370/ 0-1670
Impact rate (ipm)	1350/ 1650/ 2100/ 0-2500
Tool reception	1" square
Max. torque (Nm)	530/1020/1800/2033
Nut_busting torque (Nm)	2400
Max. bolt diameter	M42
Weight with battery pack (EPTA) (kg)	5.9 (M18 HB8)
Kit included	2 x M18 HB8 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933459734
EAN Code	4058546029067

M18 ONEFHIWF34 | M18 FUEL™ ONE-KEY™ 3/4" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING **M18 FUEL**

- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1627 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces
- The 4 -Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 4 bolt removal, provides a maximum nut-busting torque of 2034 Nm then shifts to 750 rpm for outstanding control when removing fasteners
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. Customisation function allows for precise tool adjustment to application
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- 3/4" friction ring reception
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 ONEFHIWF34-502X	
No load speed (rpm)	0-800/0-1300/0-1800/0-1800
Impact rate (ipm)	0-850/0-1850/0-2400/0-2400
Tool reception	3/4" square
Max. torque (Nm)	702/1138/1627/1627
Nut_busting torque (Nm)	2034
Max. bolt diameter	M33
Weight with battery pack (EPTA) (kg)	3.5 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933459731
EAN Code	4058546029036

M18 ONEFHIWF12 | M18 FUEL™ ONE-KEY™ 1/2" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING **M18 FUEL**

- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1356 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces
- The 4 -Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 4 bolt removal, provides a maximum nut-busting torque of 1898 Nm then shifts to 750 rpm for outstanding control when removing fasteners
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. Customisation function allows for precise tool adjustment to application
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- 1/2" friction ring reception
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 ONEFHIWF12-502X	
No load speed (rpm)	0-550/0-1400/0-1750/0-1750
Impact rate (ipm)	0-950/0-1750/0-2100/0-2100
Tool reception	1/2" square
Max. torque (Nm)	130 / 400 / 1356 / 1356
Nut_busting torque (Nm)	1898
Max. bolt diameter	M33
Weight with battery pack (EPTA) (kg)	3.3 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933459728
EAN Code	4058546029005

M18 ONEFHIWH716 | M18 FUEL™ 7/16" HEX UTILITY HIGH TORQUE IMPACT WRENCH WITH ONE-KEY™ M18 FUEL™

- Our MILWAUKEE® M18 FUEL™ 7/16" hex utility high torque impact wrench with ONE-KEY™ is the perfect match for our 7/16" accessories range giving you the power when needed in larger wood application
- With up to 1017 Nm max torque, this battery powered impact wrench gives you more power to effortlessly complete your applications or the removal of rusted and corroded hardware
- The extended handle offers you increased grip surface, perfect when wearing safety gloves for improved comfort, less fatigue, and balanced manoeuvrability
- Equipped with a QUIK-LOK™ chuck, providing faster and easier bit changes
- The integrated lanyard loop allows you to easily transfer and store the tool
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 ONEFHIWH716-502X	
No load speed (rpm)	0-900 / 0-1200 / 0-1800 / 0-2300
Impact rate (ipm)	0- 800 / 0-1300 / 0-2600 / 0-2800
Tool reception	7/16" Hex
Max. torque (Nm)	1017
Weight with battery pack (EPTA) (kg)	3.3 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933479406
EAN code	4058546372002

M18 FMTIW2F12 | M18 FUEL™ 1/2" MID-TORQUE IMPACT WRENCH WITH FRICTION RING M18 FUEL™

- Most versatile cordless impact wrench in the MILWAUKEE® impressive arsenal with an industry-leading performance at 881 Nm of nut-busting torque and 745 Nm of fastening torque
- Incredibly compact design for this performance level, with only 152 mm overall length ideal for applications in tight spaces
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- Auto shut-off control applies no more than 47 Nm of torque for hand-tight fastening applications to prevent over-tightening
- Tri-LEDs deliver high definition lighting to increase workspace visibility
- 1/2" square friction ring
- Reversible belt hook
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FMTIW2F12-502X	
No load speed (rpm)	0-1200 / 0-1950 / 0-2575 / 0-1325
Impact rate (ipm)	0-900 / 0-2100 / 0-3100
Tool reception	1/2" square
Max. torque (Nm)	475 / 610 / 745 / 47
Max. bolt diameter	M22
Weight with battery pack (EPTA) (kg)	2.3 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933478451
EAN Code	4058546346423

M18 FMTIW2F38 | M18 FUEL™ 3/8" MID TORQUE IMPACT WRENCH WITH FRICTION RING M18 FUEL™

- Most versatile cordless impact wrench in the MILWAUKEE® impressive arsenal with an industry-leading performance at 813 Nm of nut-busting torque and 745 Nm of fastening torque
- Incredibly compact design for this performance level, with only 152 mm overall length ideal for applications in tight spaces
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- Auto shut-off control applies no more than 47 Nm of torque for hand-tight fastening applications to prevent over-tightening
- Tri-LEDs deliver high definition lighting to increase workspace visibility
- 3/8" square friction ring
- Reversible belt hook
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FMTIW2F38-502X	
No load speed (rpm)	0-1200/ 0-1950/ 0-2575/ 0-1325
Impact rate (ipm)	0-900/ 0-2100/ 0-3100
Tool reception	3/8" square
Max. torque (Nm)	475/ 610/ 745/ 47
Max. bolt diameter	M22
Weight with battery pack (EPTA) (kg)	2.3 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933479405
EAN code	4058546371999

M18 ONEIWF12 | M18 FUEL™ ONE-KEY™ 1/2" IMPACT WRENCH WITH FRICTION RING M18 FUEL™

- M18 FIWF12 but with ONE-KEY™ technology
- Connect via Bluetooth® with the ONE-KEY™ app
- Complete tool customisation via ONE-KEY™ app to tune the tool to your needs
- Control speed, torque, start - end speeds and LED light
- Configure to any application choosing optimum tool settings for repeatable precision
- Program / save profiles for unmatched control
- Select from a range of application profiles or quickly create your own for perfect results on every trigger pull
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- ONE-KEY™ app also provides inventory function for total management of your complete tool / equipment fleet
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 ONEIWF12-0	M18 ONEIWF12-502X
No load speed (rpm)	900/1400/1900/2500	900/1400/1900/2500
Impact rate (ipm)	1300/2100/2550/3200	1300/2100/2550/3200
Tool reception	1/2" square	1/2" square
Max. torque (Nm)	40/120/220/300	40/120/220/300
Weight with battery pack (EPTA) (kg)	1.8 (M18 B5)	1.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933451153	4933451375
EAN Code	4002395138227	4002395160532

M18 ONEIWP12 | M18 FUEL™ ONE-KEY™ 1/2" IMPACT WRENCH WITH PIN DETENT M18 FUEL™

- M18 FIWP12 but with ONE-KEY™ technology
- Connect via Bluetooth® with the ONE-KEY™ app
- Complete tool customisation via ONE-KEY™ app to tune the tool to your needs
- Control speed, torque, start and end speeds and LED
- Configure to any application choosing optimum tool settings for repeatable precision
- Program/save profiles for unmatched control
- Select from a range of application profiles or quickly create your own for perfect results on every trigger pull
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite
- ONE-KEY™ app also provides inventory function for total management of your complete tool/equipment fleet
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 ONEIWP12-0	
No load speed (rpm)	900/1400/1900/2500
Impact rate (ipm)	1300/2100/2550/3200
Tool reception	1/2" square
Max. torque (Nm)	40/120/220/300
Weight with battery pack (EPTA) (kg)	1.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933451152
EAN Code	4002395138210

M18 FIW2F12 | M18 FUEL™ 1/2" COMPACT IMPACT WRENCH WITH FRICTION RING M18 FUEL™

- Power efficiency under load - outstanding torque of 339 Nm
- Extremely compact design - total length of just 124 mm for access into tight spaces
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- Auto shut-off control applies no more than 34 Nm of torque for hand-tight fastening applications to prevent over tightening
- Tri-LEDs deliver high definition lighting to increase workspace visibility
- 1/2" square friction ring
- Reversible belt hook
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FIW2F12-0X	M18 FIW2F12-502X
No load speed (rpm)	0-900 / 0-1650 / 0-2400 / 0-1200	0 - 900 / 0 - 1650 / 0 - 2400 / 0 - 1200
Impact rate (ipm)	0-1000 / 0-2400 / 0-3400	0 - 1000 / 0 - 2400 / 0 - 3500
Tool reception	1/2" square	1/2" square
Max. torque (Nm)	102 / 203 / 339 / 34	102 / 203 / 339 / 34
Weight with battery pack (EPTA) (kg)	1.8 (M18 B5)	1.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933478443	4933478445
EAN Code	4058546346348	4058546346362

M18 FIW2F38 | M18 FUEL™ 3/8" COMPACT IMPACT WRENCH WITH FRICTION RING M18 FUEL™

- The most compact cordless impact wrench in its class, delivering the most access in tight spaces, with performance at 339 Nm of fastening torque
- Incredibly compact design for this performance level, with only 124 mm overall length ideal for applications in tight spaces
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- Auto shut-off control applies no more than 34 Nm of torque for hand-tight fastening applications to prevent over tightening
- Tri-LEDs deliver high definition lighting to increase workspace visibility
- 3/8" square friction ring
- Reversible belt hook
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FIW2F38-0X	M18 FIW2F38-502X
No load speed (rpm)	0-800 / 0-1650 / 0-2400 / 0-1000	0-800 / 0-1650 / 0-2400 / 0-1000
Impact rate (ipm)	0-1000 / 0-2400 / 0-3500	0-1000 / 0-2400 / 0-3500
Tool reception	3/8" square	3/8" square
Max. torque (Nm)	102 / 203 / 339 / 34	102 / 203 / 339 / 34
Weight with battery pack (EPTA) (kg)	1.8 (M18 B5)	1.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933478650	4933478652
EAN Code	4058546348434	4058546348458

M18 BIW12 | M18™ 1/2" IMPACT WRENCH M18™

- Compact 1/2" impact wrench measures 155 mm in length making it ideal for working within confined spaces
- High performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 1/2" square drive for use with universal sockets
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BIW12-0	M18 BIW12-202C
No load speed (rpm)	0 - 2450	0 - 2450
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	0 - 3350	0 - 3350
Max. torque (Nm)	240	240
Weight with battery pack (EPTA) (kg)	1.9 (M18 B4)	1.9 (M18 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B2 Battery packs, M12-18 C Charger, Kitbox
Article Number	4933443590	4933443583
EAN Code	4002395003266	4002395003426

M18 BRAIW | M18™ 3/8" RIGHT ANGLE IMPACT WRENCH

- Compact right angle impact wrench measures 307 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gearbox and gears for superior durability and maximum torque
- Compact 53 mm head design
- Multi-handle design for multiple hand positions and maximum comfort
- 3/8" square drive for use with universal sockets
- 2 speed settings for wider range of applications
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

	M18 BRAIW-0
No load speed (rpm)	0 - 1500 / 0 - 2250
Tool reception	3/8" square
Impact rate (ipm)	0 - 2400 / 0 - 3400
Max. torque (Nm)	40 / 76
Weight with battery pack (EPTA) (kg)	1.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933447899
EAN Code	4002395006670

M18 ONEFLT | M18 FUEL™ LOCKBOLT TOOL WITH ONE-KEY™

- The M18 FUEL™ lockbolt tool with ONE-KEY™ is an optimised cordless solution that delivers fast, easy installations while maintaining performance, durability, and size
- 20,000 N of pulling force with a stroke length of 30 mm gives you the power to complete the larger applications effortlessly
- Installs up to 1,200 aluminium 6.4 mm lockbolts with one fully charged M18™ 5.0 Ah battery pack
- Increased productivity with faster lockbolt installations
- Installs HUCK® fasteners 4.8 mm and 6.4 mm including Bobtail® Magna-Grip®, C6L®, C120L® and Hucktainer®. All HUCK® nose assemblies and adapters are sold separately. When installing Hucktainers® an additional outer housing is required from MILWAUKEE®. HUCK® is a trade marks of Huck International Inc. and Howmet Aerospace Inc
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL

	M18 ONEFLT-0X	M18 ONEFLT-502X
Max. pulling force [N]	20,000	20,000
Lockbolt diameter range [mm]	4.8 and 6.4 (Hucktainer® : 9.53 mm)	4.8 mm and 6.4 mm (Hucktainer® : 9.53 mm)
Lockbolt fastener type	Bobtail®,C120L®,C6L®,Hucktainer®,Magna-Grip®	Bobtail®,C120L®,C6L®,Hucktainer®,Magna-Grip®
Stroke length (mm)	30	30
Dimensions (mm)	317 x 63 x 273	317 x 63 x 273
Weight with battery pack (EPTA) (kg)	2.8 (M18 B5)	2.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933478637	4933478639
EAN code	4058546348304	4058546348328

M18 ONEFPRT

M18 FUEL™ RIVET TOOL WITH ONE-KEY™

- The M18 FUEL™ rivet tool with ONE-KEY™ is an optimised cordless solution that delivers fast, easy riveting while maintaining performance, durability, and size
- Pulls up to 900 rivets with a rivet size of 4.8 mm in aluminium or 500 rivets with a size of 6.4 mm in aluminium on a fully charged M18™ 2.0 Ah battery pack
- Fasten all blind rivets including aluminium, steel, stainless steel and copper from 4.8 mm, 6.0 mm, 6.4 mm and 7.0 mm to give you a bigger range of applications to be completed
- 20,000 N of pulling force with a stroke length of 30 mm gives you the power to complete the larger diameters effortlessly
- The premium steel alloy 3-jaw design delivers more work between jaw changes
- Tool-free access to easily clean jaws. On-board nose piece storage and wrench for user convenience
- The transparent mandrel collector allows you to see when the mandrel collector is full, avoiding any mandrel jammings and minimising down time to unblock jammings also avoiding costly repairs at the same time
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL

ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE.

	M18 ONEFPRT-0X	M18 ONEFPRT-202X
Max. pulling force [N]	20,000	20,000
Max. rivets popped with M18 B2 battery [mm]	900 x 4.8 / 500 x 6.4	900 x 4.8 / 500 x 6.4
Rivet diameter range [mm]	4.8 - 7.0	4.8 - 7.0
Stroke length (mm)	30	30
Dimensions (mm)	317 x 63 x 273	317 x 63 x 273
Weight with battery pack (EPTA) (kg)	2.5 (M18 B2)	2.5 (M18 B2)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B2 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933478601	4933478603
EAN Code	4058546347949	4058546347963

PERFECT MATCH

RETENTION NOSE PIECES SET FOR M18 FUEL™ RIVET TOOL WITH ONE-KEY™

Article Number

4932478961



C18 PCG/600 | M18™ CAULK GUN WITH 600 ML TUBE

- Up to 4500 N of force. Min 40% higher than previous MILWAUKEE® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

	C18 PCG/600A-201B	C18 PCG/600T-201B
Max. pushing force (N)	4500	4500
Speed settings	6	6
Standard equipment	600 ml aluminium	600 ml transparent
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)	2.3 (M18 B2)
Kit included	1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag	1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag
Article Number	4933448758	4933441810
EAN Code	4002395810802	4002395002399

C18 PCG/400 | M18™ CAULK GUN WITH 400 ML TUBE

- Up to 4500N of force. Min 40% higher than previous MILWAUKEE® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

	C18 PCG/400T-201B
Max. pushing force (N)	4500
Speed settings	6
Standard equipment	400 ml transparent tube
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)
Kit included	1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag
Article Number	4933441814
EAN Code	4002395002382

C18 PCG/310 | M18™ CAULK GUN WITH 310 ML CANISTER

- Up to 4500 N of force. Min 40% higher than previous MILWAUKEE® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

	C18 PCG/310C-201B
Max. pushing force (N)	4500
Speed settings	6
Standard equipment	310 ml canister cartridge holder
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)
Kit included	1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag
Article Number	4933448759
EAN Code	4002395810819

M18 GG | M18™ GREASE GUN

- Powerful 18V motor delivers over 690 bar max. operating pressure
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Extreme long run time - dispenses up to 7 cartridges per charge
- Strong handle balance and ergonomics - only 355 mm long and 3.9 kg
- Air bleeder valve - priming mechanism for quick flow
- Integrated hose storage, shoulder strap loop & LED fuel gauge - added user convenience and reducing down time
- Three way loading - bulk, cartridge and suction capable
- Grease capacity 400 ml cartridge, 473 ml bulk
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Supplied with 1219 mm high pressure flex hose with spring guard



M18

	M18 GG-0
Pressure (bar)	690
Weight with battery pack (EPTA) (kg)	3.9 (M18 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933440493
EAN Code	4002395000357

GET THE RIGHT
ANGLE GRINDER
FOR THE JOB

M18

CUT-OFF GRINDER

Equivalent to 650 W

HD18 AG-115-402C



Ø 115 MM

M18 FUEL

HIGH OUTPUT™

Designed for the heavy applications, from beveling to cleaning up welds





M18 FHSAG125XPDB-552X



RAPID STOP

HIGH PERFORMANCE 125 MM BRAKING GRINDER with PADDLE SWITCH

Equivalent to 1,550 W

M18 FLAG230XPDB-121C



RAPID STOP

HIGH PERFORMANCE 230 MM BRAKING GRINDER with PADDLE SWITCH

Equivalent to 2,200 W

M18 ONEFLAG230XPDB-0C



RAPID STOP

HIGH PERFORMANCE 230 MM BRAKING GRINDER with PADDLE SWITCH and ONE-KEY

Equivalent to 2,200 W

FLAT GEAR HEAD

Design allows working within acute angles down to 42°



Equivalent to 1,200 W

M18 FSAGF125XPDB-0X



RAPID STOP

Ø 125 MM BRAKING GRINDER with PADDLE SWITCH

VARIABLE SPEED

Maximum control, ideal for working with stainless steel and aluminium & for rust and paint removal



Equivalent to 1,200 W

M18 FSAGV115XPDB-502X



RAPID STOP

Ø 115 MM BRAKING GRINDER with PADDLE SWITCH

ANGLE GRINDERS

Provides best handling and perfect for surface preparation



Equivalent to 1,200 W

M18 ONEFSAG115XPDB-552X



RAPID STOP

Ø 115 MM BRAKING GRINDER with ONE-KEY



Scan here to view our PPE range



Scan here to view compatible cutting discs

REDLITHIUM™

M18 ONEFLAG230XPDB

M18 FUEL™ ONE-KEY™ 230 MM BRAKING ANGLE GRINDER WITH PADDLE SWITCH

- Delivering corded performance similar to a 2200 W grinder
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- RAPIDSTOP™ for fastest disc brake in less than 3 seconds and best user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Anti-vibration side handle for lower vibration
- FIXTEC™ nut for tool-free wheel change (only to use with the kitted FIXTEC™ nut - 4931480289)
- Keyless guard for great cutting capacity and fast guard adjustment without using a key
- Removable dust screen to prevent debris entrance, prolonging motor life
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 ONEFLAG230XPDB-0C	
No load speed (rpm)	6600
Disc diameter (mm)	230
Cutting depth (mm)	65
Weight with battery pack (EPTA) (kg)	5.4 (M18 HB12)
Brake	Yes
Anti kickback protection	Yes
Switch type	Paddle (Deadman) switch
FIXTEC™	Yes
Line lock out function	Yes
Kit included	No batteries supplied, No charger supplied, Kitbox
Article number	4933478782
EAN code	4058546360641



M18 FLAG230XPDB | M18 FUEL™ 230 MM LARGE BRAKING GRINDER WITH PADDLE SWITCH

- The world's first single 18V battery operated large angle grinder that delivers the power to grind, lighter than corded tools and makes up to 68 cuts per charge in 42 mm stainless steel pipe
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Disc brake slows the disc down faster for improved user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Keyless guard for great cutting capacity and fast guard adjustment without using a key
- FIXTEC™ nut for tool-free disc change
- Anti-vibration side handle for lower vibration
- Removable dust screen to prevent debris entrance, prolonging motor life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FLAG230X-PDB-0C	M18 FLAG230X-PDB-121C
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Cutting depth (mm)	65	65
Spindle size	M14	M14
Weight with battery pack (EPTA) (kg)	5.3 (M18 HB12)	5.3 (M18 HB12)
Brake	Yes	Yes
Switch type	Paddle (Deadman) switch	Paddle (Deadman) switch
FIXTEC™ flange nut	Yes	Yes
Anti kickback protection	Yes	Yes
Line lock out function	Yes	Yes
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M18 HB12 Battery pack, M12-18 FC Charger, Kitbox
Article Number	4933464114	4933464116
EAN Code	4058546220594	4058546220617

M18 FHSAG125XPDB | M18 FUEL™ HIGH PERFORMANCE 125 MM BRAKING GRINDER WITH PADDLE SWITCH

- M18™ HIGH OUTPUT™ 125 mm small angle grinder that delivers the power to grind and makes up to 145 cuts per charge (5.5 Ah) in 2" electrical pipe
- RAPIDSTOP™ for fastest disc brake in less than 2.5 seconds and best user protection
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Anti-vibration side handle for lower vibration
- FIXTEC™ nut for tool-free disc change
- Removable dust screen to prevent debris entrance, prolonging motor life
- 125 mm keyless guard for great cutting capacity and fast guard adjustment without using a key
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FHSAG125X-PDB-0X	M18 FHSAG125X-PDB-552X
No load speed (rpm)	9000	9000
Disc diameter (mm)	125	125
Cutting depth (mm)	33	33
Spindle size	M14	M14
Weight with battery pack (EPTA) (kg)	3.4 (M18 HB5.5)	3.4 (M18 HB5.5)
Brake	Yes	Yes
Switch type	Paddle (Deadman) switch	Paddle (Deadman) switch
FIXTEC™ flange nut	Yes	Yes
Line lock out function	Yes	Yes
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 HB5.5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933471078	4933471081
EAN Code	4058546287061	4058546287092



M18 FSAGV115XPDB | M18 FUEL™ 115 MM VARIABLE SPEED & BRAKING ANGLE GRINDER WITH PADDLE SWITCH M18 FUEL

- Maximum control for every application - 5-step speed dial ideal for working with stainless steel and aluminum & for rust and paint removal
- Delivering corded performance similar to a 1200 W grinder
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Anti-vibration side handle for lower vibration
- Integrated FIXTEC™ system for tool-free wheel change
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- 115 mm keyless guard for great cutting capacity and fast guard adjustment without using a key
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FSAGV115XPDB-0	
No load speed (rpm)	3500 - 8500
Disc diameter (mm)	115
Cutting depth (mm)	28
Weight with battery pack (EPTA) (kg)	2.7 (M18 B5)
Brake	Yes
Anti_kickback protection	Yes
Switch type	Paddle (Deadman) switch
FIXTEC™	Yes
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933478774
EAN code	4058546360566

M18 ONEFSAG115XPDB | M18 FUEL™ ONE-KEY™ 115 MM BRAKING ANGLE GRINDER WITH PADDLE SWITCH M18 FUEL

- Delivering corded performance similar to a 1200 W grinder
- ONE-KEY™ tool locking, tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection
- Reduced gearhead size and lower angle of battery slot - for better balance & ergonomics compared to previous model
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Anti-vibration side handle for lower vibration
- Integrated FIXTEC™ system for tool-free wheel change
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- 115 mm keyless guard for great cutting capacity and fast guard adjustment without using a key
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite



M18 ONEFSAG115XPDB-552X	
No load speed (rpm)	8500
Disc diameter (mm)	115
Cutting depth (mm)	28
Weight with battery pack (EPTA) (kg)	3.1 (M18 HB5.5)
Brake	Yes
Anti_kickback protection	Yes
Switch type	Paddle (Deadman) switch
FIXTEC™	Yes
Line lock out function	Yes
Kit included	2 x M18 HB5.5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933478432
EAN code	4058546346232

M18 FSAGF125XPDB | M18 FUEL™ 125 MM FLATHEAD BRAKING ANGLE GRINDER WITH PADDLE SWITCH M18 FUEL

- Flat gear head design - allows user working within acute angles down to 42°
- Delivering corded performance similar to a 1200 W grinder
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Anti-vibration side handle for lower vibration
- FIXTEC™ nut for tool-free wheel change
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- 125 mm keyless guard for great grinding capacity and fast guard adjustment without using a key
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FSAGF125XPDB-0X	
No load speed (rpm)	8500
Disc diameter (mm)	125
Weight with battery pack (EPTA) (kg)	2.6 (M18 B5)
Brake	Yes
Anti_kickback protection	Yes
Switch type	Paddle (Deadman) switch
FIXTEC™	Yes
Line lock out function	Yes
Kit included	No batteries supplied, No charger supplied, HD Box
Article number	4933478439
EAN code	4058546346300

HD18 AG-115 | M18™ 115 MM ANGLE GRINDER WITH PADDLE SWITCH M18

- High performance 4-pole motor delivers maximum power whilst (optimising) maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gear case delivers heavy duty durability
- Reduced height of gear box and slim girth design deliver optimum ergonomics
- Non-lockable switch for best user protection and preventing automatic start up
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- Multi position side handle for ease of use
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	HD18 AG-115-0	HD18 AG-115-402C
No load speed (rpm)	9000	9000
Disc diameter (mm)	115	115
Cutting depth (mm)	28	28
Spindle size	M 14	M 14
Weight with battery pack (EPTA) (kg)	2.4 (M18 B4)	2.4 (M18 B4)
Brake	No	No
Switch type	Paddle (Deadman) switch	Paddle (Deadman) switch
FIXTEC™ flange nut	No	No
Line lock out function	No	No
Kit included	No batteries supplied, No charger supplied, No packs, M12-18 C kitbox or bag supplied	2 x M18 B4 Battery Charger, Kitbox
Article Number	4933411210	4933441303
EAN Code	4002395235681	4002395001712

M18 FROP21

M18 FUEL™ RANDOM ORBITAL POLISHER WITH 21 MM STROKE

- Delivering equal performance as corded random orbital polishers to complete polishing and heavy-correction applications
- 8 position speed dial selection for maximum control and best finishing results
- 21 mm orbital function for fast and efficient polishing with a free hologram finish
- Large ergonomic front grip area with overmold for easy and comfortable handling, especially when working with the tool vertically
- Lock-on function provides more comfortable and less strenuous use when polishing for longer periods
- 90° rotated battery slot with a clearance of more than 50 mm to prevent any touch points with the paint and allowing the tool to be stored in a horizontal or vertical position
- Line-lock-out function to prevent automatic start up
- Removable dust screen to prevent debris entrance, prolonging motor life
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FROP21-0X	
No load speed (rpm)	2400 - 4500
Backing pad diamater (mm)	150
Diameter of orbit (mm)	21
Weight with battery pack (EPTA) (kg)	3.3 (M18 B5)
Variable speed	Yes
Line lock out function	Yes
Soft start function	Yes
Standard equipment	150 mm backing pad, dust screen
Kit included	No batteries supplied, No charger supplied, HD Box
Article number	4933478836
EAN code	4058546361181

M18 FROP15 | M18 FUEL™ RANDOM ORBITAL POLISHER WITH 15 MM STROKE M18 FUEL

- Delivering equal performance as corded random orbital polishers to complete polishing and heavy-correction applications
- 8 position speed dial selection for maximum control and best finishing results
- 15 mm orbital function for fast and efficient polishing with a free hologram finish
- Large ergonomic front grip area with overmold for easy and comfortable handling, especially when working with the tool vertically
- Lock-on function provides more comfortable and less strenuous use when polishing for longer periods
- 90° rotated battery slot with a clearance of more than 50 mm to prevent any touch points with the paint and allowing the tool to be stored in a horizontal or vertical position
- Line-lock-out function to prevent automatic start up
- Removable dust screen to prevent debris entrance, prolonging motor life
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FROP15-0X	M18 FROP15-502X
No load speed (rpm)	2650 - 5100	2650 - 5100
Backing pad diamater (mm)	125	125
Diameter of orbit (mm)	15	15
Weight with battery pack (EPTA) (kg)	3.2 (M18 B5)	3.2 (M18 B5)
Variable speed	Yes	Yes
Line lock out function	Yes	Yes
Soft start function	Yes	Yes
Standard equipment	125 mm backing pad, dust screen	125 mm backing pad, dust screen
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933478834	4933479823
EAN code	4058546361167	4058546376178

M18 FAP | M18 FUEL™ POLISHER M18 FUEL

- Brushless POWERSTATE™ motor to deliver the ultimate mobility in car polishing
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- World's first cordless polisher with 8 position variable speed selection ranging from 360 - 2200 rpm
- Outstanding run time to polish one full size car per battery charge
- Constant speed electronics with soft start for smooth start up
- Maximum polishing accessory diameter of 180 mm
- Removable dust screen to prevent debris ingress, prolonging motor life
- Rubber overmold gear case for increased comfort, especially when working with the tool vertically
- Lock-on function provides more comfortable use when polishing for longer periods
- 3 position bale handle for improved tool control
- Line-lock-out function to prevent automatic start up after battery change



	M18 FAP180-0	M18 FAP180-502X
No load speed (rpm)	360 - 2200	360 - 2200
Disc diameter (mm)	180	180
Spindle size	M 14	M 14
Weight with battery pack (EPTA) (kg)	2.2 (M18 B5)	2.2 (M18 B5)
Variable speed	Yes	Yes
Line lock out function	Yes	Yes
Soft start function	Yes	Yes
Standard equipment	Polishing backing pad, dust screen, bale handle, AVS side handle	Polishing backing pad, polishing sponge white, polishing sponge orange, lambswool, dust screen, bale handle, AVS side handle
Kit included	No batteries supplied, No charger supplied, No packs, M12-18 FC kitbox or bag supplied	2 x M18 B5 Battery Charger, HD Box
Article Number	4933451549	4933451551
EAN Code	4002395144518	4002395144532



M18 FMCS66 | M18 FUEL™ 66 MM METAL CIRCULAR SAW

- First 18V cordless metal circular saw with 66 mm cutting depth and 1800 W corded performance
- Faster cutting speed compared to corded unit
- Shoe designed to connect directly on MILWAUKEE® guide rail (sold separately). This allows the user to make straight and accurate cuts with minimum setup time
- Performance light indicates when the device is pushed to hard
- Electric break stops blade in under 1 sec
- Large metal chip collector captures debris produced while cutting and provides needed visibility
- Dry-cutting technology provides fast, clean and burr-free metal cutting
- Dual-action trigger prevents any accidental start up
- Tool-free cutting depth adjustment and plunge lever for fast and effective plunge cuts
- Exclusive chip-release shield latch for fast waste disposal and blade changing
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FMCS66-0C
No load speed (rpm)	4000
Blade diameter (mm)	203
Bore size (mm)	15.87
Cutting depth (mm)	66
Weight with battery pack (EPTA) (kg)	7.5 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, Kitbox
Article Number	4933472110
EAN Code	4058546325060

M18 CBS125 | M18 FUEL™ DEEP CUT BAND SAW

- Brushless POWERSTATE™ motor provides corded cutting performance with up to 10x more motor life and up to 2x more run time compared to other cordless solutions
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Largest cutting capacity up to 125 x 125 mm material diameter
- 5 step variable speed selection from 0 - 116 m/min
- Tool-free blade locking mechanism for quick and easy saw blade changes
- Solid metal rafter hook for quick and easy jobsite storage
- Slim full metal motor housing design and LED work surface illumination for best cut visibility
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 CBS125-0	M18 CBS125-502C
No load speed [ml/min]	0 - 116	0 - 116
Cutting capacity rect. stock (mm)	125 x 125	125 x 125
Blade length (mm)	1139.83	1139.83
Weight with battery pack (EPTA) (kg)	7.3 (M18 B5)	7.3 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No packs, M12-18 FC kitbox or bag supplied	2 x M18 B5 Battery Charger, Kitbox
Article Number	4933447150	4933448198
EAN Code	4002395006038	4002395262786

M18 FBS85 | M18 FUEL™ COMPACT BAND SAW

- 20% faster cutting compared to previous model
- Large cutting capacity up to a diameter of 85 mm
- Variable speed trigger for quick & easy speed adjustments
- Band saw cover protects user from injuries by preventing any access to the blade - tool-free installation and removal within seconds
- Tool-free blade locking mechanism for quick and easy saw blade changes
- Dual action trigger to prevent accidental trigger actuation
- Tool-free & lockable adjustable shoe
- Solid metal rafter hook for easy jobsite storage
- Integrated LED light for workspace illumination
- Supplied with band saw covers and 12/14 TPI premium blade
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FBS85-0C	M18 FBS85-202C
No load speed [ml/min]	0 - 165	0 - 165
Cutting capacity rect. stock (mm)	85	85
Blade length (mm)	898.52	898.52
Weight with battery pack (EPTA) (kg)	3.9 (M18 B2)	3.9 (M18 B2)
Kit included	No batteries supplied, No charger supplied, Kitbox	2 x M18 B2 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933471496	4933471498
EAN Code	4058546293956	4058546293970

M18 FMCS | M18 FUEL™ 57 MM METAL CIRCULAR SAW

- Brushless POWERSTATE™ motor for fast cutting, longest tool life and up to 370 cuts in 3/4" EMT
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Cold cuts - reduces sparks for increased jobsite safety
- Tool-free depth adjustment, quickly and easily adjusts cutting depth from 0 to 57 mm
- Compact and light weight design for most comfortable use
- Integrated rafter hook for easy storage between uses
- On board allen key storage for easy access and preventing losing the key
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Supplied with 150 mm 34 teeth metal cutting blade



	M18 FMCS-0	M18 FMCS-502X
No load speed (rpm)	3900	3900
Blade diameter (mm)	150	150
Bore size (mm)	20	20
Cutting depth (mm)	57	57
Weight with battery pack (EPTA) (kg)	2.8 (M18 B5)	2.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No packs, M12-18 FC kitbox or bag supplied	2 x M18 B5 Battery Charger, HD Box
Article Number	4933459191	4933459194

M18 FDGROVPDB

M18 FUEL™ BRAKING DIE GRINDER WITH ONE-KEY™, VARIABLE SPEED AND PADDLE SWITCH

- Maximum control for every application - 5-step speed dial ideal for working with stainless steel, carbide burrs & accessories up to 75mm
- Delivering corded performance similar to a 1200 W grinder
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Spindle lock - increased productivity by reducing the need of 2 wrenches
- RAPIDSTOP™– stops all accessories in under the 2 seconds
- Universal reception to fit both, 6 and 8 mm accessories
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- 2 LED's around the reception to illuminate the working area
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- Rubber front provides most comfortable handling
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FDGROVPDB-0X
No load speed (rpm)	8.000 - 20.000
Collet capacity (mm)	6 & 8
Max. grinding accessories diameter [mm]	75
Kit included	No batteries supplied, No charger supplied, HD Box
Weight with battery pack (EPTA) (kg)	2.1 (M18 B5)
Article number	4933480957
EAN code	4058546412425

M18 FDGROVB

M18 FUEL™ BRAKING DIE GRINDER WITH ONE-KEY™, VARIABLE SPEED AND SLIDE SWITCH

- Maximum control for every application - 5-step speed dial ideal for working with stainless steel, carbide burrs & accessories up to 75mm
- Delivering corded performance similar to a 1200 W grinder
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Spindle lock - increased productivity by reducing the need of 2 wrenches
- RAPIDSTOP™– stops all accessories in under the 2 seconds
- Universal reception to fit both, 6 and 8 mm accessories
- 2 LED's around the reception to illuminate the working area
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- Rubber front provides most comfortable handling
- Line-lock-out function to prevent automatic start up
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FDGROVB-0X
No load speed (rpm)	8.000 - 20.000
Collet capacity (mm)	6 & 8
Max. grinding accessories diameter [mm]	75
Weight with battery pack (EPTA) (kg)	2.1 (M18B5)
Kit included	No batteries supplied , No charger supplied , HD Box
Article number	4933480955
EAN code	4058546412401



M18 FDGRB

M18 FUEL™ BRAKING DIE GRINDER WITH SLIDE SWITCH

- Delivering corded performance similar to a 1200 W grinder
- Spindle lock - increased productivity by reducing the need of 2 wrenches
- RAPIDSTOP™– stops all accessories in under the 2 seconds
- Lower angle of battery slot - for better balance & ergonomics compared to previous model
- Universal reception to fit both, 6 and 8 mm accessories
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- Rubber front provides most comfortable handling
- Line-lock-out function to prevent automatic start up
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FDGRB-0	
No load speed (rpm)	27.000
Collet capacity (mm)	6 & 8
Max. grinding accessories diameter (mm)	50
Weight with battery pack (EPTA) (kg)	2.0 (M18 B5)
Kit included	No batteries supplied , No charger supplied , HD Box
Article number	4933480952
EAN code	4058546412371

M18 FDG | M18 FUEL™ DIE GRINDER

- Brushless POWERSTATE™ motor with corded performance, up to 20 min of grinding on a 5.0 Ah battery and up to 10x more tool life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Universal reception to fit both, 6 and 8 mm accessories
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- Rubber front provides most comfortable handling
- Line-lock out function to prevent automatic start up
- Fuel gauge displays remaining charge
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Supplied with 6 mm & 8 mm collet, 15 mm & 17 mm open ended spanner, 2 x dust screens



	M18 FDG-0	M18 FDG-502X
No load speed (rpm)	27.000	27.000
Collet capacity (mm)	6 / 8	6 / 8
Max. grinding accessories diameter (mm)	50	50
Weight with battery pack (EPTA) (kg)	2.1 (M18 B5)	2.1 (M18 B5)
Kit included	No batteries supplied, No charger supplied, M12-18 FC kitbox or bag supplied	2 x M18 B5 Battery Charger, HD Box
Article Number	4933459106	4933459108
EAN Code	4002395287000	4002395287024

M18 FMDP | M18 FUEL™ MAGNETIC DRILLING PRESS WITH PERMANENT MAG-

- Brushless POWERSTATE™ motor provides corded drilling performance with strongest magnet holding force on 1/4" steel and 40 x 18 mm holes per battery charge
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- AUTOSTOP™ lift-off detection: Detects excess rotation and automatically cuts power to the drill for best user protection
- Self-powered permanent magnet with 8,890 N of holding force prevents accidental magnet deactivation for improved user protection and easy alignment
- 2 speed gear box for optimised drilling speed with 400 and 690 rpm's when using annual cutters or twist drill bits
- Maximum drilling capacity of 38 mm with use of annual cutters and 13 mm straight shank twist drill bits
- Keyless 19 mm Weldon reception for fast and easy accessory change



M18 FMDP-502C	
No load speed (rpm)	400 / 690
Max. diameter broaching capacity (mm)	38
Max. depth broaching capacity (mm)	50
Max. drilling solid bit (mm)	13
Magn. holding power (at drill point pressure) (N)	8890
Stroke length (mm)	146
Weight with battery pack (EPTA) (kg)	13.0 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933451013
EAN Code	4002395136667

M18 BMS12 | M18™ METAL SHEAR

- Accurate cuts with maximum cutting depth of 1.2 mm in steel
- Unique 360° tool-free rotating head with 12 locking positions to access tight spaces and increasing user comfort
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- In-Line wrist design for increased control during cutting
- Variable speed trigger for extra control during cutting
- Belt clip for secure mobility
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 BMS12-0	
No load speed (rpm)	0 - 2500
Max. cutting capacity steel (mm)	1.2
Max. cutting capacity aluminium (mm)	2.0
Minimum cutting radius [mm]	180
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933447925
EAN Code	4002395006731

M18 BMS20 | M18™ METAL SHEAR

- Accurate cuts with maximum cutting depth of 2.0 mm in steel
- Unique 360° tool-free rotating head with 12 locking positions to access tight spaces and increasing user comfort
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- In-Line wrist design for increased control during cutting
- Variable speed trigger for extra control during cutting
- Belt clip for secure mobility
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 BMS20-0	
No load speed (rpm)	0 - 2500
Max. cutting capacity steel (mm)	2.0
Max. cutting capacity aluminium (mm)	3.2
Minimum cutting radius [mm]	180
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933447935
EAN Code	4002395006748

M18 BHG | M18™ HEAT GUN

- High performance heat coil allows the tool to reach 470 °C
- Reaches operational temperature in six seconds allowing the user to quickly complete his application
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Durable ladder hook for work space management and safety
- Supplied with 2x nozzles: 1x reduction nozzle for heat intensity on a specific area, 1x reflector nozzle to apply heat around an object, such as pipes
- Integrated LED light to illuminate the work area
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BHG-0	M18 BHG-502C
Temperature range (°C)	470	470
Air volume (l/min)	170	170
Recommended ambient operating temperature [degrees]	-18 - +52	-18 - +52
Weight with battery pack (EPTA) (kg)	1.4 (M18 B5)	1.4 (M18 B5)
Kit included	No batteries supplied, No charger supplied, M12-18 C kitbox or bag supplied	2 x M18 B5 Battery Charger, Kitbox
Article Number	4933459771	4933459773
EAN Code	4058546029432	4058546029456



GET THE RIGHT
MITRE SAW
FOR THE JOB

MITRE SAW EXTENDABLE LEGSTANDS		
MSL 1000	MSL 2000	MSUV 280
		
Extendable up to 2 m	Extendable up to 2.5 m	Extendable up to 2.8 m



EXTERNAL

Roofing, fencing, decking

CAPACITY

M18 FUEL



M18 FMS254-0

Blade diameter 254 mm / 150 mm at fence

M18 FUEL
RED LITHIUM™
HIGH OUTPUT™
BATTERY TECHNOLOGY
ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE



M18 FMS305-0

Blade diameter 305 mm / 173 mm at fence

M18 FMS305

M18 FUEL™ ONE-KEY™ 305 MM MITRE SAW

- Delivers the power to cut at the same rate of an equivalent AC 305 mm saw, with the ability to cut up to 500 pieces of 78 mm pine base board on one 12.0 Ah battery charge
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Large sliding fences gives maximum support to the material being cut providing stability and accuracy
- Trenching stop with depth adjustment allows the user to make trenching and rebate cuts
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Integrated carry handle allows easy transportation on and off the jobsite
- Steel detent plate with preset angles gives repeatable accurate cuts
- LED light to illuminate the work piece and cut line in low light conditions
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 FMS305-0	
No load speed (rpm)	3600
Blade diameter (mm)	305
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Mitre capacity left (°)	55
Mitre capacity right (°)	60
Max. cutting capacity 45° mitre Left / 45° bevel Left (mm)	235 x 65
Max. cutting capacity 45° mitre Right / 45° bevel Right (mm)	235 x 40
Max. cutting capacity 45° mitre/ 90° bevel (mm)	235 x 97
Max. cutting capacity 90° mitre/ 45° bevel (mm)	343 x 65
Max. cutting capacity 90° mitre 90° bevel (mm)	343 x 97
Max. cutting capacity at fence 90° mitre/90° bevel (mm)	173 x 28
Bore size (mm)	30
Weight with battery pack (EPTA) (kg)	22.5 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471205
EAN Code	4058546288334



PERFECT MATCH

305 X 30 MM 60 TOOTH CIRCULAR SAW
BLADE WITH 3.0 MM CUTTING WIDTH

Article Number

4932471321



INTERNAL

Second fix, smaller cuts, skirting boards, kitchen fitting, door and window surrounds

PORTABILITY

M18

14.8 kg*



M18 SMS216-0

Blade diameter 216 mm

M18 FUEL

12.7 kg*



M18 FMS190-0

Blade diameter 190 mm

*Weight with M18 B5 battery pack

M18 FMS254 | M18 FUEL™ 254 MM MITRE SAW

- Brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 254 mm blade delivers large and accurate cut capacities
- Quick release bevel setting with detents allows the simple setting of bevel angles to the left and right
- Large sliding fences gives maximum support to the material being cut providing stability and accuracy
- Trenching stop with depth adjustment allows the user to make trenching and rebate cuts
- Up to 430 cuts in 26 mm x 142 mm decking with a 12.0 Ah battery gives the ability to work a full day without recharging the battery
- Integrated carry handle allows easy transportation on and off the jobsite
- Steel detent plate with preset angles gives repeatable accurate cuts
- LED light to illuminate the work piece and cut line in low light conditions
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 FMS254-0	
No load speed (rpm)	4000
Blade diameter (mm)	254
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Mitre capacity left (°)	50
Mitre capacity right (°)	60
Max. cutting capacity 45° mitre/45° bevel (mm)	205.23 x 51.3
Max. cutting capacity 45° mitre/ 90° bevel (mm)	205.23 x 91.2
Max. cutting capacity 90° mitre/ 45° bevel (mm)	289.3 x 51.3
Max. cutting capacity 90° mitre 90° bevel (mm)	289.3 x 91.2
Bore size (mm)	30
Weight with battery pack (EPTA) (kg)	20.0 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933451729
EAN Code	4002395279418



M18 FUEL



Scan here to view
our PPE range



Scan here to view
compatible mitre
saw blades

REDLITHIUM™

M18 SMS216 | M18™ 216 MM MITRE SAW

- Powerful frameless motor delivers 2700 rpm for fast cutting
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Accuracy and durability are achieved with dual vertical steel rails with linear bearings which deliver smooth sliding action
- Rail lock - the saw head locks in the back position automatically
- Adjustable laser - for perfect and quick alignment to cut line
- Steel detent plate with preset angles - gives repeatable accurate cuts
- Lock lever/handle over mold - allows the user to make repeated cuts comfortably and without fatigue
- Mitre release system - for quick and smooth change of the cutting orientation
- Integral LED jobsite light illuminates the work area
- Spindle lock - for quick and easy blade change
- Heavy duty cast base and fence ensures durability and accuracy
- 48°/-2° bevel capacity
- Supplied with saw blade (48 teeth), blade spanner and work clamp
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™

M18

	M18 SMS216-0
No load speed (rpm)	2700
Blade diameter (mm)	216
Bevel capacity left (°)	48
Bevel capacity right (°)	-2
Mitre capacity left (°)	50
Mitre capacity right (°)	50
Max. cutting capacity 45° mitre/45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre 90° bevel (mm)	270 x 60
Bore size (mm)	30
Weight with battery pack (EPTA) (kg)	14.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471057
EAN Code	4058546286859

M18 FCS66 | M18 FUEL™ 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS

- The M18 FUEL™ circular saw delivers the power to rip cut at the same feed rate of an equivalent AC circular saw - with the ability to cut 750 pieces of 90 mm x 45 mm pine stud on one 12.0 Ah battery charge
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- 190 mm blade which gives a 66 mm depth of cut, enabling the saw to cut 3 stacked OSB boards
- Durable metal rafter hang hook for work space management and safety
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors
- Magnesium shoe reduces weight and maximises durability
- Integrated LED light for workspace illumination
- 56° bevel capacity
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FCS66-0	M18 FCS66-121C
No load speed (rpm)	5800	5800
Max. cutting depth 90° (mm)	66	66
Max. cutting depth 45° (mm)	48	48
Blade diameter (mm)	190	190
Bore size (mm)	30	30
Weight with battery pack (EPTA) (kg)	5.4 (M18 HB12)	5.4 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No pack, M12-18 FC kitbox or bag supplied	1 x M18 HB12 Battery Charger, Kitbox
Article Number	4933464725	4933464587
EAN Code	4058546226701	4058546225322

M18 FMS190 | M18 FUEL™ 190 MM MITRE SAW

- Brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 190 mm blade delivers accurate cut capacities
- Quick release bevel setting allows the simple setting of bevel angles to the left and right
- Large sliding fences gives maximum support to the material being cut providing stability and accuracy
- Up to 299 cuts in 38 mm 89 mm soft wood with a 5.0 Ah battery gives the ability to work a full day without recharging the battery
- Light weight and portable at only 12.7 kg
- Integrated carry handle allows easy transportation on and off the jobsite
- Steel detent plate with preset angles gives repeatable accurate cuts
- LED light to illuminate the work piece and cut line in low light conditions
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL

	M18 FMS190-0
No load speed (rpm)	5000
Blade diameter (mm)	190
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Mitre capacity left (°)	48
Mitre capacity right (°)	48
Max. cutting capacity 45° mitre/45° bevel (mm)	152.7 x 39.3
Max. cutting capacity 45° mitre/ 90° bevel (mm)	152.7 x 55.4
Max. cutting capacity 90° mitre/ 45° bevel (mm)	215.5 x 39.3
Max. cutting capacity 90° mitre 90° bevel (mm)	215.5 x 55.4
Max. cutting capacity at fence 0 mitre/0 bevel (mm)	90.9 x 21.8
Max. cutting capacity at fence L45 mitre/0 bevel (mm)	90.9 x 20.3
Max. cutting capacity at fence R45 mitre/0 bevel (mm)	90.9 x 17.8
Bore size (mm)	30
Weight with battery pack (EPTA) (kg)	12.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459619
EAN Code	4058546027919

M18 FCSG66 | M18 FUEL™ 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS, GUIDE RAIL COMPATIBLE

- The M18 FUEL™ circular saw delivers the power to rip cut at the same feed rate of an equivalent AC circular saw - with the ability to cut 750 pieces of 90 mm x 45 mm pine stud on one 12.0 Ah battery charge
- 190 mm blade which gives a 66 mm depth of cut, enabling the saw to cut 3 stacked OSB boards
- Magnesium shoe compatible with MILWAUKEE® guide rail (sold separately). This allows the user to make straight and accurate cuts in sheet material with minimum setup time
- Durable metal rafter hang hook for work space management and safety
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors
- 56° bevel capacity
- Integrated LED light for workspace illumination
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FCSG66-0
No load speed (rpm)	5800
Max. cutting depth 90° (mm)	66
Max. cutting depth 45° (mm)	48
Blade diameter (mm)	190
Bore size (mm)	30
Weight with battery pack (EPTA) (kg)	5.6 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933472163
EAN Code	4058546325596

M18 FTS210 | M18 FUEL™ ONE-KEY™ TABLE SAW

- The ONE-KEY™ M18 FUEL™ table saw delivers the power to rip cut at the same feed rate of an equivalent AC saw, with the ability to cut 190 m of 19 mm OSB board on one 12.0 Ah battery charge
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Rack and pinion sliding fence allows the fence to be adjusted accurately and easily from the front of the saw giving 622 mm of rip capacity
- 210 mm blade allows 63 mm depth of cut at 90 degrees
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Quick change guard and riving knife allows the user to remove and adjust the riving knife and guard without the need to remove the throat plate
- Integrated carry handle allows easy transportation on and off the jobsite
- On board storage for all table saw attachments
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL

	M18 FTS210-0	M18 FTS210-121B
No load speed (rpm)	6300	6300
Blade diameter (mm)	210	210
Bevel capacity (°)	47	47
Rip capacity (mm)	622	622
Depth of cut capacity (mm)	63.5	63.5
Weight with battery pack (EPTA) (kg)	22.3 (M18 HB12)	22.3 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M18 HB12 Battery pack, M12-18 FC Charger, No kitbox or bag supplied
Article Number	4933464722	4933464226
EAN Code	4058546226671	4058546221713

M18 FCSRH66 | M18 FUEL™ REAR HANDLE CIRCULAR SAW FOR WOOD

- Delivers the power to rip cut at the same feed rate of an equivalent AC circular saw, with the ability to cross cut up to 570 pieces of 90 mm x 45 mm pine stud on one 12.0 Ah battery charge
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Rear handle design circular saw with blade left allows the user excellent cut line visibility
- 190 mm blade which gives a 66 mm depth of cut, enabling the saw to cut 3 stacked OSB boards
- Durable metal rafter hang hook for work space management and safety
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors
- Magnesium shoe reduces weight and maximises durability
- Integrated LED light for workspace illumination
- 53° bevel capacity
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FCSRH66-0
No load speed (rpm)	5800
Max. cutting depth 90° (mm)	66
Max. cutting depth 45° (mm)	48
Max. cutting depth 50 degrees (mm)	45
Blade diameter (mm)	190
Bore size (mm)	30
Weight with battery pack (EPTA) (kg)	5.2 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471444
EAN Code	4058546290726

TSS 1000 | TABLE SAW STAND

- Light weight of only 6.6 kg - easy to transport onto the job site
- Will hold up to 82 kg
- Quick release bracket to hold the saw firmly in place
- One point leg adjustment for leveling on uneven ground
- Comfortable work height at 559 mm
- To be used with M18 FUEL™ ONE-KEY™ table saw (M18 FTS210)



	TSS 1000
Height (mm)	559
Bearing force [kg]	82
Weight (kg)	6.6
Supplied in	No kitbox or bag supplied
Article Number	4933464227
EAN Code	4058546221720

M18 CCS55 | M18 FUEL™ 55 MM CIRCULAR SAW FOR WOOD AND PLASTICS

- Brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more cuts per charge
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 50° bevel capacity
- Magnesium upper and lower guards provide best in class durability for impact resistance
- Magnesium shoe reduces weight and maximises durability
- Integrated dust blower keeps cut line clear
- Hang hook allows safe storage of the tool
- Integrated battery fuel gauge & LED light
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 CCS55-0
No load speed (rpm)	5000
Max. cutting depth 90° (mm)	55
Max. cutting depth 45° (mm)	41
Blade diameter (mm)	165
Bore size (mm)	15.87
Weight with battery pack (EPTA) (kg)	3.2 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464223
EAN Code	4002395004959

M18 BLCS66 | M18™ BRUSHLESS 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS

M18

- M18™ brushless circular saw with a 190 mm blade giving a 66 mm depth of cut which enables the saw to cut three stacked 19 mm OSB boards
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Durable metal rafter hang hook for work space management and safety
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors
- Pressed aluminum shoe for maximum durability
- Integrated LED light for workspace illumination
- 50° bevel capacity with a 46 mm depth of cut
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BLCS66-0	M18 BLCS66-502X
No load speed (rpm)	5000	5000
Max. cutting depth 90° (mm)	66	66
Max. cutting depth 45° (mm)	48	48
Blade diameter (mm)	190	190
Bore size (mm)	30	30
Weight with battery pack (EPTA) (kg)	4.0 (M18 B5)	4.0 (M18 B5)
Kit included	No batteries supplied, No charger supplied, kitbox or bag supplied	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933464588	4933464591

HD18 CS | M18™ 55 MM CIRCULAR SAW FOR WOOD AND PLASTIC

M18

- Powerful 3500 rpm motor easily cuts most timber construction materials
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Large 50° bevel facility
- Magnesium upper guard provide best in class durability for impact resistance
- Excellent visibility of cutting line
- Electronic motor brake, saw blade stops within seconds
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Supplied with 24 tooth saw blade, parallel guide, dust port and allen key



	HD18 CS-0	HD18 CS-402B
No load speed (rpm)	3500	3500
Max. cutting depth 90° (mm)	55	55
Max. cutting depth 45° (mm)	39	39
Blade diameter (mm)	165	165
Bore size (mm)	15.87	15.87
Weight with battery pack (EPTA) (kg)	3.8 (M18 B4)	3.8 (M18 B4)
Kit included	No batteries supplied, No charger supplied, kitbox or bag supplied	2 x M18 B4 Battery packs, M12-18 C Charger, Tool bag
Article Number	4933419134	4933441403
EAN Code	4002395238248	4002395001699

M18 FPS55

M18 FUEL

M18 FUEL™ 55 MM PLUNGE SAW

- The M18 FUEL™ plunge saw delivers the power to rip cut at the same feed rate of an equivalent AC circular saw - with the ability to cut 45 metres of 18 mm plywood on one 5.5 Ah battery charge
- The depth adjustment has two scales, one for on the rail and one for off the rail, this can easily be adjusted by the press of a button
- Flat sided upper guard, the blade is only 12 mm from the outer edge of the guard allowing the saw to cut very close to a wall
- This saw has also been designed for optimal dust extraction on the job site, due to the enclosed guard. It is compatible with the DEK26 system and is also supplied with a dust bag
- Scoring stop allows a 1 mm back cut to made minimising any splintering in laminated materials
- The bevel adjustment has stops at 22.5°, 45°and 48°. It also has a -1 for making a back cut
- The saw also has a cut line window on the side for those cuts where you need to see the front of the blade against the material and also a sprung loaded riving knife
- Easy blade change system locks the switch off and the blade in position while the blade can be changed



	M18 FPS55-0P	M18 FPS55-552P
No load speed (rpm)	2500 - 5600	2500 - 5600
Max. cutting depth 0°/45°/48° (mm)	59/ 44	59/ 44
Max. cutting depth with guiderail 0°/45°/48° (mm)	55/ 42	55/ 42
Blade diameter (mm)	165	165
Bore size (mm)	20	20
Bevel capacity (°)	-1 - 48	-1 - 48
Weight with battery pack (EPTA) (kg)	4.9 (M18 HB5.5)	4.9 (M18 HB5.5)
Kit included	No batteries supplied, No charger supplied, PACKOUT™ xl toolbox	2 x M18 HB5.5 Battery packs, M12-18 FC Charger, PACKOUT™ xl toolbox
Article number	4933478777	4933478779
EAN code	4058546360597	4058546360610

CSB P W 165 X 20 X 1.6 X 40ATB	
Article Number	4932471932



M18 ONEFSZ | M18 FUEL™ ONE-KEY™ SAWZALL™

M18 FUEL

- M18 FSZ but with ONE-KEY™ technology
- Connect via Bluetooth® with the ONE-KEY™ app
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Adjustable soft start provides more accurate cut-starts in various materials minimising blade chatter and assisting in cleaner faster cuts
- Cut optimisation gives longer blade life and easier cutting in a wide range of materials
- Automatic brake allows the saw to stop the blade after it breaks through a material preventing accidental cuts in adjacent materials
- Save up to three custom settings to the tools memory allowing fast and easy selection of the most used configurations
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

ONE-KEY
UNLOCKING THE DIGITAL JOBSITE.



	M18 ONEFSZ-0X	M18 ONEFSZ-502X
Max. cutting depth in soft-wood (mm)	300	300
Max. cutting depth in steel (mm)	20	20
Max. cutting depth in aluminium (mm)	25	25
Max. cutting depth in non-ferrous metal (mm)	25	25
Max. cutting depth in metal pipe (mm)	150	150
No load stroke rate (spm)	0-3000	0-3000
Stroke length (mm)	32	32
Weight with battery pack (EPTA) (kg)	3.8 (M18 B5)	3.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933478296	4933478294
EAN Code	4058546344733	4058546344719

M18 FSX | M18 FUEL™ SUPER SAWZALL™

- The M18 FUEL™ Super SAWZALL™ delivers the power to cut at the same speed as an equivalent AC reciprocating saw - with the ability to cut 150 pieces of 290 mm x 45 mm pine on one 12.0 Ah battery charge
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Orbital action allows the saw to clear the cut of debris giving a faster cut in wood materials
- 3000 SPM with a 32 mm stroke length delivers fast and effortless cutting in a wide range of materials
- 5 variable speed settings from 1500 SPM to 3000 SPM to allow the correct speed to be set for the material being cut
- FIXTEC™ blade clamp for fast and easy blade changes without any key
- Durable metal rafter hang hook for work space management and safety
- Adjustable shoe for optimised use of blades
- Integrated LED light for workspace illumination
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



NEW LEGENDARY HIGH OUTPUT M18 FUEL

	M18 FSX-0C	M18 FSX-121C
Max. cutting depth in soft-wood (mm)	300	300
Max. cutting depth in steel (mm)	20	20
Max. cutting depth in aluminium (mm)	25	25
Max. cutting depth in non-ferrous metal (mm)	25	25
Max. cutting depth in metal pipe (mm)	150	150
No load stroke rate (spm)	0 - 3000	0 - 3000
Stroke length (mm)	32	32
Weight with battery pack (EPTA) (kg)	5.5 (M18 HB12)	5.5 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M18 HB12 Battery pack, M12-18 FC Charger, Kitbox
Article Number	4933464724	4933464484
EAN Code	4058546226695	4058546224295

M18 BSX | M18™ SAWZALL™

M18

- High performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Patented FIXTEC™ clamp for fast and easy keyless blade change
- Counter balance mechanism to reduce vibrations 15.2 m/s² in wooden beams
- 28.6 mm stroke length & 3000 strokes per minute for extremely fast cutting
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BSX-0	M18 BSX-402C
Max. cutting depth in soft_wood (mm)	300	300
Max. cutting depth in steel (mm)	20	20
Max. cutting depth in aluminium (mm)	25	25
Max. cutting depth in non_ferrous metal (mm)	25	25
Max. cutting depth in metal pipe (mm)	150	150
No load stroke rate (spm)	3000	3000
Stroke length (mm)	28.6	28.6
Weight with battery pack (EPTA) (kg)	4.0 (M18 B4)	4.0 (M18 B4)
Kit included	No batteries supplied, No charger supplied, kitbox or bag supplied	2 x M18 B4 Battery packs, M12-18 C Charger, Kitbox
Article Number	4933447275	4933447290
EAN Code	4002395006113	4002395006137

M18 FHZ | M18 FUEL™ HACKZALL™

M18 FUEL

- POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 22 mm stroke length for controlled cutting with a no load stroke rate of 3000 spm
- Pivoting shoe allows the user to optimise his cutting position
- Built in LED light improves visibility in low light cutting applications
- Patented FIXTEC™ clamp for quick and efficient blade change
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FHZ-0X	M18 FHZ-502X
No load stroke rate (spm)	0 - 3000	0 - 3000
Stroke length (mm)	22	22
Weight with battery pack (EPTA) (kg)	2.6 (M18 B5)	2.6 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933459887	4933459886
EAN Code	4058546030599	4058546030582



M18 FBJS

M18 FUEL™ BODY GRIP JIGSAW

- Brushless POWERSTATE™ motor for fast cutting, long tool life and up to 32 m in 19 mm OSB (on a 5.0 Ah pack)
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Patented FIXTEC™ blade clamp for fast and easy blade change
- 5 stage pendulum action for increased cutting performance
- Ambidextrous on / off switch allows user to turn the tool on in any position
- 6-speed settings with auto controlled start mode allows the tool to start slow and ramp up to full speed when load is detected for smooth and accurate cut starts
- 3500 SPM delivers smooth cuts, minimised chipping and vibration
- Dust blower keeps the cut line free of wood dust
- Integrated LED light for workspace illumination
- Detachable soft shoe avoids marks and scratches when cutting soft materials
- Supplied with 1 x blade, dust extraction adapter, dust cover, splinter guard, soft shoe
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

	M18 FBJS-0X	M18 FBJS-502X
No load stroke rate (spm)	800 - 3500	800 - 3500
Max. cutting capacity wood (mm)	100	100
Max. cutting capacity steel (mm)	10	10
Bevel capacity (°)	45	45
Stroke length (mm)	25	25
Weight with battery pack (EPTA) (kg)	2.8 (M18 B5)	2.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933464799	4933464801
EAN Code	4058546227449	4058546227463



JIGSAW BLADES SET (35PC) - SUITABLE FOR APPLICATIONS IN WOOD AND METAL

Article Number 4932479088



M18 FUEL

M18 FMT | M18 FUEL™ MULTI-TOOL

- POWERSTATE™ brushless motor pairs with an aggressive oscillation angle of 2.1° (left/ right) and 10,000 – 20,000 OPM to deliver one of the fastest cut speeds in the industry
- Suitable for many demanding applications with ease, such as rip cuts through hardwoods and nail embedded wood
- 10-setting dial with an auto-load feature allows users to adjust the speed to the application
- FIXTEC™ tool free blade change with universal blade change adaptor included to accept all major competitor blades
- Integrated 180 degree LED light for maximum visibility in low-light situations
- Supplied with 1x universal fit OPEN-LOK oscillating multi-tool wood blade, 1x multi-tool sanding pad, 1x 60 grit sand paper, 1x 80 grit sand paper, 2x 120 grit sand paper, and 1x 240 grit sand paper
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL

	M18 FMT-0X	M18 FMT-522X
Oscillation angle left/ right (°)	2.1	2.1
No load speed (rpm)	10,000 - 20,000	10,000 - 20,000
Weight with battery pack (EPTA) (kg)	1.9 (M18 B5)	1.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	1 x M18 B5, 1 x M18B2 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933478491	4933478493
EAN Code	4058546346843	4058546346867

M18 BMT | M18™ MULTI-TOOL

- Up to 50% faster and versatile cordless solution for cutting and removal applications with corded performance
- REDLINK™ overload protection and constant speed electronics in tool deliver best in class durability and performance
- 12 variable speed settings from 12,000 - 18,000 orbits per minute and 3.4° oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic
- Productivity enhancing FIXTEC™ tool free blade change with universal blade change adaptor included to accept all competitor blades
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Unique cutting depth stop adaptor to prevent over-cutting in material
- Unique dust extraction kit to keep the work space dust-free when connected to an AC or DC extraction system
- Brightest LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

	M18 BMT-0	M18 BMT-421C
Oscillation angle left/ right (°)	1.7	1.7
No load speed (rpm)	12,000 - 18,000	12,000 - 18,000
Weight with battery pack (EPTA) (kg)	1.7 (M18 B2)	1.7 (M18 B2)
Kit included	No batteries supplied, No charger supplied, kitbox or bag supplied	1 x M18 B4, 1 x M18 B2 Battery packs, M12-18 C Charger, Kitbox
Article Number	4933446203	4933446272
EAN Code	4002395004928	4002395005079

M18 FJS | M18 FUEL™ TOP HANDLE JIGSAW

- Brushless POWERSTATE™ motor for fast cutting, long tool life and up to 32 m in 19 mm OSB (on a 5.0 Ah pack)
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Patented FIXTEC™ blade clamp for fast and easy blade change
- Keyless bevel facility on the base plate allows for adjustment between 0 - 45°
- 5 stage pendulum action for increased cutting performance
- Dust blower keeps the cut line free of wood dust
- Integrated LED light for workspace illumination
- Detachable soft shoe avoids marks and scratches when cutting soft materials
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 BJS | M18™ TOP HANDLE JIGSAW

- High performance motor delivers 2800 spm for fast cutting
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Patented FIXTEC™ blade clamp for fast and easy blade change
- Keyless bevel facility on the base plate allows for adjustment between 0 - 45°
- Five stage pendulum action for increased cutting performance
- LED light to illuminate the work piece
- Dust blower keeps the cut line free of wood dust
- Detachable soft shoe avoids marks and scratches when cutting soft materials
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FJS-0X	M18 FJS-502X
No load stroke rate (spm)	0 - 3500	0 - 3500
Max. cutting capacity wood (mm)	135	135
Max. cutting capacity steel (mm)	10	10
Bevel capacity (°)	45	45
Stroke length (mm)	25	25
Weight with battery pack (EPTA) (kg)	2.9 (M18 B5)	2.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933464726	4933464728
EAN Code	4058546226718	4058546226732

M18 FUEL

M18 BP | M18™ PLANER

- High performance 4-pole motor delivers 14,000 rpm to achieve optimum surface finish
- REDLINK™ overload protection and constant speed electronics in tool deliver best in class durability and performance
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Faster material removal with two double edged carbide blades over a planing width of 82 mm
- Adjustable depth of cut from 0 to 2 mm with twenty locking positions allows the user to accurately set the amount of material to be removed in one pass
- Up to 10.7 mm of rebate depth
- Left or right chip ejection allows the user to keep the chips away from his face when planing
- Extended front shoe allows the tool to be placed on the work piece accurately and quickly
- A kick stand located on the base protects the work piece from accidental damage
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

	M18 BP-0	M18 BP-402C
No load speed (rpm)	14,000	14,000
Cutting width (mm)	82	82
Cutting depth (mm)	2	2
Rebate depth (mm)	10.7	10.7
Weight with battery pack (EPTA) (kg)	2.7 (M18 B4)	2.7 (M18 B4)
Kit included	No batteries supplied, No charger supplied, kitbox or bag supplied	2 x M18 B4 Battery packs, M12-18 C Charger, Kitbox
Article Number	4933451113	4933451115
EAN Code	4002395137374	4002395137398

M18 FTR | M18 FUEL™ TRIM ROUTER

- POWERSTATE™ brushless motor delivers the power of AC trim routers, max. 31,000 rpm for powerful, smooth cutting
- Variable speed dial allows users to adjust the speed between 10,000 and 31,000 rpm to choose the best control for the application at hand
- All day run time on a single charge of an M18™ 5.0 Ah battery (up to 115 m)
- Innovative height adjustment system incorporating a 0.4 mm micro adjustment
- Active brake stops the router bit quickly
- Included plunge base features 3 stop pins for multiple pass mortising
- Dual LED lights to illuminate the work surface
- Compatible with the dust collection shroud (DEK 26)
- Supplied with 2 x dust extraction attachments, 146 mm sub-baseplate which accepts 31.75 mm guide bushings, 6 mm and 6.35 mm collets, plunge base, 2 x side fences
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL

	M18 FTR-0X
Voltage (V)	18
Battery type	Li-ion
Collet capacity (mm)	6/ 6.35
Plunge capacity (mm)	50
No load speed (rpm)	10,000 - 31,000
Speed settings	6
Weight with battery pack (EPTA) (kg)	2.1 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box
Article Number	4933471604
EAN Code	4058546295035

M18 BQSS | M18™ QUARTER SHEET SANDER

- High performance motor delivers 11,000 to 13,000 sanding strokes per minute for faster material removal
- Variable speed wheel with 6 speed settings allows the correct speed to be set for different types of material
- Universal hook and loop sanding pad allows easy changing of sanding sheets
- Paper retention clips for use with standard sheet sand paper
- Low profile pommel height with rubberised textured grip provides enhanced ergonomics
- Anti swirl orbital motion ensures flawless finishes delivered with low vibration at only 5.23 m/s²
- Hole punch supplied for use with standard sheet sand paper
- Premium 4-pole brushed motor, REDLITHIUM™ battery pack and REDLINK™ electronic delivering the needed power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BQSS-0	M18 BQSS-502B
No load speed (rpm)	11,000 - 13,000	11,000 - 13,000
Oscillation diameter (mm)	1.6	1.6
Sanding pad size (mm)	113 x 104	113 x 104
Weight with battery pack (EPTA) (kg)	1.9 (M18 B5)	1.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B5 Battery packs, M12-18 C Charger, Tool bag
Article number	4933479966	4933479968
EAN code	4058546377601	4058546377625

M18 FBTS75 | M18 FUEL™ 75 MM BELT SANDER

- Compact design, with a flat front and side edge allows flush sanding capability
- Captures 90% of dust either through the universal dust port or with the multi layered dust bag
- Variable speed adjustable with a belt speed range from 230 to 410 m/s
- Tool-free adjustable pommel allows for adjustment of the front handle letting the user find the optimum sanding position
- Standard belt size of 75 x 457 mm
- Tool-free belt change with easy adjustment of the belt roller allowing for precise belt alignment
- LED lights are placed at the front and side to give 180° of illumination
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FBTS75-0	M18 FBTS75-552X
Belt speed (m/min)	230 - 410	230 - 410
Belt length (mm)	457	457
Belt width (mm)	75	75
Sanding surface (mm)	90 x 135	90 x 135
Weight with battery pack (EPTA) (kg)	4.6 (M18 HB5.5)	4.6 (M18 HB5.5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 HB5.5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933479614	4933479616
EAN code	4058546374082	4058546374105

M18 BOS125 | M18™ 125 MM RANDOM ORBITAL SANDER

- High performance motor delivers 14,000 to 24,000 sanding strokes per minute for faster material removal
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed wheel with 6 speed settings allows the correct speed to be set for different types of material
- Dust extraction box with internal filter keeps dust contained and managed
- Universal hook and loop sanding pad allows easy changing of sanding discs
- Lightweight - 1.6 kg
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BOS125-0	M18 BOS125-502B
No load speed (rpm)	12,000	12,000
Oscillation rate (opm)	14,000 - 24,000	14,000 - 24,000
Oscillation diameter (mm)	2.4	2.4
Sanding pad size (mm)	125	125
Weight with battery pack (EPTA) (kg)	1.6 (M18 B5)	1.6 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B5 Battery packs, M12-18 C Charger, Tool bag
Article Number	4933464228	4933464230
EAN Code	4058546221737	4058546221751

M18 FAC | M18 FUEL™ AIR COMPRESSOR

- POWERSTATE™ brushless motor delivers a maximum air pressure of 9.31 bar and 48 l/m at 2.8 bar which delivers enough performance to run common finish nailers and staplers
- At only 68 dB(A) this is one of the quietest cordless compressors on the market allowing for a more comfortable working environment on the jobsite
- 14 kg in weight and equipped with two carry handles allows the compressor to be easily transport to and from the jobsite
- Excellent productivity with a run time of 1600 18G brad nails on a M18™ 12.0 Ah battery pack
- Single turn regulator allows quick and easy adjustment of the pressure to the desired level
- Quick connect coupler allows the user to quickly attach and disconnect the hose for increased productivity
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FAC-0
Airflow (l/min)	48
Max. pressure (bar/PSI)	9.31 / 135
Tank capacity (l)	7.6
Sound pressure level (Lpa)(dB(A))	68
Weight with battery pack (EPTA) (kg)	15.7 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933472166
EAN Code	4058546325626

GET THE RIGHT
NAILER/STAPLER
FOR THE JOB

FRAMING NAILERS

Cut roofs, floor joists, stud walls, decking



M18 FUEL



M18 FFN-502C

Collation angle 30° - 34°

M18 FUEL



M18 FFN21-0C

Collation angle 20° - 22°

FINISHING NAILERS

Skirting boards, molding, flooring, deck railings, staircases, door and window casing, cabinet making



M18 FUEL



M18 FN18GS-202X

Collation angle STRAIGHT

M18 FUEL



M18 FN16GA-202X

Collation angle 20°

M18 FUEL



M18 FN15GA-0X

Collation angle 34°

FENCING UTILITY
STAPLER



M18 FUEL



M18 FFUS-302C

Collation angle STRAIGHT

STAPLERS

Fabric, plastic, beading, fascias & soffits



M18 FUEL



M18 FNCs18GS-202X

Collation angle STRAIGHT

M12



M12 BST-202X

Collation angle STRAIGHT

M12



M12 BCST-0

Collation angle STRAIGHT



Scan here to view
our PPE range



Scan here to
view available
nails and staples

REDLITHIUM™



M18 FFN21 | M18 FUEL™ 21° FRAMING NAILER 2-MODE

- Excellent power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Two mode selection allows for sequential fire for precision or bump fire for speed
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine
- Fires up to 700 nails per charge on a REDLITHIUM™ 5.0 Ah battery pack for maximum productivity
- Fires standard framing nails which fits an angled magazine at 20° to 22°
- Quick access and easy clearing of jams
- LED work light illuminates the work surface for better placement of nails
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability



	M18 FFN21-0C
Collation angle [degrees]	20 - 22
Nail diameter [mm]	2.8 - 3.7
Nail type (mm)	50 - 90
Magazine capacity nails	51
Weight with battery pack (EPTA) (kg)	5.0 (M18 B5)
Kit included	No batteries supplied, No charger supplied, Kitbox
Article Number	4933478993
EAN Code	4058546362751

M18 FUEL

M18 FN18GS | M18 FUEL™ 18 GS FINISH NAILER

- Excellent power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Smaller nail hole, the exact size of the nail head leaving a neater finish
- Different shaped noses stored on board allows the user to get the best finish no matter what the application
- Small work contact bracket allows the user to fire and sink nails at a more acute angle
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine
- Fires up to 1200 nails per charge on a REDLITHIUM™ 2.0 Ah battery pack for maximum productivity
- Quick access and easy clearing of jams
- LED work light illuminates the work surface for better placement of nails
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FN18GS-0X	M18 FN18GS-202X
Collation angle [degrees]	0	0
Nail diameter [mm]	1.2	1.2
Nail type (mm)	16 / 54	16 / 54
Magazine capacity nails	110	110
Cycle rate	900	900
Weight with battery pack (EPTA) (kg)	3.1 (M18 B2)	3.1 (M18 B2)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B2 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933471409	4933471408
EAN Code	4058546290375	4058546290368

M18 FUEL

M18 FFN | M18 FUEL™ 34° FRAMING NAILER 2-MODE

- Excellent power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Two mode selection allows for sequential fire for precision or bump fire for speed
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine
- Fires up to 700 nails per charge on a REDLITHIUM™ 5.0 Ah battery pack for maximum productivity
- Fires standard framing nails which fits an angled magazine at 30° or 34°
- Quick access and easy clearing of jams
- LED work light illuminates the work surface for better placement of nails
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability



	M18 FFN-0C	M18 FFN-502C
Collation angle [degrees]	30 - 34	30 - 34
Nail diameter [mm]	2.8 - 3.3	2.8 - 3.3
Nail type (mm)	50 - 90	50 - 90
Magazine capacity nails	51	51
Weight with battery pack (EPTA) (kg)	5.1 (M18 B5)	5.1 (M18 B5)
Kit included	No batteries supplied, No charger supplied, Kitbox	2 x M18 B5 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933471406	4933471405
EAN Code	4058546290344	4058546290337

M18 FUEL

M18 FFUS | M18 FUEL™ FENCING UTILITY STAPLER

- Excellent power to consistently fire 50 mm staples into fence posts
- Ready to Fire Technology eliminates ramp-up time between each staple discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Tool-free, quick and easy depth adjustment to assure staples are driven to the correct depth so as not to crush the wire
- Quick access hatch for easy clearing of jammed staples
- Dry-Fire lockout stops the tool being fired when there are no staples left in the magazine
- Fires up to 600 staples per charge on a REDLITHIUM™ 3.0 Ah battery pack for maximum productivity
- Excellent line of sight allows for quick and precise placing of each staple
- Fires MILWAUKEE® 9 gauge barbed collated staples from 40 mm to 50 mm
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FFUS-0C	M18 FFUS-302C
Magazine capacity	45	45
Staple strip	20	20
Staple strip length [mm]	38 - 51	38 - 51
Staple strip width [mm]	10.3	10.3
Cycle rate	600	600
Weight with battery pack (EPTA) (kg)	5.0 (M18 HB3)	5.0 (M18 HB3)
Kit included	No batteries supplied, No charger supplied, Kitbox	2 x M18 HB3 Battery packs, M12-18 FC Charger, Kitbox
Article number	4933479834	4933479833
EAN code	4058546376284	4058546376277

M18 FUEL

M18 FN16GA | M18 FUEL™ 16 GA ANGLED NAIL FINISH NAILER 2-MODE

- Excellent power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Smaller nail hole, the exact size of the nail head leaving a neater finish
- Different shaped noses stored on board allows the user to get the best finish no matter what the application
- Small work contact bracket allows the user to fire and sink nails at a more acute angle
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine
- Fires up to 1200 nails per charge on a REDLITHIUM™ 2.0 Ah battery pack for maximum productivity
- Quick access and easy clearing of jams
- LED work light illuminates the work surface for better placement of nails



	M18 FN16GA-0X	M18 FN16GA-202X
Collation angle [degrees]	20	20
Nail diameter [mm]	1.6	1.6
Nail type (mm)	32 - 64	32 - 64
Magazine capacity nails	110	110
Weight with battery pack (EPTA) (kg)	3.3 (M18 B2)	3.3 (M18 B2)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B2 Battery packs, M12-18 FC Charger, HD Box
Article number	4933478094	4933478093
EAN code	4058546340278	4058546340261

M18 FUEL

M18 FNCS18GS | M18 FUEL™ NARROW CROWN STAPLER 2-MODE

- Excellent power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to fire nail technology eliminates ramp-up time between each staple discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Different designed noses stored on board allows the user to get the best finish no matter what the application
- Dry-fire lockout stops the tool being fired when there are no staples left in the magazine
- Accepts narrow crown staplers from 9.5 mm to 38 mm
- Fires up to 1200 staples per charge on a REDLITHIUM™ 2.0 Ah battery pack for maximum productivity
- LED work light illuminates the work surface for better placement of staples
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FNCS18GS-0X	M18 FNCS18GS-202X
Magazine capacity	108	108
Staple strip length [mm]	9.5 - 38	9.5 - 38
Staple strip width [mm]	6.35	6.35
Cycle rate	900	900
Weight with battery pack (EPTA) (kg)	2.8 (M18 B2)	2.8 (M18 B2)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B2 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933471942	4933471941
EAN Code	4058546298418	4058546298401

M18 FUEL

M18 FN15GA | M18 FUEL™ 15 GA ANGLED NAIL FINISH NAILER 2-MODE

- Excellent power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Smaller nail hole, the exact size of the nail head leaving a neater finish
- Different shaped noses stored on board allows the user to get the best finish no matter what the application
- Small work contact bracket allows the user to fire and sink nails at a more acute angle
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine
- Fires up to 1200 nails per charge on a REDLITHIUM™ 2.0 Ah battery pack for maximum productivity
- Quick access and easy clearing of jams
- LED work light illuminates the work surface for better placement of nails



	M18 FN15GA-0X
Collation angle [degrees]	34
Nail diameter [mm]	1.8
Nail type (mm)	32 - 64
Magazine capacity nails	110
Weight with battery pack (EPTA) (kg)	3.3 (M18 B2)
Kit included	No batteries supplied, No charger supplied, HD Box
Article number	4933478091
EAN code	4058546340247

M18 FUEL

M18 F2VC23L | M18 FUEL™ 23L L-CLASS VACUUM

- The M18 FUEL™ 23 litre L class Wet/Dry Vacuum brings unmatched performance, durability, and versatility to jobsite cleanup.
- With a maximum air flow of 3086 l/min and 192 mbar this provides excellent performance for both wet and dry clean up applications.
- MAX POWER MODE delivers up to 34 minutes of continuous cleaning time (up to 480m²) and up to 49 minutes (up to 545m²) on MAX RUN-TIME MODE per charge on (2) M18™ REDLITHIUM™ HIGH OUTPUT™ 12.0ah Battery Packs.
- The highly efficient HEPA H13 filter collects 99.97 % of airborne particles down to 0.3 microns
- The anti static 2.7m long, crush and twist-resistant hose construction delivers extended hose life.
- On board storage for all attachments including floor clean up kit and powertool attachments
- Robust removable trolley with lockable wheels allows easy transportation and movement around the jobsite
- The DEK 26 power tool connector allows for efficient dust extraction from power tools



	M18 F2VC23L-0
Capacity solids (l)	23
Capacity liquids (l)	23
Hose diameter (mm)	64
Hose length (m)	2.7
Max. vacuum (mbar)	192
Air volume (l/min)	3086
Filter type	HEPA H13
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933478964
EAN code	4058546362461

M18 FUEL

M18 FBPV | M18 FUEL™ BACKPACK VACUUM

- Brushless POWERSTATE™ motor for advanced suction power and longer motor life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Dust class L. Standard MAK-factor > 1 mg/m³
- HEPA filter will collect 99.97% of airborne particles down to 0.3 microns
- DEK 26 compatible allows the vacuum to be easily connected to a powertool
- Low noise of only 76 db (operating sound level)
- Cyclonic technology for longer filter life, extended peak performance and bag-less debris collection
- Integrated hanging hook for ladders and scaffolding
- Removable harness transforms the vacuum into a canister style vacuum
- Supplied with 1 x floor tool, 1 x crevice tool, 1 x telescopic extension wand, 1 x flexible hose, 1 x dust extraction adaptor



M18 FUEL

M18 FBPV-0	
Capacity (l)	3.8
Hose diameter (mm)	36
Max. vacuum (mbar)	189
Air volume (l/min)	1557.43
Filter type	HEPA
Sealed suction [mm]	1905 v H20
Weight with battery pack (EPTA) (kg)	8.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464483
EAN Code	4058546224288

M18 FPOVCL | M18 FUEL™ PACKOUT™ WET/ DRY VACUUM

- The M18 FUEL™ PACKOUT™ wet/ dry vacuum is fully compatible with the MILWAUKEE® PACKOUT™ Modular Storage System
- POWERSTATE™ brushless motor delivers powerful performance to easily clean up common wet and dry jobsite debris
- PACKOUT™ compatibility gives this cordless wet/ dry vac outstanding mobility, saving the time spent hauling tools on and off the jobsite
- Usable on and off the PACKOUT™ stack makes this wet/ dry cleanup solution most portable and versatile
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns
- Delivers up to 30 minutes of run time on a HIGH OUTPUT™ 8.0 Ah battery pack in high mode and over 50 minutes in low mode
- Internal accessory and hose storage allows all attachments to be carried with the tool avoiding loss of equipment
- The DEK 26 power tool connector allows for efficient dust extraction from power tools
- Extendable hose up to 1.6 m for extended reach and versatility
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL

M18 FPOVCL-0	
Capacity solids (l)	9.5
Capacity liquids (l)	7.0
Hose diameter (mm)	41
Hose length (m)	1.5
Max. vacuum (mbar)	117
Air volume (l/min)	1416
Filter type	HEPA
Weight with battery pack (EPTA) (kg)	5.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933478187
EAN Code	4058546341206

M18 VC2 | M18™ WET/ DRY VACUUM

- Powerful 18 V motor with a maximum air flow of 1300 l/min / 80 bar provides excellent suction power for both wet and dry clean up applications
- HEPA filter will collect 99.97% of airborne particles down to 0.03 microns for fine dust collection
- Up to 30 minutes run time with M18™ 9.0 Ah battery pack
- Internal accessory and hose storage allows all attachments to be carried with the tool avoiding loss of equipment
- DEK 26 compatible allows the vacuum to be easily connected to a powertool
- Stackable tool box design for added portability and easier storage
- On board blower for moving debris away from the work area
- Waterproof switch prevents switch damage over the life time of the tool
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

M18 VC2-0	
Capacity solids (l)	9.79
Capacity liquids (l)	7.5
Hose diameter (mm)	41
Hose length (m)	0.47
Max. vacuum (mbar)	80
Air volume (l/min)	1300
Filter type	Wet / Dry
Weight with battery pack (EPTA) (kg)	5.3 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464029
EAN Code	4058546219741

M12 FVCL | M12 FUEL™ WET/ DRY VACUUM

- Powerful M12 FUEL™ motor with a maximum air flow of 1275 l/min & 105 mbar provides 18V performance for both wet and dry clean up applications
- With a 6.0 Ah battery the vacuum provides 14 minutes of run time on high and 26 minutes on the low setting, this compact vacuum is ideal for spot and service focused wet/ dry quick clean up needs
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns
- Internal accessory and hose storage allows all attachments to be carried with the tool avoiding loss of equipment
- The DEK 26 power tool connector allows for efficient dust extraction from power tools
- Stackable tool box design for added portability and easier storage
- Wall mount hanging plate included for increased storage options
- On board blower for moving debris away from the work area
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

M12 FVCL-0	
Capacity solids (l)	5.7
Capacity liquids (l)	6.1
Hose diameter (mm)	41
Hose length (m)	0.5
Max. vacuum (mbar)	105
Air volume (l/min)	1275
Filter type	HEPA
Weight with battery pack (EPTA) (kg)	5.0 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933478186
EAN Code	4058546341190

M18 CV | M18™ HAND VAC

- Excellent suction power for wood, metal and common debris
- HEPA filter will collect 99.97% of airborne particles down to 0.3 microns
- Lock on switch reduces fatigue during sustained use
- Versatile accessories for small or large clean up areas
- Secure canister lock guards against unwanted spillage
- Clear viewing window gives the user the ability to see debris build up
- Up to 23 minutes continuous run time on a 5.0 Ah battery
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

M18 CV-0	
Capacity solids (l)	2.5
Hose diameter (mm)	32
Hose length (m)	1.2
Max. vacuum (mbar)	84.8
Air volume (l/min)	1019.33
Filter type	Dry
Weight with battery pack (EPTA) (kg)	1.9 (M18 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459204
EAN Code	4002395289998

M18 BBL | M18™ BATTERY BLOWER

- Compact body - clears dirt and debris in tight spaces
- Power control - 3 speed settings with variable speed trigger
- Versatile attachments - nozzle extension (228.6 mm), universal inflator/ deflator attachment
- Removable nozzle for easy, convenient storage
- Lock-on switch
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

M18 BBL-0	
Air volume (m³ per minute)	0 - 2.9
Airflow speed (km/h)	0 - 42.8
Fan speed [rpm]	0 - 18,700
Length without nozzle [mm]	375
Weight with battery pack (EPTA) (kg)	1.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933446216
EAN Code	4002395004942

M18 AF | M18™ AIR FAN

- AC/DC, allows the user to run on M18™ REDLITHIUM™ or AC power when available
- Three speed settings for optimised air flow up to 1290 meters per hour
- Efficient air circulation circulates the air within a 3.6 m x 4 m room
- Adjustable head allows the user to utilise the fan in various heights and positions over a range of 120°
- Three hours run time on speed three with a M18™ REDLITHIUM™ 4.0 Ah battery pack
- Compact design with integrated carry handle to maximise portability
- Rubber feet provide stability and no surface scratches
- Fixing points gives the user the option to wall mount the fan if needed
- AC adaptor supplied
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

M18 AF-0	
Airflow speed 1 (m per h)	760
Airflow speed 2 (m³per h)	1000
Airflow speed 3 (m³per h)	1290
Weight with battery pack (EPTA) (kg)	3.4 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933451023
EAN Code	4002395136988

M18 BI | M18™ INFLATOR

- Compact lightweight design for fast inflation of car, light truck and compact equipment tyres. Top off 235/65R16 sprinter tyres in under 1 minute
- Anti-vibration stand with all rubber feet for no movement while inflating
- Top off up to 30 tyres on an M18 5.0 battery pack
- 10.3 max bar capacity
- Auto pressure check feature activates to ensure bar target is achieved
- Automatic shut-off at selected bar prevents over inflation
- Auto shut-off technology inflates to users pre-selected pressure for highly accurate inflation
- Supplied with a ball inflation needle, presta chuck, inflator nozzle and schrader chuck
- 4 bar memory presets and 3 units of measurement
- Illuminated LCD display with a digital pressure and fuel gauge that displays remaining charge
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18

M18 BI-0	
No load air delivery	40
Max. pressure [bar/PSI]	10.3/ 150
Duty Cycle	33% @ 5.5 bar
Hose length [mm]	920
Weight with battery pack (EPTA) (kg)	4.8 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933478706
EAN code	4058546348991

M18 PRCDAB+ | M18™ PACKOUT™ RADIO CHARGER

- Premium 360° surround sound speakers with a 40 W amplifier producing rich and full sound for large and outdoor spaces
- DAB+ and AM/FM tuner with the digital processor delivers highest reception accuracy, signal clarity and additional information like: song, artist and accurate time
- Digital Bluetooth® receiver: Plays music up to 30 m away from your smartphone, computer or tablet
- Compatible with any MILWAUKEE® PACKOUT™ system item
- Built in charger function for quick and convenient charging of any M18™ battery or electric devices via USB port
- IP57 in battery mode - making the radio dust and splashing water resistant
- AC/DC versatility: Powered by MILWAUKEE® M18™ batteries, or mains plug supply
- Full work day run time coverage with M18™ 5.0 Ah battery pack



M18 PRCDAB+-0	
Tuning range AM [kHz]	522 - 1620
Tuning range FM [MHz]	87.5 - 108
Tuning range DAB	174 - 240
Dimensions (mm)	558.8 x 411.5 x 172
Weight with battery pack (EPTA) (kg)	10.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933472113
EAN Code	4058546325091

M18

M18 FPP7A3

M18 FUEL™ POWER PACK

- M18 FPD3 - M18 FUEL™ percussion drill
- M18 FID3 - M18 FUEL™ ¼" Hex impact driver
- M18 FSAG115X - M18 FUEL™ 115 mm angle grinder with slide switch
- M18 FH - M18 FUEL™ 4-mode 26 mm SDS-Plus hammer
- M18 FMT - M18 FUEL™ multi-tool



M18 FPP7A3-503B	
Kit included	3 x M18 B5 Battery packs, M12-18 FC Charger, Tool bag
Article number	4933480878
EAN code	4058546411633

M18 JSR DAB+ | M18™ JOBSITE RADIO DAB+

- High performance audio system - DAB+/FM tuner with digital processor delivers highest reception accuracy and signal clarity
- DAB+ gives best sound quality and additional information like: song, artist and accurate time
- Dual speaker with passive radiators - deliver loud, clear sound with deep, accurate bass
- Customisable equalizer for enhanced sound quality and 10-station preset
- Shock absorbing end caps and metal speaker grills - protect from drops, water and debris on the jobsite
- Integrated handles - allow for easy transport and storage
- Powered by MILWAUKEE® M18™ batteries or AC outlet. Up to 12 hours of run time with an M18™ REDLITHIUM™ 5.0 Ah battery pack
- Weather sealed device compartment protects mobile devices
- Protected 2.1 A USB power outlet - charges electronic devices in both AC and DC mode
- Supplied with auxiliary input cord, 2 x AAA batteries. MILWAUKEE® batteries sold separately



M18 JSR DAB+-0	
Tuning range AM [kHz]	-
Tuning range FM [MHz]	87.5 - 108
Tuning range DAB	174.928 - 239.20
Dimensions (mm)	402 x 197 x 197
Weight with battery pack (EPTA) (kg)	5.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933451252
EAN Code	4002395167777

M18

M18 ONEPP2A2

M18 FUEL™ ONE-KEY™ POWERPACK

- M18 ONEPD2 - M18 FUEL™ ONE-KEY™ percussion drill
- M18 ONEID2 - M18 FUEL™ ONE-KEY™ ¼" Hex impact driver



M18 ONEPP2A2-502X	
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933464530
EAN Code	4058546224752

M18 RC | M18™ JOBSITE RADIO CHARGER WITH BLUETOOTH®

- Built in charger function allows for quick, convenient charging of any M18™ battery or electronic devices via USB port
- Digital Bluetooth® receiver: play music up to 30 m away from your smartphone, computer, or tablet
- AC/DC versatility: powered by MILWAUKEE® M18™ batteries, or 230 V mains supply
- Exclusive AM/FM tuner with digital processor delivers highest reception accuracy and signal clarity
- Premium speaker and 40 W amplifier produce rich, full sound
- Weather sealed auxiliary compartment protects Mp3 players and other audio devices
- Reinforced roll cage and metal handles protects against abusive jobsite conditions
- Customisable equalizer and 10-station preset
- Protected 2.1 Amp USB power outlet charges devices in both AC and DC mode
- Supplied with auxiliary input cord, 2 x AAA batteries. MILWAUKEE® batteries sold separately
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 RC-0	
Dimensions (mm)	300 x 307 x 370
Speaker output (W)	40
Weight with battery pack (EPTA) (kg)	8.4 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933446647
EAN Code	4002395005437

M18

M18 FPP2A3

M18 FUEL™ POWER PACK

- M18 FPD3 - M18 FUEL™ percussion drill
- M18 FID3 - M18 FUEL™ ¼" Hex impact driver



M18 FPP2A3-502X	
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933480876
EAN code	4058546411619

M12-18 JSSP | M12™ - M18™ BLUETOOTH® SPEAKER

- Advanced technology Bluetooth® jobsite speaker
- Bluetooth® wireless range of up to 30 m
- Flexible battery system: works with all MILWAUKEE® M12™ & M18™ batteries
- IP54 rated, water and debris resistant to withstand tough conditions on and off the jobsite
- Loud, clear sounds at all volumes
- 2.1A USB charger, charges phones, tablets and media players
- Premium speaker with bass port



M12-18 JSSP-0	
Dimensions (mm)	360 x 165 x 165
Speaker output (W)	40
Weight with battery pack (EPTA) (kg)	2.5 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459275
EAN Code	4058546002411

M12 M18

M18 BLPP2A2

M18™ BRUSHLESS POWERPACK

- M18 BLPD2 - M18™ brushless percussion drill
- M18 BLID2 - M18™ brushless ¼" Hex impact driver



M18 BLPP2A2-502X	
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933464523
EAN Code	4058546224684

M18

M12

**UPGRADE.
OUTWORK.
OUTLAST.**



**ONE SYSTEM
OVER
110
TOOLS**

**PORTABLE PRODUCTIVITY.
TRADE FOCUSED.
SYSTEM WIDE.**

ONE KEY
UNLOCKING THE DIGITAL JOBSITE.



M12 FUEL



**VIEW THE
FULL RANGE**



**VIEW M12™ ON OUR
YOUTUBE CHANNEL**

REDLITHIUM™

DRIVEN TO OUTPERFORM.™

M12 FUEL™ is engineered for the most demanding tradesmen in the world. M12 FUEL™ delivers extreme performance in a compact structure and features three MILWAUKEE® exclusive innovations - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - that deliver incredible power, run time and durability.

Simply put, M12 FUEL™ offers the best, full circle technology that drives, protects and powers your cordless tools.


NEW
MORE CAPABLE*

LIGHT WEIGHT*

MORE COMPACT*

1 POWERSTATE™ BRUSHLESS MOTOR

- Milwaukee Tool designed and built brushless motor
- Provides increased efficiency
- Lasts longer and delivers maximum power*



M12 FUEL™

DRIVEN TO OUTPERFORM.™



2 REDLINK PLUS™ INTELLIGENCE


- Individual cell monitoring to optimise tool run time and ensure long term pack durability
- Advanced system electronics with unique digital performance enhancement
- Total system communication with overload protection increases tool life

3 REDLITHIUM™ BATTERY PACKS

- Total system communication with overload protection increases tool life
- Fade-free performance to deliver more run time and more work over pack life
- Fuel gauge displays remaining charge
- Operates down to -20°C



REDLITHIUM™





M12 CH

M12 FUEL™ SUB COMPACT SDS-PLUS HAMMER

- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 - 6575 bpm & 0 - 900 rpm
- Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day
- Will drill over 60 50 mm x 6 mm holes per battery charge
- Superior power to weight ratio in its class with brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more run time
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility
- Optimised hammer drilling up to 6 - 10 mm (max 13 mm)
- 43 mm neck size - compatible with M12 DE dust extractor
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 CH-0	M12 CH-602X
Tool reception	SDS-Plus	SDS-Plus
Blow energy [EPTA][J]	1.1	1.1
No load speed (rpm)	0 - 900	0 - 900
Full load hammer action (bpm)	0 - 6575	0 - 6575
Max. drilling wood (mm)	13	13
Max. drilling steel (mm)	10	10
Max. drilling concrete (mm)	13	13
Vibration drilling (m/s ²)	4.4	4.4
Weight with battery pack (EPTA) (kg)	1.9 (M12 B4)	1.9 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B6 Battery packs, C12 C Charger, HD Box
Article Number	4933441947	4933451907
EAN Code	4002395002719	4002395282166

PERFECT MATCH

SET OF 5 SDS-PLUS DRILL BITS, Ø 5 / 6 X 110 MM AND Ø 6 / 8 / 10 X 160 MM

Article Number 4932352338



M12 FUEL

M12 FPD2 | M12 FUEL™ SUB COMPACT PERCUSSION DRILL

- Extremely compact design of 152 mm length for access into tight spaces
- 45 Nm of torque - superior power to size ratio
- 13 mm heavy duty metal chuck for quick bit changes and bit retention
- Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer
- On board fuel gauge, metal belt clip and LED light
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FPD2-602X
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1,550
Chuck capacity (mm)	13
Max. drilling wood (mm)	35
Max. drilling steel (mm)	13
Max. drilling masonry (mm)	13
Max. percussion rate (bpm)	0 - 22,500
Max. torque (Nm)	45
Weight with battery pack (EPTA) (kg)	1.4 (M12 B6)
Kit included	2 x M12 B6 Battery packs, C12 C Charger, HD Box
Article number	4933479871
EAN code	4058546376659

M12 FDD2 | M12 FUEL™ SUB COMPACT DRILL DRIVER

- Extremely compact design of 151 mm length for access into tight spaces
- 45 Nm of torque - superior power to size ratio
- 13 mm heavy duty metal chuck for quick bit changes and bit retention
- Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer
- On board fuel gauge, metal belt clip and LED light
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FDD2-602X
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1,550
Chuck capacity (mm)	13
Max. drilling wood (mm)	35
Max. drilling steel (mm)	13
Max. torque (Nm)	45
Weight with battery pack (EPTA) (kg)	1.4 (M12 B6)
Kit included	2 x M12 B6 Battery packs, C12 C Charger, HD Box
Article number	4933479970
EAN code	4058546377649

M12 H | M12™ SUB COMPACT SDS-PLUS HAMMER

- Ergonomically designed, compact and light weight allows for work in tight spaces and reduces fatigue during all day use
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- L-shape, 2 mode hammer drill for hammer & rotary drilling for maximum versatility
- Low vibration at 6.7 m/s²
- Optimised hammer drilling up to 4 - 8 mm (max 13 mm)
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 H-0	M12 H-402C
Tool reception	SDS-Plus	SDS-Plus
Blow energy [EPTA][J]	0.9	0.9
No load speed (rpm)	0 - 800	0 - 800
Full load hammer action (bpm)	0 - 5350	0 - 5350
Max. drilling wood (mm)	10	10
Max. drilling steel (mm)	8	8
Max. drilling concrete (mm)	13	13
Vibration drilling (m/s ²)	6.7	6.7
Weight with battery pack (EPTA) (kg)	1.8 (M12 B4)	1.8 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B4 Battery packs, C12 C Charger, Kitbox
Article Number	4933431355	4933443161
EAN Code	4002395243679	4002395003389

M12

M12 FDDX | M12 FUEL™ INSTALLATION DRILL/DRIVER WITH INTERCHANGEABLE HEADS

- High performance compact 4-in-1 installation drill for extreme versatility
- Removable chuck system with 4 different heads for multiples of applications
- ¼" hex drive behind chuck fitting, reduces drill length to 130 mm when required
- In-line grip for unrivaled access and control
- Brushless POWERSTATE™ motor delivers up to 34 Nm of torque
- Magnetic holder for easy bit access
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FDDXKIT-202X
No load speed gear 1 (rpm)	0 - 400
No load speed gear 2 (rpm)	0 - 1600
Chuck capacity (mm)	10
Max. drilling wood (mm)	28
Max. drilling steel (mm)	10
Max. torque (Nm)	34
Weight with battery pack (EPTA) (kg)	0.90 (M12 B2)
Standard equipment	10 mm metal chuck, right angle attachment, offset attachment and 6mm hex attachment
Kit included	2 x M12 B2 Battery packs, C12 C Charger, HD Box
Article Number	4933464980
EAN Code	4058546229252

M12 UDEL | M12™ UNIVERSAL DUST EXTRACTOR

- Fits all MILWAUKEE® SDS-plus and the majority of competitor's hammers between 41-61 mm neck size with just one adjustable side handle which can be mounted right or left of the hammer
- Delivering more than 40 min run time on a single M12 B2 2.0 Ah battery
- Due to telescopic nozzle capable of operating with up to 210 mm long SDS-plus drill bits
- Adjustable drilling depth gauge for a perfect adjustment to the task
- 2 exchangeable nozzles with brushes to cover drilling diameters up to Ø30 mm (Ø5-16 mm, Ø16-30 mm)
- 2 different vacuum modes to switch the unit either permanently on or activate it automatically when the actual drilling starts
- Automatic 5 sec switch off time delay to ensure a clean drill hole
- Equipped with a HEPA H13 class filter as well as a filter cleaning mechanism for best performance and a longer filter life time
- Equipped with a transparent tank for full capacity visibility as well as a Ø32 mm vacuum connector to empty the dust bin without any dust exposure
- Fuel gauge displays remaining charge



	M12 UDEL-0B	M12 UDEL-2018
Max. drill bit diameter [mm]	30	30
Max. drilling depth [mm]	203	203
Air volume [l/min]	466	466
Airflow speed [m per h]	28	28
Capacity liquids [l]	0.31	0.31
Capacity solids [l]	0.31	0.31
Filter type	HEPA H13	HEPA H13
Max. vacuum (mbar)	23.4	23.4
Weight with battery pack (EPTA) (kg)	2.2 (M12 B2)	2.2 (M12 B2)
Kit included	No batteries supplied, No charger supplied, Tool bag	1 x M12 B2 Battery pack, C12 C Charger, Tool bag
Article Number	4933471460	4933471462
EAN Code	4058546290887	4058546299132

M12

M12 FPDX | M12 FUEL™ SUB COMPACT PERCUSSION DRILL WITH REMOVABLE CHUCK

- High performance compact 6-in-1 percussive drill system for extreme versatility
- Removable chuck system with 3 different heads for multiples of applications
- Brushless POWERSTATE™ motor delivers up to 44 Nm of torque
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 13 mm keyless chuck, full metal right angle ¼" hex drive head and full metal offset ¼" hex drive head
- ¼" hex drive behind chuck fitting, reduces drill length to 138 mm when required
- Full metal planetary gearbox transmission for extreme durability
- LED light for workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FPDXKIT-602X
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1700
Chuck capacity (mm)	13
Max. drilling wood (mm)	35
Max. drilling steel (mm)	13
Max. drilling masonry (mm)	13
Max. percussion rate (bpm)	0 - 25,500
Max. torque (Nm)	37
Weight with battery pack (EPTA) (kg)	1.5 (M12 B6)
Standard equipment	Removable chuck, offset attachment, right angle attachment
Kit included	2 x M12 B6 Battery packs, C12 C Charger, HD Box
Article Number	4933464189
EAN Code	4058546221348

M12 FUEL

M12 BDDX | M12™ SUB COMPACT DRILL DRIVER WITH REMOVABLE CHUCK

- High performance sub compact 5-in-1 drill driver system for extreme versatility
- Removable chuck system with 3 different heads for multiples of applications
- Standard 10 mm keyless chuck, full metal right angle 1/4" hex drive head and full metal offset 1/4" hex drive head
- 1/4" hex drive behind chuck fitting, reduces drill length to 153 mm when required
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal planetary gearbox transmission for extreme durability
- LED light for workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 BDDXKIT-202C	
Battery pack capacity (Ah)	2.0
No. of batteries supplied	2
Charger supplied	40 min
No load speed gear 1 (rpm)	0 - 400
No load speed gear 2 (rpm)	0 -1500
Chuck capacity (mm)	10
Max. drilling wood (mm)	25
Max. drilling steel (mm)	10
Max. torque (Nm)	32
Weight with battery pack (EPTA) (kg)	1.2 (M12 B2)
Removable FIXTEC chuck, offset attachment, right angle drill attachment, belt clip, 25 mm P22 bit	
Standard equipment	
Supplied in	Kitbox
Article Number	4933447773
EAN Code	4002395006625

M12 BPD | M12™ SUB COMPACT PERCUSSION DRILL

- High performance sub compact percussion drill measures 190 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 10 mm metal chuck for quick bit changes and bit retention
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 BPD-202C	
No load speed gear 1 (rpm)	0 - 400
No load speed gear 2 (rpm)	0 - 1500
Chuck capacity (mm)	10
Max. drilling wood (mm)	22
Max. drilling steel (mm)	10
Max. drilling masonry (mm)	10
Max. percussion rate (bpm)	22,500
Max. torque (Nm)	30
Weight with battery pack (EPTA) (kg)	1.2 (M12 B2)
2 x M12 B2 Battery packs, C12 C Charger, Kitbox	
Article Number	4933443889
EAN Code	4002395004232

M12 BDD | M12™ SUB COMPACT DRILL DRIVER

- High performance sub compact drill driver measures 189 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 10 mm metal chuck for quick bit changes and bit retention
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 BDD-202C	
No load speed gear 1 (rpm)	0 - 400
No load speed gear 2 (rpm)	0 - 1500
Chuck capacity (mm)	10
Max. drilling wood (mm)	22
Max. drilling steel (mm)	10
Max. torque (Nm)	30
Weight with battery pack (EPTA) (kg)	1.2 (M12 B2)
2 x M12 B2 Battery packs, C12 C Charger, Kitbox	
Article Number	4933443891
EAN Code	4002395004225

C12 RAD | M12™ SUB COMPACT RIGHT ANGLE DRILL

- Heavy Duty full metal gearbox and gears for superior durability and maximum torque
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed paddle switch trigger for comfortable working in any situation
- 10 mm chuck for quick bit changes and bit retention
- Electronic clutch with indicator light for complete control
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	C12 RAD-0	C12 RAD-202B
No load speed (rpm)	0 - 800	0 - 800
Chuck capacity (mm)	10	10
Max. drilling wood (mm)	22	22
Max. drilling steel (mm)	10	10
Max. torque (Nm)	12	12
Weight with battery pack (EPTA) (kg)	1.1 (M12 B2)	1.1 (M12 B2)
No batteries supplied, 2 x M12 B2 Battery		
No charger supplied, No packs, C12 C Charger, kitbox or bag supplied Tool bag		
Article Number	4933416900	4933441218
EAN Code	4002395237678	4002395001804

M12 CD | M12 FUEL™ SUB COMPACT DRIVER

- Brushless POWERSTATE™ motor for up to 10x longer motor life, up to 2x more power and up to 2x more run time
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 1/4" Hex chuck for quick easy one handed bit change
- Fuel gauge displays remaining charge
- Bright LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 CD-202C	
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1700
Tool reception	1/4" Hex
Max. drilling wood (mm)	25
Max. drilling steel (mm)	10
Max. torque (Nm)	37
Weight with battery pack (EPTA) (kg)	1.2 (M12 B2)
2 x M12 B2 Battery packs, C12 C Charger, Kitbox	
Article Number	4933440568
EAN Code	4002395001026

M12 BD | M12™ SUB COMPACT DRIVER

- High performance sub compact screw driver measures 175 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 1/4" Hex chuck for quick easy one handed bit change
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 BD-202C	
No load speed gear 1 (rpm)	0 - 400
No load speed gear 2 (rpm)	0 - 1500
Tool reception	1/4" Hex
Max. drilling wood (mm)	22
Max. drilling steel (mm)	10
Wood screws to (mm)	6
Max. torque (Nm)	30
Weight with battery pack (EPTA) (kg)	1.0 (M12 B2)
2 x M12 B2 Battery packs, C12 C Charger, Kitbox	
Article Number	4933443885
EAN Code	4002395004171

M12 FID2 | M12 FUEL™ SUB COMPACT 1/4" IMPACT DRIVER

- The compact design with a length of only 127 mm is ideal for working in confined spaces
- Outstanding power to size ratio with 170 Nm of torque
- Fast driving speed with up to 3,600 rpm and 4,000 ipm
- Tri-LEDs deliver high definition lighting to increase workspace visibility
- 4-Mode DRIVE CONTROL allows the user to shift to three different speed and torque settings, as well as a self-tapping mode to maximise application versatility
- 1/4" Hex chuck for quick and easy bit change
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FID2-0	M12 FID2-602X
No load speed (rpm)	0 - 1,700/ 0 - 2,900/ 0 - 3,600/ 0 - 3,600	0 - 1,700/ 0 - 2,900/ 0 - 3,600/ 0 - 3,600
Impact rate (ipm)	0 - 4,000	0 - 4,000
Max. torque (Nm)	170	170
Weight with battery pack (EPTA) (kg)	1.1 (M12 B6)	1.1 (M12 B6)
No batteries supplied, 2 x M12 B6 Battery		
No charger supplied, No packs, C12 C Charger, kitbox or bag supplied HD Box		
Article number	4933479876	4933479878
EAN code	4058546376703	4058546376727

M12 FQID | M12 FUEL™ SURGE™ 1/4" HEX HYDRAULIC IMPACT DRIVER

- The M12 FUEL™ SURGE™ 1/4" Hex hydraulic impact driver is Milwaukee Tool's quietest 12V impact driver, delivers best in class sound at only 76 dB(A) in wood fastening applications
- FLUID-DRIVE™ hydraulic powertrain reduces metal on metal contact within the tool, delivering quieter operation, smoother performance and increased durability over a standard impact
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- POWERSTATE™ brushless motor delivers up to 0 - 3.200 rpm with constant power output to drive screws faster
- REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 1/4" Hex chuck for quick and easy bit change
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FQID-0	M12 FQID-202X
No load speed (rpm)	1100/2200/3200/3200	1100/2200/3200/3200
Tool reception	1/4" Hex	1/4" Hex
Impact rate (ipm)	950/2200/3400/3400	950/2200/3400/3400
Max. torque (Nm)	50	50
Weight with battery pack (EPTA) (kg)	1.1 (M12 B2)	1.1 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B2 Battery packs, C12 C Charger, HD Box
Article Number	4933464972	4933464974
EAN Code	4058546229177	4058546229191

M12 BID | M12™ SUB COMPACT 1/4" HEX IMPACT DRIVER

- High performance sub compact impact driver measures 165 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 1/4" Hex chuck for quick and easy bit change
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 BID-0	M12 BID-202C
No load speed (rpm)	0 - 2500	0 - 2500
Impact rate (ipm)	0 - 3300	0 - 3300
Tool reception	1/4" Hex	1/4" Hex
Max. torque (Nm)	112	112
Weight with battery pack (EPTA) (kg)	1.0 (M12 B2)	1.0 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B2 Battery packs, C12 C Charger, Kitbox
Article Number	4933441955	4933443895
EAN Code	4002395002689	4002395004201

M12 BRAID | M12™ SUB COMPACT RIGHT ANGLE IMPACT DRIVER

- Compact right angle impact driver measures 287 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics delivers best in class system durability
- Full metal gearbox and gears for superior durability and maximum torque of 68 Nm
- Compact head design with diameter of 35.6 mm
- Multi-handle design for multiple hand positions and maximum comfort
- 1/4" Hex chuck for quick easy one handed bit change
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 BRAID-0
No load speed (rpm)	0 - 2425
Impact rate (ipm)	0 - 3300
Tool reception	1/4" Hex
Max. torque (Nm)	68
Weight with battery pack (EPTA) (kg)	1.2 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933451247
EAN Code	4002395167715

M12 FIW38 | M12 FUEL™ SUB COMPACT 3/8" IMPACT WRENCH

- More power, more compact, more control
- Up to 339 Nm of maximum torque
- 3/8" anvil with friction ring for quick and easy socket changes
- Brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Better access in tight spaces with an overall length of only 121.9 mm
- 4-Mode DRIVE CONTROL with auto-shut off mode, offers the user precise control
- Bright LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FIW38-0	M12 FIW38-622X
No load speed (rpm)	1200/1800/2700/2700	1200/1800/2700/2700
Tool reception	3/8" square	3/8" square
Impact rate (ipm)	1100/2100/3200	1100/2100/3200
Max. torque (Nm)	339	339
Max. bolt diameter	M16	M16
Weight with battery pack (EPTA) (kg)	1.1 (M12 B2)	1.1 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B6, 1 x M12 B2 Battery packs, C12 C Charger, HD Box
Article Number	4933464612	4933464614
EAN Code	4058546225575	4058546225599

M12 FIWF12 | M12 FUEL™ SUB COMPACT 1/2" IMPACT WRENCH

- More power, more compact, more control
- Up to 339Nm of maximum torque
- 1/2" anvil with friction ring for quick and easy socket changes
- Brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Better access in tight spaces with an overall length of only 124.5 mm
- 4-Mode DRIVE CONTROL with auto-shut off mode, offers the user precise control
- Bright LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FIWF12-0	M12 FIWF12-622X
No load speed (rpm)	1200/1800/2700/2700	1200/1800/2700/2700
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	1100/2100/3200	1100/2100/3200
Max. torque (Nm)	339	339
Max. bolt diameter	M16	M16
Weight with battery pack (EPTA) (kg)	1.1 (M12 B4)	1.1 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B6, 1 x M12 B2 Battery packs, C12 C Charger, HD Box
Article Number	4933464615	4933464617
EAN Code	4058546225605	4058546225629

PERFECT MATCH 1/2" SHOCKWAVE™ IMPACT DUTY SOCKET SET STD (13PC)	
Article Number	4932480456



M12 FIW14 | M12 FUEL™ SUB COMPACT 1/4" IMPACT WRENCH

- More power, more compact, more control
- Up to 115 Nm of maximum fastening torque
- Up to 136 Nm of maximum nut busting torque
- 1/4" anvil with friction ring for quick and easy socket changes
- Brushless POWERSTATE™ motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Better access in tight spaces with an overall length of only 129.5 mm
- 4-Mode DRIVE CONTROL with auto-shut off mode, offers the user precise control
- Bright LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FIW14-0
No load speed (rpm)	1300/1900/3200/3200
Tool reception	1/4" square
Impact rate (ipm)	1300/2000/4300
Max. torque (Nm)	136
Max. bolt diameter	M12
Weight with battery pack (EPTA) (kg)	0.90 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464611
EAN Code	4058546225568

M12 BIW12 | M12™ SUB COMPACT 1/2" IMPACT WRENCH

- High performance sub compact impact wrench measures 171 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 1/2" square drive with pin detent for use with universal sockets
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 BIW12-0	M12 BIW12-202C
No load speed (rpm)	0 - 2550	0 - 2550
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	0 - 3400	0 - 3400
Max. torque (Nm)	138	138
Weight with battery pack (EPTA) (kg)	1.0 (M12 B2)	1.0 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B2 Battery packs, C12 C Charger, Kitbox
Article Number	4933447134	4933447187
EAN Code	4002395006014	4002395006076



M12 BIW38 | M12™ SUB COMPACT 3/8" IMPACT WRENCH

- High performance sub compact impact wrench measures 165 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- 3/8" square drive with friction ring for use with universal sockets
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 BIW38-0	M12 BIW38-202C
No load speed (rpm)	0 - 2500	0 - 2500
Tool reception	3/8" square	3/8" square
Impact rate (ipm)	0 - 3300	0 - 3300
Max. torque (Nm)	135	135
Weight with battery pack (EPTA) (kg)	1.0 (M12 B2)	1.0 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No packs, C12 C Charger, kitbox or bag supplied	2 x M12 B2 Battery Kitbox
Article Number	4933441985	4933443899
EAN Code	4002395002603	4002395004188

M12 FRAIWF38 | M12 FUEL™ 3/8" RIGHT ANGLE IMPACT WRENCH WITH FRICTION RING

- Delivers up to 270 Nm fastening torque and 300 Nm nut-busting torque
- 4-Mode DRIVE CONTROL includes Auto Shut-Off Mode and Bolt Removal Mode which prevents over-tightening and provides more control after bolt breakaway
- The long body profile allows for more access in hard to reach spaces
- Only 71 mm head profile design allows for more access in tight spaces
- 3/8" anvil with friction ring for quick and easy socket changes
- Bright LED workspace illumination
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FRAIWF38-0	M12 FRAIWF38-622X
No load speed (rpm)	0-1550/ 0-2300/ 0-3000/ 0-3000	0-1550/ 0-2300/ 0-3000/ 0-3000
Tool reception	3/8" square	3/8" square
Impact rate (ipm)	0-1350/ 0-2700/ 0-3600	0-1350/ 0-2700/ 0-3600
Max. torque (Nm)	270	270
Max. bolt diameter	M16	M16
Weight with battery pack (EPTA) (kg)	1.7 (M12 B4)	1.7 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B6, 1 x M12 B2 Battery packs, C12 C Charger, HD Box
Article Number	4933471700	4933478808
EAN Code	4058546295998	4058546360900

M12 BPRT | M12™ SUB COMPACT RIVET TOOL

- Up to 325 x 4.8 mm stainless steel rivets on a single charge with a 2.0 Ah battery pack
- Suitable for all aluminium, steel, stainless steel and copper rivets up to 4.8 mm
- Rivets in one stroke with a 20.32 mm stroke length
- Retention nose pieces hold rivets in any orientation
- Tool-free access to easily clean jaws. On-board nose piece storage and removal tool for user convenience
- On board fuel gauge and LED light for added user convenience and illumination in low lit working conditions
- Ergonomic design with 273 mm H x 66.8 mm W x 165 mm in length without mandrel collector
- Integrated belt hook and lanyard tie off point
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Supplied with 4 x retaining tips



	M12 BPRT-0	M12 BPRT-201X
Max. pulling force [N]	9000	9000
Max. rivets popped with M12 B2 battery	325 x 4.8	325 x 4.8
Rivet diameter range [mm]	2.4 - 4.8	2.4 - 4.8
Stroke length [mm]	20.32	20.32
Dimensions [mm]	273 x 66 x 8 x 230	273 x 66 x 8 x 230
Weight with battery pack (EPTA) (kg)	2.1 (M12 B2)	2.1 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B2 Battery pack, C12 C Charger, HD Box
Article Number	4933464404	4933464406
EAN Code	4058546223496	4058546223519

M12 ONEFTR12 | M12 FUEL™ ONE-KEY™ 1/2" DIGITAL TORQUE WRENCH

- Milwaukee Tool's first digital torque wrench, delivers up to 50% faster installation by replacing the hand tool
- Provides 16.9 - 203.4 Nm of torque range and accuracy within ±2% for torque critical fasteners
- Faster, more productive torque reporting with ONE-KEY™ providing torque data and customisable reports for inspectors or owners
- Adjustable run-down torque to control the tools output torque via the motor to prevent over torque
- Four measurement modes (ft-lb, in-lb, Nm, Kg-cm) and 15 available presets
- Durable design to withstand the most demanding jobsite environments
- Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory)
- Six pre-programmed languages including English, Spanish and French
- Two-step fastening process: Pull the trigger until tool stops prior to target torque value, then finish by hand to reach target torque.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 ONEFTR12-0C	M12 ONEFTR12-201C
Torque range [Nm]	16.9 - 203.4	16.9 - 203.4
Accuracy	CW ±2 %, CCW ±3%	CW ±2 %, CCW ±3%
Tool reception	1/2" square	1/2" square
No load speed (rpm)	0 - 100	0 - 100
Weight with battery pack (EPTA) (kg)	2.6 (M12 B2)	2.6 (M12 B2)
Kit included	No batteries supplied, No 1 x M12 B2 Battery pack, charger supplied, Kitbox	C12 C Charger, Kitbox
Article Number	4933464969	4933464970
EAN Code	4058546229146	4058546229160

PERFECT MATCH

1/2" SHOCKWAVE™ IMPACT DUTY DEEP SOCKET SET (10PC)

Article Number **4932480457**

M12 FRAIWF12 | M12 FUEL™ 1/2" RIGHT ANGLE IMPACT WRENCH WITH FRICTION RING

- Delivers up to 270 Nm fastening torque and 300 Nm nut-busting torque
- 4-Mode DRIVE CONTROL includes Auto Shut-Off Mode and Bolt Removal Mode which prevents over-tightening and provides more control after bolt breakaway
- The long body profile allows for more access in hard to reach spaces
- Only 71 mm head with anvil profile design allows for more access in tight spaces
- 1/2" anvil with friction ring for quick and easy socket changes
- Bright LED workspace illumination
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FRAIWF12-0	M12 FRAIWF12-622X
No load speed (rpm)	0-1150/ 0-2300/ 0-3000/ 0-3000	0-1150/ 0-2300/ 0-3000/ 0-3000
Tool reception	1/2" square	1/2" square
Impact rate (ipm)	0-1350/ 0-2700/ 0-3600	0-1350/ 0-2700/ 0-3600
Max. torque (Nm)	270	270
Max. bolt diameter	M16	M16
Weight with battery pack (EPTA) (kg)	1.7 (M12 B4)	1.7 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B6, 1 x M12 B2 Battery packs, C12 C Charger,
Article Number	4933471699	4933478807
EAN Code	4058546295981	4058546360894

M12 ONEFTR38 | M12 FUEL™ ONE-KEY™ 3/8" DIGITAL TORQUE WRENCH

- Milwaukee Tool's first digital torque wrench, delivers up to 50% faster installation by replacing the hand tool
- Provides 13.6 - 135.6 Nm of torque range and accuracy within ±2% for torque critical fasteners
- Faster, more productive torque reporting with ONE-KEY™ providing torque data and customisable reports for inspectors or owners
- Adjustable run-down torque to control the tools output torque via the motor to prevent over torque
- Four measurement modes (ft-lb, in-lb, Nm, Kg-cm)
- Durable design to withstand the most demanding jobsite environments
- Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory)
- Six pre-programmed languages including English, Spanish and French
- Two-step fastening process: Pull the trigger until tool stops prior to target torque value, then finish by hand to reach target torque.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 ONEFTR38-0C	M12 ONEFTR38-201C
Torque range [Nm]	13.6 - 135.6	13.6 - 135.6
Accuracy	CW ±2 %, CCW ±3%	CW ±2 %, CCW ±3%
Tool reception	3/8" square	3/8" square
No load speed (rpm)	0 - 100	0 - 100
Weight with battery pack (EPTA) (kg)	2.5 (M12 B2)	2.5 (M12 B2)
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M12 B2 Battery pack, C12 C Charger, Kitbox
Article Number	4933464966	4933464968
EAN Code	4058546229115	4058546229139

GET THE RIGHT
RATCHET
FOR THE JOB

**RIGHT ANGLE
IMPACT WRENCH**

MAXIMUM ACCESS WITH ULTIMATE CONTROL
IN HARD TO REACH APPLICATIONS



M12 FRAIWF38-0
3/8" square

PRECISION TOOLS

DELIVERING INCREASED PRODUCTIVITY,
PRECISE TORQUE ACCURACY, AND USER
DEMANDED REPORTING FUNCTIONALITY



M12 ONEFTR12-201C
1/2" square

M12 FUEL

16.9–203.4 Nm



M12 ONEFTR12-201C
1/2" square

M12 FUEL

13.6–135.6 Nm



M12 ONEFTR38-201C
3/8" square

LONG REACH

SLIM HEAD PROFILE AND AN EXTENDED
REACH THAT GIVES YOU THE LONGEST
REACH IN TIGHT SPACES



M12 FIR38LR-0
3/8" square

M12 FUEL

82 mm
extension



M12 FIR38LR-0
3/8" square

M12 FUEL

82 mm
extension



M12 FHIR14LR-0
3/8" square

M12 FUEL

82 mm
extension



M12 FHIR38LR-0
3/8" square

HIGH SPEED

FASTER SPEED WHILE INSTALLING AND
REMOVING FASTENERS



M12 FHIR14-0
1/4" square

M12 FUEL

0–450 rpm



M12 FHIR14-0
1/4" square

M12 FUEL

0–450 rpm



M12 FHIR38-201B
3/8" square

COMPACT

PERFECT MIX OF SIZE AND POWER TO GET
INTO THOSE TIGHT AREAS



M12 IR-201B 1/4
1/4" square

M12

40 Nm



M12 IR-201B 1/4
1/4" square

M12

47 Nm



M12 IR-201B 3/8
3/8" square

M12 FUEL

75 Nm



M12 FIR38-201B
3/8" square

M12 FUEL

81 Nm



M12 FIR12-0
1/2" square



Scan here to view
our PPE range



Scan here to view
compatible
impact sockets



M12 FHIR14LR | M12 FUEL™ 1/4" EXTENDED REACH HIGH SPEED RATCHET

- With up to 47 Nm of max torque and 450 rpm's, this tool delivers faster application speed and increased productivity for the professional user
- 19 mm low profile head design and extended neck allow users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and investment cast steel yoke housing provides greater durability for the professional user
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

M12 FHIR14LR-0	
Tool reception	1/4" square
Max. torque (Nm)	47
No load speed (rpm)	0 - 450
Length (mm)	348
Weight with battery pack (EPTA) (kg)	1.1 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933480790
EAN code	4058546410759

M12 FHIR38LR | M12 FUEL™ 3/8" EXTENDED REACH HIGH SPEED RATCHET

- With up to 47 Nm of max torque and 450 rpm's, this tool delivers faster application speed and increased productivity for the professional user
- 19 mm low profile head design and extended neck allow users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and investment cast steel yoke housing provides greater durability for the professional user
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

M12 FHIR38LR-0	
Tool reception	3/8" square
Max. torque (Nm)	47
No load speed (rpm)	0 - 450
Length (mm)	363
Weight with battery pack (EPTA) (kg)	1.1 (M12 B2)
Article number	4933480791
EAN code	4058546410766

M12 FIR38LR | M12 FUEL™ 3/8" EXTENDED REACH RATCHET

- With up to 75 Nm of max torque and 200 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- The industry leading FUEL™ technology combined with a reinforced mechanism and investment cast steel yoke housing provides greater durability for the professional user
- Extended reach ratchet adding additional 82 mm of length for access into tight spaces
- Variable speed trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Supplied with 1/4" adaptor



M12 FUEL

M12 FIR38LR-0	
Tool reception	3/8" square
Max. torque (Nm)	75
No load speed (rpm)	0 - 200
Length (mm)	363
Weight with battery pack (EPTA) (kg)	1.4 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471500
EAN Code	4058546293994

M12 FHIR14 | M12 FUEL™ 1/4" HIGH SPEED RATCHET

- With up to 47 Nm of max torque and 450 rpm's, this tool delivers faster application speed and increased productivity for the professional user
- 19 mm low profile head design allows users better access in tight spaces
- Variable speed metal trigger provides ultimate control of the tool
- The industry leading FUEL™ technology combined with a reinforced mechanism for greater durability
- Rubber overmold withstands most corrosive materials and provides increased comfort
- On board fuel gauge and LED light
- Fastening and removing of 210 M8 bolts with one battery charge M12 B2 for all day work
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

M12 FHIR14-0	
Tool reception	1/4" square
Max. torque (Nm)	47
No load speed (rpm)	0 - 450
Length (mm)	272
Weight with battery pack (EPTA) (kg)	1.0 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933478171
EAN Code	4058546341046

M12 FHIR38 | M12 FUEL™ 3/8" HIGH SPEED RATCHET

- With up to 47 Nm of max torque and 450 rpm's, this tool delivers faster application speed and increased productivity for the professional user
- 19 mm low profile head design allows users better access in tight spaces
- Variable speed metal trigger provides ultimate control of the tool
- The industry leading FUEL™ technology combined with a reinforced mechanism for greater durability
- Rubber overmold withstands most corrosive materials and provides increased comfort
- On board fuel gauge and LED light
- Fastening and removing of 210 M8 bolts with one battery charge M12B2 for all day work
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FHIR38-0	M12 FHIR38-201B
Tool reception	3/8" square	3/8" square
Max. torque (Nm)	47	47
No load speed (rpm)	0 - 450	0 - 450
Length (mm)	272	272
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B2 Battery pack, C12 C Charger, Bag
Article Number	4933478172	4933478809
EAN Code	4058546341053	4058546360917

M12 GG | M12™ SUB COMPACT GREASE GUN

- Powerful 12 V motor delivers over 562 bar max operating pressure
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Extreme long run time - dispenses up to 7 cartridges per charge
- Strong handle balance and ergonomics - only 355 mm long and 3.2 kg
- Air bleeder valve - priming mechanism for quick flow
- Integrated hose storage & shoulder strap loop - added user convenience and reducing down time
- Three way loading - bulk, cartridge and suction capable
- Grease capacity 400 ml cartridge, 473 ml bulk
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Supplied with 914 mm x 14.4 mm high pressure flex hose with spring guard and grease coupler



	M12 GG-0
Pressure (bar)	562
Weight with battery pack (EPTA) (kg)	3.2 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933440435
EAN Code	4002395000951

M12 FIR12 | M12 FUEL™ SUB COMPACT 1/2" RATCHET

- With up to 81 Nm of max torque and 175 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- Low profile head design allows users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and investment cast steel yoke housing provides greater durability for the professional user
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- Supplied with 3/8" adaptor
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FIR12-0
Tool reception	1/2" square
Max. torque (Nm)	81
No load speed (rpm)	0 - 175
Length (mm)	290
Weight with battery pack (EPTA) (kg)	1.5 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459800
EAN Code	4058546029722

M12 PCG/600 | M12™ SUB COMPACT CAULK GUN WITH 600 ML TUBE

- Up to 1780 N of force
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all construction adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 PCG/600A-201B
Max. pushing force (N)	1780
Speed settings	6
Standard equipment	600 ml alum. tube
Weight with battery pack (EPTA) (kg)	1.9 (M12 B2)
Kit included	1 x M12 B2 Battery pack, C12 C Charger, Tool bag
Article Number	4933448764
EAN Code	4002395810864

M12 FIR38 | M12 FUEL™ SUB COMPACT 3/8" RATCHET

- With up to 75 Nm of max torque and 200 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- Low profile head design allows users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and investment cast steel yoke housing provides greater durability for the professional user
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- Supplied with 1/4" adaptor
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FIR38-0	M12 FIR38-201B
Tool reception	3/8" square	3/8" square
Max. torque (Nm)	75	75
No load speed (rpm)	0 - 200	0 - 200
Length (mm)	281	281
Weight with battery pack (EPTA) (kg)	1.4 (M12 B2)	1.4 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B2 Battery pack, C12 C Charger, Tool bag
Article Number	4933459797	4933459799

M12 PCG/400 | M12™ SUB COMPACT CAULK GUN WITH 400 ML TUBE

- Up to 1780 N of force
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all construction adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 PCG/400A-201B
Max. pushing force (N)	1780
Speed settings	6
Standard equipment	400 ml alum. tube
Weight with battery pack (EPTA) (kg)	1.9 (M12 B2)
Kit included	1 x M12 B2 Battery pack, C12 C Charger, Tool bag
Article Number	4933451225
EAN Code	4002395137459

M12 IR | M12™ SUB COMPACT RATCHET

- Pneumatic performance with cordless convenience, 47 Nm of torque and no load speed of 250 rpm
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Reinforced housing - provides high durability similar to steel ratchets
- Compact design - ideal for tight spaces and small engine bays
- Variable speed metal paddle switch trigger - provides greater user control during application
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12

	M12 IR-201B 1/4	M12 IR-201B 3/8
Tool reception	1/4" square	3/8" square
Max. torque (Nm)	40	47
No load speed (rpm)	0 - 250	0 - 250
Length (mm)	274	274
Weight with battery pack (EPTA) (kg)	0.90 (M12 B2)	0.9 (M12 B2)
Kit included	1 x M12 B2 Battery pack, C12 C Charger, Tool bag	1 x M12 B2 Battery pack, C12 C Charger, Tool bag
Article Number	4933451019	4933448110

M12 PCG/310 | M12™ SUB COMPACT CAULK GUN WITH 310 ML CARTRIDGE HOLDER

- Up to 1780 N of force
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all construction adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 PCG/310C-201B
Max. pushing force (N)	1780
Speed settings	6
Standard equipment	310 ml cart. holder
Weight with battery pack (EPTA) (kg)	1.9 (M12 B2)
Kit included	1 x M12 B2 Battery pack, C12 C Charger, Tool bag
Article Number	4933448763
EAN Code	4002395810857

M12 BI | M12™ SUB COMPACT INFLATOR

- Compact lightweight design for fast inflation of car, light truck and compact equipment tires
- High efficiency motor & pump
- Anti-vibration stand with all rubber feet for no movement while inflating
- Auto shut-off technology inflates to users pre-selected pressure for highly accurate inflation
- Illuminated LCD display with a digital pressure and fuel gauge that displays remaining charge
- Nozzle & hose storage, easily stores 66 cm hose and attachments, with an all-brass schrader chuck
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life (Battery sold separately)
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Supplied with a ball inflation needle, presta chuck, inflator nozzle and schrader chuck



	M12 BI-0
Hose length (mm)	660
Max. pressure [bar(PSI)]	8.27 / 120
No load air delivery	24.9
Duty Cycle	50% at 10 min On and 10 min Off
Gauge Accuracy [%]	±3
Weight with battery pack (EPTA) (kg)	1.6 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464124
EAN Code	4058546220693

M12

C12 RT | M12™ SUB COMPACT ROTARY TOOL

- Versatile cordless solution for cutting and removal applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed (5000 - 32,000 rpm)
- 3.2 mm collet fits most current accessories in the market
- Spindle lock mechanism for easy accessory changes
- Superior ergonomics and lightweight
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	C12 RT-0
No load speed (rpm)	5000 - 32,000
Collet capacity (mm)	3.2
Weight with battery pack (EPTA) (kg)	0.60 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933427183
EAN Code	4002395239030

M12

M12 SI | M12™ SUB COMPACT SOLDERING IRON

- Quick heat up time: the tool is ready to use in 20 - 30 seconds
- 3 locking head positions to work in multiple orientations - 0°, 45°, 90°
- Tool free replaceable tips
- Dual color LED lights to notify user: flashing green when tool is heating up, solid green when the tool is ready for operation and solid red when the tool is off but the tip is hot to touch until the red LED turns off
- Temperature monitoring to maintain heat throughout tough applications
- Bright LED light for increased visibility of soldering application
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 SI-0	M12 SI-201C
Heater power [W]	90	90
Temperature range (°C)	400	400
Weight with battery pack (EPTA) (kg)	0.50 (M12 B2)	0.50 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No pack, C12 C Charger, kitbox or bag supplied	1 x M12 B2 Battery Kitbox
Article Number	4933459760	4933459762
EAN Code	4058546029326	4058546029340

M12

M12 FCOT | M12 FUEL™ SUB COMPACT MULTI-MATERIAL CUT-OFF TOOL

- Fast accurate cutting with up to 20,000 RPM
- Optimised ergonomic design for easy control and one-handed use. Only 1.1 kg and 226 mm in length
- Multi-material cutting capability with variety of blades available (metal cut-off wheel, carbide abrasive blade and diamond tile blade)
- A very capable problem solving tool for cutting steel, stainless steel, non-ferrous materials, drywall, fibre cement, plastic and ceramics
- Easily adjustable guard and unique forward/reverse selectable blade rotation direction to protect user from debris in various cutting positions
- Quick release dust shoe with depth adjustment and optional dust extraction port
- On board fuel gauge and LED light
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- 76 mm blade offers up to 16.3 mm depth of cut



	M12 FCOT-0	M12 FCOT-622X
No load speed (rpm)	20,000	20,000
Cutting depth (mm)	16.3	16.3
Disc diameter (mm)	76	76
Bore size (mm)	10	10
Weight with battery pack (EPTA) (kg)	1.1 (M12 B2)	1.1 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B6, 1 x M12 B2 Battery packs, C12 C Charger, HD Box
Article Number	4933464618	4933464620
EAN Code	4058546225636	4058546225650

M12 FUEL

M12 FTB

M12 FUEL™ LOW SPEED TYRE BUFFER

- The M12 FUEL™ low speed tyre buffer has a two-speed mode selector for reaming & buffing applications
- Optimal speed settings of 1200 RPM in first mode and 2500 RPM in second mode help to avoid burning the rubber and damaging the tyre
- Pneumatic performance with cordless convenience for better accessibility and manoeuvrability in tight spaces
- 7/16" quick change chuck ensures fast and easy accessory changes
- Sustained power without bogging down
- Variable speed trigger provides outstanding control of the tool
- Trigger lock-off extends the life of the tool and battery
- On board fuel gauge and LED light
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FTB-0
No load speed gear 1 (rpm)	0-1200
No load speed gear 2 (rpm)	0-2500
Max. drilling accessories diameter (mm)	9.5
Max. buffing accessories diameter (mm)	80
Tool reception	7/16" Hex
Weight with battery pack (EPTA) (kg)	1.1 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933472215
EAN Code	4058546326111

M12 FBS64 | M12 FUEL™ SUB COMPACT BAND SAW WITH 64 MM CUTTING CAPACITY

- First 12V band saw with 64 mm cutting capacity on the market
- Compact light weight design, especially for cutting overhead with one hand in existing installations and in tight spaces
- Variable speed trigger for quick & easy speed adjustments
- Integrated blade cover protects user from injuries by preventing any access to the blade
- Tool-free blade locking mechanism for quick and easy saw blade changes
- Dual action trigger to prevent accidental trigger actuation
- Lockable adjustable shoe
- Solid metal rafter hook for easy jobsite storage
- Integrated LED light for workspace illumination
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FBS64-0C	M12 FBS64-402C
No load speed (rpm)	0-174	0-174
Cutting capacity rect. stock (mm)	64	64
Blade length (mm)	776.3	776.3
Weight with battery pack (EPTA) (kg)	3.2 (M12 B4)	3.2 (M12 B4)
Kit included	No batteries supplied, No charger supplied, Kitbox	2 x M12 B4 Battery packs, C12 C Charger, Kitbox
Article Number	4933478440	4933478442
EAN Code	4058546346317	4058546346331

M12 FUEL

M12 BS | M12™ SUB COMPACT BANDSAW

- Compact light weight design for cutting with one hand overhead in existing installations and in tight spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Cuts a multitude of materials: steel, stainless steel, copper, plastic, aluminium
- Cold cutting - spark and burr free
- Clean cut - balanced handle design combined with 8-large ball bearing blade supports provide best in class cut quality
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Supplied with a 18 Tpi blade



	M12 BS-0	M12 BS-402C
No load speed (rpm)	0 - 85	0 - 85
Max. cutting capacity (mm)	41 x 41	41 x 41
Blade length (mm)	687.57	687.57
Weight with battery pack (EPTA) (kg)	1.6 (M12 B2)	3.2 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B4 Battery packs, C12 C Charger, Kitbox
Article Number	4933431310	4933446135
EAN Code	4002395242092	4002395004751

M12



M12 FNB16 | M12 FUEL™ 1.6 MM NIBBLER

- First 12V Nibbler with max. cutting capacity in mild Steel: 1.6 mm, in Stainless Steel: 1.2 mm, in Aluminium: 2.1 mm
- With only 1.6 kg (6.0 Ah battery included) it is the lightest cordless Nibbler on the market, while still outperforming 18V brushed competitors
- Maximum control for any material, with a 5-step speed dial it is ideal for working with stainless steel and aluminium
- Auto-control start feature, it starts slow and ramps to full speed when the tool detect the user is making a cut
- Tool-free change of cutting direction in 90° steps
- Tool-free die holder and punch change
- Chip collection bag for a clean working environment
- LED lights up your work area for better visibility
- Integrated belt hook and lanyard tie off point
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FNB16-0X
Stroke rate (spm)	1,400 - 2,200
Maximum sheet thickness steel 400 N/mm ² (mm)	1.6
Maximum sheet thickness steel 600 N/mm ² (mm)	1.2
Maximum sheet thickness steel 800 N/mm ² (mm)	0.7
Maximum sheet thickness aluminum up to 250 N/mm ² (mm)	2.1
Cutting width (mm)	5
Smallest radius (mm)	40.7
Starting hole diameter (mm)	21
Weight with battery pack (EPTA) (kg)	1.6 (M12 B6)
Kit included	No batteries supplied, No charger supplied, HD Box
Article number	4933479618
EAN code	4058546374129

M12 FDGS | M12 FUEL™ STRAIGHT DIE GRINDER

- The first cordless in-line die grinder that delivers more power vs. pneumatic models
- Best-in-class size (262 mm long) to help reach in tight places, and offers great mobility and access
- Features a 3-mode speed control and responsive variable speed trigger enabling outstanding control
- To be used with discs up to Ø50 mm
- Supplied with 6 and 8 mm collets
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FDGS-0	M12 FDGS-422B
Collet capacity (mm)	6/ 8	6/ 8
No load speed (rpm)	0 - 10,000/ 0 - 15,000/ 0 - 21,000	0 - 10,000/ 0 - 15,000/ 0 - 21,000
Weight with battery pack (EPTA) (kg)	0.94 (M12 B4)	0.94 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No Battery packs, C12 C kitbox or bag supplied	1 x M12 B4, 1 x M12 B2 Charger, Tool bag
Article Number	4933471435	4933471437
EAN Code	4058546290634	4058546290658

M12 FDGA | M12 FUEL™ ANGLED DIE GRINDER

- The first cordless right angle die grinder that delivers more power vs. pneumatic models
- Compact size (only 119 mm long) to help fit in tight places, and offers great mobility and access
- Features a 4-mode speed control and responsive variable speed trigger enabling outstanding control
- To be used with discs up to Ø50 mm
- Supplied with 6 and 8 mm collets
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FDGA-0	M12 FDGA-422B
Collet capacity (mm)	6/ 8	6/ 8
Disc diameter (mm)	50	50
No load speed (rpm)	0 - 10,000/ 0 - 15,000/ 0 - 20,000/ 0 - 24,500	0 - 10,000/ 0 - 15,000/ 0 - 20,000/ 0 - 24,500
Weight with battery pack (EPTA) (kg)	1.0 (M12 B4)	1.0 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No Battery packs, C12 C kitbox or bag supplied	1 x M12 B4, 1 x M12 B2 Charger, Tool bag
Article Number	4933471438	4933471440
EAN Code	4058546290665	4058546290689

M12 BPS | M12™ SUB COMPACT POLISHER / SANDER

- Variable 2 speed selection (0-2800 / 0-8300 RPM) for both polishing and sanding applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Large capacity of 76 mm polishing sponge and 50 mm sanding pad size for fast job completion
- Long run time allows frequent task completion with one battery charge
- Compact design with only 130 mm allows access to hard areas
- Spindle lock allows fast, tool free accessory change
- Detachable 2 position side handle
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Supplied with polishing pad, sanding pad, polishing sponge white, polishing sponge yellow, lambswool, side handle



M12

	M12 BPS-0	M12 BPS-421X
No load speed gear 1 (rpm)	0 - 2800	0 - 2800
No load speed gear 2 (rpm)	0 - 8300	0 - 8300
Disc diameter (mm)	76	76
Spindle size	M9 x 0.75	M9 x 0.75
Weight with battery pack (EPTA) (kg)	1.0 (M12 B2)	1.0 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No Battery packs, C12 C kitbox or bag supplied	1 x M12 B4, 1 x M12 B2 Charger, HD Box
Article Number	4933447791	4933447802
EAN Code	4002395006557	4002395006571

M12 FBFL10 | M12 FUEL™ BAND FILE 10 MM

- Lightest cordless band file on the market, only 1.0kg with a 2.0 Ah battery
- Outperforms pneumatic competitor while providing better balance
- 2 speed modes and variable speed trigger provide maximum control from taking down welds to precise work with inox, aluminium and wood
- Reverse mode allows the user to choose the belt orientation to manage the direction of sparks/ chips
- One-hand design allows working in tight areas and ideal for overhead work
- 360° tool-free head adjustment allows the best handling for each working environment and provides compact storage
- Dual action safety trigger with lock-on function for less strenuous on longer working periods
- Tool-free belt change
- LED lights up your work area for better visibility
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FBFL10-0
No load speed (rpm)	0 - 7,200/ 0 - 14,500
Belt speed (m/min)	0 - 550/ 0 - 1,110
Belt length (mm)	330
Belt width (mm)	10
Kit included	No batteries supplied , No charger supplied , No kitbox or bag supplied
Weight with battery pack (EPTA) (kg)	1.2 (M12 B4)
Article number	4933480958
EAN code	4058546412432

M12 FBFL13 | M12 FUEL™ BAND FILE 13 MM

- Worlds first cordless 12V band file with a capacity of 13mm belt width
- Lightest cordless band file on the market, only 1.1kg with a 2Ah battery.
- Outperforms pneumatic competitor while providing better balance
- 2 speed modes + variable speed trigger - provides maximum control from taking down welds to precise work with inox, aluminium and wood
- Reverse mode - allows the user to choose the belt orientation to manage the direction of sparks / chips
- One-hand design - allows working in tight areas and ideal for overhead work
- 360° tool-free head adjustment - best handling for each working enviroment + provides compact storage
- Dual action safety trigger with lock-on function for less strenuous on longer working periods
- Tool-free belt change
- LED lights up your work area for better visibility
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FBFL13-0	M12 FBFL13-402B
No load speed (rpm)	0 - 7,200/ 0 - 14,500	0 - 7,200/ 0 - 14,500
Belt speed (m/min)	0- 560/ 0 - 1,105	0- 560/ 0 - 1,105
Belt length (mm)	457	457
Belt width (mm)	13	13
Kit included	2 x M12 B4 Battery packs, C12 C Charger, Tool bag	No batteries supplied , No charger supplied , No kitbox or bag supplied
Weight with battery pack (EPTA) (kg)	1.3 (M12 B4)	1.3 (M12 B4)
Article number	4933480961	4933480962
EAN code	4058546412463	4058546412470

M12 FDSS | M12 FUEL™ SUB COMPACT SPOT SANDER

- Compact detail sander with a penta shaped pad allows uncompromised corner accessibility
- Four speed modes allows the correct speed to be set for different types of material
- Low vibration at only 4.3 m/s²
- Sponge interface pad included optimises the tool for profiles and contours which increases the precision and removal of material
- Hook and loop pad allows the user to change quickly between different grit types
- LED lights up your work area for better visibility
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

	M12 FDSS-0B	M12 FDSS-422X
No load speed (rpm)	0-8,000/ 0-10,000/ 0-12,000/ 0-14,000	0-8,000/ 0-10,000/ 0-12,000/ 0-14,000
Oscillation diameter (mm)	1.5	1.5
Sanding pad size (mm)	88.8 x 63.5	88.8 x 63.5
Weight with battery pack (EPTA) (kg)	0.8 (M12 B2)	0.8 (M12 B2)
Kit included	No batteries supplied, No charger supplied, Tool bag	1 x M12 B4, 1 x M12 B2 Battery packs, C12 C Charger, HD Box
Article number	4933479680	4933479682
EAN code	4058546374747	4058546374761

M12 BCST | M12™ SUB COMPACT CABLE STAPLER

- The new battery powered cable stapler is twice as fast than manual staple installation. It eliminates majority of hand stapling of low voltage cable into wood
- Moveable cable guides ensure proper alignment over cable prior to fastening over a variety of cable sizes
- The compact, lightweight design provides users with access to tight stud bays and improved ergonomics when stapling overhead or during hard to reach applications
- Dry-Fire lockout stops the tool being fired when there are no staples left in the magazine
- Power to drive 25 mm staples adequately into range of framing materials
- Large magazine capacity holding 45 staples for less down time reloading
- LED work light allows users to perform applications in low light environments
- Fires up to 1200 staples per charge on a REDLITHIUM™ 2.0 Ah battery
- Reversible belt hook allows users to choose which side of the stapler they want the belt hook
- Premium 4-pole brushed motor, REDLITHIUM™ battery pack and REDLINK™ electronic delivering the needed power, run time and durability



M12

	M12 BCST-0
Magazine capacity	45
Staple strip length (mm)	25.4
Staple strip width (mm)	19
Weight with battery pack (EPTA) (kg)	2.3 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933480488
EAN code	4058546407735

M12 FMT | M12 FUEL™ MULTI-TOOL

- Brushless POWERSTATE™ motor delivers fast cutting speed through common materials without slowing or bogging down in hardwoods
- Adjustable 10,000 to 20,000 opm allow the user to get the perfect cut whatever the material
- Lowest vibration in its class, 4.56 m/s² driving productivity through performance and safety
- 1.8° left/right oscillation angle allowing faster cuts
- Ability to make up to 59 cuts in oak on one 2.0 Ah battery charge
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- FIXTEC™ tool free blade change with universal blade change adaptor included to accept all major competitor blades
- LED work light illuminates the cut line in low light conditions
- Supplied with an adapter, plunge cut blade OSC 112, sanding backing pad, 5 x sanding sheets and a DEK26 dust guard to use when sanding
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 FMT-0	M12 FMT-422X
Oscillation angle left/ right (°)	1.8	1.8
No load speed (rpm)	10,000 - 20,000	10,000 - 20,000
Weight with battery pack (EPTA) (kg)	1.6 (M18 B2)	1.6 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B4, 1 x M12 B2 Charger, HD Box
Article Number	4933472238	4933472240
EAN Code	4058546326340	4058546326364

C12 HZ | M12™ SUB COMPACT HACKZALL™

- High performance compact one handed use HACKZALL™, measuring only 280 mm in length, making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Patented FIXTEC™ clamp for fast and easy keyless blade change
- Low vibration at 10.5 m/s²
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	C12 HZ-0	C12 HZ-202C
No load stroke rate (spm)	0 - 3000	0 - 3000
Stroke length (mm)	13	13
Weight with battery pack (EPTA) (kg)	1.2 (M12 B2)	1.2 (M12 B2)
Kit included	No batteries supplied, No charger supplied, kitbox or bag supplied	2 x M12 B2 Battery No packs, C12 C Charger, Kitbox
Article Number	4933411925	4933441198
EAN Code	4002395236367	4002395001798

C12 MT | M12™ SUB COMPACT MULTI-TOOL

- Versatile cordless solution for cutting and removal applications
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed (5000 - 20,000 rpm) and 1.5° left/right oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic
- Will accept competitor accessories
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Supplied with Hex wrench, 1 x adapter, 1 x plunge cut blade for wood, 1 x sanding backing pad, 3 x grit 60, 3 x grit 80, 3 x grit 120, 3 x grit 240



	C12 MT-0	C12 MT-402B
Oscillation angle left/ right (°)	1.5	1.5
No load speed (rpm)	5000 - 20,000	5000 - 20,000
Weight with battery pack (EPTA) (kg)	1.0 (M12 B2)	1.2 (M18 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B4 Battery packs, C12 C Charger, Tool bag
Article Number	4933427180	4933441708
EAN Code	4002395239276	4002395001996

M12 JS | M12™ SUB COMPACT JIGSAW

- New grip design combines the best features from both top handle and barrel grip jigsaw design
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed - electronic trigger provides user flexibility and control
- Smooth cut - minimal vibration during cutting provides ultra smooth performance
- Precision roller guide increases user control and reduces blade deviation
- Line of sight - the compact tool design improves cut line visibility
- Tool free bevel facility - quick and easy bevel adjustment up to 45°
- QUIK-LOK™ T-Shank blade clamp
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Non marking shoe comes as standard to protect work surfaces from scratching



	M12 JS-0	M12 JS-402B
No load stroke rate (spm)	0 - 2800	0 - 2800
Stroke length (mm)	19	19
Weight with battery pack (EPTA) (kg)	2.1 (M12 B4)	2.1 (M12 B4)
Kit included	No batteries supplied, No charger supplied, kitbox or bag supplied	2 x M12 B4 Battery No packs, C12 C Charger, Tool bag
Article Number	4933431305	4933441703
EAN Code	4002395242085	4002395001972

M12 CCS44 | M12 FUEL™ SUB COMPACT CIRCULAR SAW

- Brushless POWERSTATE™ motor for up to 2x longer motor life and up to 2x more cuts per charge
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 50° bevel capacity
- Magnesium upper and lower guards provide best in class durability for impact resistance
- Magnesium shoe reduces weight and maximises durability
- Integrated dust blower keeps cut line clear
- LED light illuminates the cut line
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 CCS44-0	M12 CCS44-602X
No load speed (rpm)	3600	3600
Max. cutting depth 90° (mm)	44	44
Max. cutting depth 45° (mm)	33	33
Blade diameter (mm)	140	140
Bore size (mm)	20	20
Weight with battery pack (EPTA) (kg)	2.7 (M12 B4)	2.7 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B6 Battery packs, C12 C Charger, HD Box
Article Number	4933448225	4933451909
EAN Code	4002395262809	4002395282180

M12 BST | M12™ SUB COMPACT STAPLER

- Breakthrough performance limits user fatigue by eliminating the repetitive motion of hand tools
- Ready to Fire Technology eliminates ramp-up time between each staple discharge
- Bump fire and sequential fire operation allows the user to fire quickly and accurately
- 2000 staples fired with one 2.0 Ah battery pack
- Fires standard T11 T50 and T140 10.6 mm staples from 6 to 14 mm
- Dry-Fire lock out stops the stapler from being fired when empty
- Compact length, height and width for easier access to compact spaces
- Adjustable belt hook for user convenience
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 BST-0
Staple strip	Type 11 / 140, T50
Staple strip width [mm]	10.6
Staple strip length [mm]	6 - 14
Magazine capacity	89
Cycle rate [min]	140
Weight with battery pack (EPTA) (kg)	1.6 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459634
EAN Code	4058546028060

M12 CHZ | M12 FUEL™ SUB COMPACT HACKZALL™

- Brushless POWERSTATE™ motor for up to 6x longer motor life and up to 70% faster cutting in certain applications
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Patented FIXTEC™ clamp for fast and easy keyless blade change
- Counter balance mechanism lowers vibration to 6.5 m/s² allowing the operator to work safely for longer periods of time reducing fatigue
- Sealed gearbox prevents water and debris entering the housing
- LED light illuminates the outline in low light conditions
- Compact and light weight allows users to complete applications in restricted areas
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 CHZ-0	M12 CHZ-602X
No load stroke rate (spm)	0 - 3000	0 - 3000
Stroke length (mm)	15.9	15.9
Weight with battery pack (EPTA) (kg)	1.6 (M12 B4)	1.6 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B6 Battery packs, C12 C Charger, HD Box
Article Number	4933446960	4933451908
EAN Code	4002395005727	4002395282173

C12 PN | M12™ SUB COMPACT PALM NAILER

- Professional power effectively drives 100 mm framing nails in less than 3 seconds
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Superior ergonomics - user-preferred palm style grip provides outstanding comfort and control
- Fits into locations where a hammer cannot be swung
- Increased run time: drives up to 100 x 90 mm nails on a single charge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	C12 PN-0
Max. percussion rate (bpm)	2700
Max. nail size (mm)	90
Blow energy [EPTA][J]	2.9
Weight with battery pack (EPTA) (kg)	1.6 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933427182
EAN Code	4002395239238

M12 AUN | M12™ AIR-TIP™ UTILITY NOZZLE

- The M12™ powered utility nozzle is a great accessory that is designed to clean jobsite debris on short and medium hair carpeted surfaces
- The universal reception fits to all MILWAUKEE® M12™ and M18™ cordless vacs and covers most common hose sizes (Ø 31.8 mm, 47.6 mm and 63.5 mm)
- The M12™ powered brush with a 152 mm cleaning width gives a better cleaning than non-powered standard nozzles
- The curved skid plate on the M12™ powered floor tool rotates, allowing for easy back and forth motion, for a more enjoyable user experience
- Tool-less roller change for ease of troubleshooting
- LED light bar on the front of the unit lights up the cleaning pathway for better visibility
- Compatible with AIR-TIP™ trade focused vacuum accessories
- Premium 4-pole brushed motor, REDLITHIUM™ battery pack and REDLINK™ electronic delivering the needed power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12

M12 AUN-0	
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Weight with battery pack (EPTA) (kg)	1.2 (M12 B2)
Article number	4932479461
EAN code	4058546372552

M12 AF | M12™ AIR FAN

- Three speed settings delivering max air speed of 22,53 km/h
- High efficient 150 mm blade diameter generates a maximum air volume of 680 m³/h
- The 360° head rotation allow an unlimited directional airflow
- Boundless hanging and mounting possibilities with the integrated magnets, key holes, hooks and pass through holes
- Two hours run time on speed three with an M12™ REDLITHIUM™ 3.0 Ah battery pack
- Lightweight and compact design for easy manoeuvre in tight spaces
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12

M12 AF-0	
Air speed [km per hour]	22,53
Air volume 1 [m³/h]	300
Air volume 2 [m³/h]	450
Air volume 3 [m³/h]	680
Weight with battery pack (EPTA) (kg)	2.3 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933478228
EAN code	4058546344054

M12 FVCL | M12 FUEL™ WET/ DRY VACUUM

- Powerful M12 FUEL™ motor with a maximum air flow of 1275 l/min & 105 mbar provides 18V performance for both wet and dry clean up applications
- With a 6.0 Ah battery the vacuum provides 14 minutes of run time on high and 26 minutes on the low setting, this compact vacuum is ideal for spot and service focused wet/ dry quick clean up needs
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns
- Internal accessory and hose storage allows all attachments to be carried with the tool avoiding loss of equipment
- The DEK 26 power tool connector allows for efficient dust extraction from power tools
- Stackable tool box design for added portability and easier storage
- Wall mount hanging plate included for increased storage options
- On board blower for moving debris away from the work area
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

M12 FVCL-0	
Capacity solids (l)	5.7
Capacity liquids (l)	6.1
Hose diameter (mm)	41
Hose length (m)	0.5
Max. vacuum (mbar)	105
Air volume (l/min)	1275
Filter type	HEPA
Weight with battery pack (EPTA) (kg)	5.0 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933478186
EAN Code	4058546341190

M12 RCDAB+ | M12™ RADIO CHARGER DAB+

- Premium speaker and high frequency tweeter provides high sound quality
- DAB+ and AM/FM tuner with the digital processor delivers highest reception accuracy, signal clarity and additional information like: song, artist and accurate time
- Digital Bluetooth® receiver: Plays music up to 30 m away from your smartphone, computer or tablet
- Built in charger function for quick and convenient charging of any M12™ battery or electric devices via USB port
- IP54 in battery mode - making the radio dust and splashing water resistant
- AC/DC versatility: Powered by MILWAUKEE® M12™ batteries, or mains plug supply



M12

M12 RCDAB+-0	
Tuning range AM [kHz]	522 - 1620
Tuning range FM [MHz]	87.5 - 108
Tuning range DAB	174 - 240
Weight with battery pack (EPTA) (kg)	1.9 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933472115
EAN Code	4058546325114

M12 HV | M12™ SUB COMPACT STICK VAC

- Excellent suction power for wood, metal and common debris
- Clear viewing window gives the user the ability to see debris build up
- Lock on switch reduces fatigue during sustained use
- Versatile accessories for small or large clean up areas
- Compact design makes it easy to clean in tight spaces
- Secure canister lock guards against unwanted spillage
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12

M12 HV-0	
Air volume (l/min)	934
Airflow speed [m per h]	56
Max. vacuum (mbar)	31.1
Capacity solids (l)	0.6
Hose diameter (mm)	22.5
Weight with battery pack (EPTA) (kg)	1.2 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933448390
EAN Code	4002395262908

M12 JSSP | M12™ JOBSITE BLUETOOTH® SPEAKER

- Advanced technology Bluetooth® jobsite speaker
- Connect wirelessly with portable electronic devices from up to 10 m away
- Loud, clear sound at all volumes
- Premium speaker with bass port
- Drop, water and debris resistant to withstand tough conditions on and off the jobsite
- Rugged over mould, metal speaker grill
- 2.1 A USB charger, charges phones, tablets and media players
- Up to 25 hrs run time per charge with M12™ 4.0 Ah battery
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12

M12 JSSP-0	
Dimensions (mm)	105.5 x 153
Speaker output (W)	5
Weight with battery pack (EPTA) (kg)	0.70 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933448380
EAN Code	4002395262892

M12 BBL | M12™ BLOWER

- Powerful motor can generate up to 4.81 m³/min of air volume at 177 km/h for fast cleaning of the jobsite
- Lightweight, compact body - clears dirt and debris in tight spaces
- Perfect control of the power with the 2 speed adjustable trigger
- Versatile attachments like the nozzle extension (25.5 cm) and a tip tube for accurate working are included
- Removable nozzle for easy, convenient storage
- Axial fan design
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12

M12 BBL-0	
Air volume 1 [m³ per minute]	0 - 3.5
Air volume 2 [m³ per minute]	0 - 4.9
Airflow speed (km/h)	0 - 128/ 0 - 177
Length without nozzle [mm]	380
Weight with battery pack (EPTA) (kg)	1.9 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933472214
EAN code	4058546326104

M12-18 JSSP | M12™ - M18™ BLUETOOTH® SPEAKER

- Advanced technology Bluetooth® jobsite speaker
- Bluetooth® wireless range of up to 30 m
- Flexible battery system: works with all MILWAUKEE® M12™ & M18™ batteries
- IP54 rated, water and debris resistant to withstand tough conditions on and off the jobsite
- Loud, clear sounds at all volumes
- 2.1A USB charger, charges phones, tablets and media players
- Premium speaker with bass port



M12 M18

M12-18 JSSP-0	
Dimensions (mm)	360 x 165 x 165
Speaker output (W)	40
Weight with battery pack (EPTA) (kg)	2.5 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459275
EAN Code	4058546002411

M12 FPP2A2

M12™ POWERPACK

- M12 FPD2 - M12 FUEL™ sub compact percussion drill
- M12 FID2 - M12 FUEL™ sub compact 1/4" impact driver

M12 FUEL



M12 FPP2A2-602X	
Kit included	2 x M12 B6 Battery packs, C12 C Charger, HD Box
Article number	4933480589
EAN code	4058546408749

M12 BPP2B

M12™ POWERPACK

- M12 BPD - M12™ sub compact percussion drill
- M12 BID - M12™ sub compact 1/4" Hex impact driver

M12



M12 BPP2B-421C	
Kit included	1 x M12 B4, 1 x M12 B2 Battery packs, C12 C Charger, Kitbox
Article Number	4933446607
EAN Code	4002395005338

LASERS RANGE



M12 3PL | M12™ GREEN 360° 3 PLANE LASER

- M12™ green 360° 3 plane laser provides an all-in-one functionality with one horizontal line and two vertical lines for fast and easy alignment, leveling, squaring, and transfers allowing you to easily layout large spaces with one tool
- Built with high intensity green diodes to provide maximised visibility - up to 4x better visibility vs red lasers
- High intensity green beams provide a working range of 38 m and up to 100 m with a detector
- Provides all-day run time of 15+ hours with an M12 B4 battery pack
- 3 mode pendulum system: Manual Mode for use at any angle, Self-Levelling Mode that indicates out-of-level condition with a 4° self-levelling range and Pendulum Lock Mode to protect components during transport
- Integrated magnetic bracket with rear mounted amplified rare earth magnets, 1/4" and 5/8" tripod thread and hang hole - allows attachment to steel stud, wooden stud and tripod
- The bracket also provides the laser 330° rotation that pivots on plumb point, with an integrated micro control knob for faster point to point alignment
- Robust over-moulded construction with an IP 54 rating, the laser is water/ debris resistant and can withstand up to 1 m drops
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 3PL-0C	M12 3PL-401C	M12 3PLKIT-401P
Colour of laser line	Green	Green	Green
Laser projection	2x vertical, 1x horizontal	2x vertical, 1x horizontal	2x vertical, 1x horizontal
Working range visible [m]	38	38	38
Accuracy [mm/m]	0.3	0.3	0.3
Self levelling range [°]	4	4	4
Compatible laser detector	LLD50 / LRD100	LLD50 / LRD100	LLD50 / LRD100
Weight with battery pack (EPTA) (kg)	1.5 (M12 B4)	1.5 (M12 B4)	1.5 (M12 B4)
Standard equipment	Track clip, HVIST	Track clip, HVIST	HVIST, LLD50, Track Clip
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M12 B4 Battery pack, C12 C Charger, Kitbox	1 x M12 B4 Battery pack, C12 C Charger, PACKOUT™ box
Article Number	4933478103	4933478246	4933478990
EAN Code	4058546340360	4058546344238	4058546362720

M12 CLL4P | M12™ CROSS LINE LASER WITH 4 POINTS

- M12™ green cross line laser with 4 points, provides an all-in-one functionality with horizontal levelling, vertical alignment, plumb point transfer from floor to ceiling and horizontal point transfer
- High intensity green beams provide a working range of 38 m and up to 100 m with a detector
- Provides all-day run time of 9+ hours with an M12 B3 battery pack
- 3 mode pendulum system: Manual Mode for use at any angle, Self-Levelling Mode that indicates out-of-level condition with a 4° self-levelling range and Pendulum Lock Mode to protect components during transport
- Integrated magnetic bracket with rear mounted amplified rare earth magnets, 1/4" and 5/8" tripod thread and hang hole - allows attachment to steel stud, wooden stud and tripod
- The bracket also provides the laser 360° rotation that pivots on plumb point, with an integrated mico control knob for faster point to point alignment
- Robust over-moulded construction with an IP 54 rating, the laser is water/debris resistant and can withstand up to 1 m drops
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Includes 1x high visibility target plate and 1x track clip



	M12 CLL4P-0C	M12 CLL4P-301C
Colour of laser line	Green	Green
Laser projection	1x horizontal, 1x vertical, 2x plumb points and 2x horizontal points	1x horizontal, 1x vertical, 2x plumb points and 2x horizontal points
Working range visible [m]	38	38
Accuracy [mm/m]	0.3	0.3
Self levelling range [°]	4	4
Compatible laser detector	LLD50 / LRD100	LLD50 / LRD100
Weight with battery pack (EPTA) (kg)	1.3	1.3
Standard equipment	Track clip, HVIST	Track clip, HVIST
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M12 B3 Battery pack, C12 C Charger, Kitbox
Article number	4933479202	4933479204
EAN code	4058546369965	4058546369989

M12 CLLP | M12™ GREEN CROSS LINE LASER WITH PLUMB POINTS

- M12™ green cross line laser with plumb points provides an all-in-one functionality with horizontal levelling, vertical alignment and plumb point transfer from floor to ceiling
- Built with high intensity green diodes to provide maximised visibility - up to 4x better visibility vs red lasers
- High intensity green beams provide a working range of 38 m and up to 100 m with a detector
- Provides all-day run time of 15+ hours with an M12 B3 battery pack
- 3 mode pendulum system: Manual Mode for use at any angle, Self-Levelling Mode that indicates out-of-level condition with a 4° self-levelling range and Pendulum Lock Mode to protect components during transport
- Integrated magnetic bracket with rear mounted amplified rare earth magnets, 1/4" and 5/8" tripod thread and hang hole - allows attachment to steel stud, wooden stud and tripod
- The bracket also provides the laser 360° rotation that pivots on plumb point, with an integrated mico control knob for faster point to point alignment
- Robust over-moulded construction with an IP 54 rating, the laser is water/debris resistant and can withstand up to 1 m drops



	M12 CLLP-0C	M12 CLLP-301C
Laser projection	1x horizontal, 1x vertical, 2x plumb points	1x horizontal, 1x vertical, 2x plumb points
Working range visible [m]	38	38
Accuracy [mm/m]	0.3	0.3
Self levelling range [°]	4	4
Compatible laser detector	LLD50 / LRD100	LLD50 / LRD100
Weight with battery pack (EPTA) (kg)	1.2 (M12 B3)	1.2 (M12 B3)
Standard equipment	Track clip, HVIST	Track clip, HVIST
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M12 B3 Battery pack, C12 C Charger, Kitbox
Article Number	4933478101	4933478245
EAN Code	4058546340346	4058546344221

L4 CLLP | USB RECHARGEABLE GREEN CROSS LINE LASER WITH PLUMB POINTS








- REDLITHIUM™ USB rechargeable green cross line laser with plumb points provides an all-in-one functionality with horizontal levelling, vertical alignment and plumb point transfer from floor to ceiling
- Built with high intensity green diodes to provide uncompromised visibility - up to 4x better visibility vs red lasers
- High intensity green beams provide a working range of 30 m and up to 100 m with a detector
- The rechargeable and removable REDLITHIUM™ USB 3.0 Ah battery provides all day run time of over 8 hours
- 1x REDLITHIUM™ USB 3.0 battery replaces up to 6,000 alkaline batteries over the lifetime of the battery
- 3 mode pendulum system: Manual Mode for use at any angle, Self-Levelling Mode that indicates out-of-level condition with a 4° self-levelling range and Pendulum Lock Mode to protect components during transport
- Integrated magnetic bracket with rear mounted amplified rare earth magnets, 1/4" tripod thread and hang hole - allows attachment to steel stud, wooden stud and tripod



	L4 CLLP-301C
Laser projection	1x horizontal, 1x vertical, 2x plumb points
Working range visible [m]	30
Accuracy [mm/m]	0.3
Self levelling range [°]	4
Compatible laser detector	LLD50
Weight with battery pack (EPTA) (kg)	0.90 (L4 B3)
Standard equipment	Track clip
Kit included [L4]	1 x L4 B3 Battery pack, USB cable and wall plug, Kitbox
Article Number	4933478244
EAN Code	4058546344214

TRUEVIEW™

LASER ATTACHMENTS

	Description		Article Number	EAN Code	
LLD50	Line laser detector	<ul style="list-style-type: none">The MILWAUKEE® LLD50 laser line detector extends laser line functionality up to 50 metresThe LEDs on front and back allow easy and accurate detection of the laser beam to improve the set-up processRare earth magnets located on two sides of the detector allow it to easily attach to metal surfaces, ideal for suspended ceiling installationsThe included clamp is ideal for attaching to non-metal surfaces for setting elevationsThe detector has adjustable audio feedback and has over 65 hours of run time with included AA batteriesCompatible with all MILWAUKEE™ line & plane lasersAdjustable accuracy settings for greater precisionIP54 protects detector from jobsite conditions1 m impact resistance	4932478104	4058546340377	
LRD100	Line/ rotary laser detector	<ul style="list-style-type: none">The MILWAUKEE® LRD100 detector extends laser line functionality up to 100 metre in combination with all MILWAUKEE® cross line and plane lasers and can be universally used with rotary lasers up to 250 metre radiusThe millimetre display on front and back allows easy and accurate detection of the laser beam to improve the set-up processRed and green laser diodes detection for most versatile useSupplied with 1x AA battery and a material clamp to attach to rod, stud, pipe or levels for setting elevationIP67 rated for dust and water protectionStrong magnets located on top of the detector allow it to easily attach to metal surfaces, ideal for suspended ceiling installations5 mode adjustable accuracy settings for setting up the laser detector specifically to the applicationLED & audio indication to align from distance	4932479555	4058546373498	
LM360	360° laser mount	<ul style="list-style-type: none">The MILWAUKEE® 360° laser mount is an adaptable laser attachment that provides the fastest laser setupMulti-plane rotational adjustment, users can easily attach all MILWAUKEE® lasers to the mountA micro vertical adjustment that makes aligning horizontal lines much fasterThe amplified rare earth magnets on both sides provide a strong hold even on thin steel stud materialIntegrated screw and nail hang holes make setup easy and efficient in any environmentIntegrated 1/4" & 5/8" thread to easily attach to most tripods	4932478105	4058546340384	
HI-VIST	High visibility laser target plate	<ul style="list-style-type: none">The MILWAUKEE® high visibility laser target plate provides fast and visible alignment with a wide magnetic base for floors & ferrous surfacesHigh contrast reflective surface for use with green lasersThe X design provides responsive centering feedback that guides the line to the centre, making the alignment process faster	4932478108	4058546340414	
TRP180	1.8 meter laser tripod	<ul style="list-style-type: none">The MILWAUKEE® laser tripod with a 1/4" mounting thread is ideal for setting the height of a horizontal laser line or elevating the laser when neededHeight can be adjusted easily from 72 cm to 180 cmLaser can be mounted to the bottom of the tripod with the 360° mount (not included) for low level applications like socket installationAdjustable pan tilt head with removable laser mounting plateReinforced gearing on the centre shaft for longer tool lifeLight weight aluminium design	4932478106	4058546340391	
TRP120	1.2 meter compact laser tripod	<ul style="list-style-type: none">The MILWAUKEE® compact laser tripod with a 1/4" mounting thread and a flat head design is ideal for setting the height of a horizontal laser line or elevating the laser when neededHeight can be adjusted easily from 47 cm to 120 cm29 cm elevating range for fine adjusting the heightLaser can be mounted to the bottom of the tripod with the LM360 bracket (not included) for low level applications like socket installationDurable and light weight aluminium frame for a longer life	4932478959	4058546362416	
LMP	3.6 m telescoping laser pole	<ul style="list-style-type: none">The MILWAUKEE® telescoping laser pole with 3.6 m extension range is ideal to setting up line lasers even on high ceilingsThe spring loaded swivel head makes setup easy, even at uneven surfacesThe included quick release clamp opens to 6.3 cm and can be attached to round and square materialsAll MILWAUKEE® lasers can be mounted to the clamp by using the rare earth magnets on the integrated bracketThe tick marks helps to identify the right position of the laser	4932479205	4058546369996	

L4 CLL | USB RECHARGEABLE GREEN CROSS LINE LASER

- REDLITHIUM™ USB rechargeable green cross line laser provides an all-in-one functionality with horizontal levelling and vertical alignment
- Built with high intensity green diodes to provide uncompromised visibility - up to 4x better visibility vs red lasers
- High intensity green beams provide a working range of 30 m and up to 100 m with a detector
- The rechargeable and removable REDLITHIUM™ USB 3.0 Ah battery provides all day run time of over 8 hours
- 1x REDLITHIUM™ USB 3.0 battery replaces up to 6,000 alkaline batteries over the lifetime of the battery
- 3 mode pendulum system: Manual Mode for use at any angle, Self-Levelling Mode that indicates out-of-level condition with a 4° self-levelling range and Pendulum Lock Mode to protect components during transport
- Integrated magnetic bracket with rear mounted amplified rare earth magnets, 1/4" tripod thread and hang hole - allows attachment to steel stud, wooden stud and tripod
- The bracket also provides the laser 360° rotation, with an integrated micro control knob for faster point to point alignment



L4 CLL-301C	
Laser projection	1x vertical, 1x horizontal
Working range visible [m]	30
Accuracy [mm/m]	0.3
Self levelling range [°]	4
Compatible laser detector	LLD50
Weight with battery pack (EPTA) (kg)	0.90 (L4 B3)
Standard equipment	Track clip
Kit included [L4]	1 x L4 B3 Battery pack, USB cable and wall plug, Kitbox
Article Number	4933478243
EAN Code	4058546344207

LDM 50 | 50 M LASER DISTANCE METER

- Easy to use one person point and shoot system
- Very slim housing design with belt clip for easy transport
- Area/volume/indirect height and patent pending surface measurement
- Min/Max sweep & continuous tracking
- Distance addition & subtraction for layouting
- Indirect height measurements (Pythagoras 2-point, 3-point, partial height)
- Large 3 line LCD graphical display with automatic white backlight
- Fold-out end piece for diagonal corner measurements
- Memory recall for the last 20 measurements
- IP54 water & dust protection
- Auto shut off and low power indication
- Metric units of measurement only

LDM 50	
Max. measurement range (m)	50
Accuracy	± 1.5
Display	LCD
Display size (mm)	26 x 37
Laser classification	Class 2
Dimensions (mm)	119 x 40 x 32
Range (m)	0.05 - 50
Weight with battery pack (EPTA) (kg)	0.1 (2 x AAA)
Pythagoras function	2-point, 3-point, partial height
Inclination Sensor	No
Height tracking	No
Kit included	2 x AAA Batteries, No kitbox or bag supplied
Article Number	4933447700
EAN Code	4002395006540



LDM 30 | 30 M LASER DISTANCE METER

- Easy to use one person point and shoot system
- IP54 water & dust protection
- Auto shut off and low power indication
- Metric & Imperial units of measurement
- Very slim housing design with belt clip for easy transport
- Two easy to touch measure buttons on the front and side of the housing
- Enables user to perform single measurements & continuous tracking
- Large 3 line LCD graphical display with automatic white backlight
- Display shows last three measurements



LDM 30	
Max. measurement range (m)	30
Accuracy	± 2
Display	LCD
Display size (mm)	25 x 25
Laser classification	Class 2
Dimensions (mm)	101 x 38 x 28
Range (m)	0.15 - 30
Weight with battery pack (EPTA) (kg)	0.10 (2 x AAA)
Auto_level measurements	No
Pythagoras function	No
Inclination Sensor	No
Height tracking	Yes
Kit included	2 x AAA Batteries, Blister packaging
Article Number	4933459276
EAN Code	4058546002428



M12 HJ BL5
M12™ HEATED JACKET - BLACK



- Heat on demand - sewn in carbon fibre heating wires, distribute heat to core body areas and to the front pockets
- Superior run time, up to 8 hours of heat on low level with a single battery charge of an M12™ REDLITHIUM™ 3.0 Ah battery pack
- Easy touch heat controller - 3 heat settings: High, Medium, Low
- TOUGHSHELL™ stretch 90% polyester and 10% spandex material to withstand harsh working conditions and deliver up to 5x longer life
- FREE FLEX™ mobility - additional material under the arms increases range of movement for working overhead
- New battery pocket design providing users multiple options for battery placement, allowing adaptability to the situation
- Improved slim fit design with extended back prevents heat loss and keeps the user warm
- M12™ battery controller with 1 A USB port, to charge mobile devices stored in concealed battery pocket
- Water and wind resistant, provides comfort and durability in harsh environments
- Big hand & chest pocket, ideal for storing mobile devices
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Available in sizes S-XXXL
- Machine washable and dryable



	M12 HJ BL5-0 (S)	M12 HJ BL5-0 (M)	M12 HJ BL5-0 (L)	M12 HJ BL5-0 (XL)	M12 HJ BL5-0 (XXL)
Size	S	M	L	XL	XXL
Weight with battery pack (EPTA) (kg)	1.6 (M12 B3)	1.6 (M12 B3)	1.7 (M12 B3)	1.7 (M12 B3)	1.8 (M12 B3)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933478967	4933478968	4933478969	4933478970	4933478971
EAN code	4058546362492	4058546362508	4058546362515	4058546362522	4058546362539

M12 HJ GREY5
M12™ HEATED JACKET - GREY



- Heat on demand - sewn in carbon fibre heating wires, distribute heat to core body areas and to the front pockets
- Superior run time, up to 8 hours of heat on low level with a single battery charge of an M12™ REDLITHIUM™ 3.0 Ah battery pack
- Easy touch heat controller - 3 heat settings: High, Medium, Low
- TOUGHSHELL™ stretch 90% polyester and 10% spandex material to withstand harsh working conditions and deliver up to 5x longer life
- FREE FLEX™ mobility - additional material under the arms increases range of movement for working overhead
- New battery pocket design providing users multiple options for battery placement, allowing adaptability to the situation
- Improved slim fit design with extended back prevents heat loss and keeps the user warm
- M12™ battery controller with 1 A USB port, to charge mobile devices stored in concealed battery pocket
- Water and wind resistant, provides comfort and durability in harsh environments
- Big hand & chest pocket, ideal for storing mobile devices
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Available in sizes S-XXXL
- Machine washable and dryable



	M12 HJ GREY5-0 (S)	M12 HJ GREY5-0 (M)	M12 HJ GREY5-0 (L)	M12 HJ GREY5-0 (XL)	M12 HJ GREY5-0 (XXL)
Size	S	M	L	XL	XXL
Weight with battery pack (EPTA) (kg)	1.6 (M12 B3)	1.6 (M12 B3)	1.7 (M12 B3)	1.7 (M12 B3)	1.8 (M12 B3)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933478972	4933478973	4933478974	4933478975	4933478976
EAN code	4058546362546	4058546362553	4058546362560	4058546362577	4058546362584



M12 HPJBL2

M12™ HEATED PUFFER JACKET - BLACK

- M12™ Heated Jacket powered by an M12™ Battery with carbon fibre heating elements creates and distributes heat to chest, back and shoulders.
- Superior run time, up to 11 hours of heat on a single battery charge of an M12™ 12V REDLITHIUM™ 3 Ah battery pack.
- Lightweight and highly durable ripstop polyester provides a slim design that can be worn as an outer-shell or a mid-layer (100 % Polyester outer and inner shell).
- Reinforced high-wear zones protect from abrasion and tears.
- Provides comfort and durability in harsh, rainy or windy environments.
- Optimized hidden battery pocket to place M12™ Battery in front or rear for increased comfort.
- Multiple heating zones - 5 sewn in carbon fibre heating zones distribute heat to core body areas.
- Easy one-touch heat controller - 3 heat settings: High, Medium, Low.
- Machine washable and dryable.
- Battery controller included.
- New hood design.
- Flexible battery system: works with all MILWAUKEE® M12™ Batteries.



	M12 HPJBL2-0 (S)	M12 HPJBL2-0 (M)	M12 HPJBL2-0 (L)	M12 HPJBL2-0 (XL)	M12 HPJBL2-0 (XXL)
Size	S	M	L	XL	XXL
Weight with battery pack (EPTA) (kg)	1,3 kg	1,4 kg	1,4kg	1,5kg	1,5kg
Kit included	No batteries supplied , No charger supplied , Gift box	No batteries supplied , No charger supplied , Gift box	No batteries supplied , No charger supplied , Gift box	No batteries supplied , No charger supplied , Gift box	No batteries supplied , No charger supplied , Gift box
Article number	4932480071	4932480072	4932480073	4932480074	4932480075
EAN code	4058546403560	4058546403577	4058546403584	4058546403591	4058546403607

M12 HPVBL2 | M12™ HEATED PUFFER VEST

- M12™ Heated Jacket powered by an M12™ Battery with carbon fibre heating elements creates and distributes heat to chest, back and shoulders.
- Superior run time, up to 11 hours of heat on a single battery charge of an M12™ 12V REDLITHIUM™ 3 Ah battery pack.
- Lightweight and highly durable ripstop polyester provides a slim design that can be worn as an outer-shell or a mid-layer (100 % Polyester outer and inner shell).
- Reinforced high-wear zones protect from abrasion and tears.
- Provides comfort and durability in harsh, rainy or windy environments.
- Optimized hidden battery pocket to place M12™ battery in front or rear for increased comfort.
- Multiple heating zones - 3 sewn in carbon fibre heating zones distribute heat to core body areas.
- Easy one-touch heat controller - 3 heat settings: High, Medium, Low.
- Machine washable and dryable.
- Battery holder included.



	M12 HPVBL2-0 (S)	M12 HPVBL2-0 (M)	M12 HPVBL2-0 (L)	M12 HPVBL2-0 (XL)	M12 HPVBL2-0 (XXL)
Size	S	M	L	XL	XXL
Weight with battery pack (EPTA) (kg)	0,9 kg	1,0kg	1,0kg	1,0kg	1,1kg
Kit included	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box
Article number	4932480076	4932480077	4932480078	4932480079	4932480080
EAN code	4058546403614	4058546403621	4058546403638	4058546403645	4058546403652

M12 HVGREY1 | M12™ HEATED VEST - GREY

- M12™ Heated TOUGHSHELL™ vest powered by an M12™ battery with carbon fibre heating elements creates and distributes heat to chest & back.
- Superior run time, up to 11 hours of heat on a single battery charge of an M12™ 12V REDLITHIUM™ 3 Ah Battery pack.
- TOUGHSHELL™ stretch 90 % Polyester and 10 % spandex material to withstand harsh working conditions.
- Optimized hidden battery pocket to place M12™ battery in front or rear for increased comfort.
- Multiple heating zones - 3 sewn in carbon fibre heating zones distribute heat to core body areas.
- Easy one-touch heat controller - 3 heat settings: High, Medium, Low.
- Machine washable and dryable.
- Battery holder included.
- Flexible battery system: works with all MILWAUKEE® M12™ Batteries.



	M12 HVGREY1-0 (S)	M12 HVGREY1-0 (M)	M12 HVGREY1-0 (L)	M12 HVGREY1-0 (XL)	M12 HVGREY1-0 (XXL)	M12 HVGREY1-0 (XXXL)
Size	S	M	L	XL	XXL	XXXL
Weight with battery pack (EPTA) (kg)	1,0kg	1,0kg	1,1kg	1,1kg	1,2kg	1,2kg
Kit included	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box
Article number	4932480100	4932480101	4932480102	4932480103	4932480104	4932480105
EAN code	4058546403850	4058546403867	4058546403874	4058546403881	4058546403898	4058546403904



M12 HHBL4 | M12™ HEATED HOODIE - BLACK

- M12™ Heated Hoodie powered by an M12™ battery with carbon fibre heating elements creates and distributes heat to chest and back.
- Superior run time, up to 11 hours of heat on a single battery charge of an M12™ 12V REDLITHIUM™ 3 Ah Battery pack.
- Rugged heated hoodie made from durable cotton (53%) exterior with durable reinforced utility pockets and polyester fleece (47%) lining to withstand tough outdoor conditions.
- Optimized hidden battery pocket to place M12™ battery in front or rear for increased comfort.
- In autumn and spring the hoodie can be worn as a rugged outer layer. In winter, it is best as a base layer that allows to shed bulky undergarments while generating and holding heat close to the body.
- Multiple heating zones - 3 sewn in carbon fibre heating zones distribute heat to core body areas.
- Easy one-touch heat controller - 3 heat settings: High, Medium, Low.
- Integrated cell phone pocket.
- Machine washable and dryable.
- Battery holder included.



	M12 HHBL4-0 (S)	M12 HHBL4-0 (M)	M12 HHBL4-0 (L)	M12 HHBL4-0 (XL)	M12 HHBL4-0 (XXL)
Size	S	M	L	XL	XXL
Weight with battery pack (EPTA) (kg)	1,2kg	1,3kg	1,3kg	1,4kg	1,5kg
Kit included	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box
Article number	4932480061	4932480062	4932480063	4932480064	4932480065
EAN code	4058546403461	4058546403478	4058546403485	4058546403492	4058546403508

M12 HHLBL1 | M12™ HEATED LADIES HOODIE - BLACK

- M12™ Heated Hoodie for ladies powered by an M12™ Battery with carbon fibre heating elements creates and distributes heat to chest and back.
- Superior run time, up to 11 hours of heat on a single battery charge of an M12™ 12V REDLITHIUM™ 3 Ah Battery pack.
- Optimized hidden battery pocket to place M12™ Battery in front or rear for increased comfort.
- Rugged heated hoodie made from durable cotton (53%) exterior with durable reinforced utility pockets and polyester fleece (47%) lining to withstand tough outdoor conditions.
- In autumn and spring the hoodie can be worn as a rugged outer layer. In winter, it is best as a base layer that allows to shed bulky undergarments while generating and holding heat close to the body.
- Multiple heating zones - 3 sewn in carbon fibre heating zones distribute heat to core body areas.
- Easy one-touch heat controller - 3 heat settings: High, Medium, Low.
- Integrated cell phone pocket.
- Machine washable and dryable.



	M12 HHLBL1-0 (S)	M12 HHLBL1-0 (M)	M12 HHLBL1-0 (L)	M12 HHLBL1-0 (XL)
Size	S	M	L	XL
Weight with battery pack (EPTA) (kg)	1,1kg	1,2kg	1,2kg	1,3kg
Kit included	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box	No batteries supplied, No charger supplied, Gift box
Article number	4932480090	4932480091	4932480092	4932480093
EAN code	4058546403751	4058546403768	4058546403775	4058546403782

L4 HBLB | USB RECHARGEABLE HEATED WORKSKIN™ BASE LAYER

- Mid-weight construction out of durable, pilling resistant material, keeps body warm and dry
- Fully heats-up in 2.5 min
- Heat is created and distributed to the chest and back
- Powered by L4 USB rechargeable REDLITHIUM™ battery pack
- A one-touch LED controller allows the user to select from 2 heat settings, delivering ideal heat for any environment
- Durable, pilling resistant material with raglan designed sleeves and seamless shoulders for improved mobility and comfort
- Superior run time – Up to 180 min of heat on low level
- L4 battery holder - concealed battery pocket for minimal user interference
- Machine washable



	L4 HBLB-301S	L4 HBLB-301M	L4 HBLB-301L	L4 HBLB-301XL	L4 HBLB-301XXL
Size	S	M	L	XL	XXL
Weight with battery pack (EPTA) (kg)	0.50 (L4 B3)	0.50 (L4 B3)	0.60 (L4 B3)	0.60 (L4 B3)	0.70 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, No charger supplied, No kitbox or bag supplied	1 x L4 B3 Battery pack, No charger supplied, No kitbox or bag supplied	1 x L4 B3 Battery pack, No charger supplied, No kitbox or bag supplied	1 x L4 B3 Battery pack, No charger supplied, No kitbox or bag supplied	1 x L4 B3 Battery pack, No charger supplied, No kitbox or bag supplied
Article Number	4933478459	4933478460	4933478461	4933478462	4933478463
EAN Code	4058546346508	4058546346515	4058546346522	4058546346539	4058546346546

WWLSG | WORKSKIN™ LIGHT WEIGHT PERFORMANCE LONG SLEEVE SHIRT - GREY

- Light weight to stay productive on the jobsite in hot weather conditions.
- Moisture wicking fabric, 100 % Polyester.
- Fast-drying, multi-layer mesh material in core sweat zones for great ventilation under the armpits, on the sides of the body and on the back.
- Raglan sleeves for comfortable carrying of tool bags, backpacks or climbing harnesses and providing a greater range of motion.



	WWLSG (S)	WWLSG (M)	WWLSG (L)	WWLSG (XL)	WWLSG (XXL)
Size	S	M	L	XL	XXL
Weight (kg)	0.1	0.1	0.1	0.1	0.1
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933478188	4933478189	4933478190	4933478191	4933478192
EAN Code	4058546341213	4058546341220	4058546341237	4058546341244	4058546341251

WWSSG | WORKSKIN™ LIGHT WEIGHT PERFORMANCE SHORT SLEEVE SHIRT - GREY

- Light weight to stay productive on the jobsite in hot weather conditions.
- Moisture wicking fabric, 100 % Polyester.
- Fast-drying, multi-layer mesh material in core sweat zones for great ventilation under the armpits, on the sides of the body and on the back.
- Raglan sleeves for comfortable carrying of tool bags, backpacks or climbing harnesses and providing a greater range of motion.



	WWSSG (S)	WWSSG (M)	WWSSG (L)	WWSSG (XL)	WWSSG (XXL)
Size	S	M	L	XL	XXL
Weight (kg)	0.1	0.1	0.1	0.1	0.1
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933478194	4933478195	4933478196	4933478197	4933478198
EAN Code	4058546341275	4058546341282	4058546341299	4058546341305	4058546341312

WTLSG | WORK T-SHIRT LONG SLEEVE - GREY

- Tear, abrasion resistant and breathable fabric
- 60/40 cotton-poly blend enables moisture wicking and water repels
- Heavy duty 230 GSM fabric weight



	WTLSG (S)	WTLSG (M)	WTLSG (L)	WTLSG (XL)	WTLSG (XXL)
Size	S	M	L	XL	XXL
Weight (kg)	0.1	0.1	0.1	0.1	0.1
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied
Article number	4933478237	4933478238	4933478239	4933478240	4933478241
EAN code	4058546344146	4058546344153	4058546344160	4058546344177	4058546344184

WTSSG | WORK T-SHIRT SHORT SLEEVE - GREY

- Tear, abrasion resistant and breathable fabric
- 60/40 cotton-poly blend enables moisture wicking and water repels
- Heavy duty 230 GSM fabric weight



	WTSSG (S)	WTSSG (M)	WTSSG (L)	WTSSG (XL)	WTSSG (XXL)
Size	S	M	L	XL	XXL
Weight (kg)	0.1	0.1	0.1	0.1	0.1
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied
Article number	4933478231	4933478232	4933478233	4933478234	4933478235
EAN code	4058546344085	4058546344092	4058546344108	4058546344115	4058546344122

WHB | WORK HOODIE BLACK

- Made from durable, breathable fabric for all-day protection to outlast the job
- Built with a tear- and abrasion-resistant 75/25 cotton/poly blend
- The fabric is wind resistant, and has comfortable fit rib-knit cuffs and waists, make these work hoodies great for the most demanding conditions
- Drawstring adjustable hood for perfect comfort
- Reinforced pocket seams, for a longer lifetime



	WHB (S)	WHB (M)	WHB (L)	WHB (XL)	WHB (XXL)
Size	S	M	L	XL	XXL
Weight (kg)	0.2	0.2	0.2	0.2	0.2
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied
Article number	4933478212	4933478213	4933478214	4933478215	4933478216
EAN code	4058546343897	4058546343903	4058546343910	4058546343927	4058546343934

PREMIUM HIGH-VISIBILITY VEST

- 15 pockets - increased carrying capacity.
- 1 clear ID badge holder - easy identification on the jobsite.
- 1 back pocket - ideal to carry tablet or notebook.
- Quick internal size adjustment - size up or size down for better fit.
- Padded collar - added comfort for extended wear.
- Harness tethering hole - ideal to fit over harness to add more safety on the jobsite.
- European Certified as Class 2 High Visibility Clothing according to EN ISO 20471: 2013/A1:2016.



	Colour	Size	Article Number	EAN Code
Premium high-visibility vest yellow - S/M	Yellow	S / M	4932471895	4058546297947
Premium high-visibility vest yellow - L/XL	Yellow	L / XL	4932471896	4058546297954
Premium high-visibility vest yellow - 2XL/3XL	Yellow	2XL / 3XL	4932471897	4058546297961
Premium high-visibility vest orange - S/M	Orange	S / M	4932471898	4058546297978
Premium high-visibility vest orange - L/XL	Orange	L / XL	4932471899	4058546297985
Premium high-visibility vest orange - 2XL/3XL	Orange	2XL / 3XL	4932471900	4058546297992

HIGH-VISIBILITY VEST

- 10 pockets - increased carrying capacity.
- 1 clear ID badge holder - easy identification on the jobsite.
- Quick internal size adjustment - size up or size down for better fit.
- Harness tethering hole - ideal to fit over harness to add more safety on the jobsite.
- European Certified as Class 2 High Visibility Clothing according to EN ISO 20471: 2013/A1:2016.



	Colour	Size	Article Number	EAN Code
High-visibility vest yellow - S/M	Yellow	S / M	4932471889	4058546297886
High-visibility vest yellow - L / XL	Yellow	L / XL	4932471890	4058546297893
High-visibility vest yellow - 2XL/3XL	Yellow	2XL / 3XL	4932471891	4058546297909
High-visibility vest orange - S/M	Orange	S / M	4932471892	4058546297916
High-visibility vest orange - L / XL	Orange	L / XL	4932471893	4058546297923
High-visibility vest orange - 2XL/3XL	Orange	2XL / 3XL	4932471894	4058546297930

NGFM | NECK GAITER & FACE MASK

- Multi-functional, wear it as a neck gaiter, face mask, headband, sweatband or headgear protection on the jobsite
- Moisture wicking fabric dries quickly, repels sweat & water, keeps users dry on the jobsite
- Breathable, comfortable fabric made from 86 % Polyester and 14 % Spandex
- 50+ UPF sun protection blocks 98 % of UV rays
- Shields from wind, dust and jobsite debris
- Turnback hem prevents the fabric from sliding down
- Washer and dryer safe
- One size fits most
- Available in colours grey and red



	NGFM-R	NGFM-G
Colour	Red	Grey
Material	86 % Polyester and 14 % Spandex	86 % Polyester and 14 % Spandex
Article Number	4933478780	4933478766
EAN Code	4058546360627	4058546360481

PERFORMANCE FACE COVERING

- Structured Fit Design - Separates mask from mouth.
- 3 Soft and Breathable Layers - all day comfort for long time wear.
- Comfortable Adjustable Ear Loops - No pressure on the ears.
- Water Repellent Outer Layer.
- Flexible Nose Bridge - Adjustability for a better sealing and to reduce fog on glasses.
- Moisture Wicking Inner Layer - Stay Cool, Dry Fast.
- Machine Washable.



	Size	Article number	EAN code
Performance Face Covering S/M - 3pcs	S / M	4932478865	4058546361471
Performance Face Covering L/XL - 3pcs	L / XL	4932478866	4058546361488

MILWAUKEE® GLOVES GUIDE

Rating		4	3	4	3	C	X
Abrasion	1-4	←	←	←	←	←	←
Cut (Coup Test)	1-5	←	←	←	←	←	←
Tear	1-4	←	←	←	←	←	←
Puncture	1-4	←	←	←	←	←	←
Cut (TDM-100 Test)	A-F	←	←	←	←	←	←
Impact Protection	P,FX	←	←	←	←	←	←
X= Not tested P= Pass X= Fail							

FEATURES KEY



EN388:2016



COMFORT



DEXTERITY



SMARTSWIPE™



CUT RESISTANCE



CUT RESISTANCE



CUT RESISTANCE



CUT RESISTANCE



CUT RESISTANCE



CUT RESISTANCE



HIGH VISIBILITY



BREATHABILITY



PUNCTURE RESISTANCE
& GRIP PERFORMANCE



WINTER



LEATHER



IMPACT RESISTANT



REINFORCED PALM



DURABILITY



REINFORCED WITH
ARMORTEX®



REINFORCEMENT

GLOVE TYPES

CUT RESISTANT GLOVES

PROTECTIVE SLEEVES

HI-VIS CUT RESISTANT GLOVES

HI-DEX CUT RESISTANT GLOVES

	CUT LEVEL A	CUT LEVEL B	CUT LEVEL C	CUT LEVEL D	CUT LEVEL E	CUT LEVEL F	CUT LEVEL C	CUT LEVEL E	HI-VIS CUT LEVEL A	HI-VIS CUT LEVEL B	HI-VIS CUT LEVEL C	HI-VIS CUT LEVEL D	HI-VIS CUT LEVEL E	HI-DEX CUT LEVEL B	HI-DEX CUT LEVEL C	HI-DEX CUT LEVEL D
FEATURES																
EN 388 RATING	4121A	4242B	4343C	4X43D	4X44E	4X43F	2342C	3X42E	3121A	3242B	4X42C	4X43D	4X43E	4242B	4342C	4X42D
COLOUR CODE																
GAUGE	13	15	15	13	13	18	15	13	15	15	15	13	13	18	18	18
COATING	Nitrile - Sandy	Nitrile - Sandy	Nitrile - Microfoam	Nitrile - Sandy	Nitrile - Sandy	Nitrile - Sandy	-	-	Polyurethane (PU)	Polyurethane (PU)	Polyurethane (PU)	Polyurethane (PU)	Polyurethane (PU)	Polyurethane (PU)	Polyurethane (PU)	Polyurethane (PU)
ENVIRONMENT	Dry, damp, oily (WASHABLE)	Dry, damp, oily (WASHABLE)	Dry, damp, oily (WASHABLE)	Dry, damp, oily (WASHABLE)	Dry, damp, oily (WASHABLE)	Dry, damp, oily (WASHABLE)	-	-	Dry (WASHABLE)	Dry (WASHABLE)	Dry (WASHABLE)	Dry (WASHABLE)	Dry (WASHABLE)	Dry (WASHABLE)	Dry (WASHABLE)	Dry (WASHABLE)
APPLICATIONS																
AUTOMOTIVE/ TRANSPORTATION	✓	✓	✓	-	-	-	✓	-	✓	✓	✓	✓	✓	✓	✓	✓
CARPENTRY	✓	✓	-	-	-	-	✓	-	✓	✓	-	-	-	✓	✓	-
CIVIL ENGINEERING	✓	✓	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CONSTRUCTION	✓	✓	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
DEMOLITION	-	-	✓	✓	✓	-	✓	✓	-	-	-	-	-	-	-	-
DRYWALL, CEILING AND PARTIONING	-	✓	✓	✓	-	-	✓	✓	-	✓	✓	✓	-	✓	✓	✓
LANDSCAPING AND HORTICULTURAL	✓	✓	-	-	-	-	✓	-	-	-	-	-	-	-	-	-
MAINTENANCE, REPAIR AND OPERATIONS	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MANUFACTURING	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ASSEMBLE	✓	✓	-	-	-	-	✓	-	✓	✓	-	-	-	✓	✓	✓
METALWORKING AND ENGINEERING	-	-	✓	✓	✓	✓	✓	✓	-	-	✓	✓	✓	-	✓	✓
HVAC	-	-	✓	✓	✓	✓	-	✓	-	-	✓	✓	✓	-	✓	✓
PLUMBING	✓	✓	✓	-	-	-	-	-	-	-	-	-	-	-	-	-
UTILITIES	✓	✓	✓	-	-	-	✓	-	✓	✓	✓	-	-	✓	✓	✓
OIL & GAS	✓	✓	✓	✓	✓	✓	-	-	-	-	-	-	-	-	-	-



MILWAUKEE® GLASSES GUIDE

GLASSES
TYPE

ENHANCED
SAFETY GLASSES



MAGNIFIED
SAFETY GLASSES



PERFORMANCE
SAFETY GLASSES



PREMIUM
SAFETY GLASSES



	CLEAR	GREY	TINTED	YELLOW
PART NUMBER	4932478763	4932478907	4932478764	4932478927
FRAME RATING	MT 166 FT CE	MT 166 FT CE	MT 166 FT CE	MT 166 FT CE
LENS RATING	2C-1.2 MT 1FT KN CE	—	5-3.1 MT 1FT KN CE	—
FEATURES				
REMOVABLE NOSE PIECE	✓	✓	✓	✓
COMFORT FIT	✓	✓	✓	✓
OPTICAL CLASS (CLASS 1)	✓	✓	✓	✓
EXTREME TEMP RESISTANCE (-5° C / +55° C)	✓	✓	✓	✓
ANTI-SCRATCH	✓	✓	✓	✓
ANTI-FOG	✓	✓	✓	✓
REMOVABLE GASKET	—	—	—	—
LIGHTWEIGHT	✓	✓	✓	✓
MAGNIFIEDED	—	—	—	—
SOFT CASE	—	—	—	—
POLARIZED LENSES	—	—	—	—
OPTICAL CORRECTION	—	—	—	—
APPLICATIONS				
INDOOR WORK	✓	✓	—	—
OUTDOOR WORK	—	✓	✓	—
SUNNY ENVIRONMENT	—	—	✓	—
INDUSTRIAL LIGHTNING	—	—	—	✓
CLOSE APPLICATION	—	—	—	—
DUSTY ENVIRONMENT	—	—	—	—

MAGNIFIED
49324789- 09 / 10 / 11 / 12
MT 166 FT CE
MT 1FT K CE
✓
✓
✓
✓
✓
—
—
✓
✓
+1 / +1.5 / +2 /+ 2.5
✓
—
—
—
✓
—

CLEAR	GREY	TINTED	YELLOW
4932471883	4932478908	4932471884	4932478928
MT 166 FT CE	MT 166 FT CE	MT 166 FT CE	MT 166 FT CE
2C-1.2 MT 1FT KN CE	—	5-3.1 MT 1FT KN CE	—
—	—	—	—
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
✓	✓	—	—
—	✓	✓	—
—	—	✓	—
—	—	—	✓
—	—	—	—
—	—	—	—

CLEAR	POLARIZED
4932471885	4932471886
MT 166 FT CE	MT 166 FT CE
2C-1.2 MT 1FT KN CE	5-3.1 MT 1FT KN CE
—	—
✓	✓
✓	✓
✓	✓
✓	✓
✓	✓
✓	✓
✓	✓
—	—
—	—
✓	✓
—	✓
—	—
✓	—
—	✓
—	✓
—	—
—	—
✓	✓

TOOL DROP PREVENTION

MILWAUKEE® LANYARDS



WHY MILWAUKEE® LANYARDS?

A **FALLING OBJECT** IS THE **3RD HIGHEST** CAUSE OF **FATALITY** ON A JOBSITE.

(Peoplesafe.co.uk, 2019)

TOOL DROP PREVENTION

LOCKING TOOL LANYARDS

WRIST TOOL LANYARD

RETRACTABLE TOOL LANYARD

TOOL LANYARD ACCESSORIES

NAME	4.5 KG LOCKING TOOL LANYARD	4.5 KG QUICK CONNECT LOCKING TOOL LANYARD	6.8 KG LOCKING TOOL LANYARD	15.8 KG LOCKING TOOL LANYARD	WRIST LANYARD	WRIST LANYARD W/ QUICK CONNECT		QUICK CONNECT RETRACTABLE TOOL LANYARD		ANCHORING STRAP	D-RING WEB	SMALL QUICK CONNECT	SPLIT RINGS 38 mm / 50 mm	SELF-ADHERING TAPE 3.6 m
PART NUMBER	4932471351	4932471429	4932471352	4932471353	4932472107	4932472108		4932472106		4932472105	4932471431	4932471430	4932471433 (38 mm) 4932471434 (50 mm)	48228860
WEIGHT CAPACITY	4.5 KG	4.5 KG	6.8 KG	15.8 KG	2.2 KG	2.2 KG		2.2 KG		22.7 KG	2.2 KG	2.2 KG	1 KG	-
COLOUR CODING	RED	RED	BLACK	GREY	WHITE	WHITE		WHITE		GREEN	WHITE	WHITE	-	-
TETHER MECHANISM													-	-
COMPATIBLE WITH	ANCHORING STRAP	ALL ACCESSORIES	ANCHORING STRAP	ANCHORING STRAP	-	ALL ACCESSORIES		ALL ACCESSORIES		ALL LOCKING TOOL LANYARDS	SELF-ADHERING TAPE & 4.5 KG QUICK CONNECT LOCKING TOOL LANYARD	4.5 KG QUICK CONNECT LOCKING TOOL LANYARD	4.5 KG QUICK CONNECT LOCKING TOOL LANYARD	D-RING WEB
INTEGRATED SWIVEL	✓	✓	✓	✓	-	-		✓		-	-	-	-	-
SUITABLE PRODUCTS*	DRILL DRIVER IMPACT DRIVER IMPACT WRENCH JIGSAW HACKZALL SAWZALL SHEARS	HANDTOOLS WITH LANYARD ACCESSORY ATTACHED	ANGLE GRINDER DRILL DRIVER IMPACT DRIVER IMPACT WRENCH SDS PLUS HACKZALL SAWZALL BANDSAWS	SDS PLUS SDS MAX MAG PRESS IMPACT DRIVER IMPACT WRENCH BANDSAWS CHAINSAW	DRILL DRIVERS IMPACT DRIVERS IMPACT WRENCH HANDTOOLS	DRILL DRIVERS IMPACT DRIVERS IMPACT WRENCH HANDTOOLS		DRILL DRIVERS IMPACT DRIVERS IMPACT WRENCH HANDTOOLS		ALL LOCKING TOOL LANYARDS	HANDTOOLS WITHOUT LANYARD HOLE HAMMERS CUTTERS PLIERS	HANDTOOLS WITH LANYARD HOLE SCREWDRIVERS TAPES PLIERS	HANDTOOL WITH LANYARD HOLE KNIVES TAPES PLIERS	D-RING WEB
APPLICATION														

*All product recommendations are only references and are not guaranteed!
Please make sure that the total weight of the tethered product (+ Battery) does not exceed the weight capacity of the tool lanyard!

ELECTRICAL SPECIALIST



M18 HCC75R

M18™ FORCE LOGIC™ HYDRAULIC REMOTE UNDERGROUND CABLE CUTTER

- FORCE LOGIC™ hydraulic remote underground cable cutter cuts cables in less than 10 seconds with 77.8 kN of force
- Wireless remote communicates with the tool via a mutually exclusive Bluetooth® connection, removing any physical connection to the tool and allowing Linemen to make remote cuts WIRELESSLY
- Balanced design, handle and hang hook enable easiest set-up in vaults
- Cuts aluminium & copper cables up to 75 mm
- Green LED light on wireless remote gives positive indication that the tool is done cutting
- Converts from Local to Remote cutting mode easily
- Open jaw design provides easiest access in trenches
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. The reporting function delivers a complete tool activity and accuracy protocol
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 HCC75R-502C	
Cutting force (kN)	77.8
Max. cutting diameter (mm)	75
Cutting time [s]	<10
Weight with battery pack (EPTA) (kg)	7.9 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933459272
EAN Code	4058546002381

UNDERGROUND CUTTER BLADE M18 HCC75	
Article Number	49162774
	



M18 HCC45 | M18™ FORCE LOGIC™ HYDRAULIC 44 MM CABLE CUTTER

- FORCE LOGIC™ hydraulic cable cutter cuts ACSR/ACSS cables in less than 9 seconds with 77.8 kN of force
- Patent pending jaw design enables opening with just two fingers, enhancing alignment while delivering easiest operation with Class 3 gloves
- Wire automatically closes the jaw, providing hands-free jaw closure and the easiest mid-span cuts. Fully balanced design delivers the best control
- Cuts ACSR and ACSS transmission line cables up to 44 mm
- 340° rotatable head powered by a 77.8 kN hydraulic pump delivers the fastest transmission wire cuts for enhanced productivity
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. The reporting function delivers a complete tool activity and accuracy protocol
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 HCC45-522C	
Cutting force (kN)	77.8
Max. cutting diameter (mm)	44
Cutting time [s]	<9
Weight with battery pack (EPTA) (kg)	6.0 (M18 B2)
Kit included	1 x M18 B5, 1 x M18 B2 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933459267
EAN Code	4058546002336












M18 ONEHCC | M18™ FORCE LOGIC™ HYDRAULIC 35 MM CABLE CUTTER

- FORCE LOGIC™ hydraulic cable cutter cuts cables in less than 3 seconds with 53 kN of force
- Brushless POWERSTATE™ motor provides more power, more run-time and longer life
- Fully balanced tool provides secure control during one hand operation
- One tool provides cutting solutions for ACSR wire, steel guy wire, fine stranded or standard copper and aluminium cable
- Quick jaw reception enables user to retool for a complete new application in less than 15 seconds
- Compact in-line and slim jaw design with 350° rotatable head allows easy cuts, even in narrow spaces
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. The reporting function delivers a complete tool activity and accuracy protocol
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 ONEHCC-0C CU/AL- SET	M18 ONEHCC-201C CU/AL-SET	M18 ONEHCC-0C ACSR SET	M18 ONEHCC-201C ACSR SET	M18 ONEHCC-201C SWA
Cutting force (kN)	53	53	53	53	53
Max. cutting diameter (mm)	35	35	22.5	22.5	35
Cutting time [s]	<3	<3	<3	<3	<3
Suitable for cutting material	Cu & AL cable (Class 1-4)	Cu & AL cable (Class 1-4)	Cu & AL cable (Class 1-4)	AL conductor steel reinforced	Steel wire armored Cu/AL cable
Weight with battery pack (EPTA) (kg)	3.7 (M18 B2)	3.7 (M18 B2)	3.7 (M18 B2)	3.7 (M18 B2)	3.7 (M18 B2)
Standard equipment	Cu/AL jaw	Cu/AL jaw	ACSR jaw	ACSR jaw	SWA jaw
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox	No batteries supplied, No charger supplied, Kitbox	1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox	1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox
Article Number	4933464300	4933464302	4933464303	4933464305	4933464307
EAN Code	4058546222451	4058546222475	4058546222482	4058546222505	4058546222529

M18 ONEHCC HYDRAULIC CABLE CUTTER JAWS AND BLADES

	Description	Article Number	EAN Code	
1.	Cable cutter jaw and blade set for cutting copper/aluminium. Copper/aluminium standard stranded cable up to 4 x 50 mm², 1 x 500 mm² in aluminium and 1 x 400 mm² in copper. Not suitable for fine stranded/highly flexible cable. Max. cutting Ø35 mm	4932430839	4002395385010	
	Cu/Al standard copper & aluminium cable cutting blades. The blades fit for the Cu/Al cutting jaws for M18HCC & ONEHCC cutters + M18 HCCT crimper cutting jaw	4932464498	4058546224431	
2.	Cable cutter jaw and blade set for cutting aluminium-steel transmission cable. ACSS-aluminium conductor steel supported cable and ACSR-aluminium conductor steel reinforced cable i.e. 94-AL1 / 15-ST1A (EN 50182). Not suitable for armoured cable or steel rods. Max. cutting Ø22.5 mm	49162773	045242350070	
	Replacement cable cutter blades for ACSR-jaw. Not suitable for armoured cable or steel rods.	48440412	045242355235	
3.	Cutting jaw and blades for EHS grade guy wire, stay wire & steel wire according to DIN48201/3 guy wire of grade ST1/ST2/ST3. Not suitable for fine stranded steel ropes. Max. cutting Ø15 mm	49162777	045242505449	
	EHS guy wire/steel wire cutting blades	48442777	045242505456	
4.	Cable cutter jaw and blades for class 5 fine stranded wire and class 6 finest stranded wire according to IEC 60228/DIN VDE 0295 standards. Also suitable for high flexible data- and telecomcable. Not suitable for thick stranded cables. Max. cutting Ø35 mm	49162778	045242505722	
	FSW fine stranded wire cutting blade	48442778	045242505739	
5.	Armoured cable cutting Jaw for M18 HCC	4932464867	4058546228125	

M18 HKP | M18™ FORCE LOGIC™ HYDRAULIC KNOCKOUT PUNCH

- FORCE LOGIC™ hydraulic knockout punch is the most compact and lightweight tool on the market with 60 kN of force
- The easiest way to punch - for fast, accurate, round, and burr free holes
- Highest accuracy due to industry's finest exact alignment system for dies
- Best balanced tool and easiest control due to one hand operation
- Quick connector allows easy set-up of punch and die without carrying the weight of the tool
- Tool punches up to Ø100 mm holes into 3.0 mm mild steel or 2.5 mm stainless steel
- Compatible with most common punches and dies available on market
- Easiest, less strenuous and nonexpendable way of making holes into sheet metal
- On board fuel gauge and LED light
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 HKP-201CA	
Punching force [kN]	60
Max. punching diameter [mm]	100
Max. material thickness (mm)	2.5 in stainless and 3.0 in mild steel
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)
Standard equipment	11.1mm (7/16) draw stud, 19mm (3/4) draw stud, quick connector, ball pull, adaptor, punches and dies: M16, M20, M25, M32, M40
Kit included	1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox
Article Number	4933451205
EAN Code	4002395138937

M18 HKP HYDRAULIC KNOCKOUT PUNCH ACCESSORIES

Description	Ø (mm)	Article Number	EAN Code		Description	Ø (mm)	Article Number	EAN Code	
Punch M16	16.2	4932430841	4002395385034		Die M16	16.2	4932430913	4002395385751	
Punch PG16	22.5	4932430843	4002395385058		Die PG16	22.5	4932430915	4002395385775	
Punch M20	20.4	4932430842	4002395385041		Die M20	20.4	4932430914	4002395385768	
Punch PG21	28.3	4932430845	4002395385072		Die PG21	28.3	4932430917	4002395385799	
Punch M25	25.4	4932430844	4002395385065		Die M25	25.4	4932430916	4002395385782	
Punch M32	32.5	4932430846	4002395385089		Die M32	32.5	4932430918	4002395385805	
Punch M40	40.5	4932430847	4002395385096		Die M40	40.5	4932430919	4002395385812	
Punch M50	50.5	4932430848	4002395385102		Die M50	50.5	4932430920	4002395385829	
Punch M63	63.5	4932430849	4002395385119		Die M63	63.5	4932430921	4002395385836	
Draw bolt 11.1 mm (7/16)		49162680	045242311774						
Draw bolt 19 mm (3/4)		49162681	045242311781						

M18 HUP700
M18™ HYDRAULIC UTILITY PUMP

- FORCE LOGIC™ hydraulic utility pump powers every single acting 700 bar crimping, cutting or punching head attachment
- Significantly faster work cycles due to a large 1.6 litre total oil reservoir and 2x higher flow rate compared to other pumps
- The pump is equipped with a industry standard CEJN Series 115, G1/4" female quick connection coupler to suit most common attachments
- 1.8 meter long corded controller enables user to work away from pump and can be extended up to 7 meters with accessory extension cords
- IP54 rated ingress protection with sealed battery door delivers best protection in harsh environments such as dirt, dust and moisture
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. The reporting function delivers a complete tool activity and accuracy protocol
- Well balanced lifting handle provides even weight distribution for easy transportation from truck to bucket
- PFM™ (Predictive Force Monitoring) provides you with instant pressure verification via a green indicator
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 HUP700-121	
Max. pressure [bar/PSI]	700 / 10.000
IP protection class	54
Flow Rate Low Pressure [litres per minute]	2.05
Flow Rate High Pressure [litres per minute]	0.42
Coupler Type	CEJN G1/4"
Total oil volume [l]	1.6
Consumable oil volume [l]	1.3
Weight with battery pack (EPTA) (kg)	16.5 (M18 HB12)
Kit included	1 x M18 HB12 Battery pack, M12-18 FC Charger, No kitbox or bag supplied
Article Number	4933471860
EAN Code	4058546297596



1.8 meter long corded controller enables user to work away from pump



Well balanced lifting handle



ONE-KEY™ technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the cloud

M18 HUP700 HYDRAULIC PUMP SYSTEM ATTACHMENTS

1.8 m extension cord for M18 HUP controller	Bucket hanger for M18 HUP700	Replacement oil M18 HUP700
49122775 4058546326487	49122776 045242535231	4932472004 4058546324001

M18 FPFT | M18 FUEL™ POWERED FISH TAPE

- The M18 FUEL™ Fish Tape is the world's first professional battery powered cable pulling solution
- POWERSTATE™ brushless motor that provides the ability to pull a maximum length of 72 m wire
- AUTO-RUN™ powered feeding and cable pulling is a fast and efficient solution providing higher productivity vs other solutions
- Less user fatigue due to powered wire pulling, especially when working on overhead installations
- Quick tool free drum exchange with 4 compatible interchangeable drums, Steel Tape: 36 and 72 m / Non-conductive Tape: 30 and 60 m
- Proprietary anti-binding drum design for smoother feeding and retracting
- Variable speed trigger for maximum control during tape feeding and wire pulling
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FPFT-0	M18 FPFT-202 30m NC Set
Weight with battery pack (EPTA) (kg)	6.4 (M18 B2)	6.4 (M18 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B2 Battery packs, M12-18 FC , No kitbox or bag supplied
Article Number	4933471952	4933478591
EAN Code	4058546298517	4058546347840

M18 FUEL™ FISH TAPE COMPATIBLE DRUMS

	Description	Article Number	EAN Code	
Steel fish drums	36 m x 3 mm steel fish drum	48445176	4058546326432	
	72 m x 3 mm steel fish drum	48445178	4058546326449	
Non-conductive drums	30 m non-conductive polyester drum	48445195	4058546326463	
	60 m non-conductive polyester drum	48445197	4058546326470	

M18 HDCT | M18™ FORCE LOGIC™ HYDRAULIC DIELESS CRIMPER

- M18™ FORCE LOGIC™ HDCT crimps connectors on flexible wire from 10 to 300 mm² without changing dies
- Auto distance control continuously measures distance & pressure for uniform crimp appearance across every size of the crimping range
- 180° rotating head and easy access latch deliver easy alignment and free-up second hand to hold material
- PFM™ (Predictive Force Monitoring) with auto complete ensures full pressure and provides instant pressure verification with green indicator
- The tool records & stores every crimp made for professional report building through both ONE-KEY™ App
- Pre-crimp battery check automatically ensures enough charge to complete each crimp
- Up to 90 crimps per charge on a M18™ REDLITHIUM™ 2.0 Ah battery pack
- Sealed electronics resist harsh environments with dirt, dust and moisture
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 HDCT-0C
Crimping range [mm2]	10 - 300
Crimps per battery	Up to 90 crimps on a M18™ 2.0 Ah pack
Weight with battery pack (EPTA) (kg)	4.5 (M18 B2)
Kit included	No batteries supplied, No charger supplied, Kitbox
Article Number	4933471949
EAN Code	4058546298487

M18 HCCT109/42 | M18™ FORCE LOGIC™ HYDRAULIC 109 KN CABLE CRIMPER

- Lightest, most balanced tool with ergonomic grip design
- Red alignment marks on the tool jaws aid accuracy in crimp placement
- Sealed electronics resist harsh environments with dirt, dust and moisture
- 42 mm jaw opening and 350° head rotation provides easy positioning and access, even for large connectors
- Crimps connectors with 109 kN of force
- PFM™ (Predictive Force Monitoring) with auto complete ensures full pressure and provides instant pressure verification with green indicator
- Allows to crimp connectors up to 400 mm²
- Universal die reception to fit most common U-Dies (C shaped dies) on the market
- The tool records & stores every crimp made for professional report building through both ONE-KEY™ app and ONE-KEY™ adaptor
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Pre-crimp battery check automatically ensures enough charge to complete each crimp
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 HCCT109/42-522C
Crimping force [kN]	109
Crimping range [mm2]	16 - 400
Jaw opening capacity for connector [mm]	42
Weight with battery pack (EPTA) (kg)	5.6 (M18 B2)
Kit included	1 x M18 B5, 1 x M18 B2 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933459274
EAN Code	4058546002404

M18 ONEHCCT60 | M18™ FORCE LOGIC™ HYDRAULIC 60 KN CABLE CRIMPER

- FORCE LOGIC™ hydraulic cable crimper crimps connectors in less than 5 seconds with 60 kN of force
- Easy die alignment and linear movement ensure most uniform crimp results
- Improved ergonomics and slim handle design provide for a comfortable one-handed operation
- Easy to reach electronic release button within grip area allows users to reset a crimp conveniently at any time
- The quick latching head is rotatable by 350° and has an integrated light which perfectly illuminates the crimp surface
- PFM™ (Predictive Force Monitoring): Automatically modifies output based on connector, ensuring optimal pressure every time and visualises with a green light
- Allows crimping of connectors up to 300 mm² in copper and aluminium
- Universal die reception is compatible with MILWAUKEE® 22-series die range and most common 60 kN U-dies (C shaped dies) on the market
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. The reporting function delivers a complete tool activity and accuracy protocol



	M18 ONEHCCT60-202C
Crimping force [kN]	60
Crimping range [mm2]	6 - 300
Crimping time [s]	5
Crimps per battery	>150 on a 50 mm² copper connector
Weight with battery pack (EPTA) (kg)	3.8 (M18 B2)
Kit included	2 x M18 B2 Battery packs, M12-18 C Charger, Kitbox
Article number	4933479685
EAN code	4058546374792

M18 HCCT | M18™ FORCE LOGIC™ HYDRAULIC 53 KN CABLE CRIMPER

- FORCE LOGIC™ hydraulic cable crimper crimps connectors in less than 3 seconds with 53 kN of force
- Revolutionary jaw holds connector for best alignment of cable and connector
- 2 in 1 solution: crimping jaw can be exchanged for an CU/AL cable cutting jaw
- Best balanced tool and easiest control due to one hand operation
- Compact in-line and slim jaw design with 350° rotatable head allows easy crimps, even in narrow spaces
- PFM™ (Predictive Force Monitoring): Automatically modifies output based on connector, ensuring optimal pressure every time and visualises with a green light
- Allows crimping of connectors up to 300 mm²
- Universal die reception to fit most common 60 kN U-Dies (C shaped dies) on the market
- The tool records & stores every crimp made for professional report building through both ONE-KEY™ app and ONE-KEY™ adaptor
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Pre-crimp battery check automatically ensures enough charge to complete each crimp



	M18 HCCT-201C	M18 HCCT-201C L-SET
Crimping force [kN]	53	53
Crimping range [mm2]	16 - 300	16 - 240
Crimping time [s]	< 3	< 3
Crimps per battery	> 250 on a 70 mm² copper connector	> 250 on a 70 mm² copper connector
Weight with battery pack (EPTA) (kg)	3.7 (M18 B2)	3.7 (M18 B2)
Kit included	1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox	1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox
Article Number	4933451195	4933464313
EAN Code	4002395138838	4058546222581

M18 BLTRC | M18™ BRUSHLESS THREADED ROD CUTTER

- M18™ brushless threaded rod cutter delivers a fast and effortless solution for cutting threaded rods
- Integrated brushless motor provides the user the power to cut through M6, M8, M10 and M12 mild steel or M6, M8 and M10 stainless steel threaded rod, with a run time of up to 300 cuts with a 2.0 Ah battery
- Included cutting dies cover the most common sizes of threaded rod: M6, M8, M10 and M12, which can be changed by rotating the dies
- Optimised tool handling allows better visibility, guarantees easy alignment and precise cut accuracy
- Intelligent design delivers optimum balance for overhead cutting, as well as great stability for pre-fab applications
- Fully balanced tool, with a centred grip design, provide a perfect one handed operation
- Automatically opens dies after a cut is complete to allow the user to do fast repetitive cuts
- The tool provides the ability to cut short pieces with a minimum length of 3.8 cm
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BLTRC-0X	M18 BLTRC-522X
Weight with battery pack (EPTA) (kg)	3.9 (M18 B2)	3.9 (M18 B2)
Standard equipment	M6, M8, M10 & M12 cutting dies	M6, M8, M10 & M12 cutting dies
Kit included	No batteries supplied, No charger supplied, HD Box	1 x M18 B5, 1 x M18 B2 Battery packs, M12-18 C Charger, HD Box
Article Number	4933471150	4933471152
EAN Code	4058546287788	4058546287801



CRIMPING DIES

Type	Form	Cable lug size [mm2]	Imprint code	M18 HCCT			M18 HCCT109/42		
				Description	Article number	EAN code	Description	Article number	EAN code
DIN 46235 for copper compression cable lugs and connectors (DIN 46267)	Hex	16	8	DIN22 Cu 16	4932451744	4002395277551	DIN13 Cu 16	4932459465	4058546011260
		25	10	DIN22 Cu 25	4932451745	4002395277568	DIN13 Cu 25	4932459466	4058546011277
		35	12	DIN22 Cu 35	4932451746	4002395277575	DIN13 Cu 35	4932459467	4058546011284
		50	14	DIN22 Cu 50	4932451747	4002395277582	DIN13 Cu 50	4932459468	4058546011291
		70	16	DIN22 Cu 70	4932451748	4002395277599	DIN13 Cu 70	4932459469	4058546011307
		95	18	DIN22 Cu 95	4932451749	4002395278206	DIN13 Cu 95	4932459470	4058546011314
		120	20	DIN22 Cu 120	4932451750	4002395278213	DIN13 Cu 120	4932459471	4058546011321
		150	22	DIN22 Cu 150	4932451751	4002395278220	DIN13 Cu 150	4932459472	4058546011338
		185	25	DIN22 Cu 185	4932451752	4002395278237	DIN13 Cu 185	4932459473	4058546011345
		240	28	DIN22 Cu 240	4932451753	4002395278244	DIN13 Cu 240	4932459474	4058546011352
		300	32	DIN22 Cu 300	4932451754	4002395278251	DIN13 Cu 300	4932459475	4058546011369



Type	Form	Cable lug size [mm2]	Imprint code	M18 HCCT			M18 HCCT109/42		
				Description	Article number	EAN code	Description	Article number	EAN code
Tubular cable lugs and connectors	Hex	16	16	R22 Cu 16	4932451755	4002395278268	R13 Cu 16	4932459494	4058546011550
		25	25	R22 Cu 25	4932451756	4002395278275	R13 Cu 25	4932459495	4058546011567
		35	35	R22 Cu 35	4932451757	4002395278282	R13 Cu 35	4932459496	4058546011574
		50	50	R22 Cu 50	4932451758	4002395278299	R13 Cu 50	4932459497	4058546011581
		70	70	R22 Cu 70	4932451759	4002395278909	R13 Cu 70	4932459498	4058546011598
		95	95	R22 Cu 95	4932451760	4002395278916	R13 Cu 95	4932459499	4058546011604
		120	120	R22 Cu 120	4932451761	4002395278923	R13 Cu 120	4932459500	4058546011611
		150	150	R22 Cu 150	4932451762	4002395278930	R13 Cu 150	4932459501	4058546011628
		185	185	R22 Cu 185	4932451763	4002395278947	R13 Cu 185	4932459502	4058546011635
		240	240	R22 Cu 240	4932451764	4002395278954	R13 Cu 240	4932459503	4058546011642
		300	300	R22 Cu 300	4932451765	4002395278961	R13 Cu 300	4932459504	4058546026769
		400	400	-	-	-	R13 Cu 400	4932459505	4058546026776



Type	Form	Cable lug size [mm2]	Imprint code	M18 HCCT			M18 HCCT109/42		
				Description	Article number	EAN code	Description	Article number	EAN code
NF C 20-130 for copper compression cable lugs	Hex	16	16	NF22 Cu 16	4932451733	4002395276837	NF13 Cu 16	4932459453	4058546011147
		25	25	NF22 Cu 25	4932451734	4002395276844	NF13 Cu 25	4932459454	4058546011154
		35	35	NF22 Cu 35	4932451735	4002395276851	NF13 Cu 35	4932459455	4058546011161
		50	50	NF22 Cu 50	4932451736	4002395276868	NF13 Cu 50	4932459456	4058546011178
		70	70	NF22 Cu 70	4932451737	4002395276875	NF13 Cu 70	4932459457	4058546011185
		95	95	NF22 Cu 95	4932451738	4002395276882	NF13 Cu 95	4932459458	4058546011192
		120	120	NF22 Cu 120	4932451739	4002395276899	NF13 Cu 120	4932459459	4058546011208
		150	150	NF22 Cu 150	4932451740	4002395277506	NF13 Cu 150	4932459460	4058546011215
		185	185	NF22 Cu 185	4932451741	4002395277513	NF13 Cu 185	4932459461	4058546011222
		240	240	NF22 Cu 240	4932451742	4002395277520	NF13 Cu 240	4932459462	4058546011239
		300	300	NF22 Cu 300	4932451743	4002395277544	NF13 Cu 300	4932459463	4058546011246
		400	400	-	-	-	NF13 Cu 400	4932459464	4058546011253



Type	Form	Cable lug size [mm2]	Imprint code	M18 HCCT			M18 HCCT109/42		
				Description	Article number	EAN code	Description	Article number	EAN code
Copper solderless terminals (DIN 46234, DIN 46230, DIN 46341)	Half round indent	16	16	Q22 CU 16	4932451766	4002395278978	Q13 CU 16	4932459477	4058546011383
		25	25	Q22 CU 25	4932451767	4002395278985	Q13 CU 25	4932459478	4058546011390
		35	35	Q22 CU 35	4932451768	4002395278992	Q13 CU 35	4932459479	4058546011406
		50	50	Q22 CU 50	4932451769	4002395279609	Q13 CU 50	4932459480	4058546011413
		70	70	Q22 CU 70	4932451770	4002395279616	Q13 CU 70	4932459481	4058546011420
		95	95	-	-	-	Q13 CU 95	4932459482	4058546011437



Type	Form	Cable lug size [mm2]	Imprint code	M18 HCCT			M18 HCCT109/42		
				Description	Article number	EAN code	Description	Article number	EAN code
DIN Aluminium for aluminium compression cable lugs and connectors (DIN 46329, 46267 Part 1 and 2, DIN EN 50182)	Hex	16/25	12	DIN22 AL 16/25	4932451771	4002395279623	DIN13 AL 16/25	4932459506	4058546026783
		35	14	DIN22 AL 35	4932451772	4002395279630	DIN13 AL 35	4932459507	4058546026790
		50	16	DIN22 AL 50	4932451773	4002395279647	DIN13 AL 50	4932459508	4058546026806
		70	18	DIN22 AL 70	4932451774	4002395279654	DIN13 AL 70	4932459509	4058546026813
		95/120	22	DIN22 AL 95/120	4932451775	4002395279661	DIN13 AL 95/120	4932459510	4058546026820
		150	25	DIN22 AL 150	4932451776	4002395279678	DIN13 AL 150	4932459511	4058546026837
		185	28	-	-	-	DIN13 AL 185	4932459512	4058546026844
		240	32	-	-	-	DIN13 AL 240	4932459513	4058546026851
		300	34	-	-	-	DIN13 AL 300	4932459514	4058546026868



Type	Form	Cable lug size [mm2]	Imprint code	M18 HCCT			M18 HCCT109/42		
				Description	Article number	EAN code	Description	Article number	EAN code
Copper tubular cable lugs and connectors like L series	Hex	16	8	L22 Cu 16	4932464487	4058546224325	L13 Cu 16	4932464500	4058546224455
		25	10	L22 Cu 25	4932464488	4058546224332	L13 Cu 25	4932464501	4058546224462
		35	12	L22 Cu 35	4932464489	4058546224349	L13 Cu 35	4932464502	4058546224479
		50	14	L22 Cu 50	4932464490	4058546224356	L13 Cu 50	4932464503	4058546224486
		70	16	L22 Cu 70	4932464491	4058546224363	L13 Cu 70	4932464504	4058546224493
		95	18	L22 Cu 95	4932464492	4058546224370	L13 Cu 95	4932464505	4058546224509
		120	20	L22 Cu 120	4932464493	4058546224387	L13 Cu 120	4932464506	4058546224516
		150	22	L22 Cu 150	4932464494	4058546224394	L13 Cu 150	4932464507	4058546224523
		185	25	L22 Cu 185	4932464495	4058546224400	L13 Cu 185	4932464508	4058546224530
		240	28	L22 Cu 240	4932464496	4058546224417	L13 Cu 240	4932464509	4058546224547
		300	32	-	-	-	L13 Cu 300	4932464510	4058546224554



Type	Form	Cable lug size [mm2]	Imprint code	M18 HCCT			M18 HCCT109/42		
				Description	Article number	EAN code	Description	Article number	EAN code
Pre rounding of triangular shaped aluminium and copper conductors	Round	16	-	RU22 Cu/Al 16	4932451780	4002395276912	RU13 Cu/Al16	4932459483	4058546011444
		35/25	-	RU22 Cu35/AL25	4932451781	4002395276929	RU13 Cu35/AL25	4932459484	4058546011451
		50/35	-	RU22 Cu50/AL35	4932451782	4002395276936	RU13 Cu50/AL35	4932459485	4058546011468
		70/50	-	RU22 Cu70/AL50	4932451783	4002395276943	RU13 Cu70/AL50	4932459486	4058546011475
		95/70	-	RU22 Cu95/AL70	4932451784	4002395276950	RU13 Cu95/AL70	4932459487	4058546011482
		120/95	-	RU22 Cu120/AL95	4932451785	4002395276967	RU13 Cu120/AL95	4932459488	4058546011499
		150/120	-	RU22 Cu150/AL120	4932451786	4002395276974	RU13 Cu150/AL120	4932459489	4058546011505
		185/150	-	RU22 Cu185/AL150	4932451787	4002395276981	RU13 Cu185/AL150	4932459490	4058546011512
		240/185	-	RU22 Cu240/AL185	4932451788	4002395276998	RU13 Cu240/AL185	4932459491	4058546011529
		300/240	-	RU22 Cu300/AL240	4932451789	4002395277605	RU13 Cu300/AL240	4932459492	4058546011536



Type	Form	Cable lug size [mm2]	Imprint code	M18 HCCT			M18 HCCT109/42		
				Description	Article number	EAN code	Description	Article number	EAN code
Ferruls	Trapezoid	16	-	-	-	-	AEH13 Cu 16	4932459515	4058546026875
		25	-	-	-	-	AEH13 Cu 25	4932459516	4058546026882
		35	-	-	-	-	AEH13 Cu 35	4932459517	4058546026899
		50	-	-	-	-	AEH13 Cu 50	4932459518	4058546026905
		70	-	-	-	-	AEH13 Cu 70	4932459519	4058546026912
		95	-	-	-	-	AEH13 Cu 95	4932459520	4058546026929
		120	-	-	-	-	AEH13 Cu 120	4932459521	4058546026936
		150	-	-	-	-	AEH13 Cu 150	4932459522	4058546026943
		185	-	-	-	-	AEH13 Cu 185	4932459523	4058

M18 UBL

M18™ LED UTILITY BUCKET LIGHT

- Dual light head design with 180° of vertical and horizontal head rotation, heads can be rotated individually
- 3 output modes: Spot, Flood, Spot/Flood provides up to 2500 lumens and up to 457 m of beam distance on Flood mode
- Patented spring loaded bucket clamp for most bucket sizes
- IP56 to withstand harsh weather conditions
- Low battery indicator alerts users when the battery is nearing end of charge



	M18 UBL-0
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output Spot_flood/FloodSpot/Strobe [lumens]	2200/ 2500/ 800/ -
Max. run time with M18 B9 battery [h]	4/ 4/ 6/ -
Weight with battery pack (EPTA) (kg)	4.3 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459433
EAN Code	4058546010942

TRUEVIEW™

2235-40 | LIGHT COMMERCIAL CLAMP METER

- TRMS always guarantees accurate readings
- CAT III 600 V for increased safety
- Rugged over-moulding increases durability and user grip
- Built-in LED work light – lights the work area
- Side mounted dial for one-handed use
- Thin jaw profile for easier wire measurement in panels or in bundles
- Supplied with electrical test lead set and 2 x AA batteries



	2235-40
Jaw size (mm)	25
AC Amps [A]	400
Lo-Z measurement	No
Resistance (kΩ)	0.4
Continuity	Yes
Weight with battery pack (EPTA) (kg)	0.30 (2 x AA)
Kit included	2 x AA Batteries, No kitbox or bag supplied
Article Number	4933427315
EAN Code	4002395240135

2200-40 | VOLTAGE DETECTOR

- Wide 50 - 1000 AC voltage range
- CAT IV 1000 V for highest safety rating
- Tip for checking outlets
- Green light indicates tool is on
- Loud beeper indicates voltage
- Blinking red light indicates voltage
- On/Off button
- Pocket clip for easy storage



	2200-40
Safety rating	CAT IV 1000 V
Weight with battery pack (EPTA) (kg)	0.40 (AAA)
Kit included	2 x AAA Batteries, No kitbox or bag supplied
Article Number	4932352561
EAN Code	4002395372195

2212-20 | AUTO VOLTAGE / CONTINUITY TESTER

- Provides measurements down to decimals and displays them on an easy-to-read backlit LCD
- Automatically determines the need for voltage or continuity tests and display all measurements with proper resolution
- Compatible with accessories for carrying or mounting
- LED worklight for low lit areas
- Dual LED and audible indicators for fast and convenient test results
- Replaceable test leads for greater flexibility
- Rugged over-moulding protects your meter in any environment



	2212-20
Temperature range (°C)	0 - 50
Safety rating	CAT IV 600 V
Continuity	Yes
Weight with battery pack (EPTA) (kg)	0.30 (2 x AAA)
Kit included	2 x AAA Batteries, No kitbox or bag supplied
Article Number	4933447776
EAN Code	4002395006526

2267-40

10:1 INFRARED TEMP-GUN™

- 10:1 distance to spot ratio, a 1 m spot from 10 m away
- Up to -30°C to 400°C temperature range
- Premium LCD display for high readability
- Simplified buttons and setup for faster scanning
- Raised overmolding protects lens and screen from direct impact



	2267-40
Temperature range (°C)	-30 - 400
Basic accuracy (%)	±2
Repeatability (%)	±0.08
Emissivity	0.95
Weight with battery pack (EPTA) (kg)	0.30 (2 x AA)
Kit included	2 x AA Batteries, No kitbox or bag supplied
Article Number	4933451906
EAN Code	4002395282159

2217-40 | DIGITAL MULTIMETER

- TRMS always guarantees accurate readings
- High contrast, easy to read display provides clearer readings
- Cat III 600 V for increased safety
- Side mounted dial for one-handed use
- Feature set tailored to electrician – for intuitive use
- Lo-Z – always guaranteed accurate readings
- Versatile contact temperature measurement
- Slide rail for accessory mount
- Supplied with electrical test lead set, thermocouple (dual banana) and 2 x AA batteries



	2217-40
Current AC/ DC (amps)	10
Lo-Z measurement	Yes
Resistance (kΩ)	40,000
Continuity	Yes
Capacitance (µF)	1000
Contact temperature (°C)	-40 - +538
Frequency (Hz)	2.00 Hz - 50.00 kHz
Weight with battery pack (EPTA) (kg)	0.40 (2 x AA)
Kit included	2 x AA Batteries, Tool bag
Article Number	4933416976
EAN Code	4002395238064

PLUMBING SPECIALIST



M18™ FORCE LOGIC™ BRUSHLESS PRESS TOOL WITH ONE-KEY™



- Compact brushless motor in FORCE LOGIC™ press tools delivers up to 10 % faster connections and 20 % more run time
- FORCE LOGIC™ press indicator: provides visual confirmation of a quality connection
- One hand operated tool for over head applications and working in narrow spaces
- Tool records & stores every press made. ONE-KEY™ enabled for professional report buildings via ONE-KEY™ app or ONE-KEY™ browser version
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- FORCE LOGIC™ long life reliability: No press cycle limitation within the 3 year maintenance interval
- Allows to press system related up to 108 mm metal pipes and 110 mm composite pipes
- Universal jaw reception to fit most common jaws available on the market
- Auto-Cycle ensures a full press cycle is completed with every press connection
- Battery-tool communication: press operation doesn't start to prevent incomplete pressing in case of low charged battery. Pre-press battery check ensures enough charge to complete each press
- REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18™ FORCE LOGIC™ BRUSHLESS PRESSTOOL



- New compact brushless motor in FORCE LOGIC™ press tools delivers up to 10% faster connections and 20% more runtime
- FORCE LOGIC™ press indicator: provides visual confirmation of a quality connection
- One hand operated tool for over head applications and working in narrow spaces
- Most compact in-line design with 13% less weight for easy operation
- Battery-tool communication: press operation doesn't start to prevent incomplete pressing in case of low charged battery. Pre-press battery check ensures enough charge to complete each press
- FORCE LOGIC™ long life reliability: No press cycle limitation within the 3 year maintenance interval
- Allows to press system related up to 108 mm metal pipes and 110 mm composite pipes
- Universal jaw reception to fit most common jaws available on the market
- On board fuel gauge and LED light
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 ONEBLHPT-0C	M18 ONEBLHPT-302C U-SET	M18 ONEBLHPT-302C M-SET
Press force [kN]	32	32	32
Max. press size in metal (mm)	108	108	108
Max. press size in plastic (mm)	110	110	110
Weight with battery pack (EPTA) (kg)	2.9 (M18 HB3)	2.9 (M18 HB3)	2.9 (M18 HB3)
Standard equipment	-	3 x U-profile jaws (16/20/25 mm)	3 x M-profile jaws (15/22/28 mm)
Kit included	No batteries supplied, No charger supplied, Kitbox	2 x M18 HB3 Battery packs, M12-18 FC Charger, Kitbox	2 x M18 HB3 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933478305	4933478628	4933478629
EAN Code	4058546344825	4058546348212	4058546348229

	M18 BLHPT-202C	M18 BLHPT-202C M-SET	M18 BLHPT-202C V-SET	M18 BLHPT-202C TH-SET	M18 BLHPT-202C U-SET
Press force [kN]	32	32	32	32	32
Max. press size in metal (mm)	108	108	108	108	108
Max. press size in plastic (mm)	110	110	110	110	110
Weight with battery pack (EPTA) (kg)	2.9 (M18 B2)	2.9 (M18 B2)	2.9 (M18 B2)	2.9 (M18 B2)	2.9 (M18 B2)
Standard equipment	-	3 x M-profile jaws (15/22/28 mm)	3 x V-profile jaws (15/22/28 mm)	3 x TH-profile jaws (16/20/32 mm)	3 x U-profile jaws (16/20/25 mm)
Kit included	2 x M18 B2 Battery packs, M12-18 C Charger, Kitbox	2 x M18 B2 Battery packs, M12-18 C Charger, Kitbox	2 x M18 B2 Battery packs, M12-18 C Charger, Kitbox	2 x M18 B2 Battery packs, M12-18 C Charger, Kitbox	2 x M18 B2 Battery packs, M12-18 C Charger, Kitbox
Article Number	4933451137	4933451138	4933451139	4933451140	4933451141
EAN Code	4002395138067	4002395138074	4002395138081	4002395138098	4002395138104



ONE-KEY™ technology

One-handed operation

FORCE LOGIC™ press indicator



Most compact in-line design

One handed operation

FORCE LOGIC™ press indicator

M18 BLHPTXL

M18™ FORCE LOGIC™ BRUSHLESS XL PRESS TOOL

- New compact brushless motor in FORCE LOGIC™ press tools delivers up to 10% faster connections and 20% more run time
- FORCE LOGIC™ press indicator: provides visual confirmation of a quality connection
- Extended press range up to 108 mm in copper, C- steel & stainless steel & up to 4" in steel pipe
- One hand operated tool for over head applications and working in narrow spaces
- Adjustable stroke length allows usage of all standard MILWAUKEE® J18 jaws + most common competitive jaws available on the market
- FORCE LOGIC™ long life reliability: No press cycle limitation within the 3 year maintenance interval
- Auto-cycle ensures a full press cycle is completed with every press connection
- Battery-tool communication: press operation doesn't start to prevent incomplete pressing in case of low charged battery. Pre-press battery check ensures enough charge to complete each press
- On board fuel gauge and LED light
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



FORCELOGIC™



	M18 BLHPTXL-OP
Press force [kN]	32
Max. press size in c. steel & stainless steel [mm]	108
Max. press size in composite [mm]	110
Max. press size in copper [mm]	108
Max. press size in steel [inch]	102
Weight with battery pack (EPTA) (kg)	3.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, PACKOUT™ box
Article number	4933479440
EAN code	4058546372347



Extended press range up to 108 mm in copper, C-steel and stainless steel + 4" in steel pipe



FORCE LOGIC™ press indicator



Auto cycle press completion

M12 HPT

M12™ SUB COMPACT FORCE LOGIC™ HYDRAULIC PRESS TOOL

- The industry's smallest, lightest press tool: weighs only 1.8 kg for greater user comfort
- Patented one hand operation allows to work in restricted areas
- Press indicator: provides visual confirmation of a quality connection
- Outstanding pressing range up to 35 mm metal and 40 mm composite pipes
- Battery-tool communication: press operation doesn't start to prevent incomplete pressing in case of low charged battery. Pre-press battery check ensures enough charge to complete each press
- FORCE LOGIC™ long life reliability: No press cycle limitation within the 3 year maintenance interval
- 4-step and precise battery status indicator
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12

FORCELOGIC™



	M12 HPT-202C M-SET	M12 HPT-202C V-SET	M12 HPT-202C TH-SET	M12 HPT-202C U-SET
Press force [kN]	19	19	19	19
Max. press size in metal [mm]	35	35	35	35
Max. press size in plastic [mm]	40	40	40	40
Weight with battery pack (EPTA) (kg)	1.8 (M12 B2)	1.8 (M12 B2)	1.8 (M12 B2)	1.8 (M12 B2)
Standard equipment	3 x M-profile jaws (15/22/28 mm)	3 x V-profile jaws (15/22/28 mm)	3 x TH-profile jaws (16/20/32 mm)	3 x U-profile jaws (16/20/25 mm)
Kit included	2 x M12 B2 Battery packs, C12 C Charger, Kitbox	2 x M12 B2 Battery packs, C12 C Charger, Kitbox	2 x M12 B2 Battery packs, C12 C Charger, Kitbox	2 x M12 B2 Battery packs, C12 C Charger, Kitbox
Article Number	4933448748	4933448749	4933448750	4933448751
EAN Code	4002395810109	4002395810116	4002395810123	4002395810130



One handed use



360° rotating head



Press indicator



PRESS JAWS

M12™ and M18™ FORCE LOGIC™ press jaws are manufactured for the highest standards of press quality and durability in the industry. Designed for easy opening with one thumb, these jaws when used with the M12™ and M18™ FORCE LOGIC™ press tools represent a one handed pressing solution for up to 108 mm pipe. The press jaws will deliver quality press connections on all major fitting brands.



		M12 HPT			M18 BLHPT			M18 BLHPTXL		
Jaw profile	Nominal size	Description	Article number	EAN code	Description	Article number	EAN code	Description	Article number	EAN code
M	12	J12-M12	4932430243	4002395379040	J18-M12	4932430244	4002395379057	J18-M12	4932430244	4002395379057
	15	J12-M15	4932430245	4002395379064	J18-M15	4932430246	4002395379071	J18-M15	4932430246	4002395379071
	18	J12-M18	4932430247	4002395379088	J18-M18	4932430248	4002395379095	J18-M18	4932430248	4002395379095
	22	J12-M22	4932430249	4002395379101	J18-M22	4932430250	4002395379118	J18-M22	4932430250	4002395379118
	28	J12-M28	4932430251	4002395379125	J18-M28	4932430252	4002395379132	J18-M28	4932430252	4002395379132
	35	J12-M35	4932430253	4002395379149	J18-M35	4932430254	4002395379156	J18-M35	4932430254	4002395379156
	42	-	-	-	RJ18-M42	4932430255	4002395379163	RJ18-M42	4932430255	4002395379163
	54	-	-	-	Ringadaptor RJA-1 required	4932430256	4002395379170	Ringadaptor RJA-1 required	4932430256	4002395379170
					RJ18-M54			Ringadaptor RJA-1 required		
	76.1	-	-	-	-	-	-	RJ18XL-M76.1	4932479458	4058546372521
								Ringadaptor RJAXL-1 required		
	88.9	-	-	-	-	-	-	RJ18XL-M88.9	4932479459	4058546372538
Ringadaptor RJAXL-1 required										
108	-	-	-	-	-	-	RJ18XL-M108	4932479460	4058546372545	
							1. Press RJAXL-1 & 2. Press RJAXL-2 required!			
V	12	J12-V12	4932430260	4002395379217	J18-V12	4932430261	4002395379224	J18-V12	4932430261	4002395379224
	14	J12-V14	4932451660	4002395273423	J18-V14	4932471086	4058546287146	J18-V14	4932471086	4058546287146
	15	J12-V15	4932430262	4002395379231	J18-V15	4932430263	4002395379248	J18-V15	4932430263	4002395379248
	16	J12-V16	4932451661	4002395273430	J18-V16	4932471087	4058546287153	J18-V16	4932471087	4058546287153
	18	J12-V18	4932430264	4002395379255	J18-V18	4932430265	4002395379262	J18-V18	4932430265	4002395379262
	22	J12-V22	4932430266	4002395379279	J18-V22	4932430267	4002395379286	J18-V22	4932430267	4002395379286
	28	J12-V28	4932430268	4002395379293	J18-V28	4932430269	4002395379309	J18-V28	4932430269	4002395379309
	35	J12-V35	4932430270	4002395379316	J18-V35	4932430271	4002395379323	J18-V35	4932430271	4002395379323
	42	-	-	-	RJ18-V42	4932430272	4002395379330	RJ18-V42	4932430272	4002395379330
	54	-	-	-	Ringadaptor RJA-1 required	4932430273	4002395379347	Ringadaptor RJA-1 required	4932430273	4002395379347
					RJ18-V54			Ringadaptor RJA-1 required		
	TH	14	J12-TH14	4932430274	4002395379354	J18-TH14	4932430275	4002395379361	J18-TH14	4932430275
16		J12-TH16	4932430276	4002395379378	J18-TH16	4932430277	4002395379385	J18-TH16	4932430277	4002395379385
18		J12-TH18	4932430278	4002395379392	J18-TH18	4932430279	4002395379408	J18-TH18	4932430279	4002395379408
20		J12-TH20	4932430280	4002395379415	J18-TH20	4932430281	4002395379422	J18-TH20	4932430281	4002395379422
25		J12-TH25	4932430282	4002395379439	J18-TH25	4932430355	4002395380169	J18-TH25	4932430355	4002395380169
26		J12-TH26	4932430283	4002395379446	J18-TH26	4932430284	4002395379453	J18-TH26	4932430284	4002395379453
32		J12-TH32	4932430285	4002395379460	J18-TH32	4932430286	4002395379477	J18-TH32	4932430286	4002395379477
40		J12-TH40	4932430287	4002395379484	RJ18-TH40	4932430288	4002395379491	RJ18-TH40	4932430288	4002395379491
50		-	-	-	Ringadaptor RJA-1 required	4932430289	4002395379507	Ringadaptor RJA-1 required	4932430289	4002395379507
					RJ18-TH50			Ringadaptor RJA-1 required		
63		-	-	-	Ringadaptor RJA-1 required	4932430290	4002395379514	Ringadaptor RJA-1 required	4932430290	4002395379514
					RJ18-TH63			Ringadaptor RJA-1 required		
U	14	J12-U14	4932430291	4002395379521	J18-U14	4932430292	4002395379538	J18-U14	4932430292	4002395379538
	16	J12-U16	4932430293	4002395379545	J18-U16	4932430294	4002395379552	J18-U16	4932430294	4002395379552
	18	J12-U18	4932430295	4002395379569	J18-U18	4932430296	4002395379576	J18-U18	4932430296	4002395379576
	20	J12-U20	4932430297	4002395379583	J18-U20	4932430298	4002395379590	J18-U20	4932430298	4002395379590
	25	J12-U25	4932430299	4002395379606	J18-U25	4932430300	4002395379613	J18-U25	4932430300	4002395379613
	32	J12-U32	4932430301	4002395379620	J18-U32	4932430302	4002395379637	J18-U32	4932430302	4002395379637
	40	J12-U40	4932430303	4002395379644	RJ18-U40	4932430304	4002395379651	RJ18-U40	4932430304	4002395379651
	50	-	-	-	Ringadaptor RJA-1 required	4932430305	4002395379668	Ringadaptor RJA-1 required	4932430305	4002395379668
					RJ18-U50			Ringadaptor RJA-1 required		
	63	-	-	-	Ringadaptor RJA-1 required	4932430306	4002395379675	Ringadaptor RJA-1 required	4932430306	4002395379675
					RJ18-U63			Ringadaptor RJA-1 required		
	ACz	12	J12-ACz 12	4932459388	4058546010492	-	-	-	-	-
16		J12-ACz 16	4932459389	4058546010508	-	-	-	-	-	-
20		J12-ACz 20	4932459390	4058546010515	-	-	-	-	-	-
25		J12-ACz 25	4932459391	4058546010522	-	-	-	-	-	-
G	16	J12-G16	4932464217	4058546221621	J18-G16	4932464544	4058546224899	J18-G16	4932464544	4058546224899
	20	J12-G20	4932464218	4058546221638	J18-G20	4932464545	4058546224905	J18-G20	4932464545	4058546224905
	26	J12-G26	4932464219	4058546221645	J18-G26	4932464546	4058546224912	J18-G26	4932464546	4058546224912
	32	J12-G32	4932464220	4058546221652	J18-G32	4932464547	4058546224929	J18-G32	4932464547	4058546224929
	40	J12-G40	4932464221	4058546221669	J18-G40	4932464548	4058546224936	J18-G40	4932464548	4058546224936
	50	-	-	-	J18-G50	4932464549	4058546224943	J18-G50	4932464549	4058546224943
Adaptor Jaws					RJA-1	4932430307	4002395379682	RJAXL-1	4932479451	4058546372453
					RJAV-2	4932479604	4058546373986	RJAXL-2	4932479452	4058546372460

GEBERIT MAPRESS PRESS JAWS

- Original Geberit Mapress press profiles
- Full system approval for Geberit press fittings
- Most durable, service & inspection free jaw design



Fits Milwaukee Press tool	Description [non translating]	Fits to following pipe system suppliers	Nominal size	Pipe Diameter	Jaw profile	Article number	EAN code
M12 HPT	J12-M12 Geberit	Geberit: Mapress	12	12 mm	M	4932480879	4058546411640
	J12-M15 Geberit	Geberit: Mapress	15	15 mm	M	4932480880	4058546411657
	J12-M18 Geberit	Geberit: Mapress	18	18 mm	M	4932480881	4058546411664
	J12-M22 Geberit	Geberit: Mapress	22	22 mm	M	4932480882	4058546411671
	J12-M28 Geberit	Geberit: Mapress	28	28 mm	M	4932480883	4058546411688
M18 BLHPT, M18 ONEBLHPT	J12-M35 Geberit	Geberit: Mapress	35	35 mm	M	4932480884	4058546411695
	J18-M12 Geberit	Geberit: Mapress	12	12 mm	M	4932480885	4058546411701
	J18-M15 Geberit	Geberit: Mapress	15	15 mm	M	4932480886	4058546411718
	J18-M18 Geberit	Geberit: Mapress	18	18 mm	M	4932480887	4058546411725
	J18-M22 Geberit	Geberit: Mapress	22	22 mm	M	4932480888	4058546411732
	J18-M28 Geberit	Geberit: Mapress	28	28 mm	M	4932480889	4058546411749
	J18-M35 Geberit	Geberit: Mapress	35	35 mm	M	4932480890	4058546411756

GEBERIT MEPLA PRESS JAWS

- Original Geberit Mepla and Mepla Therm press profiles
- Full system approval for Geberit press fittings
- Most durable, service & inspection free jaw design



Fits Milwaukee Press tool	Description [non translating]	Fits to following pipe system suppliers	Nominal size	Pipe Diameter	Jaw profile	Article number	EAN code
M12 HPT	J12-G16 Geberit	Geberit: Mepla & Mepla Therm	16	16 mm	G	4932480891	4058546411763
	J12-G20 Geberit	Geberit: Mepla & Mepla Therm	20	20 mm	G	4932480892	4058546411770
	J12-G26 Geberit	Geberit: Mepla & Mepla Therm	26	26 mm	G	4932480893	4058546411787
	J12-G32 Geberit	Geberit: Mepla & Mepla Therm	32	32 mm	G	4932480894	4058546411794
	J12-G40 Geberit	Geberit: Mepla & Mepla Therm	40	40 mm	G	4932480895	4058546411800
M18 BLHPT, M18 ONEBLHPT	J18-G16 Geberit	Geberit: Mepla & Mepla Therm	16	16 mm	G	4932480896	4058546411817
	J18-G20 Geberit	Geberit: Mepla & Mepla Therm	20	20 mm	G	4932480897	4058546411824
	J18-G26 Geberit	Geberit: Mepla & Mepla Therm	26	26 mm	G	4932480898	4058546411831
	J18-G32 Geberit	Geberit: Mepla & Mepla Therm	32	32 mm	G	4932480899	4058546411848
	J18-G40 Geberit	Geberit: Mepla & Mepla Therm	40	40 mm	G	4932480900	4058546411855
			50	50 mm	G	4932480901	4058546411862

RING JAW GEBERIT MEPLA

- Original Geberit Mepla and Mepla Therm press profiles
- Full system approval for Geberit press fittings



Fits Milwaukee Press tool	Description [non translating]	Fits to following pipe system suppliers	Nominal size	Pipe Diameter	Pipe fittings brand	Jaw profile	Article number	EAN code
M18 BLHPT, M18 HPT	RJ18-G63 Geberit	Geberit: Mepla & Mepla Therm	63	63 mm	Geberit: Mepla, Mepla Therm	G	4932480966	4058546412517
	RJ18-G75 Geberit	Geberit: Mepla & Mepla Therm	75	75 mm	Geberit: Mepla, Mepla Therm	G	4932480967	4058546412524

GEBERIT FLOWFIT PRESS JAWS

- Original Geberit FlowFit press profiles
- Full system approval for Geberit press fittings
- Most durable, service & inspection free jaw design



Fits Milwaukee Press tool	Description [non translating]	Fits to following pipe system suppliers	Nominal size	Pipe Diameter	Jaw profile	Article number	EAN code
M12 HPT	J12-FF 16-40 Geberit	Geberit FlowFit	16-40	16 mm, 20 mm, 25 mm, 32 mm, 40 mm	FF	4932480981	4058546412661
M18 BLHPT, M18 ONEBLHPT	J18-FF 16-40 Geberit	Geberit FlowFit	16-40	16 mm, 20 mm, 25 mm, 32 mm, 40 mm	FF	4932480982	4058546412678
M18 BLHPT, M18 ONEBLHPT	J18-FF 50-75 Geberit	Geberit FlowFit	50-75	50 mm, 63 mm, 75 mm	FF	4932480983	4058546412685

B PRESS JAWS

- Original Conex & Bänninger MaxiPro >B< press profiles
- Full system approval for Conex&Bänninger MaxiPro refrigerant fittings

Fits Milwaukee Press tool



M18 FPT2 | M18 FUEL™ PIPE THREADER 2" WITH ONE-KEY™

- World's first 18V 2" pipe threader on the market that is fully universal with competitive die heads. It threads pipes from 1/8" up to 2"
- Unique to MILWAUKEE®, pipe threader with AUTO-STOP™ kickback control, senses binding and shuts tool off to provide the user with more safety
- Directly compatible with Ridgid 12-R, with adapter kits MILWAUKEE® FPT2AK-RI for Ridgid 11-R, MILWAUKEE® FPT2AK-RE for Rems Quick Change and MILWAUKEE® FPT2AK-RO for Rothenberger SUPER CUT
- Multi-speed selector: speed 1, 0 - 29 rpm, for 1-1/4" - 2", and speed 2, 0 - 41 rpm, for 1/8" - 1", for optimised thread quality across pipe sizes for faster threading and more productivity
- Full days work on one battery charge, with over 25, 2" threads and over 60, 1/2" threads on one M18™ 12.0 Ah battery pack
- Side-grip allows for no engagement with the spinning die head before or during the threading process
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FPT2-0C	
Speed settings	2
No load speed (rpm)	0 - 29/ 0 - 41
Thread size (mm)	3.2 - 52 / 1/8" - 2"
Weight with battery pack (EPTA) (kg)	11.3 (M18 HB12)
Standard equipment	1x support arm
Kit included	No batteries supplied, No charger supplied, Kitbox
Article Number	4933478596
EAN Code	4058546347895

M18 FPT114 | M18 FUEL™ PIPE THREADER 1 1/4" WITH ONE-KEY™

- Wide threading capacity from 1/8" up to 1 1/4"
- Unique to MILWAUKEE®, pipe threader with AUTOSTOP™ kickback control, senses binding and shuts tool off to provide the user with more safety
- Low weight and compact size allows convenient usage on installed pipes in confined spaces
- Compatible with new MILWAUKEE® FPT114H die heads and Ridgid 11R heads until 1 1/4"
- Up to 50 threads on a 3/4" pipe with one charge of a M18™ HIGH OUTPUT™ 8.0 Ah battery pack
- Side-grip allows for no engagement with the spinning die head before or during the threading process
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FPT114-0C	
Speed settings	1
No load speed (rpm)	0 - 35
Thread size [inch]	1/8" - 1 1/4"
Weight with battery pack (EPTA) (kg)	5.9 (M18 HB8)
Included heads	-
Standard equipment	1x support arm
Kit included	No batteries supplied, No charger supplied, Kitbox
Article number	4933480220
EAN code	4058546405052

MPS MILWAUKEE® PIPE STAND

- Worlds first pipe stand, that is flat foldable, which allows for easier transportation and more efficient storage
- Able to clamp materials, such as pipe, strut, channel, angled iron and other materials, up to 165 mm or 6"
- The MILWAUKEE® pipe stand can be used with threaders, angle grinders, sawzalls, hackzalls, metal circular saws and various other tools
- Removable shelf allows the user to easily install and remove the bottom material shelf as they like
- Different jaws for different materials available. MPS-SSJ for stainless steel and MPS-NCJ for soft materials, such as pvc. MPS-RJ, delivered standard with the tool, is a jaw for universal use



MPS	
Weight (kg)	22.7
Article number	4933472022
EAN code	4058546324186

PIPE STAND ATTACHMENTS

	Article number	EAN code	
MILWAUKEE® pipe stand replaceable jaws	4932478923	4058546362058	
MILWAUKEE® pipe stand neoprene jaws	4932478924	4058546362065	
MILWAUKEE® pipe stand stainless steel jaws	4932478925	4058546362072	
MILWAUKEE® pipe stand removeable shelf	4932478926	4058546362089	

PIPE THREADER DIES

- High performance threader dies ensure perfect threads and long lasting performance in combination with the MILWAUKEE® threaders
- Dies are available in two types of thread geometries: BSPT (British Standard Pipe Taper) and NPT (National Taper Pipe)
- Dies are available in two diferent grades: Alloy dies for long lasting performance on black and galvanised pipes and HS dies for best performance on stainless steel pipes
- One set contains 4 single cutting dies that are needed to equip one die head



Model Variant	Type	Thread size [inch]	Article number	EAN code
FPTD 1/2" NPT HS	NPT HS	1/2	48361107	045242608713
FPTD 3/4" NPT HS	NPT HS	3/4	48361108	045242608720
FPTD 1" NPT HS	NPT HS	1	48361109	045242608737
FPTD 1-1/4" NPT HS	NPT HS	1 - 1/4	48361110	045242608744
FPTD 1-1/2" NPT HS	NPT HS	1 - 1/2	48361111	045242608751
FPTD 2" NPT HS	NPT HS	2	48361112	045242608768
FPTD 1/2" BSPT Alloy	BSPT Alloy	1/2	4932480227	4058546405120
FPTD 3/4" BSPT Alloy	BSPT Alloy	3/4	4932480228	4058546405137
FPTD 1" BSPT Alloy	BSPT Alloy	1	4932480229	4058546405144
FPTD 1-1/4" BSPT Alloy	BSPT Alloy	1 - 1/4	4932480230	4058546405151
FPTD 1-1/2" BSPT Alloy	BSPT Alloy	1 - 1/2	4932480231	4058546405168
FPTD 2" BSPT Alloy	BSPT Alloy	2	4932480232	4058546405175
FPTD 1/2" BSPT HS	BSPT HS	1/2	4932480233	4058546405182
FPTD 3/4" BSPT HS	BSPT HS	3/4	4932480234	4058546405199
FPTD 1" BSPT HS	BSPT HS	1	4932480235	4058546405205
FPTD 1-1/4" BSPT HS	BSPT HS	1 - 1/4	4932480236	4058546405212
FPTD 1-1/2" BSPT HS	BSPT HS	1 - 1/2	4932480237	4058546405229
FPTD 2" BSPT HS	BSPT HS	2	4932480238	4058546405236

PIPE THREADER HEADS

- Up to 50% lighter than competitive die heads
- Available sizes from 1/2" up to 2"
- Die heads always include a set of BSPT alloy dies



Model Variant	Type	Thread size [inch]	Suitable	Article number	EAN code
FPT2H 1/2" BSPT Alloy	BSPT Alloy	1/2	M18 FPT2	4932480239	4058546405243
FPT2H 3/4" BSPT Alloy	BSPT Alloy	3/4	M18 FPT2	4932480240	4058546405250
FPT2H 1" BSPT Alloy	BSPT Alloy	1	M18 FPT2	4932480241	4058546405267
FPT2H 1-1/4" BSPT Alloy	BSPT Alloy	1 1/4	M18 FPT2	4932480242	4058546405274
FPT2H 1-1/2" BSPT Alloy	BSPT Alloy	1 1/2	M18 FPT2	4932480243	4058546405281
FPT2H 2" BSPT Alloy	BSPT Alloy	2	M18 FPT2	4932480244	4058546405298
FPT114H 1/2" BSPT Alloy	BSPT Alloy	1/2	M18 FPT114	4932480245	4058546405304
FPT114H 3/4" BSPT Alloy	BSPT Alloy	3/4	M18 FPT114	4932480246	4058546405311
FPT114H 1" BSPT Alloy	BSPT Alloy	1	M18 FPT114	4932480247	4058546405328
FPT114H 1-1/4" BSPT Alloy	BSPT Alloy	1 1/4	M18 FPT114	4932480248	4058546405335
FPT2HK BSPT Alloy	BSPT Alloy	1/2, 3/4, 1", 1 1/4, 1 1/2, 2"	M18 FPT2	4932480249	4058546405342
FPT114HK BSPT Alloy	BSPT Alloy	1/2, 3/4, 1", 1 1/4"	M18 FPT114	4932480250	4058546405359



M12 PCSS

M12™ RAPTOR™ PIPE CUTTER STAINLESS STEEL

- The MILWAUKEE® RAPTOR™ is the worlds first 12V pipe cutter that is able to cut installed pipe in stainless steel, c-steel and copper
- High performance 380 rpm motor cuts 28 mm stainless steel pipe in less than 20 seconds
- Up to 90 cuts in 15 mm stainless steel with one M12™ 2.0 Ah battery pack
- Auto locking cut mechanism cuts installed pipe with as little as 40 mm clearance
- Auto adjusting jaws automatically adjust to pipe size
- Able to cut stainless steel, c-steel and copper in the sizes 12, 15, 18, 22, 28 mm
- All metal sealed front end – rust and corrosion resistant cut head and internal drainage system make the tool water resistant
- Viewing window at cutting mechanism and build in light, allow the user to precisely cut the pipe
- On board fuel gauge and LED light
- Premium 4-pole brushed motor, REDLITHIUM™ battery pack and REDLINK™ electronic delivering the needed power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 PCSS-0	M12 PCSS-202C
No load speed (rpm)	380	380
Pipe diameter [mm]	12, 15, 18, 22, 28	12, 15, 18, 22, 28
Minimum space for tube cutting (mm)	40	40
overall length (mm)	362	362
Weight with battery pack (EPTA) (kg)	1.5 (M12 B2)	1.5 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B2 Battery packs, C12 C Charger, Kitbox
Article number	4933479241	4933492052
EAN code	4058546370350	4058546414191



VIEW ON OUR YOUTUBE CHANNEL

C12 PC | M12™ SUB COMPACT COPPER PIPE CUTTER

- High performance 500 rpm motor cuts 12 mm copper pipe in less than 3 seconds
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Auto locking cut mechanism cuts installed copper tubing with as little as 40 mm clearance
- Auto adjusting jaws automatically adjust to pipe size
- All metal sealed front end – rust and corrosion resistant cut head
- Slimline soft grip handle
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	C12 PC-0
copper tubes (mm)	12, 15, 18, 22, 25, 28
Minimum space for tube cutting (mm)	80
Length (mm)	360
Weight with battery pack (EPTA) (kg)	1.5 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933411920
EAN Code	4002395236374

C12 PPC | M12™ SUB COMPACT PEX CUTTER

- Massive cutting pressure of 175 kg/cm²
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Powerful mechanism cuts up to 50 mm PVC pipe in 3 seconds
- Heavy Duty full metal gearbox and gears for superior durability and maximum torque
- Variable speed trigger for complete cut out control
- Super sharp blade for blur free cuts
- Highly efficient mechanism delivers over 200 cuts per charge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	C12 PPC-0
Max. cutting capacity (mm)	50
No load speed (rpm)	0 - 500
Weight with battery pack (EPTA) (kg)	1.9 (M12 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933416550
EAN Code	4002395237203

M18 BTP | M18™ COMPACT TRANSFER PUMP

- 18V transfer pump with 3.4 kg in weight, it's lighter than other corded transfer pumps with an equal performance
- With a flow rate of 1817 l/h, it can deliver 908 l of transferred water with one M18™ 5.0 Ah battery charge
- REDLINK™ intelligence can recognise when the tool stops moving water and automatically shuts itself off to avoid dry pumping
- The tool's flexible impeller and powerful motor generate a lift height up to 5.5 m and a head height up to 23 m
- 3/4" BSPT male thread reception for any standard water hose available. For the inlet, a hose with 19 mm inner diameter is recommended, for optimised performance
- To be used for water, clear of debris only
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BTP-0
Flow rate [litres per hour]	1817
Flow rate [litres per minute]	30.3
Max. suction height (m)	5.5
Max. head height (m)	23
Max. water temperature [°C]	60
IP protection class	IP54
Thread size (mm)	3/4" (19 mm) Male thread
Weight with battery pack (EPTA) (kg)	4.1 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471494
EAN Code	4058546293932

M12 BSWP

M12™ HYDROPASS™ BRUSHED STICK WATER PUMP

- HYDROPASS™ unique filter system, prevents blocking of the inlet and allows the user to pump water at all times, regardless of the debris encountered
- Pumps more then 2000 l/hour and up to 1000 l on 1x M12™ 6.0 Ah battery, perfect for emptying trenches, storm drains, outside meter boxes, rain barrels and various other applications
- Submersible up to 85 cm, allows users to easily pump large puddles of water with a max head height of 4.5 m
- 3/4" BSPT thread outlet allows for connecting 19m m (inner diameter) hoses for maximum volume movement
- This pump is suitable for, white, grey and black water only
- Fuel gauge displays remaining charge
- Premium 4-pole brushed motor, REDLITHIUM™ battery pack and REDLINK™ electronic delivering the needed power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 BSWP-0
Flow rate [litres per hour]	2040
Flow rate [litres per minute]	34
Max. head height (m)	4.5
Max. water temperature [°C]	60
Thread size (mm)	3/4" (19mm) Male thread
Weight with battery pack (EPTA) (kg)	2.0 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933479639
EAN code	4058546374334

2267-40 | 10:1 INFRARED TEMP-GUN™

- 10:1 distance to spot ratio, a 1 m spot from 10 m away
- Up to -30°C to 400°C temperature range
- Premium LCD display for high readability
- Simplified buttons and setup for faster scanning
- Raised overmolding protects lens and screen from direct impact



	2267-40
Temperature range (°C)	-30 - 400
Basic accuracy (%)	±2
Repeatability (%)	±0.08
Emissivity	0.95
Weight with battery pack (EPTA) (kg)	0.30 (2 x AA)
Kit included	2 x AA Batteries, No kitbox or bag supplied
Article Number	4933451906
EAN Code	4002395282159



M18 ONEBLPXPL | M18™ ONE-KEY™ FORCE LOGIC™ UPONOR™ Q&E HYDRAULIC PIPE EXPANDING

- The ONE-KEY™ FORCE LOGIC™ hydraulic expander is the world's first cordless expander for UPONOR™ Q&E PE-Xa pipe sizes up to DN75
- Brushless POWERSTATE™ motor delivers outstanding run time and quick expansions
- Expands dimensions DN40, DN50, DN63 and DN75 of 6 and 10 bar pipes
- Intelligent design delivers optimum balance for overhead connections, and flips over for extended use on table-tops
- Auto-rotating head expands PEX pipe quickly and evenly
- Auto-cycle rotates, expands and resets automatically simplifying installation process
- Expander resets automatically after every expansion to speed up repetitive connections
- Side handle and integrated tethering point for improved jobsite safety
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. The reporting function delivers a complete tool activity and accuracy protocol
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 ONEBLPXPL-502C
Stroke length (mm)	55.5
Head type	Auto-rotating
Weight with battery pack (EPTA) (kg)	10.1 (M18 B5)
Kit included	2 x M18 B5 Battery packs, M12-18 C Charger, Kitbox
Article Number	4933457610
EAN Code	6414905472864

M18 FPXP | M18 FUEL™ UPONOR™ Q&E EXPANSION TOOL

- Auto-rotating heads from 9.9 mm to 50 mm provide the most accurate, one-handed expansions
- Most compact 50 mm battery powered pipe expander
- Compatible with all existing M12™ and M18™ expansion heads up to 50 mm
- Fast solution for 50 mm Q&E installations
- Two speed settings: one for up to 32 mm and one for 40 mm and above
- On board LED light for illumination in low lit working conditions
- Ideal solution for 40 mm and 50 mm expansions
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FPXP-0C
Stroke length (mm)	31.1
Head type	Auto-rotating
Included heads	-
Weight with battery pack (EPTA) (kg)	6.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, Kitbox
Article number	4933479436
EAN code	4058546372309

HD18 PXP | M18™ UPONOR™ Q&E EXPANSION TOOL

- Auto rotating head 12 mm to 40 mm (6 bar) and to 32 mm (10 bar) provides accurate, one-handed expansion
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Quick cam mechanism - single pull continuous action installs Q&E up to 4x faster
- Steel gears and integrated magnesium frame
- Robust D-handle design for easy installation of Q&E fittings
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	HD18 PXP-H06202C
Stroke length (mm)	25
Speed (spm)	45
Included heads	16/20/25/32 mm
Head type	Auto-rotating
Weight with battery pack (EPTA) (kg)	3.5 (M18 B2)
Kit included	2 x M18 B2 Battery packs, M12-18 C Charger, Kitbox
Article Number	4933451162
EAN Code	4002395138319

M12 FPXP | M12 FUEL™ SUB COMPACT UPONOR™ Q&E EXPANSION TOOL

- Auto-rotating head 9.9 mm to 32 mm (6 bar) and to 25 mm (10 bar) provides accurate, one-handed expansion
- Quick cam mechanism - single pull, continuous action installs Q&E up to 7 seconds faster
- RAPID SEAL™ heads improve time to seal by 20% or more (depending on the ambient temperatures)
- Dual acting trigger allows expansions from any grip position
- Right angle design for easy installation of Q&E fittings in confined spaces
- On board fuel gauge and LED light
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- 100% backwards compatible with current heads but improved sealing time only with new RAPID SEAL™ heads



	M12 FPXP-0C
Stroke length (mm)	14
Included heads	-
Head type	-
Weight with battery pack (EPTA) (kg)	2.2 (M12 B2)
Kit included	No batteries supplied, No charger supplied, Kitbox
Article Number	4933472018
EAN Code	4058546324148

C12 PXP | M12™ SUB COMPACT UPONOR™ Q&E EXPANSION TOOL

- Auto-rotating head 12 mm to 32 mm (6 bar) and to 25 mm (10 bar) provides accurate, one-handed expansion
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Quick cam mechanism - single pull, continuous action installs Q&E up to 4x faster
- Steel gears and integrated frame
- Right angle design for easy installation of Q&E fittings
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	C12 PXP-I06202C
Stroke length (mm)	14
Speed (spm)	60
Included heads	16/ 20/ 25 mm
Weight with battery pack (EPTA) (kg)	1.9 (M12 B2)
Kit included	2 x M12 B2 Battery packs, C12 C Charger, Kitbox
Article Number	4933381990
EAN Code	6414905426706

EXPANDER HEADS

The Q&E expansion heads are precision engineered for accurate expansion of Uponor™ PEX-a tubing for Q&E fittings. Featuring the auto-rotation interface for MILWAUKEE® cordless Q&E expansion tools, the heads are not only compatible with M12™, M18™ tools, but also fit most Uponor™ tools. Made from high strength steel, the chrome plated segments and black oxide ring combine durability and weather resistance. Colour coded rings for easy size recognition add convenience.



	Pipe diameter [mm]	Pipe wall thickness [mm]	Pipe pressure [bar]	Suitable	Article number	EAN code
PXPH 12I - 14	12	1.7/ 1.8/ 2	6-10	M12, M18	4932352716	4002395373741
PXPH 16I - 14	16	1.8/ 2.0/ 2.2	10	M12, M18	4932352717	4002395373758
PXPH 20I - 1406	20	1.9/ 2.0/ 2.3	6, (8 bar - Ø 2.3 mm)	M12, M18	4932352718	4002395373765
PXPH 20I - 1410	20	2.8	10	M12, M18	4932352719	4002395373772
PXPH 25I - 1406	25	2.3	6	M12, M18	4932352720	4002395373789
PXPH 40I - 2510	40	5.5	10	M18 FPXP	4932479581	4058546373757
PXPH 50I - 25	50	4.6/ 6.9	6-10	M18 FPXP	4932479582	4058546373764
Grease				For lubrication of cone and expander heads.	4932352726	4002395373840

RAPID SEAL™ EXPANDER HEADS

Best performance when used with the new FUEL™ expansion tools



	Pipe diameter [mm]	Pipe wall thickness [mm]	Pipe pressure [bar]	Suitable	Article number	EAN code
FPXPH9.9I-14	9.9	1.1	4-8	M12, M18	4932472150	4058546325466
FPXPH16I-14	16	1.5/ 1.8/ 2.0/ 2.2	6-10	M12, M18	4932472151	4058546325473
FPXPH20I-1406	20	1.9/ 2.0/ 2.3	6-8	M12, M18	4932472152	4058546325480
FPXPH20I-1410	20	2.8	10	M12, M18	4932472153	4058546325497
FPXPH25I-1406	25	2.3	6	M12, M18	4932472271	4058546339173
FPXPH25I-1410	25	3.5	10	M12, M18	4932472272	4058546339180
FPXPH32I-1406	32	2.9	6	M12, M18	4932472273	4058546339197

DRAIN CLEANING,
DIAGNOSTICS AND
INSPECTION





MXF LSDP

MX FUEL™ LARGE SEWER DRUM MACHINE WITH POWERREDZ™

- The MX FUEL™ large sewer drum machine with integrated POWERREDZ™ assists one-person only to move the sewer machine in and out of the service van, up and down building stairs
- World's first battery powered large drum machine that uses MILWAUKEE® 16 mm and 20 mm inner core spirals in drains from 75 mm up to 200 mm, with the power to clear roots up to 60 m down the line
- Fully enclosed drum eliminates free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclogging drains
- Electronic foot pedal with non-slip grip and an integrated drum brake electronically slows the drum very fast for maximum end user control and safety
- MX FUEL™ drum capacity for 16 mm x 30 m long and 20 mm x 30 m long drain cleaning cables
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Building on the strengths of the FUEL™ technology, MX FUEL™ system reaches new levels of cordless performance. Focused on petrol, corded and pneumatic performance, these tools deliver without the hazards associated with emissions, noise, vibration, tripping hazards and the frustrations of complex maintenance

MXF LSDP-301	
No load speed (rpm)	200
Drain capacity (mm)	75 - 200
Spiral diameter (mm)	20
Spiral length (m)	23
Weight with battery pack (EPTA) (kg)	56.6 (MXF CP203)
Standard equipment	1 x 20 mm x 15.2 m inner core cable, 1 x 20 mm x 7.6 m inner core cable, 1 x 9 pc head attachment kit
	1 x MXF CP203 Battery pack, MXF C Charger, No kitbox or bag supplied
Kit included	
Article Number	4933471852
EAN Code	4058546297510



M18 FFSDC16 | M18 FUEL™ FREE STANDING DRAIN CLEANER 16 MM

- World's first free standing drum machine on a 18V battery, with electronic footpedal and integrated drum brake that electronically slows drum super-fast for more control and safety
- M18 FUEL™ SWITCH PACK™ tool-free sectional drum connection system allows users to quickly interchange between cable sizes, 8 mm, 10 mm, 13 mm inner core and 16 mm open wind spirals, or add a second drum to reach 30 m down the line
- Built-in backpack straps allow the user to carry their drive unit separate from their drum(s) for easier transport to any roof, drain, crawl space, or clean out
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- The M18™ SWITCH PACK™ incorporates fully enclosed drums to eliminate free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclogging drains
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- On-tool accessory attachment storage allows the user to keep all their drums and accessories stored together
- The M18™ SWITCH PACK™ is upgradable to a drum machine with automatic feed and retract, sold separately



M18 FFSDC16-0	
No load speed (rpm)	250
Drain capacity (mm)	32 - 75
Spiral diameter (mm)	16
Spiral length (m)	15
Weight with battery pack (EPTA) (kg)	13.4 (M18 B5)
Standard equipment	1 x backpack assembly, 2 x drum assembly's, 2 x 16 mm x 15 m cables, 1 x cutter set & removal tool
	No batteries supplied, No charger supplied, No kitbox or bag supplied
Kit included	
Article Number	4933459709
EAN Code	4058546028817

AUTO FEED SYSTEM ATTACHMENTS

	SAF	GHSAF	BPSAF
Description	Switch Pack Autofeed	Guidehose Switchpack	Base Plate Autofeed
  			
Article Number	4932471993	4932471994	4932478225
EAN Code	4058546298920	4058546298937	4058546344023

M18 FFSDC10 | M18 FUEL™ FREE STANDING DRAIN CLEANER 10 MM

- World's first free standing drum machine on a 18V battery, with electronic footpedal and integrated drum brake that electronically slows drum super-fast for more control and safety
- M18 FUEL™ SWITCH PACK™ tool-free sectional drum connection system allows users to quickly interchange between cable sizes, 8 mm, 10 mm, 13 mm inner core and 16 mm open wind spirals, or add a second drum to reach 30 m down the line
- Built-in backpack straps allow the user to carry their drive unit separate from their drum(s) for easier transport to any roof, drain, crawl space, or clean out
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- The M18™ SWITCH PACK™ incorporates fully enclosed drums to eliminate free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclogging drains
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- On-tool accessory attachment storage allows the user to keep all their drums and accessories stored together
- The M18™ SWITCH PACK™ is upgradable to a drum machine with automatic feed and retract, sold separately

M18 FFSDC10-0	
No load speed (rpm)	250
Drain capacity (mm)	32 - 75
Spiral diameter (mm)	10
Spiral length (m)	15
Weight with battery pack (EPTA) (kg)	13.4 (M18 B5)
Standard equipment	1 x backpack assembly, 1 x drum assembly, 1 x 10 mm x 15 m cables, 1 x cutter set & removal tool
	No batteries supplied, No charger supplied, No kitbox or bag supplied
Kit included	
Article Number	4933459707
EAN Code	4058546028794



M18 FDCPF10 | M18 FUEL™ DRAIN CLEANER - POWER FEED 10 MM

- World's first hand held drain cleaner on a 18V battery with automatic feed and retract that can be used with 6 mm, 8 mm and 10 mm spirals from both MILWAUKEE® and other manufacturers, in pipes from 32 mm up to 75 mm, up to 15 m down the line, eliminating all electrocution hazards users encounter today with their corded tools
- Flat base enables user to put tool down and have one hand free to guide the cable in and out of the drain giving the user more control whilst unclogging drains
- CABLE-DRIVE locking feed system maintains selected feed speed, and auto-adjusts to compatible cable sizes for the best cable grip when feeding and working the clog
- Fully enclosed drum eliminates free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclogging drains
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- LED light illuminates work area underneath sinks and other dark spaces
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FDCPF10-0C	
No load speed (rpm)	0 - 600
Drain capacity (mm)	32 - 75
Spiral diameter (mm)	10
Spiral length (m)	10.6
Bucket capacity (l)	23
Weight with battery pack (EPTA) (kg)	6.9 (M18 B2)
Standard equipment	1 x 10 mm x 10.6 m cable (48532675), retriever bulb, removal pin
	No batteries supplied, No charger supplied, Closed bucket
Kit included	
Article Number	4933459684
EAN Code	4058546028565






















M18 FDCPF8 | M18 FUEL™ DRAIN CLEANER - POWER FEED 8 MM

- World's first hand held drain cleaner on a 18V battery with automatic feed and retract that can be used with 6 mm, 8 mm and 10 mm spirals from both MILWAUKEE® and other manufacturers, in pipes from 32 mm up to 75 mm, up to 15 m down the line, eliminating all electrocution hazards users encounter today with their corded tools
- Flat base enables user to put tool down and have one hand free to guide the cable in and out of the drain giving the user more control whilst unclogging drains
- CABLE-DRIVE locking feed system maintains selected feed speed, and auto-adjusts to compatible cable sizes for the best cable grip when feeding and working the clog
- Fully enclosed drum eliminates free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclogging drains
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- LED light illuminates work area underneath sinks and other dark spaces
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FDCPF8-0C	
No load speed (rpm)	0 - 600
Drain capacity (mm)	32 - 75
Spiral diameter (mm)	8
Spiral length (m)	15
Bucket capacity (l)	23
Weight with battery pack (EPTA) (kg)	6.9 (M18 B2)
Standard equipment	8 mm x 10.6 m cable (48532673)
	No batteries supplied, No charger supplied, Closed bucket
Kit included	
Article Number	4933459683
EAN Code	4058546028558

DRUM MACHINE ATTACHMENTS

	Description	Fits drain cleaners M12BDC6, M12 BDC8	Fits drain cleaners M18 FDCPF8, M18 FDCPF10	Fits drain cleaners M18 FFSDC16, M18 FFSDC13, M18 FFSDC10	Fits drain cleaners MXF LSPD	Article Number	EAN Code	
Open wind spiral SD	16 mm x 15 m spiral			✓		48532775	045242513109	
Tight wind spiral HH	Ø 6 mm x 7.6 m spiral, bulb auger	✓				48532573	045242471270	
	Ø 8 mm x 7.6 m pivot bulb auger spiral	✓				48532572	045242364206	
	Ø 6 mm x 7.6 m pivot bulb auger spiral	✓				48532574	045242471287	
	6 mm x 10.5 m spiral bulb auger		✓			48532671	045242482740	
	6 mm x 15 m spiral bulb auger		✓			48532672	045242482757	
	Ø 8 mm x 7.6 m spiral, bulb auger	✓				48532571	045242364213	
	8 mm x 10.5 m spiral bulb auger		✓			48532673	045242482764	
	8 mm x 15 m spiral bulb auger.		✓			48532674	045242482771	
	10 mm x 10.5 m spiral		✓			48532675	045242482788	
	Ø 6 mm x 7.6 m spiral, bulb auger with drum	✓				48532581	045242480586	
	Ø 6 mm x 7.6 m spiral, pivot bulb auger with drum	✓				48532582	045242480593	
	Ø 8 mm x 7.6 m spiral, bulb auger with drum	✓				48532583	045242480609	
	Ø 8 mm x 7.6 m spiral, pivot bulb auger with drum	✓				48532584	045242480616	
Tight wind spiral SD	8 mm x 23 m inner core bulb head			✓		48532772	045242513079	
	10 mm x 15.2 m inner core coupling end			✓		48532773	045242513086	
	13 mm x 15 m spiral			✓		48532774	045242513093	
	16 mm x 7.6 m inner core coupling end				✓	4932471701	4058546296001	
	16 mm x 15.2 m inner core coupling end				✓	4932471702	4058546296018	
	20 mm x 7.6 m inner core coupling end				✓	4932471703	4058546296025	
	20 mm x 15.2 m inner core coupling end				✓	4932471704	4058546296032	
	16 mm anchor cable coupling end				✓	4932471707	4058546296063	
	16 mm x 60 cm leader cable coupling end				✓	4932471708	4058546296070	
	20 mm x 600 mm leader cable coupling end				✓	4932471709	4058546296087	
Bulb auger HH	Retriever bulb		✓	✓		48532681	045242503803	
C-cutter HH	25 mm grease cutter		✓	✓		48532684	045242503834	
C-cutter SD	Medium C cutter for 10, 13, 16 mm cables		✓	✓		48532789	045242006137	
Chain knocker SD	75 mm chain knocker for 16, 20 mm cables				✓	48532837	4058546323448	
	100 mm chain knocker for 16, 20 mm cables				✓	48532838	4058546323455	
Drop head HH	Down retriever bulb		✓	✓		48532682	045242503810	
Drop head SD	Drop head		✓	✓		48532787	045242006113	
Funnel auger SD	Funnel auger for 16, 20 mm cables				✓	48532831	4058546323387	
	Funnel retriever		✓	✓		48532786	045242006106	
Head kit HH	M18™ small 5 pcs attachment set		✓	✓		48532685	045242503841	
	M18™ medium 5 pcs attachment set		✓	✓		48532790	045242006144	
Head kit SD	9 pc head kit 16, 20 mm cables				✓	48532840	4058546296131	
Opening tool SD	Small opening tool for 16, 20 mm cables				✓	48532835	4058546323424	
	Medium opening tool for 16, 20 mm cables				✓	48532836	4058546323431	
Root cutter SD	75 mm root cutter for 16, 20 mm cables				✓	48532832	4058546323394	
	100 mm root cutter for 16, 20 mm cables				✓	48532833	4058546323400	
	150 mm root cutter for 16, 20 mm cables				✓	48532834	4058546323417	
Spade bit HH	25 mm spade bit		✓	✓		48532683	045242503827	
Spade bit SD	36 mm spade bit		✓	✓		48532788	045242006120	
Straight auger SD	Straight auger for 16, 20 mm cables				✓	48532830	4058546323370	
SAF	SWITCH PACK™ auto feed for M18 FFSDC series			✓		4932471993	4058546298920	
GHSAF	Guide hose for SWITCH PACK™ auto feed			✓		4932471994	4058546298937	
BPSAF	Base plate for SWITCH PACK™ auto feed			✓		4932478225	4058546344023	
SWITCH PACK™ drum	Drain cleaner drum only			✓		4932464277	4058546222222	
MX drum guide hose	Guide hose for MXFLSDP				✓	4932478110	4058546340421	
Pin key	Pin key for all cables		✓	✓	✓	4932471717	4058546296162	

M12 BDC8 | M12™ SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 8 MM

M12

- Lightest professional drain cleaner on the market
- Versatile design, provides benefits of both handheld and floor based drain cleaners in one machine
- Best user flexibility and manoeuvrability due to the independence of electric power supply
- Tool includes a tough 8 mm spiral for strong blockages in pipes up to 50 mm. It can also be used with all standard Ø 6 & 8 mm spirals, from both MILWAUKEE® and other manufacturers
- Robust drum shield protects user & fixtures from spinning drum during use
- Easy removable inner drum helps to prevent spiral bind up and contains dirt inside the drum
- Quick cable lock mechanism for manual feeding and releasing the spiral
- Integrated LED light illuminates work area underneath sinks and other dark spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 BDC8-0C	
No load speed (rpm)	0 - 500
Drain capacity [mm]	32 - 50
Spiral diameter [mm]	8
Spiral length [m]	7.6
Bucket capacity [l]	22.5
Weight with battery pack (EPTA) (kg)	4.8 (M12 B2)
Standard equipment	8 mm x 7.6 m inner core bulb head
Kit included	No batteries supplied, No charger supplied, Bucket
Article Number	4933451632
EAN Code	4002395140992

M12 BDC6 | M12™ SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 6 MM

M12

- Lightest professional drain cleaner on the market
- Versatile design, provides benefits of both handheld and floor based drain cleaners in one machine
- Best user flexibility and manoeuvrability due to the independence of electric power supply
- Tool includes a highly flexible 6 mm spiral for easy access in drainpipes up to 50 mm. It can also be used with all standard Ø 6 & 8 mm spirals, from both MILWAUKEE® and other manufacturers
- Robust drum shield protects user & fixtures from spinning drum during use
- Easy removable inner drum helps to prevent spiral bind up and contains dirt inside the drum
- Quick cable lock mechanism for manual feeding and releasing the spiral
- Integrated LED light illuminates work area underneath sinks and other dark spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 BDC6-0C	
No load speed (rpm)	0 - 500
Drain capacity [mm]	32 - 50
Spiral diameter [mm]	6
Spiral length [m]	7.6
Bucket capacity [l]	22.5
Weight with battery pack (EPTA) (kg)	4.2 (M12 B2)
Standard equipment	6 mm x 7.6 m inner core bulb head
Kit included	No batteries supplied, No charger supplied, Bucket
Article Number	4933451634
EAN Code	4002395141616

M18 FSSM | M18 FUEL™ SECTIONAL SEWER MACHINE

M18 FUEL

- World's first cordless sectional sewer machine on a 18V battery with automatic feed and retract that can be used with 22 mm and 32 mm sectional spirals from both MILWAUKEE® and other manufacturers in pipes from 50 mm up to 200 mm, up to 60m down the line, eliminating all electrocution hazards users encounter today with their corded tools
- CABLE-DRIVE locking feed system maintains selected feed speed, and auto-adjusts to compatible cable sizes, 22 mm and 32 mm, for the best cable grip when feeding and working the clog
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Rear wheels with extendable front carry handle and fully enclosed cable drum provide the user with better mess containment and easier transportation
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Spirals and attachment heads sold separately



M18 FSSM-0	
No load speed (rpm)	700
Drain capacity [mm]	50 - 200
Spiral length [m]	60
Autofeed	Yes
Weight with battery pack (EPTA) (kg)	33.3 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471411
EAN Code	4058546290399

M18 FCSSM | M18 FUEL™ COMPACT SECTIONAL SEWER MACHINE













M18 FUEL

- World's first compact sectional sewer machine on a 18V battery that uses 16 mm and 22 mm sectional spirals from both MILWAUKEE® and other manufacturers, eliminating all electrocution hazards users encounter today with their corded tools
- Extremely light weight, 14 kg including M18™ 12.0 Ah battery, allowing user to comfortably transport the compact sectional up multiple flights of stairs or over longer distances
- Can be used in pipes from 32 mm up to 160 mm, maximum 46 m down the line
- MILWAUKEE® fully enclosed drums for better mess containment during transportation for 16 mm and 22 mm spirals are available and sold separately
- Extremely small footprint allowing users to work in tight spaces
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Spirals and attachment heads sold separately



M18 FCSSM-0	
No load speed (rpm)	650
Drain capacity [mm]	32 - 160
Spiral length [m]	46
Autofeed	No
Weight with battery pack (EPTA) (kg)	14.0 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933478408
EAN Code	4058546345990

SECTIONAL SEWER MACHINE ATTACHMENTS

	Description	Fits sewer machine M18 FCSSM	Fits sewer machine M18 FSSM	Article Number	EAN Code	
Open wind spiral SM	16 mm x 2.3 m open wind coupling end	✓		4932478413	4058546346041	
	16 mm x 2.3 m open wind inner core coupling	✓		4932478414	4058546346058	
	22 mm x 4.5 m open wind inner core coupling end	✓	✓	4932478415	4058546346065	
	22 mm x 4.5 m open wind coupling end	✓	✓	4932471712	4058546296117	
	22 mm x 4.5 m open wind coupling end kit	✓	✓	4932471713	4058546296124	
	32 mm x 4.5 m open wind coupling end		✓	4932471710	4058546296094	
	32 mm x 4.5 m open wind heavy duty coupling end		✓	4932471711	4058546296100	
Drop head SM	Drop head bulb 16 mm cables	✓		48533811	4058546346133	
	Drop head straight 16 mm cables	✓		48533812	4058546346126	
Funnel auger SM	Funnel auger for 16 mm cables	✓		48533813	4058546346140	
	Small funnel auger for 22 mm cables	✓	✓	48533828	4058546346089	
	Medium funnel auger for 22 mm cables	✓	✓	48533831	4058546323479	
	Funnel auger for 32 mm cables		✓	48534831	4058546323561	
Opening tool SM	Extra small opening tool for 16 mm cables	✓		48533814	4058546346157	
	Small opening tool for 16 mm cables	✓		48533815	4058546346164	
	Small opening tool for 22 mm cables	✓	✓	48533827	4058546346096	
	Small opening tool for 22 mm cables	✓	✓	48533835	4058546323516	
	Medium opening tool for 22 mm cables	✓	✓	48533836	4058546323523	
	Small opening tool for 32 mm cables		✓	48534835	4058546323608	
	Medium opening tool for 32 mm cables		✓	48534836	4058546323615	
Spring cleaner SM	Spring cleaner for 16 mm cables	✓		48533816	4058546346171	
	Spring cleaner for 22 mm cables	✓	✓	48533826	4058546346102	
Root cutter SM	50 mm root cutter for 22 mm cables	✓	✓	48533825	4058546346119	
	75 mm root cutter for 22 mm cables	✓	✓	48533832	4058546323486	
	100 mm root cutter for 22 mm cables	✓	✓	48533833	4058546323493	
	150 mm root cutter for 22 mm cables	✓	✓	48533834	4058546323509	
	75mm root cutter for 32 mm cables		✓	48534832	4058546323578	
	100 mm root cutter for 32 mm cables		✓	48534833	4058546323585	
	150 mm root cutter for 32 mm cables		✓	48534834	4058546323592	
Straight auger SM	Small straight auger for 22 mm cables	✓	✓	48533829	4058546346072	
	Medium straight auger for 22 mm cables	✓	✓	48533830	4058546323462	
	Straight auger for 32 mm cables		✓	48534830	4058546323554	
Chain knocker SM	75 mm chain knocker for 22 mm spirals	✓	✓	48533837	4058546323530	
	100 mm chain knocker 22 mm cables	✓	✓	48533838	4058546323547	
	75 mm chain knocker for 32 mm spirals		✓	48534837	4058546323622	
	100 mm chain knocker 32 mm cables		✓	48534838	4058546323639	
Head kit SM	9pc head kit for 22 mm cables	✓	✓	48533840	4058546296148	
	9pc head kit for 32 mm cables		✓	48534839	4058546296155	
Small guide hose	Small guide hose for FCSSM	✓		4932478410	4058546346010	
Medium guide hose	Medium guide hose for FCSSM	✓		4932478409	4058546346003	
Large guide hose	Large guide hose for FSSM		✓	4932471720	4058546296193	
Cable drum	Cable drum for 16mm spirals	✓		4932478412	4058546346034	
	Cable drum for 22mm spirals	✓	✓	4932478411	4058546346027	
	Cable drum for 32mm spirals		✓	4932471719	4058546296186	
Pin key	Pin key for all cables	✓	✓	4932471717	4058546296162	

M12 PL
M12™ PLUMBING LOCATOR

- Easy to use plumbing locator: 2 omni directional antennas make locating sondes and tracing energised lines easy without any ghost signals
- First locator on the market on a 12V battery with 13 hours run time on a M12™ 2.0Ah battery, no alkaline batteries that need frequent changing
- 4.3" colour LCD screen with backlit buttons for better visibility
- Active guiding indicators: arrow icon points to direction of sonde and compass indicator direct the path of the energised line
- Sealed battery door for IP65 rated protection against the toughest conditions
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 PL-OC	
Display Size [Inch]	4.3
IP protection class	65
Line trace frequency (k)/Hz	33, 83
Sonde Frequency (k)/Hz	512, 640, 33
Weight with battery pack (EPTA) (kg)	2.6 (M12 B2)
Kit included	No batteries supplied, No charger supplied, Kitbox
Article Number	4933471995
EAN Code	4058546298944

M12 IC | M12™ SUB COMPACT M-SPECTOR™ 360° CAMERA

- Rotating screen: screen rotates 270 degrees providing the user fluid image control
- Optimised 68.6 mm LCD: digital image and large screen delivers crisp, clear picture
- 9 mm 640 x 480 digital image sensor: outstanding image quality in nearly half the size
- 4 surround LED lights: best in class brightness without shadow or glare
- Enhanced cable: aluminium head and improved flexibility deliver unmatched durability and pipe manoeuvrability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries
- Accessories: hook, magnet, and mirror attachments help to inspect and solve



M12 IC-201C (S)	
Display size (mm)	68
Display resolution (pixels)	320 x 240
Camera head diameter (mm)	9
Camera cable length (mm)	914
Weight with battery pack (EPTA) (kg)	0.60 (M12 B2)
Kit included	1 x M12 B2 Battery pack, C12 C Charger, Kitbox
Article Number	4933451024
EAN Code	4002395136995

M12 IC AV3 | M12™ DIGITAL INSPECTION CAMERA

- Removable screen, screen can be removed from console and works within a range of 10 m
- M12™ digital inspection camera 4x zoom and screen rotation
- Optimised 85 mm LCD, digital image and larger screen delivers crisp, clear picture
- 12 mm 320 x 240 digital image sensor, superior image quality in improved larger screen
- 4 surround LED lights, for best in class brightness without shadow or glare
- Supplied with 8 GB SD memory card and 2.7 m digital cable
- Enhanced cable, aluminium head and improved flexibility delivers unmatched durability and manoeuvrability
- Articulating head attachment available as an accessory
- Flexible battery system, works with all Milwaukee® M12™ batteries



M12 IC AV3-201C	
Display size (mm)	85
Display resolution (pixels)	320 x 240
Camera head diameter (mm)	12
Cable length (m)	2.7
Image zoom	4x
Weight with battery pack (EPTA) (kg)	0.70 (M12 B2)
Kit included	1 x M12 B2 Battery pack, C12 C Charger, Kitbox
Article Number	4933459154
EAN Code	4002395289899

NEW **M18 MODULAR PIPELINE INSPECTION SYSTEM**

CLEAR IMAGES.
EASY INSPECTIONS.



ONE-KEY

TRACK AND MANAGE.



Track your tool's location, and if lost, get alerts when found.

Lock your tool and disable remotely.

DOWNLOAD THE FREE APP NOW!



STEP 1

CHOOSE YOUR DESIRED REEL



36 m, 25 mm Camera



60 m, 34 mm Camera

STEP 2

SMART HUB



- Save HD images and video recordings to M18™ 500 GB smart hub
- Maintain live video when swapping M18™ REDLITHIUM™ batteries

STEP 3

CHOOSE YOUR VIEWING DEVICE



- Choose MILWAUKEE® monitor and/or tablet/smartphone with MILWAUKEE® Pipeline Inspection app

STEP 4

SAVE YOUR RECORDINGS

USB  OR



- Download large files to USB
- Send saved recordings from mobile device

M18 SIC60SC

M18™ SEWER INSPECTION SMALL CAMERA 60 M

- 25 mm 1080 p HD camera with pan zoom, allowing the user to zoom in on the entire picture
- 12 LED's for better illumination of drains
- 60 m long, 10 mm thick push rod for easier reach of longer runs but still flexible enough to run through 50 mm 90 degree bends
- Fully enclosed reels for better mess containment
- Rubber stand for putting reel on back
- Extendable handle for easier transportation
- Build-in sonde for easy locating: 512 Hz, 640 Hz, 33 kHz to be used with all common locators
- Build-in line trace for locating the push rod
- Imbedded TICK™ ensures ONE-KEY™ tool tracking and security, which offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Supplied with 1x 75 mm skid and 1x 100 mm skid

	M18 SIC60SC
Cable diameter (mm)	10
Camera Cable Length (m)	60
Camera head diameter (mm)	25
Camera Head Ingress Protection [P]	67
Camera Resolution (px)	1080
Drain capacity (mm)	50 - 150
Line trace frequency (k)(Hz)	33, 83
Sonde Frequency (k)(Hz)	512, 640, 33
Weight (kg)	16.6
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933480585
EAN code	4058546408701



M18 SIC60 | M18™ SEWER INSPECTION CAMERA 60 M

- 34 mm 1080 p HD camera with pan zoom, allowing the user to zoom in on the entire picture
- 20 LED's for better illumination of drains
- 60 m long, 12 mm thick push rod for easier reach of longer runs but still flexible enough to run through 75 mm 90 degree bends
- Fully enclosed reels for better mess containment
- Rubber stand for putting reel on back
- Extendable handle for easier transportation
- Build-in sonde for easy locating: 512 Hz, 640 Hz, 33 kHz to be used with all common locators
- Build-in line trace for locating the push rod
- Imbedded TICK™ ensures ONE-KEY™ tool tracking and security, which offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Supplied with 1x 75 mm skid and 1x 115 mm skid



	M18 SIC60
Cable diameter (mm)	12
Camera Cable Length (m)	60
Camera head diameter (mm)	34
Camera Head Ingress Protection [P]	67
Camera Resolution (px)	1080
Drain capacity (mm)	75 - 250
Line trace frequency (k)(Hz)	33, 83
Sonde Frequency (k)(Hz)	512, 640, 33
Weight (kg)	20.5
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471412
EAN Code	4058546290405

M18 SIC36 | M18™ SEWER INSPECTION CAMERA 36 M

- 25 mm 1080 p HD camera with pan zoom, allowing the user to zoom in on the entire picture
- 12 LED's for better illuminating pipe
- 36 m long, 10 mm thick push rod for easier reach of longer runs but still flexible enough to run through 50 mm 90 degree bends
- Fully enclosed reels for better mess containment
- Rubber stand for putting reel on back
- Back pack straps for easier transportation
- Build-in sonde for easy locating: 512 Hz, 640 Hz, 33 kHz to be used with all common locators
- Imbedded TICK™ ensures ONE-KEY™ tool tracking and security, which offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- Supplied with 1x 75 mm and 1x 100 mm skid
- Build-in line trace for locating the push rod



	M18 SIC36
Cable diameter (mm)	10
Camera Cable Length (m)	36
Camera head diameter (mm)	25
Camera Head Ingress Protection [P]	67
Camera Resolution (px)	1080
Drain capacity (mm)	50 - 160
Line trace frequency (k)(Hz)	33, 83
Sonde Frequency (k)(Hz)	512, 640, 33
Weight (kg)	12.4
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471413
EAN Code	4058546290412

M18 SISH

M18™ SEWER INSPECTION SMART HUB

- Easily interchangeable between reels with one push on the button
- Integrated WI-FI for connection with MILWAUKEE® monitor and tablet or smartphone with NEW MILWAUKEE® App
- Share customised reports
- Multiple screen viewing and recording
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- 500 GB SSD-drive store multiple jobs and extract when needed
- USB 3.0 and USB-C ports
- Battery compartment accepts all MILWAUKEE® M18™ batteries
- Integrated line trace for tracking push cable of camera reel with 33kHz or 83kHz



ONE-KEY
UNLOCKING THE DIGITAL JOBSITE.

M18 SISH-0	
IP protection class	54
Line trace frequency (k)(Hz)	33 65, 83
SSD Harddrive (GB)	500
USB Drive	Yes
Video Connection	MILWAUKEE® sewer inspection monitor or MILWAUKEE® pipeline inspection app with Android and IOS
Weight with battery pack (EPTA) (kg)	3.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471415
EAN Code	4058546290436

M18 SIM

M18™ SEWER CAMERA MONITOR

- Wireless 8" high resolution, 800 x 600, LCD screen for optimal viewing
- Sun readable screen for best viewing of inspection
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Easy reporting function with flag moments to highlight problems in pipe
- Recording video and pictures to add to reports created on site
- USB 3.0 and USB-C ports
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Connect to M18 SISH with USB-C cable for wired connection



ONE-KEY
UNLOCKING THE DIGITAL JOBSITE.

M18 SIM-0	
Display resolution (pixels)	600 x 800
Display Size (Inch)	8
IP protection class	54
USB Drive	Yes
Video Connection	Wireless and USB-C
Weight with battery pack (EPTA) (kg)	2.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471414
EAN Code	4058546290429

SEWER INSPECTION TABLET MOUNT	
Article Number	4932478406



M12 360IC12 | M12™ 360° INSPECTION CAMERA 1.2 M 2ND GEN

M12

- Large LCD screen size of 4.3 inches delivers sharp and clear images and allows users to see objects in greater detail
- 270° rotating screen provides the user fluid image control in every position of use
- 1.2 meter cable balances flexibility and rigidity for both drain line and behind wall inspections
- 5 modes of brightness provide best in class illumination without shadow or glare
- Included 32 GB micro SD card allows to record and store images and videos
- 10mm camera head for easy access in tight spaces
- 720p camera resolution provides outstanding image quality
- 3 level zoom to quickly focus on points of interest
- Digital 180° image rotation to easily adjust the perspective
- IP67 camera head and camera cable withstands toughest jobsite conditions
- Included hook, magnet, mirror and plumbing ball attachments for added functionality
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 360IC12-0C	
Display Size (Inch)	4.3
Display resolution (pixels)	480×272
Camera head diameter (mm)	10
Camera cable length (mm)	1200
Weight with battery pack (EPTA) (kg)	0.88kg
Kit included	No batteries supplied, No charger supplied, Kitbox
Article number	4933480739
EAN code	4058546410247

M12 360IC32 | M12™ 360° INSPECTION CAMERA 3 M 2ND GEN

M12

- Large LCD screen size of 4.3 inches delivers sharp and clear images and allows users to see objects in greater detail
- 270° rotating screen provides the user fluid image control in every position of use
- 3 meter cable balances flexibility and rigidity for both drain line and behind wall inspections
- 5 modes of brightness provide best in class illumination without shadow or glare
- Included 32 GB micro SD card allows to record and store images and videos
- 10mm camera head for easy access in tight spaces
- 720p camera resolution provides outstanding image quality
- 3 level zoom to quickly focus on points of interest
- Digital 180° image rotation to easily adjust the perspective
- IP67 camera head and camera cable withstands toughest jobsite conditions
- Included hook, magnet, mirror and plumbing ball attachments for added functionality
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 360IC32-0C	
Display Size (Inch)	4.3
Display resolution (pixels)	480×272
Camera head diameter (mm)	10
Camera cable length (mm)	3000
Weight with battery pack (EPTA) (kg)	1.19kg
Kit included	No batteries supplied, No charger supplied, Kitbox
Article number	4933480741
EAN code	4058546410261

AIC2 | ALKALINE INSPECTION CAMERA 2ND GEN

- Large LCD screen size of 4.3 inches delivers sharp and clear images and allows users to see objects in greater detail
- 1.2 meter cable balances flexibility and rigidity for both drain line and behind wall inspections
- 5 modes of brightness provide best in class illumination without shadow or glare
- 720p camera resolution provides outstanding image quality
- 3 level zoom to quickly focus on points of interest
- Digital 180° image rotation to easily adjust the perspective
- Powered by 4 AA batteries (Included)
- IP67 camera head and camera cable withstands toughest jobsite conditions
- Included hook, magnet, mirror and plumbing ball attachments for added functionality
- 10mm camera head for easy access in tight spaces




AIC2	
Display Size (Inch)	4.3
Display resolution (pixels)	480×272
Camera head diameter (mm)	10
Camera cable length (mm)	1200
Weight with battery pack (EPTA) (kg)	0.71kg
Kit included	4 x AA , Kitbox
Article number	4933480738
EAN code	4058546410230



OUTDOOR EQUIPMENT



M18 F2LM53
M18 FUEL™ DUAL BATTERY SELF-PROPELLED
LAWN MOWER 53 CM



- 53 cm steel deck and blade design paired with M18 FUEL™ technology deliver best-in-class quality of cut
- Instant start in tall grass, outstanding peak power and start up torque to complete demanding applications
- 3-in-1 grass management system to mulch, bag, or rear side discharge
- Automatic blade speed adjustment to the required power for more efficiency
- Adjustable self-propelled mechanism with 5 speed settings delivers up to 6.4 km/h cutting speed
- Active speed management paddle delivers ultimate user control
- Runs on 2 x 18V batteries for outstanding power and performance
- Cuts areas up to 2000 m² on a single charge of two M18™ HIGH OUTPUT™ 12.0 Ah battery packs
- Front and side headlights deliver 180° visibility for increased awareness & precision
- 7-position, single point cutting height adjustment from 2.5 – 10 cm to cover a range of grass types
- Folding handles and upright storage for easy and compact transportation
- Includes mulch plug, 70 litre bag and a rear side discharge chute
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

	M18 F2LM53-0	M18 F2LM53-122
Blade speed [min 1]	3.300	3.300
Decksize [cm]	53	53
Drive mechanism	Self propelled	Self propelled
Mulching capable	Yes	Yes
Front wheel Ø [cm]	20.3	20
Rear wheel Ø [cm]	26.4	26
Weight with battery pack (EPTA) [kg]	38.5 (2 x M18 HB12)	38.5 (2 x M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 HB12 Battery packs, M18 DFC Charger, No kitbox or bag supplied
Article number	4933479584	4933479822
EAN code	4058546373788	4058546376161



PERFECT
MATCH

MOWER BLADE 21" 53 CM

Article Number 4932479818



M18 BLLT | M18™ BRUSHLESS LINE TRIMMER

- The M18™ brushless line trimmer has the power to clear thick brush and reaches full throttle in under 1 second
- Up to 4600 RPM in first mode and 6200 RPM in second mode
- 2-speed variable trigger allows the user to choose between higher performance or extended run time
- Adjustable cutting swath of 35 cm – 40 cm
- Up to 1 hour of run time with M18™ HIGH OUTPUT™ 8.0 Ah battery pack
- Easy load trimmer head and adjustable auxiliary handle for optimum user comfort and control
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 BLLT-0
Cutting line diameter [mm]	2.4
Cutting path width [cm]	40
Weight with battery pack (EPTA) [kg]	5.3 (M18 HB8)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933472218
EAN Code	4058546326142

M18 FBCU | M18 FUEL™ BRUSH CUTTER

- Powerful brush cutter designed to clear grass, weeds, thick brush and saplings up to 3 cm diameter
- Full throttle in under 1 second for instantaneous power and ultimate control
- Supplied with a trimmer head for a 35-40 cm cutting swath and a 23 cm blade featuring a 4-tooth design, meant to take on more demanding applications
- Two speed modes allow the user to choose between maximum performance or extended run time
- Great ergonomics from the bike handle design and double shoulder harness allowing for more user comfort
- Optimized guard design for the best material containment
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FBCU-0	M18 FBCU-802
Cutting path width blade [cm]	23	23
Cutting path width (string head) [cm]	40	40
Speed settings	2	2
Handle type	Bike handle	Bike handle
Weight with battery pack (EPTA) [kg]	4.9	6.5 (M18 HB12)
Article number	4933492297	4933492299
EAN code	4058546416645	4058546416669



M18 CHT | M18 FUEL™ HEDGE TRIMMER 60 CM

- POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Power to cut 20 mm branches
- 600 mm blade trims more material in a single pass, increasing reach and productivity
- Up to 2 hours run time with an M18™ HIGH OUTPUT™ 8.0 Ah battery pack
- Cuts up to 30% faster vs. cordless competitor
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL	
M18 CHT-0	
No load speed [ml/min]	3400
Blade length (mm)	610
Tooth spacing [mm]	20
Cutting Capacity [mm]	20
Sharpening angle to horizontal [Degrees]	< 30
Weight with battery pack (EPTA) (kg)	5.0 (M18 HB8)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459346
EAN Code	4058546010072

M18 FHT45 | M18 FUEL™ HEDGE TRIMMER 45 CM

- 45 cm blade for more flexibility and the power to cut 19 mm branches
- Sustains power under load without bogging down
- Up to 2 hours run time with an M18™ HIGH OUTPUT™ 8.0 Ah battery pack
- All-metal gear case fully encloses and completely protects the gear drive system from jobsite abuse
- Blade tip guard to protect the blades and prevent accidental damage of fences or other objects
- Bail handle placement and weight distribution provide the best combination of balance and control
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL	
M18 FHT45-0	
No load speed [ml/min]	3400
Blade length (mm)	450
Tooth spacing [mm]	17.5
Cutting Capacity [mm]	19
Sharpening angle to horizontal [Degrees]	< 30
Weight with battery pack (EPTA) (kg)	4.7 (M18 HB8)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933479677
EAN code	4058546374716

M12 FHT20 | M12 FUEL™ HEDGE TRIMMER 20 CM

- 20 cm blade ideal for small detail work like trimming overgrowth or topiary of hedges, shrubs and small bushes
- Delivers fast and precise cuts for upmost productivity
- All metal gear case for increased durability
- Slim ergonomic gripping area for outstanding control in tight to reach areas
- Well balanced and low weight for better control and effortless cutting in multiple positions
- Blade tip guard to protect the blades and prevent accidental damage of other objects
- Fuel gauge displays remaining charge
- Complete with protective blade cover when not in use
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE™s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL	
M12 FHT20-0	M12 FHT20-402
No load speed [ml/min]	2700
Blade length (mm)	200
Tooth spacing [mm]	14
Cutting Capacity [mm]	12.5
Sharpening angle to horizontal [Degrees]	< 30
Weight with battery pack (EPTA) (kg)	1.7 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933479675
EAN code	4058546374693

M18 FCHS | M18 FUEL™ CHAINSAW WITH 40 CM BAR

- The M18 FUEL™ chainsaw delivers the power to outperform on the most demanding chainsaw applications vs. petrol chainsaws
- FUEL™ technology allows the saw to maintain speed in tough application without bogging down, giving it the ability to outperform petrol chainsaws up to 40cc
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Provides extremely high work per charge the saw will cut 150 pieces of 100 mm x 100 mm pine on one full charge of a 12.0 Ah battery pack
- High strength all metal gearing delivers best in class torque
- Variable speed trigger allows the user to have full control over the power curve, giving instantaneous throttle response to reach full speed in under one second
- All metal bucking spikes allows the user increased leverage when cutting
- No-spill oil reservoir with easy to access tank and clear viewing window
- Supplied with 80cc of oil, chain tool and bar cover
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL	
M18 FCHS-0	M18 FCHS-121B
Chain bar length (cm)	40
Chain speed (m/s)	12.4
Weight with battery pack (EPTA) (kg)	6.4 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464723
EAN Code	4058546226688

M18 FCHS35 | M18 FUEL™ CHAINSAW WITH 35 CM BAR

- Delivers the power to outperform on the most demanding applications vs. petrol chainsaws
- Maintains speed in tough applications without bogging down
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- It cuts up to 150 pieces of 100 mm x 100 mm pine on a full charge of an M18™ HIGH OUTPUT™ 12.0 Ah battery pack
- High strength all metal gearing delivers best in class torque
- Variable speed trigger allows the user to have full control over the power curve, giving instantaneous throttle response to reach full speed in under one second
- All metal bucking spikes allows the user increased leverage when cutting
- No-spill oil reservoir with easy to access tank and clear viewing window
- Supplied with 80cc of oil, chain tool and bar cover
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL	
M18 FCHS35-0	M18 FCHS35-121
Chain bar length (cm)	35
Chain speed (m/s)	12.4
Weight with battery pack (EPTA) (kg)	6.4 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933479678
EAN code	4058546374723

M18 FCHSC | M18 FUEL™ CHAINSAW WITH 30 CM BAR

- Delivers the power to outperform on the most demanding chainsaw applications vs. petrol chainsaws
- FUEL™ technology allows the saw to maintain speed in tough application without bogging down, giving it the ability to outperform petrol chainsaws up to 40cc
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Provides extremely high work per charge the saw will cut 150 pieces of 100 mm x 100 mm pine on one full charge of a 12.0 Ah battery pack
- Shorter bar of 30 cm allows users to work in confined areas
- Variable speed trigger allows the user to have full control over the power curve, giving instantaneous throttle response to reach full speed in under one second
- All metal bucking spikes allows the user increased leverage when cutting
- No-spill oil reservoir with easy to access tank and clear viewing window
- Supplied with 80cc of oil, chain tool and bar cover
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 FUEL	
M18 FCHSC-0	M18 FCHSC-121
Chain bar length (cm)	30
Chain speed (m/s)	12.4
Weight with battery pack (EPTA) (kg)	6.4 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933471441
EAN Code	4058546290696

M18 FHS20
M18 FUEL™ HATCHET™ PRUNING SAW 20 CM

- M18 FUEL™ HATCHET™ pruning saw delivers outstanding power and torque to cut hardwood without bogging down
- Designed to meet the ergonomic, performance, and durability needs of landscape maintenance professionals
- Compact design for increased control and manoeuvrability in tight access areas
- Up to 180 cuts in 10 x 10 cm cedar on a full M18™ HIGH OUTPUT™ 5.5 Ah battery charge for outstanding productivity
- Easy access chain tensioner ensures quick adjustment to chain tension
- Variable speed trigger gives the user full control over the power range
- All metal bucking spikes allow for increased leverage during applications
- Automatic oiler for ease of use and proper chain lubrication
- Onboard storage for scrench



M18 FUEL	
M18 FHS20-0	M18 FHS20-552
Chain bar length (cm)	20
Chain speed (m/s)	5.0
Weight with battery pack (EPTA) (kg)	3.9 (M18 HB12)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933480117
EAN code	4058546404024



M18 FTHCHS35

M18 FUEL™ TOP HANDLE CHAINSAW WITH 35 CM BAR



- Outstanding speed of cut in hardwood vs certain petrol or higher voltage top handle chainsaws
- High torque to complete cuts in demanding materials and maintains speed under heavy loads without bogging down
- FUEL™ technology to reach full throttle in under 1 second
- Up to 150 cuts in 10 x 10 cm cedar on a full M18™ HIGH OUTPUT™ 8.0 Ah battery charge for outstanding productivity
- Top handle design and optimised balance perfectly suited for arboricultural work
- Variable speed trigger allows for full control over the power curve
- Lanyard hang loop for quick attachment and removal from the harness
- Ergonomic angled bail handle for convenient handling in multiple positions
- Onboard scrench storage and easy access chain tensioner for improved user comfort
- All metal bucking spikes allow the user increased leverage when cutting
- No-spill oil reservoir with easy to access tank and clear viewing window
- Supplied with 76cc of oil, chain tool and bar cover
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries




	M18 FTHCHS35-0	M18 FTHCHS35-802
Chain bar length (cm)	35	35
Chain speed (m/s)	15	15
Weight with battery pack (EPTA) (kg)	4.7 (M18 HB8)	4.7 (M18 HB8)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 HB8 Battery packs, M12-18 FC Charger, No kitbox or bag supplied
Article number	4933479588	4933479991
EAN code	4058546373825	4058546377854

AVAILABLE FROM JUNE

*This chainsaw is to be used only by trained tree surgeons. Use without proper training can result in serious injury.

M18 FTHCHS30

M18 FUEL™ TOP HANDLE CHAINSAW WITH 30 CM BAR



- Outstanding speed of cut in hardwood vs certain petrol or higher voltage top handle chainsaws
- High torque to complete cuts in demanding materials and maintains speed under heavy loads without bogging down
- FUEL™ technology to reach full throttle in under 1 second
- Up to 150 cuts in 10 x 10 cm cedar on a full M18™ HIGH OUTPUT™ 8.0 Ah battery charge for outstanding productivity
- Top handle design and optimised balance perfectly suited for arboricultural work
- Variable speed trigger allows for full control over the power curve
- Lanyard hang loop for quick attachment and removal from the harness
- Ergonomic angled bail handle for convenient handling in multiple positions
- Onboard scrench storage and easy access chain tensioner for improved user comfort
- All metal bucking spikes allow the user increased leverage when cutting
- No-spill oil reservoir with easy to access tank and clear viewing window
- Supplied with 76cc of oil, chain tool and bar cover
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FTHCHS30-0	M18 FTHCHS30-802
Chain bar length (cm)	30	30
Chain speed (m/s)	15	15
Weight with battery pack (EPTA) (kg)	4.7 (M18 HB8)	4.7 (M18 HB8)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 HB8 Battery packs, M12-18 FC Charger, No kitbox or bag supplied
Article number	4933479586	4933479990
EAN code	4058546373801	4058546377847

AVAILABLE FROM JUNE

*This chainsaw is to be used only by trained tree surgeons. Use without proper training can result in serious injury.

M12 FHS

M12 FUEL™ HATCHET™ PRUNING SAW 15 CM



- M12 FUEL™ HATCHET™ pruning saw delivers outstanding control & access, has the power to cut 75 mm hardwoods, and delivers up to 120 cuts per charge on an M12 B4 battery pack
- Designed to meet the ergonomic, performance, and durability needs of landscape maintenance professionals
- Weighing 2.3 kg and featuring a compact design, the cordless pruning saw gives you increased control and manoeuvrability in tight access areas
- Easy access chain tensioner ensures quick adjustment to chain tension
- Translucent oil reservoir allows for clear visibility to oil levels
- Variable speed trigger gives the user full control over the power range
- All metal bucking spikes allow for increased leverage during applications
- Automatic oiler for ease of use and proper chain lubrication
- Onboard storage for scrench
- Supplied with 1x Oregon 15 cm (6") bar and chain, 1x scabbard, and 1x scrench
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability



	M12 FHS-0	M12 FHS-602X
Chain bar length (cm)	15	15
Chain speed (m/s)	5	5
Usable cutting length (cm)	14	14
Weight with battery pack (EPTA) (kg)	2.3 (M12 B6)	2.3 (M12 B6)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M12 B6 Battery packs, C12 C Charger, HD Box
Article Number	4933472211	4933472213
EAN Code	4058546326074	4058546326098

M18 F2BL

M18 FUEL™ DUAL BATTERY BLOWER



- Up to 17 m³/min of air volume at 233 km/h to clear leaves, gravel and debris
- High constant clearing force with a consistent blowing force of 17.7 N over the entire battery discharge
- Best clearing control due to balanced design and ambidextrous variable speed lock allowing the user to lock on to any speed for precise applications
- Interchangeable nozzle attachments to optimise the blowing pattern for various applications
- Achieves full throttle in under 1 second
- Second handle for greater maneuverability in tight spaces
- Variable speed trigger for full power control
- Runs on 2 x 18V batteries for outstanding power and performance
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 F2BL-0	M18 F2BL-802
Air speed [km per hour]	0 - 233	0 - 233
Air volume (m³ per minute)	0 - 17	0 - 17
Weight with battery pack (EPTA) (kg)	5.9	5.9
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 HB8 Battery packs, M18 DFC Charger, No kitbox or bag supplied
Article number	4933479987	4933479989
EAN code	4058546377816	4058546377830

M18 FBL

M18 FUEL™ BLOWER



- POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Ergonomic inline design clears debris and dirt in tight spaces
- Up to 12.74 m³/min of air volume at 193 km/h to clear debris
- Variable trigger and speed lock for full power control
- Lock-on switch
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 FBL-0
Air volume 1 [m³ per minute]	8.75
Air volume 2 [m³ per minute]	12.7
Airflow Speed 1 (km/h)	133
Airflow speed 2 [km per h]	193
Fan speed [rpm]	14,000
Weight with battery pack (EPTA) (kg)	3.3 (M18 HB8)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459825
EAN Code	4058546029975

M12 BHCS3L

M12™ HANDHELD CHEMICAL SPRAYER 3.7 L



- Instant, constant and adjustable pressure for best in class control
- Three pressure settings deliver the capability to optimize performance for a wide range of applications like spot, broadcast and distance spraying
- No manual pumping allows faster application speed and reduces user fatigue versus other manual sprayers
- 5.5 bar maximum working pressure and 5.2 m vertical spray distance for increased performance
- Delivers up to 300 litres of spraying per charge with M12™ B2 battery
- Detachable trigger handle ensures optimize ergonomics for one or two handed use
- Trigger lock off eliminates the risk of unintended chemical spray
- Can be used for pesticides, herbicides, insecticides, fungicides and fertilizers
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



	M12 BHCS3L-0	M12 BHCS3L-201
Weight with battery pack (EPTA) (kg)	3.5	3.5
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M12 B2 Battery pack, C12 C Charger, No kitbox or bag supplied
Article number	4933480781	4933480783
EAN code	4058546410667	4058546410681

M18 BPFPH

M18™ SWITCH TANK™

- The M18™ SWITCH TANK™ 15 l backpack fluid pump sprayer delivers the industry's first interchangeable tank design with no manual pumping
- The interchangeable tank design isolates the pump, hose and wand, separating wearable components from the M18™ SWITCH TANK™ powered base
- Add on and replace tank assemblies to eliminate cross-chemical contamination and lower cost of ownership
- 120 PSI (8.27 Bar) pump pressure
- Features adjustable pressure selection dial to best suit user requirements
- Up to 2 hours of run time (12 or more tanks) with 4.0 Ah battery pack
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

	M18 BPFPH-0	M18 BPFPH-401
Weight with battery pack (EPTA) (kg)	5.0 (M18 B4)	5.0 (M18 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	1 x M18 B4 Battery pack, M12-18 C Charger, No kitbox or bag supplied
Article Number	4933464961	4933464963
EAN Code	4058546229061	4058546229085



M18 BPFPH-CST	M18 BPFPH-WST
M18™ SWITCH TANK™ 15L Chemical Sprayer	M18™ SWITCH TANK™ 15L Water Supply
<ul style="list-style-type: none">◦ Fully compatible with SWITCH TANK™◦ Chemical sprayer tank for pesticides/fertilizers/treatments/herbicides/fungicides/insecticides/de-icing agents and more◦ Semi-transparent tank with measuring scale to know how much liquid is inside the tank◦ Carry handle lid with wide mouth makes easy transport and pouring of water/chemicals into tank◦ Comfortable rubber gripped spray wand handle with ability to lock-on for larger jobs◦ Sprayer wand storage to save space and avoid damage during transport◦ Integrated strainer prevents debris from entering the tank◦ Adjustable spray pattern - from cone to straight stream for end user preference and application. Up to 7.6 m spray distance◦ 5-mode pressure adjustment knob	<ul style="list-style-type: none">◦ Fully compatible with SWITCH TANK™◦ Water sprayer tank for efficient water delivery for concrete cutting and coring applications. Also useful for washing up slurry's, areas and equipment◦ Semi-transparent tank with measuring scale to know how much liquid is inside the tank◦ Carry handle lid with wide mouth makes easy transport and pouring of water into tank◦ Replaceable hose with standard garden hose quick coupling and spray nozzle - attaches easily to concrete cutting and coring equipment. Also compatible with standard garden nozzle accessories◦ Integrated strainer prevents debris from entering the tank◦ 5-mode pressure adjustment knob◦ UV resistant
4933464964	4933464965
4058546229092	4058546229108



The interchangeable tank design



Add on and replace tank assemblies to eliminate cross-chemical contamination




Wide straps for comfort during extended duty cycles

M18 FOPH

M18 FUEL™ OUTDOOR POWER HEAD WITH QUIK-LOK™

- Versatile outdoor power equipment system, powered by a single power head
- Delivers the capability to swap between multiple attachments to complete a wide range of applications
- Full throttle in under 1 second
- 2-speed with variable speed trigger
- POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- Adjustable auxiliary handle, strap and carrying ring help set the tool up for the optimum user comfort and control
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

	M18 FOPH-0
No load speed gear 1 (rpm)	0 - 6860
No load speed gear 2 (rpm)	0 - 8680
Weight with battery pack (EPTA) (kg)	4.1 (M18 HB8)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464954
EAN Code	4058546228996



M18 FOPH-LTA	M18 FOPH-CSA	M18 FOPH-EA	M18 FOPH-HTA	M18 FOPH-EXA
QUIK-LOK™ line trimmer attachment	QUIK-LOK™ chainsaw attachment	QUIK-LOK™ edger attachment	QUIK-LOK™ hedge trimmer attachment	QUIK-LOK™ extension attachment
4932464955	4932464957	4932464958	4932464959	4932464960
4058546229009	4058546229023	4058546229030	4058546229047	4058546229054

M18 FOPH-BCA	M18 FOPH-RBA	M18 FOPH-BBA
QUIK-LOK™ brush cutter attachment	QUIK-LOK™ rubber broom attachment	QUIK-LOK™ bristle brush attachment
4932479986	4932479984	4932479985
4058546377809	4058546377786	4058546377793



Perfect for cutting down overhead limbs or branches




Articulating head offers 12 positions from 0° to 270° for the most comfortable user sculpting angles and easy trimming the top of tall hedges



Has the capability to clear thick brush

TRUEVIEW™ HIGH DEFINITION LIGHTING



TRUEVIEW™

HIGH DEFINITION LIGHTING

BUILT TO WITHSTAND THE TOUGHEST CONDITIONS ON AND OFF THE JOBSITE.

MILWAUKEE® lights combine the best cordless battery and LED technology delivering convenient, portable solutions that increase productivity and safety. TRUEVIEW™ high definition output delivers consistent beam, optimised colour temperature and true representation of colours & details.

ALL OUR MILWAUKEE® LIGHTS ARE DESIGNED TO:

ADAPT

Industrial portable lighting TRUEVIEW™ offers professionals the ability to bring light directly to their work as well as control the beam intensity and direction for greater productivity on the jobsite.

PORTABILITY



MAGNETIC ATTACHMENT



QUICK & EASY SET UP, ADJUSTABLE HEIGHT



ROTATING AND PIVOTING HEADS FOR MAXIMUM COVERAGE



PROTECTIVE BITE ZONE



PERFORM

Through the use of high quality LEDs, MILWAUKEE® designed optics and REDLITHIUM™ battery packs, TRUEVIEW™ industrial LED lights shine brighter and last longer.

MAX. 27,000 LUMEN OUTPUT



EXTENDED RUN TIME WITH 2 BATTERY PACKS



ALL-DAY RUN TIME*



* Dependent on mode selection and based on 10 hour work day

SURVIVE

Reinforced, impact resistant housing and lenses stand up to the challenges of industrial use.

Superior temperature management protects LEDs throughout their life.

IP67




IMPACT RESISTANT LENS



CHEMICAL RESISTANT LENS




MXF TL | MX FUEL™ TOWER LIGHT

- TRUEVIEW™ high definition light output with up to 27,000 lumens in AC and up to 20,000 lumens in DC mode for both task and area lighting
 - Has the ability to manoeuvre the light heads in multiple orientations, allowing the user to direct light to wherever it's needed
 - Low weight of 48 kg with the two big all-terrain wheels, this tower light is easy to transport across wet and uneven job site terrains with minimum effort
 - Due to the motorised mast, the tower light is capable to be set up in less than 10 sec. The mast is extendable up to 3.10 meter and can withstand up to 55 km/h of wind
 - To withstand the toughest conditions on the toughest job sites, the MX FUEL™ Tower Light is built with a durable, high impact polycarbonate lenses that delivers superior impact durability
 - A sealed battery box ensures batteries are kept protected from the elements at all times
 - ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality. Customisation function allows for precise tool adjustment to application
 - The built-in MX FUEL™ charger gives you the freedom to charge any MX FUEL™ battery in the AC mode
 - IP 55 rating
- 

TRUEVIEW™ MX FUEL

	MXF TL-601
System	MX FUEL™
Battery compatibility	All MX FUEL™ batteries
Bulb type	LED
Max. AC light output High Medium Low Strobe [lumens]	27,000/ 14,000/ 7000/ -
Max. DC light output High Medium Low Strobe [lumens]	20,000/ 10,000/ 5000/ -
Max. run time AC mode [h]	Endless
Max. run time with MXF XC406 [h]	3/ 6/ 10
Max. mast height [m]	3.1
Weight with battery pack (EPTA) (kg)	53 (MXF XC406)
Kit included [L4]	1 x MXF XC406 Battery pack, Integrated charger, No kitbox or bag supplied
Article Number 110V	4933471845
Article Number 240V	4933471846

M18 ONESLDP | M18™ ONE-KEY™ LED COMPACT SITE LIGHT CHARGER

- Optimise brightness and run time by adjusting the light output from 0 - 9000 lumens
 - ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely
 - ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
 - Program automatic schedules to decide during which days/times the light is running
 - Integrated M18™ charger - charges up to 2 batteries sequentially
 - Dual power source, powered by either M18™ REDLITHIUM™ battery packs or use of 2.5 m hardwired cord
 - AC outlet gives the possibility to string multiple lights together
 - Highly durable and impact resistant polycarbonate lens to protect the light from rough jobsite conditions
 - IP54 rating in battery mode - light is protected from dust and splashing water
 - TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail
 - Securable battery door helps to protect batteries from theft (lock not included)
- 

TRUEVIEW™


ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE.

M18 ONESLDP-0

Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	9000/ 4800/ 2500/ -
Max. run time with 2 x M18 B9 battery [h]	3.5/ 7/ 14/ -
Weight with battery pack (EPTA) (kg)	12.5 (M18 B9)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459161
EAN Code	4002395287161

M18

M18 ONESLSP | M18™ ONE-KEY™ LED COMPACT SITE LIGHT

- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely
 - ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
 - Optimise brightness and run time by adjusting the light output between 0 - 4400 lumens
 - Program automatic schedules to decide during which days/times the light is running
 - TRUEVIEW™ high definition lighting solutions combine the most advanced LED technology
 - 180° and 360° electronic light control for large area and task lighting
 - Self-centering metal hook designed for hanging the light from studs or pipes
 - Dual power source, powered by either M18™ REDLITHIUM™ battery packs or use of 2.5 m hardwired cord
 - AC outlet gives the possibility to string multiple lights together
 - Up to 8 hours of run time on low setting when powered by an M18™ REDLITHIUM™ 5.0 Ah battery pack
 - Highly durable and impact resistant polycarbonate lens to protect the light from rough jobsite conditions
- 

TRUEVIEW™


ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE.

M18 ONESLSP-0

Battery compatibility	All MILWAUKEE® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	4400/ 2100/ 1000/ -
Max. run time with M18 B5 battery [h]	2/ 4/ 8/ -
Weight with battery pack (EPTA) (kg)	6.7 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459156
EAN Code	4002395287116

M18


M18 TAL | M18™ TRADESMAN AREA LIGHT

- TRUEVIEW™ high definition lighting with 2,200 lumens of light output in Area mode and 1,000 lumens in Flood mode
 - Advanced LED technology provides 360° of area light, while an independent array of LEDs on the side provide 90° of task lighting
 - Compact design allowing for one-handed transport on the jobsite, with a built-in carry handle
 - Impact polycarbonate lens design that is impact and chemical resistant, delivering superior impact durability
 - Equipped with a 10.8 cm self-centering metal hook, users can hang the light overhead on studs and piping
 - Low battery indicator, light flashes when battery pack is low on charge
 - Flexible battery system: works with all MILWAUKEE® M18™ batteries
- 

TRUEVIEW™ M18

	M18 TAL-0
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output Area Mode High Medium Low [lumens]	2200/ 1100/ 550
Max. light output Flood Mode High Medium Low [lumens]	1000 / 500 / 250
Max. run time on area mode with M18 B5 battery [h]	4/ 8/ 16
Max. run time on flood mode with M18 B5 battery [h]	6/ 12/ 24
Weight with battery pack (EPTA) (kg)	2.5 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464134
EAN Code	4058546220792


HOBL 7000 | HIGH OUTPUT BAY LIGHT

- TRUEVIEW™ high definition lighting - 7700 lumens of even light output for best jobsite illumination (110 lumens / Watt)
 - Impact resistant polycarbonate lens withstands drops from up to 2.7 m
 - Integrated wiring terminal accepts voltages from 90 - 277 V, allows easy wiring and stringing of multiple lights
 - Wire strain relief accepts cables up to H07RNF 3 x 2.5 mm²
 - Spring-loaded cable retention allows easy adjustment of installation height with 1.2 m steel hanging cable
 - 4 m AC power cord for out of the box operation
 - Conical lens design and small footprint allow simple storage and safe stacking of up to 3 units
- 

TRUEVIEW™

	HOBL 7000
Voltage (AC) (V)	90 - 277
Bulb type	LED
Weight (kg)	3.7
Supplied in	No kitbox or bag supplied

M18 ONERSAL | M18™ ONE-KEY™ LED REMOTE STAND LIGHT

- Optimise brightness and run time by adjusting the light output from 0 - 5400 lumens
 - ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely
 - ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
 - IP67 allows use in all weather conditions (heavy rain, snow, dusty environments)
 - Reinforced leg design with 3 different leg deployment options for best durability and stability
 - Highly durable and impact resistant polycarbonate lens and all aluminium cam design to protect the light from rough working conditions
 - TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail
 - Sealed battery compartment for up to 2 packs to extend run time
 - Change height from 0.5 m to 1.65 m to cast light from overhead to limit shadows
 - Collapsible to only 55 cm for easy storage and transportation
 - Flexible battery system: works with all MILWAUKEE® M18™ batteries
- 

TRUEVIEW™


ONE-KEY™
UNLOCKING THE DIGITAL JOBSITE.

M18 ONERSAL-0

Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	5400/ 3000/ 1550/ -
Max. run time with 2 x M18 B9 battery [h]	7/ 12.5/ 26/ -
Weight with battery pack (EPTA) (kg)	10.1 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459431
EAN Code	4058546010928

M18


M18 HOSALC | M18™ HIGH OUTPUT STAND AREA LIGHT CHARGER

- 6000 lumens TRUEVIEW™ of High Definition Output
 - Up to 10 hours of run time on M18™ REDLITHIUM™ 8.0 Ah battery pack
 - 3 impact resistant adjustable heads with highly durable lens can be rotated 180° vertically and pivoted 240° horizontally to have the perfect workplace illumination
 - Integrated M18™ charger and 2.1 AMP USB output for USB device charging
 - AC/DC versatility: Powered by MILWAUKEE® M18™ batteries, or mains plug supply
 - IP34 rating, the light is protected from dust and splashing waters
 - Extendable mast which reaches from 1 m to over 2.2 m to light up work spaces from top without casting shadows
 - Compact footprint with low centre of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
 - Full length carry handle rail that allows balanced carry with all available M18™ REDLITHIUM™ batteries
 - Low battery indicator, light flashes when battery pack is low on charge
- 

TRUEVIEW™ M18

	M18 HOSALC-0	M18 HOSALC-552B
System	M18™	M18™
Battery compatibility	All MILWAUKEE® M18™ batteries	All MILWAUKEE® M18™ batteries
Bulb type	LED	LED
Max. light output High/Medium/Low/Strobe (lumens)	6000/ 4000/ 1700/-	6000 / 4000 / 1700 /-
Max. run time with M18 HB8 battery [h]	3.5/ 5/ 10	2.5 / 3.5 / 7.5
Weight with battery pack (EPTA) (kg)	11 (M18 HB8)	11.1 (M18 HB.5)

M18 SAL2 | M18™ LED STAND LIGHT

- TRUEVIEW™ high definition lighting
 - Twelve high performance LEDs provides up to 2800 lumens on high light output
 - Impact resistant adjustable head with highly durable polycarbonate lens can be rotated 230° vertically and pivoted 240° horizontally
 - Protective guard secures the head and lens when the light is collapsed for storage or transport
 - Extendable mast which reaches from 1.10 m to over 2.20 m to light up work spaces from top without casting shadows
 - Extendable mast which reaches from 1.10 m to over 2.20 m to light up work spaces from top without casting shadows
 - IP54 - protected from dust and splashing water
 - Compact footprint with low center of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
 - Carry handles on two positions for easy one handed transport: weight is evenly balanced when compressed
 - Low battery indicator - light flashes when battery pack is low
 - Flexible battery system: works with all MILWAUKEE® M18™ batteries
 - IP54: water and dust resistant
- 

M18 SAL2-0

M18 SAL2-502B

Battery compatibility	All Milwaukee® M18™ Batteries	All MILWAUKEE® M18™ batteries
Bulb type	LED	LED
Max. light output High/Medium/Low/Strobe (lumens)	2800/ 1300/ 860/ -	2800/1300/860
Max. run time with M18 B5 battery [h]	4.5/8.5/13.5	4.5/8.5/13.5
Weight with battery pack (EPTA) (kg)	7.6 (M18 B5)	7.6 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B5 Battery packs, M12-18 C , Tool bag
Article number	4933492486	4933492903
EAN code	4058546418533	4058546477745

M18 SAL | M18™ LED STAND LIGHT

- TRUEVIEW™ high definition lighting
- Twelve high performance LEDs provide 2000 lumens on high light output which is brighter than 250 Watt halogen
- Impact resistant adjustable head with highly durable polycarbonate lens can be rotated 230° vertically and pivoted 240° horizontally
- Protective guard secures the head and lens when the light is collapsed for storage or transport
- Extendable mast which reaches from 1.10 m to over 2.20 m to light up work spaces from top without casting shadows
- IP54 - protected from dust and splashing water
- Compact footprint with low center of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
- Carry handles on two positions for easy one handed transport: weight is evenly balanced when compressed
- Low battery indicator - light flashes when battery pack is low
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™ M18

	M18 SAL-0	M18 SAL-502B
System	M18™	M18™
Battery compatibility	All Milwaukee® M18™ batteries	All Milwaukee® M18™ batteries
Bulb type	LED	LED
Max. light output High/Medium/Low/Strobe (lumens)	2000/ 1300/ 850/ -	2000/ 1300/ 850/ -
Max. run time with M18 B5 battery [h]	4/ 6/ 10/ -	4/ 6/ 10/ -
Weight with battery pack (EPTA) (kg)	7.6 (M18 B5)	7.6 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B5 Battery packs, M12-18 C Charger, Tool bag
Article Number	4933451246	4933451895

M18 HOAL | M18™ HIGH OUTPUT AREA LIGHT

- 4000 lumens TRUEVIEW™ of High Definition Output
- Up to 12 hours of run time on M18™ REDLITHIUM™ 5.0 Ah battery pack
- 120° rotatable light head and integrated key holes for horizontal and vertical hanging
- Impact resistant design and durable roll cage to protect the light from rough jobsite conditions
- AC/DC versatility: Powered by MILWAUKEE® M18™ batteries, or mains plug supply
- Easy one-handed transport with built-in carry handles
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™ M18

	M18 HOAL-0
System	M18™
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	4000/ 2000/ 1200
Max. run time with M18 B5 battery [h]	3/ 6/ 12
Weight with battery pack (EPTA) (kg)	3.3 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number 110 V	4933478119

M12 SAL | M12™ STAND LIGHT

- TRUEVIEW™ high definition lighting
- 12 high performance LEDs provide 1400 lumens on high light output to withstand drops up to 3 m
- Head can be rotated 210° vertically and pivoted 270° horizontally to have the best perfect workplace illumination
- Protective guard secures the head and lens when the light is collapsed for storage or transport
- Extendable mast which reaches from 0.91 m to over 1.72 m to light up work spaces
- Compact footprint with low center of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
- Carry handles on 2 positions for easy one handed transport: weight is evenly balanced when compressed
- Low battery indicator - light flashes when battery pack is low
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

	M12 SAL-0
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	1400/ -/ 700/ -
Max. run time with M12 B4 battery [h]	4/ -/ 10/ -
Weight with battery pack (EPTA) (kg)	3.4 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464823
EAN Code	4058546227685

M18 AL | M18™ LED AREA LIGHT

- TRUEVIEW™ high definition lighting
- Eight high performance LEDs provide 1500 lumens of light output - up to 30% brighter than 250 W halogen lights
- Compact roll cage design provides superior durability
- Convenient built-in handle - ability to hang vertically or horizontally
- Flexibility to mount vertically on a max. 13 mm diameter pipe, threaded rod or rebar to maximise hands-free operation
- Flexible battery system: works with all MILWAUKEE® M18 batteries™



TRUEVIEW™ M18

	M18 AL-0
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	1500/ -/ 780
Weight with battery pack (EPTA) (kg)	2.1 (M18 B5)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4932430392
EAN Code	4002395380534

M18 POALC | M18™ PACKOUT™ AREA LIGHT CHARGER

- Three independent pivoting light heads provide 3000 lumens of TRUEVIEW™ High Definition Output
- All three pivot light heads combined provide up to 12 hours of run time on a M18™ REDLITHIUM™ 5.0 Ah battery pack
- IP54: water and dust resistant
- Built in charger function for quick and convenient charging of any M18™ battery or electric devices via the 2.1 AMP USB output port
- Full system compatibility with the PACKOUT™ Modular Storage System – lighting on and off the stack
- AC/DC versatility: Powered by MILWAUKEE® M18™ batteries, or mains plug supply
- Storage compartment for devices and small items
- 9 total output modes to manage output or run time
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™ M18

	M18 POALC-0
System	M18™
Battery compatibility	All MILWAUKEE® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	3000/ 1500/ 1000/ -
Max. run time with M18 B5 battery [h]	12/ 8/ 4/ -
Weight with battery pack (EPTA) (kg)	5.9 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number 240V	4933479583
EAN Code	4058546373771

M12 AL | M12™ LED AREA LIGHT

- TRUEVIEW™ high definition lighting
- Five high performance LEDs provide 1000 lumens of light output replacing 250 W halogen lights
- Highly durable and impact resistant polycarbonate lens to withstand drops up to 2.7 metres
- Integrated magnets, clamping mechanism, and key hole for screws / nails provide multiple mounting options for different surfaces
- Most compact flood light designed for the on-the-go needs of service and maintenance trades
- IP54 rating, the light is protected from dust and splashing water
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

	M12 AL-0
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	1000/ 400/ 200
Max. run time with M12 B4 battery [h]	3.5/ 7.5/ 15
Weight with battery pack (EPTA) (kg)	1.6 (M12 B6)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4933451394
EAN Code	4002395158621

M12 POAL | M12™ PACKOUT™ AREA LIGHT 1400 LUMENS

- 1400 Lumens of TRUEVIEW™ high definition output
- IP 54: water and dust resistant
- 3 modes to manage output and runtime
- 300° of horizontal rotation and 180° of vertical rotation for complete light head adjustability
- Self-centering metal hook for easy overhead hanging
- Storage compartment for devices and small items
- Full system compatibility with the PACKOUT™ Modular Storage System – lighting on and off the stack (top-stack only)
- Built in charger function for quick and convenient charging of electric devices via the 2.1 AMP USB Type-C and Type-A output port
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

	M12 POAL-0
Battery compatibility	All MILWAUKEE® M12™ batteries
Bulb type	LED
Max. light output Area Mode High/Medium/Low (lumens)	1400/700/350
Weight with battery pack (EPTA) (kg)	2.5 (M12B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933480473
EAN code	4058546407582

M18 PAL | M18™ PIVOTING AREA LIGHT

- TRUEVIEW™ high definition lighting with up to 1500 lumens and up to 20 hours of run time, allows replacement of 500 W halogen
- Two powerful magnets, a spring loaded clamp and a folding rotating light head design provide multiple mounting options and illumination possibilities from any angle
- Highly durable and impact resistant polycarbonate lens to withstand drops up to 2.7 metres
- Most compact M18™ flood light designed for the on-the-go needs of service and maintenance trades
- IP54 rating, the light is protected from dust and splashing water
- Integrated handle/tie off zone, designed to be carried or tethered while used on a scissor lift
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™ M18

	M18 PAL-0
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	1500/ 600/ 300
Max. run time with M18 B5 battery [h]	4.5/ 10/ 20
Weight with battery pack (EPTA) (kg)	2.2 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933464105
EAN Code	4058546220501

M12 PAL | M12™ PIVOT AREA LIGHT

- TRUEVIEW™ high definition lighting with up to 700 lumens
- Up to 24 hours of run time on M12™ 4.0 Ah battery pack
- With powerful magnets as well as a rotating light head design with 110° rotation in each direction to provide multiple beam options
- Highly durable and impact resistant design to withstand drops up to 3 m
- Most compact M12™ flood light designed for the on-the-go needs of service and maintenance trades
- 2.1 AMP USB output for USB device charging
- IP54 rating, the light is protected from dust and splashing water
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

M12 PAL-0	
System	M12™
Battery compatibility	All MILWAUKEE® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	700/ 250/ -/ -
Max. run time with M12 B4 battery [h]	8/ 24/ -/ -
Weight with battery pack (EPTA) (kg)	0.9 (M12 B4)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4933478226
EAN Code	4058546344030

M12 SL | M12™ LED STICK LIGHT

- TRUEVIEW™ high definition lighting
- Powerful three LED design provides 220 lumens
- Adjustable metal hook allows for light to be hung in multiple orientations when being used
- Compact design - operates in locations other lights cannot
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

M12 SL-0	
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	220/ -/ -/ -
Weight with battery pack (EPTA) (kg)	0.63 (M12 B4)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4932430178
EAN Code	4002395378395

M18 SLED | M18™ LED SEARCH LIGHT

- TRUEVIEW™ high definition lighting
- Pivoting head provides 1250 lumens with up to 650 m beam distance
- 4 output modes: Spot, Flood, Spot/Flood, Strobe delivering multiple options in work space illumination
- Spot mode for long range identification: utility pole/ high voltage cable inspection, inspection of long runs of conduit, cast or copper pipe, under ground work, bridge work...
- Flood mode for illuminating close work spaces
- IP54 rating, the light is protected from dust and splashing water
- Ergonomic grip with rubber overmould enhances user comfort and grip during use
- Key hole for hanging function
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™ M18

M18 SLED-0	
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output Spot_flood-Flood/Spot/Strobe (lumens)	1250/ 1200/ 600/ 1200
Max. run time with M18 B5 battery [h]	4/ 4/ 7/ 5
Beam distance [m]	650
Weight with battery pack (EPTA) (kg)	2.2 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459159
EAN Code	4002395287147

M12 UCL | M12™ UNDERCARRIAGE LIGHT

- TRUEVIEW™ high definition lighting with up to 1,200 Lumens
- Up to 15 hours of run time on M12™ 4.0 Ah battery pack
- Designed for the on-the-go needs of automotive maintenance and service trades
- Dual joints swivel 300° horizontally and 180° vertically to ensure full undercarriage illumination coverage
- Magnetic base for mounting applications & 30 cm magnetic storage tray to hold nuts & bolts
- Highly durable and impact resistant design to withstand drops up to 2 m
- Resistances to most common chemicals found in auto shops
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

M12 UCL-0	
Battery compatibility	All MILWAUKEE® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	1200/ 800/ 600/ -
Max. run time with M12 B4 battery [h]	5/ 8/ 15/ -
Weight with battery pack (EPTA) (kg)	1.7 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article number	4933478868
EAN code	4058546361501

M12 SLED | M12™ LED SPOT LIGHT

- TRUEVIEW™ high definition lighting
- Up to 35% longer beam distance than competition - 650 m intense and highly focused beam of light with 750 lumens
- Especially useful for long range identification - utility pole/high voltage cable inspection, inspection of long runs of conduit, cast or copper pipe, under ground work, bridge work
- Metal housing and impact resistant polycarbonate lens with gasketed rubber cap which protects from moisture for harsh jobsite conditions
- The reflector produces narrow centre beam with wide peripheral beam
- Ergonomic grip with rubber overmold - enhances user comfort and grip during use
- 45° rubber overmold stand for aiming beam upward during prolonged use when the light is equipped with a compact battery pack
- Up to 8 hours of run time with an M12™ REDLITHIUM™ 4.0 Ah battery pack
- Dual function trigger allows momentary or lock-on use
- Battery fuel gauge displays battery status
- Hand wrist lanyard to keep the light safe and handy
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

M12 SLED-0	
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	750/ -/ 400/ 750
Max. run time with M12 B4 battery [h]	4/ -/ 8/ 8
Beam distance [m]	640
Weight with battery pack (EPTA) (kg)	1.2 (M12 B4)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4933451261
EAN Code	4002395170159

M12 CML | M12™ COLOUR MATCHING LIGHT

- High definition lighting with up to 1000 lumens
- 98+ colour rendering index for use to identify accurate and reliable colour recognition
- Featuring 5 different colour temperatures, for end users to replicate real sunlight requirements
- Up to 14 hours of run time on M12™ 4.0 Ah battery pack
- IP54 rated for water and dust resistant and 2 m impact resistant
- Magnetic attachment for hands-free use
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

M12 CML-401	
Battery compatibility	All MILWAUKEE® M12™ batteries
Bulb type	LED
Max. light output Area Mode High/Low (lumens)	1000/ 600/ 300
Max. run time with M12 B4 battery [h]	6/ 8/ 14
Weight with battery pack (EPTA) (kg)	0.73 (M12 B4)
Kit included	1 x M12 B4 Battery pack, C12 C Charger, No kitbox or bag supplied
Article number	4933479367
EAN code	4058546371616

M18 IL | M18™ LED INSPECTION LIGHT

- TRUEVIEW™ high definition lighting
- Three LED design with 2 light settings provides 300 lumens on High and 130 lumens on Low setting
- Pivoting 45° forward & backward head allows for 180° coverage
- 2 adjustable metal hooks for hanging in vertical and horizontal position
- Thanks to its compact design it operates in locations other lights cannot
- Protected against splashing water at all angles (IP24)
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™ M18

M18 IL-0	
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	300/ -/ 130/ -
Weight with battery pack (EPTA) (kg)	1.2 (M18 B5)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4932430564
EAN Code	4002395382255

M12 UHL | M12™ LED UNDERHOOD LIGHT

- TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail
- Two light output settings with 1350 and 600 lumens to maximise run time and to optimise lighting output
- M12™ 4.0 Ah battery provides 4 hours of run time in high and 8 hours of run time in low setting
- Mounting hooks extend 119 cm - 196 cm (47" - 77") covering wide cars and trucks
- Flexible and versatile light bar to rotate vertically, adjust position and remove from the carrier to suit user needs
- Rubber gripping surface for maximum hold
- FINISHGUARD™ hooks provide lasting protection against scratches to a vehicle's finish
- Stainless hook allows to hang the light bar independently from the carrier
- Aircraft grade aluminium frame ensures maximum durability
- Impact and chemical resistant polycarbonate lens to withstand common automotive fluids
- IP54 - protected from dust and splashing water
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

M12 UHL-0	
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	1350/ -/ 600/ -
Max. run time with M12 B4 battery [h]	4/ -/ 8/ -
Weight with battery pack (EPTA) (kg)	1.1 (M12 B4)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933459432
EAN Code	4058546010935

M18 LL | M18™ LED LANTERN LIGHT

- TRUEVIEW™ high definition lighting
- 180° - 360° adjustable beam - versatile design, allows the user to select between area lighting and task lighting
- Best-in-class performance - outstanding light output 700 lumens, designed to illuminate large areas
- High powered USB charger charges tablets, smart phones, MP3 players and other electronic devices
- Job site durability - rugged designed with impact resistant lens to withstand abusive job site conditions
- 4 light settings - provides 700 lumens on High & Strobe (100%), 350 lumens on Medium (50%), 70 lumens on Low (10%)
- 2 hooks for hanging
- Protected against splashing water at all angles (IP24)
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™ M18

M18 LL-0	
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	700/ 350/ 70/ 700
Beam distance [m]	29
Weight with battery pack (EPTA) (kg)	0.96 (M18 B2)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4932430563
EAN Code	4002395382248

L4 SL | USB RECHARGEABLE STICK LIGHT 550 LUMENS

- TRUEVIEW™ high definition lighting with up to 550 lumens
- Up to 5 hours of run time on USB REDLITHIUM™ 3.0 Ah battery pack
- The 4-in-1 stick light features 4 selection functions for precision focusing during inspection, task or directional lighting that allows for full control of the beam output and intensity in any position
- 220° vertical light head rotations with single or both panel light option for convenient directional lighting
- IP52 rated for water and dust resistance and can withstand up to 2 m drops
- Magnetic attachment for hands-free use and hook attachment for secure storage
- Conveniently charge REDLITHIUM™ USB battery internally with USB-C cable from USB power source or AC outlet (wall plug not included)
- Includes USB cable



TRUEVIEW™ REDLITHIUM™ USB

L4 SL550-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output on front, back, dual and inspection function (high) [h]	550/550/550/250
Max. run time with L4 B3 battery w/ front, back, dual and inspection function [h]	2/2/2/4
Weight with battery pack (EPTA) (kg)	0.30 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article number	4933478869
EAN code	4058546361518

M12 LL | M12™ LED LANTERN LIGHT

- TRUEVIEW™ high definition lighting
- 180° - 360° adjustable beam - versatile design, allows the user to select between area lighting and task lighting
- Best-in-class performance - outstanding light output 400+ lumens, designed to illuminate large areas
- High powered 2.1A USB charger charges tablets, smart phones, MP3 players and other electronic devices
- Job site durability - rugged designed with impact resistant lens to withstand abusive job site conditions
- 2 hooks for hanging
- Protected against splashing water at all angles (IP24)
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

M12 LL-0	
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	400/ 200/ 40/ 400
Beam distance [m]	23
Weight with battery pack (EPTA) (kg)	0.64 (M12 B2)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4932430562
EAN Code	4002395382231

L4 FL | USB RECHARGEABLE POCKET FLOOD LIGHT

- 445 lumens of TRUEVIEW™ high definition output
- Can be mounted with double magnet and clipped on pockets
- Compact size allows easy storage in pocket
- IP54 rating, light is protected from dust and splashing water
- Impact and chemical resistant lens
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ REDLITHIUM™ USB

L4 FL-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	445/ - / 100/ -
Max. run time with L4 B3 battery [h]	2.5/ - / 12.5/ -
Weight with battery pack (EPTA) (kg)	0.20 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article Number	4933479763
EAN Code	4058546375577

M18 TLED | M18™ LED TORCH

- The 120 lumen LED light is 2x brighter and whiter than conventional incandescent bulbs
- M18™ LED electronics deliver 2x longer run time on a single charge with less heat than conventional removable light bulbs
- Sealed aluminium head is designed for impact- and weather-resistant durability
- 135° rotating head allows the user to easily direct the light beam at the desired work area
- Integrated hook for hands-free use
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



TRUEVIEW™ M18

M18 TLED-0	
Battery compatibility	All Milwaukee® M18™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	120/ - / - / -
Weight with battery pack (EPTA) (kg)	0.70 (M18 B2)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4932430361
EAN Code	4002395380220

IR FL | INTERNAL USB RECHARGEABLE FLASHLIGHT 500 LUMENS

- 500 lumens of TRUEVIEW™ high definition output with up to 100 m beam distance
- The flashlight features 3 modes and bulls-eye beam pattern, optimised for distance and up-close illumination
- IP67 rated for submersion in up to 2 metres of water and protection from dust
- Magnetic attachment for hands-free use and storage
- Reversible/ removable clip for optimised attachment
- Safety blinking feature allows end user to be informed of low battery status
- Conveniently charge MILWAUKEE® RECHARGEABLE internal battery with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ RECHARGEABLE

IR FL500	
Battery compatibility	Internal rechargeable
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	500 / 100 / 10/ -
Max. run time [h]	3.5/ - / 16/ 40/ -
Weight with battery pack (EPTA) (kg)	0.10 (w/ internal battery)
Kit included	Integrated battery, USB cable, Blister packaging
Article number	4933478586
EAN code	4058546347796

M12 TLED | M12™ LED TORCH

- The 120 lumen LED light is 2x brighter and whiter than conventional incandescent bulbs
- M12™ LED electronics deliver 2x longer run time on a single charge with less heat
- Sealed aluminium head is designed for impact- and weather-resistant durability
- 90° rotating head allows the user to easily direct the light beam at the desired work area
- Magnetic back for hands-free use
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



TRUEVIEW™ M12

M12 TLED-0	
Battery compatibility	All Milwaukee® M12™ batteries
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	120/ - / -
Weight with battery pack (EPTA) (kg)	0.50 (M12 B2)
Kit included	No batteries supplied, No charger supplied, Blister packaging
Article Number	4932430360
EAN Code	4002395380213

FL-LED | ALKALINE FLOOD LIGHT

- 300 lumens of TRUEVIEW™ high definition output delivers consistent beam, optimised colour temperature and true representation of colours & details
- Can be mounted with double magnet and clipped on pockets
- Compact size and lightweight construction allows easy storage in pocket
- IP54 rating, light is protected from dust and splashing water
- Impact and chemical resistant lens for more durability
- Includes 2x AA alkaline batteries



TRUEVIEW™

FL-LED	
Battery compatibility	Alkaline
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	300/ - / 100/ -
Max. run time [h]	5/ - / 16/ -
Weight with battery pack (EPTA) (kg)	0.10 (2 x AA)
Kit included	2 x AA Batteries, Blister packaging
Article Number	4933464824
EAN Code	4058546227692



L4 FFL | USB RECHARGEABLE FOLDING FLOOD LIGHT

- 550 lumens of TRUEVIEW™ high definition output delivers consistent beam, optimised colour temperature and true representation of colours & details
- Can be mounted with double magnet or hanging the light with an integrated carabiner hook gives more versatility
- Compact size allows easy storage in pocket
- IP54 rating, light is protected from dust and splashing water
- Impact and chemical resistant lens for more durability on the jobsite
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ REDLITHIUM USB

L4 FFL-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	550/ 250/ 100/ -
Max. run time with L4 B3 battery [h]	2.5/ 6/ 13.25/ -
Weight with battery pack (EPTA) (kg)	0.20 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article Number	4933479766
EAN Code	4058546375607

L4 TMLED | USB RECHARGEABLE 1100L TWIST FOCUS FLASHLIGHT

- 1100 lumens of TRUEVIEW™ high definition output with up to 175 m beam distance
- The flashlight features 3 modes and precision twist focusing that allows for full control of the beam size and intensity in any position
- IP67 rated for submersion in up to 2 metres of water and protection from dust
- Momentary & constant power on button
- Removable clip for secure attachment
- Safety blinking feature allows end user to be informed of low battery status
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ REDLITHIUM USB

L4 TMLED-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	1100/ 600/ 100/ -
Max. run time with L4 B3 battery [h]	1.5/ 4/ 12/ -
Beam distance [m]	175
Weight with battery pack (EPTA) (kg)	0.20 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article Number	4933479769
EAN Code	4058546375638

L4 PWL | USB RECHARGEABLE PIVOTING WORK LIGHT

- 500 lumens Spot & Flood beam with TRUEVIEW™ high definition output delivers consistent beam, optimised colour temperature and true representation of colours & details
- Spot & Flood beam options in different output modes for optimal brightness and up to 10 hrs run time
- Light head can be maneuvered up to 45° to help users direct light where it's needed most
- Impact and chemical resistant lens for a longer durability
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ REDLITHIUM USB

L4 PWL-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output Flood [High Medium Low] Spot Mode [lumens]	400/ -/ 100/ 500
Max. run time with L4 B3 battery [h]	3.5/ -/ 11.75/ 3.5
Weight with battery pack (EPTA) (kg)	0.20 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article Number	4933479765
EAN Code	4058546375591

ML-LED | ALKALINE FLASHLIGHT

- 325 lumens of TRUEVIEW™ high definition light output deliver up to 50 m beam distance for inspection tasks
- Impact and corrosion resistant aircraft aluminium body with knurling grip for best durability
- IP67 rated for submersion in up to 1 metre of water and protection from dust
- Removable metal pocket clip
- Impact and chemical resistant lens
- Includes 3x AAA batteries



TRUEVIEW™ 3 AAA

ML-LED	
Battery compatibility	Alkaline
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	325/ -/ 25/ -
Max. run time [h]	5/ -/ 18/ -
Beam distance [m]	50
Weight with battery pack (EPTA) (kg)	0.10 (3 x AAA)
Kit included	3 x AAA Batteries, Blister packaging
Article Number	4933464825
EAN Code	4058546227708

L4 FL2000 | USB RECHARGEABLE FLASHLIGHT 2000 LUMENS

- TRUEVIEW™ high definition lighting with up to 2000 lumens with 200 m beam distance
- The flashlight features 4 modes with precision slide focusing that allows quick and easy customization of the beam size and intensity
- Rear switch to meet user grip preference
- IP66 rated for splashing water and protection from dust
- Removable metal clip for optimised attachment
- A state of charge light as well as safety blinking feature allows end user to be informed of low battery status
- Conveniently charge REDLITHIUM™ USB battery internally with USB-C cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends



TRUEVIEW™ REDLITHIUM USB

L4 FL2000-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output Boost High Medium Low [lumens]	2000/ 1300/ 800/ 100
Max. run time with L4 B3 battery [h]	4/ 8/ 24
Weight with battery pack (EPTA) (kg)	0.264
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article number	4933479637
EAN code	4058546374310

IR PL | INTERNAL USB RECHARGEABLE PEN LIGHT 250 LUMENS

- 250 lumens of TRUEVIEW™ high definition output with up to 100 m beam distance
- IP67 rated for submersion in up to 1 metre of water and protection from dust
- Laser pointer provides accuracy needed in jobsite communication
- Protective rubber bite zone for hands-free use
- Two modes to optimise brightness and run time
- Conveniently charge MILWAUKEE® RECHARGEABLE internal battery with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Safety blinking feature allows end user to be informed of low battery status
- Reversible/ removable clip for optimised attachment
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ RECHARGEABLE

IR PL250	
Battery compatibility	Internal rechargeable
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	250/ -/ 50/ -
Max. run time [h]	1.5/ -/ 8/ -
Weight with battery pack (EPTA) (kg)	0.06 (w/ internal battery)
Kit included	Integrated battery, USB cable, Blister packaging
Article number	4933478705
EAN code	4058546348984

L4 FMLED | USB RECHARGEABLE 800L FIXED FLASHLIGHT

- 800 lumens of TRUEVIEW™ high definition output with up to 150 m beam distance
- The flashlight features 2 modes and bulls-eye beam pattern, optimised for distance and up-close illumination
- IP67 rated for submersion in up to 2 metres of water and protection from dust
- Momentary & constant power on button
- Removable clip for secure attachment
- Safety blinking feature allows end user to be informed of low battery status
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ REDLITHIUM USB

L4 FMLED-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	800/ -/ 100/ -
Max. run time with L4 B3 battery [h]	2.5/ -/ 11/-
Beam distance [m]	175
Weight with battery pack (EPTA) (kg)	0.20 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article Number	4933479770
EAN Code	4058546375645

IPL-LED | ALKALINE PEN LIGHT

- 100 lumens of TRUEVIEW™ high definition light output deliver up to 30 m beam distance for inspection tasks
- Impact and corrosion resistant aircraft aluminium body with knurling grip for best durability
- IP67 rated for submersion in up to 1 metre of water and protection from dust
- Features a protective rubber bite zone for occasional hands-free use
- Removable metal pocket clip
- On/off and momentary-on button
- Includes (2) AAA batteries



TRUEVIEW™ REDLITHIUM USB

IPL-LED	
Bulb type	LED
Max. light output High/Medium/Low/Strobe (lumens)	100
Max. run time [h]	3
Weight without battery pack (kg)	0.04
Kit included	2 x AAA Batteries, Blister packaging
Article Number	4933459440
EAN Code	4058546011017

L4 HL2 | USB RECHARGEABLE HEADLAMP 600 LUMENS

- 600 lumens Spot & Flood beam with TRUEVIEW™ high definition output
- Flood, Spot and Spot/ Flood beam options in different output modes for optimal brightness and up to 20 hrs run time
- 4 mounting clips for securing to helmets and adjustable strap with rubber grip
- The light head features 180° tilting motion to help users direct light where it's needed most
- Removable strap connector allows for handheld use
- IP54 rating, light is protected from dust and falling water
- Impact and chemical resistant lens
- State of charge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with USB-C cable from USB power source or AC outlet (wall plug not included)
- Includes USB cable



TRUEVIEW™ REDLITHIUM™ USB

L4 HL2-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output Hybrid Mode Spot Low Spot High Flood Low Flood High [lumens]	600/ 100/ 400/ 100/ 400
Max. run time with L4 B3 battery [h]	5/ 20/ 9/ 14/ 9
Weight with battery pack (EPTA) (kg)	0.20 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article number	4933479963
EAN code	4058546377571

HL-SF | ALKALINE SPOT FLOOD HEADLAMP

- 450 lumens of TRUEVIEW™ high definition output with 100 m spot beam distance and a wide flood beam
- Gives users up to 25 hours of run time with five light output modes to optimise run time, beam type, and brightness
- Supplied with four universal hard hat clips for secure connection to all hardhats
- IP52 rated for water and dust resistance and can withstand up to 2 m drops
- Equipped with a soft, sweat absorbing microfiber strap and forehead pad that provides users with all day comfort when worn on a bare head
- Allows users to direct the pivoting light head using seven adjustable positions
- Powered by (3) AAA batteries (included)



TRUEVIEW™ 3 AAA

HL-SF	
Battery compatibility	Alkaline
Bulb type	LED
Max. light output Hybrid Spot Flood, Flood High Medium Low, Spot High [lumens]	450/ 350/ 150/ 25/ 350
Max. run time [h]	2/ 4/ 10/ 26/ 4
Beam distance [m]	100
Weight with battery pack (EPTA) (kg)	0.10 (3 x AAA)
Kit included	3 x AAA Batteries, Blister packaging
Article Number	4933471388
EAN Code	4058546290160

L4 HL-VIS | USB RECHARGEABLE HI-VIS HEADLAMP

- Exceptional hands-free task lighting with safety light provides 600 lumens of TRUEVIEW™ high definition output with spot and flood beam options
- The safety light has steady and blinking options that make you visible up to 400 m from all directions when used with the front headlamp
- The clip on hard hat light has an elastic strap, silicon grip, includes two universal hard hat clips and is compatible with all hardhats
- Provides all-day run time with five light output modes: Hybrid Spot/ Flood, Flood High, Flood Medium, Flood Low, Spot High
- IP53 water and dust resistant and can withstand up to 2 m drops
- Ideal for roadside, tunnel or underground work, spotters, signalers and professionals working around moving equipment
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Includes USB cable



TRUEVIEW™ REDLITHIUM™ USB

L4 HL-VIS-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output Hybrid Spot Flood, Flood High Medium Low, Spot High [lumens]	600/ 400/ 200/ 25/ 400
Max. run time with L4 B3 battery [h]	2.5 / 4.5/ 8.5/ 22/ 4.5
Weight with battery pack (EPTA) (kg)	0.20 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article Number	4933479768
EAN Code	4058546375621

ISHL-LED | ALKALINE INTRINSICALLY SAFE HEADLAMP

- The intrinsically safe headlamp comes with a certified Zone 0 (category 1) approved ATEX rating
- Exceptional hands-free task lighting provides both Spot and Flood beam options with 310 lumens of TRUEVIEW™ high definition up to 100 m beam distance
- Designed with safety in mind, it has explicit on-tool intrinsically safe logos and the light strap is designed with a hi-visibility colour combination for easy identification, even at far distances
- Powered by 3 AAA batteries, it provides up to 40 hours of run time and features 5 output modes to manage the brightness and run time
- IP64 water and dust resistant and can withstand up to 2 m drops
- Ideal for fire & rescue, oil & gas workers and professionals working around continuous long term gaseous, vaporous and fog/mist areas
- Includes rubber strap for hard hat use & nylon strap for bare head use. Also includes DUAL LOCK™ adhesive for a strapless option to connect straight to a hard hat



TRUEVIEW™

ISHL-LED	
Battery compatibility	Alkaline
Battery type	3 x AAA
Max. light output Hybrid Spot Flood, Flood High Medium Low, Spot High [lumens]	310/ 235/ 155/ 25/ 155
Max. run time [h]	4/ 6/ 10/ 40/ 8
Beam distance [m]	100
Weight with battery pack (EPTA) (kg)	0.10 (3 x AAA)
Kit included	3 x AAA Batteries, No kitbox or bag supplied
Article Number	4933478112
EAN Code	4058546340452

L4 HLRP | USB RECHARGEABLE HARD HAT HEADLAMP

- 600 lumens of TRUEVIEW™ high definition output
- Features an ultra-thin light head that provides an unobstructed view with 125° of flood beam coverage
- Designed with the battery pack in the rear for maximum maneuverability in tight spaces and a balanced design for all-day use
- Equipped with a sweat absorbing microfiber strap for comfort on bare heads and four included hard hat clips for secure connections on all hardhats
- It has four light output modes: High, Medium, Low and Eco for 25+ hours of run time to maximise light output or extend run time
- The clip on hard hat light is IP54 rated for water and dust resistance and can withstand up to 2 m drops
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Includes USB cable



TRUEVIEW™ REDLITHIUM™ USB

L4 HLRP-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output Flood Mode High Medium Low Eco [lumens]	600/ 350/ 125/ 25
Max. run time with L4 B3 battery [h]	3/ 7.5/ 13/ 28
Weight with battery pack (EPTA) (kg)	0.20 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article Number	4933479767
EAN Code	4058546375614

HL2-LED | ALKALINE SLIM HEADLAMP

- 350 lumens of TRUEVIEW™ high definition output
- Washable micro fiber sweat-absorbing strap for all day comfort on the head
- Ultra compact and lightweight product
- 6-position tilt adjustment for directing light
- 4 mounting clips for securing to helmets
- Light is protected from impact as well as from weather and dust
- Includes (3) AAA batteries



TRUEVIEW™ 3 AAA

HL2-LED	
Battery compatibility	Alkaline
Bulb type	LED
Max. light output High Medium Low Strobe (lumens)	350/ 150/ 25/ -
Max. run time [h]	4/ 8.5/ 28/ -
Weight with battery pack (EPTA) (kg)	0.10 (3 x AAA)
Kit included	3 x AAA Batteries, Blister packaging
Article Number	4933471286
EAN Code	4058546289140

IR HL | INTERNAL USB RECHARGEABLE HEADLAMP 450 LUMENS

- 450 lumens of TRUEVIEW™ high definition output with up to 100 m beam distance
- Flood, Spot and Spot/ Flood beam options in different output modes for optimal brightness and up to 16 hrs run time
- 4 mounting clips for securing to helmets and adjustable strap with rubber grip
- Detachable magnetic light head attachment for hands-free use and storage
- IP54 rating, light is protected from dust and falling water
- Conveniently charge MILWAUKEE® RECHARGEABLE internal battery with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Fuel gauge allows fast checking of battery charge
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ RECHARGEABLE

IR HL450	
Battery compatibility	Internal rechargeable
Bulb type	LED
Max. light output Hybrid Mode Spot Low Spot High Flood Low Flood High [lumens]	450/ 100/ 250/ 50/ 250
Max. run time [h]	2.5/ 8/ 4/ 14/ 4
Weight with battery pack (EPTA) (kg)	0.12 (w/ internal battery)
Kit included	Integrated battery, USB cable, Blister packaging
Article number	4933478587
EAN code	4058546347802

L4 NL400 | USB RECHARGEABLE NECK LIGHT 400 LUMENS

- TRUEVIEW™ high definition lighting with up to 400 lumens
- Up to 8 hours of run time on USB REDLITHIUM™ 3.0 Ah battery pack
- 2 total output modes for better beam control and memory for last mode when light is switched on
- 130° vertical light head rotations for complete light head adjustability
- Ergonomic, sweat resistant band for increased comfort
- Resistance to most chemicals found in auto body shops
- IP50 rated for dust resistance and can withstand up to 2 m drops
- Conveniently charge REDLITHIUM™ USB battery internally with USB-C cable from USB power source or AC outlet (wall plug not included)
- Includes USB cable



TRUEVIEW™ RECHARGEABLE

L4 NL400-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. run time with L4 B3 battery [h]	8
Weight with battery pack (EPTA) (kg)	0.23 (L4 B3)
Kit included [L4]	1 x L4 B3, USB cable, Gift box
Article number	4933479898
EAN code	4058546376925

BOLT™ 200

HIGH RESISTANCE MATERIAL

COLOURS AVAILABLE

LEXAN SHELL
SUPERIOR IMPACT RESISTANCE

ADJUSTABLE CHIN STRAP

- Vented version delivered with 1x EN397 and 1x EN12492 chin strap.
 - Unvented version delivered with 1x EN397 chin strap.
- COMPLIANT WITH EN 397 & EN 12492 (VENTED)**
- 40°C (Vented + Unvented)
 - 440 V a.c. c.(Unvented
 - LD (Vented + Unvented)

INNER FOAM TECHNOLOGY

Foam progressively stiffens when impacted: distributes pressure evenly across entire head when impacts, independent of impact location.

L4 BOLTHL | USB RECHARGEABLE BOLT HEADLAMP 600 LUMENS

- 600 lumens of multi-directional TRUEVIEW™ high definition light output
- Full BOLT compatibility with low profile design works with all BOLT visors and helmets
- Direct mount to helmet without straps
- Pivoting light head to help users direct light where it is needed most
- 4 modes to manage output or runtime with up to 12 hours of runtime on (1) USB 3.0 Battery
- Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM™ USB battery internally with micro-USB Type C cable from USB power source or AC outlet (wall plug not included)
- IP54 rating, light is protected from dust and falling water
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



TRUEVIEW™ REDLITHIUM™

L4 BOLTHL-301	
Battery compatibility	REDLITHIUM™ USB battery
Bulb type	LED
Max. light output Flood Mode High/Medium/Low/Eco (lumens)	600 / 400 / 150 / 25
Max. run time with L4 B3 battery (h)	4 / 8 / 14 / 40
Weight with battery pack (EPTA) (kg)	0.24 (L4 B3)
Kit included [L4]	1 x L4 B3 Battery pack, USB cable, Blister packaging
Article number	4933479902
EAN code	4058546376963

BATTERIES

M12 M14 M18 MX FUEL

	Model Variant	Catalogue product description	Charge time M12_18 SC charger	Charge time M12_18 FC charger	Charge time M12_18 C charger	Charge time M12_18 AC charger	Charge time M1418C6 charger	Charge time M18 DFC charger	Charge time C12 C charger	Charge time M12 TC charger	Charge time M12 C4 charger	Charge time MXF C charger	Article number
	M18 HB12	M18™ HIGH OUTPUT™ 12.0 Ah battery	60 min	130 min	250 min	285 min	270 min	130 min	-	-	-	-	4932464260
	M18 HB8	M18™ HIGH OUTPUT™ 8.0 Ah battery	45 min	87 min	167 min	190 min	190 min	87 min	-	-	-	-	4932471070
	M18 HB5.5	M18™ HIGH OUTPUT™ 5.5 Ah battery	35 min	60 min	115 min	130 min	125 min	60 min	-	-	-	-	4932464712
	M18 HB3	M18™ HIGH OUTPUT™ 3.0 Ah battery	36 min	36 min	65 min	75 min	70 min	36 min	-	-	-	-	4932471069
	M18 B5-CR	M18™ 5.0 Ah battery	59 min	59 min	100 min	100 min	59 min	59 min	-	-	-	-	4932479265
	M18 B5	M18™ 5.0 Ah battery	59 min	59 min	100 min	100 min	100 min	59 min	-	-	-	-	4932430483
	M18 B4	M18™ 4.0 Ah battery	52 min	52 min	80 min	80 min	80 min	52 min	-	-	-	-	4932430063
	M18 B2	M18™ 2.0 Ah battery	26 min	26 min	40 min	40 min	40 min	26 min	-	-	-	-	4932430062
	M12 HB5	M12™ 5.0 Ah HIGH OUTPUT™ battery pack	75 min	75 min	110 min	110 min	-	-	110 min	380 min	110 min	-	4932480165
	M12 HB2.5	M12™ 5.0 Ah HIGH OUTPUT™ battery pack	40 min	40 min	55 min	55 min	-	-	55 min	200 min	55 min	-	4932480164
	M12 B6	M12™ 6.0 Ah battery	95 min	95 min	130 min	165 min	-	-	130 min	525 min	130 min	-	4932451395
	M12 B4	M12™ 4.0 Ah battery	52 min	52 min	80 min	115 min	-	-	80 min	347 min	80 min	-	4932430065
	M12 B3	M12™ 3.0 Ah battery	50 min	50 min	70 min	90 min	-	-	70 min	264 min	70 min	-	4932451388
	M12 B2	M12™ 2.0 Ah battery	26 min	26 min	40 min	55 min	-	-	40 min	174 min	40 min	-	4932430064
	MXF XC406	MX FUEL™ REDLITHIUM™ 6.0 Ah battery	-	-	-	-	-	-	-	-	-	90 min	4933471837
	MXF CP203	MX FUEL™ REDLITHIUM™ 3.0 Ah battery	-	-	-	-	-	-	-	-	-	55 min	4933471838

CHARGERS

REDLITHIUM USE M12 M14 M18

	Model Variant	Catalogue product description	Charging ports	Charge type	Power source	Carry handle	Wall mountable	Article number
	M12-18SC	M12™ - M18™ super charger	1 x M12™, 1 x M18™	Sequential	AC	-	✓	4932471735
	M12-18 FC	M12™ - M18™ fast charger	1 x M12™, 1 x M18™	Sequential	AC	-	✓	4932451080
	M12-18 AC	M12™-M18™ car charger	1 x M12™, 1 x M18™	Sequential	DC	No	✓	4932459205
	M18 DFC	M18™ dual bay rapid charger	2 x M18™	Simultaneous	AC	No	✓	4932472074
	M1418 C6	M14™ - M18™ multibay charger	6 x M14™ or 6 x M18™	Sequential	AC	✓	✓	4932430087
	C12 C	M12™ charger	1 x M12™	Single	AC	-	✓	4932352069
	M12 C4	M12™ 4 bay charger	4 x M12™	Sequential	AC	-	✓	4932430555
	L4 C	REDLITHIUM™ USB charger	1 x REDLITHIUM™ USB	Single	AC, USB	-	-	4932459446

PROMOTIONAL BATTERIES AND CHARGER KITS

M12 M18

①



②



③



		Voltage (V)	Battery type	Battery pack capacity (Ah)	No. of batteries supplied	Charger supplied	Article Number	EAN Code
1.	M18 HNRG-122	18	Li-ion	M18™ 12.0	2	M12-18 FC	4933464262	4058546222079
2.	M18 HNRG-802	18	Li-ion	M18™ 8.0	2	M12-18 FC	4933471074	4058546287023
3.	M18 HNRG-302	18	Li-ion	M18™ 3.0	2	M12-18 FC	4933471072	4058546287009

BATTERIES AND CHARGER KITS

REDLITHIUM USE M12 M18

①



		Voltage (V)	Battery type	Battery pack capacity (Ah)	No. of batteries supplied	Charger supplied	Article Number	EAN Code
1.	M12 NRG-201	12	Li-ion	2.0	1	C12 C	4933451901	4002395282104

CONSTRUCTION



K 2628 H

25 KG CLASS 28 MM HEX BREAKING HAMMER

- Heavy Duty breaker provides 64 blow Joules of impact energy for toughest demolition applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- Additional third handle gives maximum control when lifting the breaker between applications
- 1200 BPM provides maximum productivity in all applications
- Brushless motor allows for maximum run time in-between service intervals
- 10 m cable allows for a working area of up to 314 m²
- 28 mm Hex reception
- Separately available trolley with 4 chisel location and cable management makes it easy to transport breaker on the jobsite



K 2628 H	
Power input (W)	2400
Blow energy [EPTA](J)	64
Full load hammer action (bpm)	1200
Tool reception	K-Hex
Vibration chiseling (m/s²)	6.2
Weight (kg)	25.7
Supplied in	No kitbox or bag supplied
Article Number	4933471685
EAN Code	4058546295844

28 MM HEX 400 X 35 MM FLAT CHISEL	
Article Number	4932459775



BRT | BREAKER TROLLEY

- Breaker trolley with 4 chisel location and cable management makes it easy to transport breaker on the jobsite
- 100 kg loading capacity
- Powder coated finish protects against jobsite abuse
- Compatible with K 2000 H and K 2500 H



BRT	
Loading capacity	100Kg
Weight (kg)	14.3
Supplied in	No kitbox or bag supplied
Article Number	4933459794
EAN Code	4058546029661

K 1000 S | 10 KG CLASS SDS-MAX BREAKING HAMMER

- Compact chiseling hammer delivering up to 26 blow Joules of impact energy for a wide variety of applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- 1400 – 1950 BPM provides maximum productivity in all applications
- 6 m cable allows for working area over 110 m²
- Variolock (12 positions) for selecting the most appropriate chisel angle
- SDS-Max tool reception
- Service reminder light to indicate when service will be needed
- Dedicated brush window for easy maintenance
- BMC with wheels for ease of transport on site

K 1000 S	
Power input (W)	1750
Blow energy [EPTA](J)	26
Full load hammer action (bpm)	1400 - 1950
Tool reception	SDS-Max
Vibration chiseling (m/s²)	6.7
Weight (kg)	12.7
Supplied in	Plastic case
Article Number	4933464121
EAN Code	4058546220662



K 950 | 10 KG CLASS DRILLING AND BREAKING HAMMER

- 20 J blow energy for hard hitting performance
- 1700 watt motor - best in class with plenty in reserve for the toughest applications
- DIGITRONIC™ - fullwave electronics for precise power adjustment to application
- 3 handles - all with AVS (Anti-Vibration-System) and soft grip for comfortable and less tiring use
- All metal gearcase - optimum seating of the gears for enhanced service life
- Service indicator light
- Automatic lubrication system for longer life time
- In-Line motor design for more comfort in below waist applications
- Ideal for usage with generators
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 950 S	
Power input (W)	1700
No load speed (rpm)	125 - 250
Blow energy [EPTA](J)	20
Full load hammer action (bpm)	975 - 1950
Full load speed (soft hammer) (rpm)	125 - 250
Max. drilling solid bit (mm)	50
mx. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s²)	12.5
Vibration chiseling (m/s²)	11
Weight (kg)	11.8
Supplied in	Kitbox
Article Number 110 V	4933375752
EAN Code	4002395232055

K 900 | 10 KG CLASS BREAKING HAMMER

- 20 J blow energy for hard hitting performance
- 1600 watt motor - best in class with plenty in reserve for the toughest applications
- DIGITRONIC™ - fullwave electronics for precise power adjustment to application
- 3 handles - all with AVS (Anti-Vibration-System) and soft grip for comfortable and less tiring use
- Service indicator light
- Automatic lubrication system for longer life time
- In-Line motor design for more comfort in below waist applications
- Ideal for usage with generators
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



	K 900 S	K 900 K
Power input (W)	1600	1600
Blow energy [EPTA](J)	20	20
Full load hammer action (bpm)	975 - 1950	975 - 1950
Tool reception	SDS-Max	K-Hex
Vibration chiseling (m/s²)	11	11
Weight (kg)	11.0	11.0
Supplied in	Kitbox	Kitbox
Article Number 110 V	4933375756	4933375670
EAN Code	4002395232062	4002395231638

K 750 S | 7 KG CLASS DRILLING AND BREAKING HAMMER

- Large, heavy weight striker delivers maximum 11.9 J impact energy
- Powerful 1550 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Fullwave electronics for precise power adjustment to application
- Soft start for precise start of drilling/chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 750 S	
Power input (W)	1550
No load speed (rpm)	300
Blow energy [EPTA][J]	11.9
Full load hammer action (bpm)	2740
Full load speed (soft hammer) (rpm)	240
Max. drilling solid bit (mm)	50
mx. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s²)	9.5
Vibration chiseling (m/s²)	9.1
Weight (kg)	8.2
Supplied in	Kitbox
Article Number 110 V	4933398601
EAN Code	4002395235209
Article Number 240 V	4933449370
EAN Code	4002395245802

K 545 S | 5 KG CLASS DRILLING AND BREAKING HAMMER

- Large, heavy weight striker delivers maximum 8.5 J impact energy
- Powerful 1300 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Constant electronic for keeping the speed uniform even under load
- Soft start for precise start of drilling/chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for drilling/chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 545 S	
Power input (W)	1300
No load speed (rpm)	450
Blow energy [EPTA][J]	8.5
Full load hammer action (bpm)	2840
Full load speed (soft hammer) (rpm)	350
Max. drilling solid bit (mm)	45
mx. drilling tunnel bit (mm)	65
Max. drilling core bit (mm)	100
Tool reception	SDS-Max
Vibration drilling (m/s²)	13
Vibration chiseling (m/s²)	9
Weight (kg)	6.7
Supplied in	Kitbox
Article Number 110 V	4933398280
EAN Code	4002395234066
Article Number 240 V	4933405347
EAN Code	4002395234561

K 540 S | 5 KG CLASS DRILLING AND BREAKING HAMMER

- Best power to weight ratio in its class - 7.5 J and 6.3 kg
- Powerful 1100 watt ensures maximum power, guarantees maximum possible durability
- Soft start for precise start of drilling/chiselling
- Low vibration construction enhances usage time per day
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle
- Safety clutch protects operator and machine if drill bit jams
- Soft grip main side handle
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 4 m cable



K 540 S	
Power input (W)	1100
No load speed (rpm)	450
Blow energy [EPTA][J]	7.5
Full load hammer action (bpm)	3000
Full load speed (soft hammer) (rpm)	430
Max. drilling concrete (mm)	40
mx. drilling tunnel bit (mm)	65
Max. drilling core bit (mm)	105
Tool reception	SDS-Max
Vibration drilling (m/s²)	16.8
Vibration chiseling (m/s²)	16.7
Weight (kg)	6.3
Supplied in	Kitbox
Article Number 110 V	4933418140
EAN Code	4002395238446
Article Number 240 V	4933418120
EAN Code	4002395238439

K 500 ST | 5 KG CLASS TRADESMAN BREAKING HAMMER

- Best power to weight ratio in its class - 7.5 J and 5.9 kg
- Powerful 1100 watt ensures maximum power, guarantees maximum possible durability
- Soft start for precise start of chiselling
- Low vibration construction enhances usage time per day
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle
- Safety clutch protects operator and machine if drill bit jams
- Soft grip main side handle
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 4 m cable



K 500 ST	
Power input (W)	1100
Blow energy [EPTA][J]	7.5
Full load hammer action (bpm)	3000
Tool reception	SDS-Max
Vibration chiseling (m/s²)	16.7
Weight (kg)	5.9
Supplied in	Kitbox
Article Number 110 V	4933443345
EAN Code	4002395003761
Article Number 240 V	4933443920
EAN Code	4002395004287

K 500 S | 5 KG CLASS BREAKING HAMMER

- Large, heavy weight striker delivers maximum 8.5 J impact energy
- Powerful 1300 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Constant electronic for keeping the speed uniform even under load
- Soft start for precise start of chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 500 S	
Power input (W)	1300
Blow energy [EPTA][J]	8.5
Full load hammer action (bpm)	2840
Tool reception	SDS-Max
Vibration chiseling (m/s²)	11.5
Weight (kg)	6.3
Supplied in	Kitbox
Article Number 110 V	4933398290
EAN Code	4002395234042
Article Number 240 V	4933449375
EAN Code	4002395245819

DD 2-160 XE
2-SPEED DRY DIAMOND DRILL

- Powerful robust motor delivers constant high torque
- Dual protection from the interlinked mechanical and electronic clutches to protect both user and tool
- Robust construction with metal gearbox
- Safe handling from the long AVS side handle and "D- shaped" back handle
- 2-speed gear box
- M16 FIXTEC™ adaptor for fast core bit changing
- Soft hammer action - when activated allows the core bit to cut faster and easier
- Soft start via accelerator switch for precision and controlled drilling
- FIXTEC™ Cleanline rotor (additional accessory) the best solution for dust extraction
- 4 m cable
- Supplied with quick change adaptor for M16 diamond cores, SDS-plus pilot drill bit (8 x 140 mm)



DD 2-160 XE	
Power input (W)	1100, 1500
No load speed (rpm)	0 - 1500 / 0 - 3000
Full load speed [rpm]	0 - 890 / 0 - 1770
No load hammer stroke (rpm)	24,000 / 48,000
Max. drilling masonry (mm)	162
Max. static stalling torque (Nm)	50
Tool reception	M18 x 2.5
Weight (kg)	4.2
Supplied in	Kitbox
Article Number 110 V	4933368700
EAN Code	4002395232512
Article Number 240 V	4933368705
EAN Code	4002395232628

82 MM M16 DIAMOND CORE

Article Number	4932371979
----------------	------------



DR 152 T | DIAMOND DRILL STAND FOR DD 3-152

- Cast aluminium base for easy transportation
- 45° tilt for angle drilling
- Quick-in connection - precise and quick connection of tool and rig
- Compact base - saves space for drilling in confined spaces
- 4 leveling screws for fast adjustment
- Horizontal and vertical spirit levels
- Transport handle
- Locking knob locks unit at highest position to aid fixing of machine and core bit
- Two spoke wheel feed for left and right hand operation
- Vacuum plate is available as accessory (4932352676)



DR 152 T	
Max. drilling core bit (mm)	152
Base size (mm)	330 x 210
Angle capacity (°)	45
Weight (kg)	10
Supplied in	No kitbox or bag supplied
Article Number	4933428020
EAN Code	4002395239818

SYSTEM ATTACHMENTS - WET DIAMOND DRILLING

Description	Fits to DD3 152	Fits DCM2 250C & DCM2 350C	Fits MXF DCD150	Article Number	EAN Code	
Fixing kit. For exclusive use in concrete. Ø 16 mm drill bit is required to set the drop anchor	✓	✓	✓	4932399731	4002395363827	
Stud bolt, setting tool, wing nut, washer and 5 pcs M12 drop anchor						
1 3/8" open ended spanner. For holding the motor output spindle while removing a core bit		✓		49964705	04524222766	
32 mm ended spanner. For holding the motor output spindle while removing a core bit.	✓			4931428009	4002395844791	
41 mm open ended spanner. For removing the core bit from the motor spindle.	✓	✓		4931428010	4002395844807	
Fixtec release. Suitable for all diamond motors with 1 1/4" spindle reception. Prevents the core bit from locking itself too tight onto the machine spindle. The core bits can then be released and removed with minimum effort	✓	✓		4932352053	4002395367108	
1 1/4" female to 1/2" female adaptor. To enable the connection of <50 mm diamond core bits on a 1 1/4" machine spindle thread	✓	✓		4932352627	4002395372850	
1 1/4" female / male extention rod, length 300 mm	✓	✓	✓	4932399724	4002395363759	
1 1/4" female / male extention rod, length 500 mm	✓	✓	✓	4932399725	4002395363766	
Telescopic extention. Extension pole used to fix drill rig to the ground instead of anchor bolts. Maximum load of 500 kg and adjustable extension height from 1.8-2.9 m	✓	✓	✓	4932399732	4002395363834	
Vacuum pump VP6: For fastening of the diamond drill rig on smooth and even surfaces. Suction capacity: 850 mbar. Max. vacuum pressure: 6 m³/h / 100 l/min. Rated voltage: 220-240 V	✓	✓	✓	4932352094	4002395367474	
Vacuum plate. Replacement rubber seal 4931428665	✓			4932352676	4002395373345	
WT 10 watertank. 10 liters capacity, steel, water tank with inside and outside polyester coating. Reliable brass pump with a max. pressure bar of 6 bar. 2.5 m hose with quick connection system fits direct to Milwaukee® diamond drills	✓	✓	✓	4932399726	4002395363773	
Water collection ring: For use with drill rig DR 152 T. For use with max. Ø 152 mm core bits				4932352677	4002395373352	
Replacement rubber ring for DR 152 T				4932352678	4002395373369	
Water collection ring: For use with drill rig DR 250 TV. For use with max. Ø 180 mm core bits			✓	4932399727	4002395363780	
Replacement rubber ring for DR 250 TV			✓	4932399729	4002395363803	
Water collection ring: For use with drill rig DR 350 T. For use with max. Ø 300 mm core bits				4932399728	4002395363797	
Replacement rubber ring for DR 350 T				4932399730	4002395363810	
Spacer block T = 50 mm. Needs to be mouted between drill rig and motor cores > 250 mm and max. 350 mm. Included in drill rig DR 350 T		✓		4932399736	4002395363872	
Quick connection motor mounting plate. Included in both drill rigs DR 250 TV and DR 350 T		✓		4932399733	4002395363841	
Water collection ring: For universal use with diamond drilling tools. For use with max. Ø 152 mm core bits	✓	✓	✓	4932478073	4058546340063	

FIXTEC™ SOLUTION WITH DUST EXTRACTION

Description	Tool reception	Core reception	Article Number	EAN Code	
FIXTEC Clean Line Rotor (CLR)	M18 x 2.5	1 1/4" UNC	4932352172	4002395368242	

FIXTEC™ SOLUTION WITHOUT DUST EXTRACTION

Description	Tool reception	Core reception	Article Number	EAN Code	
FIXTEC™ adaptor. Tool changing in seconds. No extra tool required	M18 x 2.5	M16	4932399174	4002395357819	
	11 mm Hex	M16	4932399220	4002395358342	

GUIDE RODS FOR DIAMOND CORE DRILLS

Description	Article Number	EAN Code	
Guide rod for DD2-160. Supplied with locking screw (4931622432). Requires allen key (4931616044) and SDS-plus pilot drill bit (Ø 8 x 160 mm, 4932307071)	4932399173	4002395357802	
Guide rod for DD3-152. Requires SDS-plus pilot drill bit (Ø 8 x 110 mm, 4932307070)	4932352679	4002395373376	

METALWORKING



AGV 22 | 2200 W ANGLE GRINDER WITH AVS

- Powerful, 2200 W motor with powder field coating for long life time and outstanding performance in all applications
- Extreme compact design with an overall short length of 485 mm and 5.4 kg for most comfortable handling
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- 2-postions Anti-vibration side handle for less vibrations to the user and more comfortable work
- External brush doors for easy access to the brushes for fast servicing
- 4 m rubber cable



AGV 22-230 DMS	
Power input (W)	2200
No load speed (rpm)	6600
Disc diameter (mm)	230
Cutting depth (mm)	68
Spindle size	M 14
Weight (kg)	5.4
FIXTEC™ flange nut	No
Deadman switch	Yes
Line lock out function	No
Autobalancer system	No
AVS side handle	Yes
Rotatable main handle	No
Supplied in	No kitbox or bag supplied
Article Number 240V	4933440910
EAN Code	4002395001118

AGV 17 | 1750 W ANGLE GRINDER WITH AVS

- Powerful, 1750 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Constant power electronics with soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Thermal overload protection to prevent overheating
- Safety clutch to protect the user from kickback injuries
- FIXTEC™ nut for tool-free disc change
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- Anti-vibration side handle for lower vibration
- 4 m rubber cable



AGV 17-125 XE	
Power input (W)	1750
No load speed (rpm)	2600 - 11,000
Disc diameter (mm)	125
Cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2.8
Variable speed	Yes
Brake	No
Switch type	Trigger lock-on switch
FIXTEC™ flange nut	Yes
Line lock out function	Yes
AVS side handle	Yes
Autobalancer system	No
Supplied in	No kitbox or bag supplied
Article Number	4933449660
EAN Code	4002395247202

AGV 13 XSPDE | 1250 W ANGLE GRINDER WITH AVS AND SLIM PADDLE

- Powerful, 1250 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Most compact design with only 160 mm body size for comfortable handling
- Soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Overload protection to prevent overheating
- Safety clutch to protect the user from kickback injuries
- Integrated and innovative FIXTEC™ tool-free disc change system
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Anti-vibration side handle for less user fatigue



AGV 13-115 XSPDE	
Power input (W)	1250
No load speed (rpm)	12,000
Disc diameter (mm)	115
Cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2.4
FIXTEC™	Yes
Deadman switch	Yes
Line lock out function	Yes
AVS side handle	Yes
Switch type	Paddle switch
Supplied in	No kitbox or bag supplied
Article Number 110V	4933451579
EAN Code	4002395141401

AGV 10 EK | 1000 W ANGLE GRINDER WITH AVS

- Powerful, 1000 W motor for strong performance in all applications
- Extreme compact design with an overall short length of 276 mm and 2.2 kg for most comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Soft start for smooth start up
- Anti-vibration side handle for less fatigue
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Ramped slide switch for easy start up, even when wearing gloves
- 4 m cable



	AGV 10-115 EK	AGV 10-125 EK
Power input (W)	1000	1000
No load speed (rpm)	11,000	11,000
Disc diameter (mm)	115	125
Cutting depth (mm)	28	33
Spindle size	M 14	M 14
Weight (kg)	2.2	2.2
FIXTEC™ flange nut	No	No
Line lock out function	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number 110V	4933451224	4933451516
EAN Code	4002395260218	4002395149889

AG 800 E | 800 W ANGLE GRINDER

- Powerful 800 Watt motor for various applications with only 2.0 kg of weight for comfortable use during longer working periods
- Very compact and slim body grip design with only 194 mm for most comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Soft start for smooth start up
- Durable steel gears for long life time
- Protected air inlets for improved cooling
- Flat metal gear head for excellent visibility of workpiece, optimised cutting depth and work in restricted areas



AG 800-115 E	
Power input (W)	800
No load speed (rpm)	11,500
Disc diameter (mm)	115
Cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2.0
FIXTEC™ flange nut	No
Line lock out function	Yes
Supplied in	No kitbox or bag supplied
Article Number 110V	4933451215
EAN Code	4002395260829
Article Number 240V	4933451214
EAN Code	4002395260812

AP 14-2 200 E | 1450 W POLISHER

- Powerful 1450 watt motor for high performance polishing
- Premium high torque gear maintains speed under load
- Variable speed selection from 490 - 2100 RPM for all applications
- 7 speed settings for accurate speed selection
- Thermal overload protection to prevent overheating
- Unique "finger grip" for comfortable working position, especially when working with the tool vertically
- Protected spindle lock button ensures against accidental use
- Lock-on function
- Flexible and soft hook and loop backing pad avoids scratches on paint work
- 6 m long PUR cord to prevent marks on the paint work and allows the user to work easily around the complete car



	AP 14-2 200 E	AP 14-2 200 E SET
Power input (W)	1450	1450
No load speed (rpm)	490 - 2100	490 - 2100
Disc diameter (mm)	200	200
Spindle size	M 14	M 14
Standard equipment	Side handle, flexible backing pad	Side handle, flexible backing pad, soft & hard polishing sponge, lambswool pad, sanding & finishing compound, cloth
Weight (kg)	2.3	2.3
Variable speed	Yes	Yes
Line lock out function	Yes	Yes
Soft start function	Yes	Yes
Supplied in	No kitbox or bag supplied	HD Box
Article Number 240 V	4933442350	4933442355
EAN Code	4002395005451	4002395005468

AP 12 E | 1200 W POLISHER WITH ELECTRONIC VARIABLE SPEED

- 1200 watt motor
- Ergonomic design for long work shifts
- Special gear for high spindle torque and ideal polishing speed
- Variable speed selection for ideal speed
- Thermal overload protection
- No load speed limitation
- 6 m cable



AP 12 QE	
Power input (W)	1200
No load speed (rpm)	900 - 2500
Disc diameter (mm)	150
Spindle size	M 14
Weight (kg)	2.2
Variable speed	Yes
Supplied in	No kitbox or bag supplied
Article Number 240 V	4933449380
EAN Code	4002395245826

BS 125 | DEEP CUT BAND SAW

- Powerful 1100 watt motor provides maximum performance and durability
- Largest cutting capacity up to 125 x 125 mm material diameter
- 4 step variable speed selection from 0 - 116 m/min
- Constant power technology maintains cut speed in the toughest applications for optimal performance
- Gear protecting clutch extends gear and motor life by absorbing high impact forces caused by blade lock-ups
- Slim full metal motor housing design and LED work surface illumination for best cut visibility
- Tool-free blade locking mechanism for quick and easy saw blade changes
- Tool-free adjustable shoe



BS 125	
Power input (W)	1100
No load speed [ml/min]	0 - 116
Cutting capacity rect. stock (mm)	125 x 125
Max. cutting capacity metal pipe	125
Blade length (mm)	1139.83
Weight (kg)	6.5
Supplied in	Kitbox
Article Number 240V	4933448860
EAN Code	4002395811502

WOODWORKING



SSPE 1500 X | 1500 W SUPER SAWZALL™

- 1500 W motor - highest overload protection in the industry; prevents motor burn up/failure
- Constant power technology - maintains constant speed under load for unmatched cutting performance
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups
- FIXTEC™ blade clamp system - provides fast and easy blade changes
- Patented AVS Anti-Vibration-System ensures unsurpassed low-vibration running at 12.5 m/s²
- Variable speed trigger and dial speed control - maximum speed control
- Adjustable shoe for optimised use of saw blades
- Supplied with a SAWZALL™ blade, additional keyed blade clamp and 4 m cable



SSPE 1500 X	
Power input (W)	1500
No load stroke rate (spm)	0 - 2800
Stroke length (mm)	32
Weight (kg)	4.5
Supplied in	Kitbox
Article Number 110 V	4933429145
EAN Code	4002395241712

SSD 1100 X | 1100 W SAWZALL™

- High cutting performance due to powerful 1100 watt motor combined with a 28 mm saw stroke
- FIXTEC™ blade clamp for fast and easy blade changes without any key
- Water & finger protection nose for safer work and better rust protection
- Variable speed trigger switch
- Durable long lasting slider mechanism
- Supplied with a SAWZALL™ blade and 4 m cable



SSD 1100 X	
Power input (W)	1100
No load stroke rate (spm)	0 - 2900
Stroke length (mm)	28
Weight (kg)	3.2
Supplied in	Kitbox
Article Number	4933410780
EAN Code	4002395237630

JSPE 135 | HEAVY DUTY TOP HANDLE JIGSAW

- Robust and powerful top handle jig saw for fast cutting action in wood, aluminium, steel or ceramics
- Powerful 750 W motor
- Precision blade guidance for precise cuts
- Patented FIXTEC™ system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°
- Electronic with variable speed preselection, soft start and constant speed under load
- Four-stage pendulum action adjustment for even more powerful cutting performance and longer saw blade life
- Adjustable chipping blower to the front and the rear
- LED light for illumination of cutting area
- Supplied with 5 saw blades, anti-splintering device, dust cap, absorption adaptor, sliding shoe and 4 m cable



JSPE 135 TX	
Power input (W)	750
No load stroke rate (spm)	800 - 3000
Max. cutting capacity wood (mm)	135
Max. cutting capacity steel (mm)	10
Max. cutting capacity aluminium (mm)	30
Mitre capacity (°)	45
Stroke length (mm)	26
Weight (kg)	2.5
Supplied in	Kitbox
Article Number 110 V	4933381645
EAN Code	4002395232543

CS 60 | 184 MM CIRCULAR SAW (61 MM DOC)

- 1600 W powerful motor with 5800 rpm for fast cutting through tough materials
- Large cutting capacity of 61 mm
- 0 - 56° bevel capacity and 45° positive stop
- Quick release locking lever design for fast bevel adjustments
- Integrated dust blower keeps cut line clear
- Large, ergonomic handles and levers for improved ergonomics and control
- Long side fence for straight cuts and precise guidance
- Supplied with a carbide tipped 24 tooth saw blade, parallel guide and 4 m cable



CS 60	
Power input (W)	1600
No load speed (rpm)	5800
Blade diameter (mm)	184
Bore size (mm)	30
Max. cutting depth 45° (mm)	49
Max. cutting depth 90° (mm)	61
Supplied in	No kitbox or bag supplied
Weight (kg)	4.8
Article Number - 110V	4933429070
EAN Code	4002395240005

SPS 140 | 1/4" SHEET SANDER

- Powerful 260 W motor for sustained use
- 1.6 mm oscillation movement allows for fine sanding
- Quick connection to dust extractor or dust bag
- Sanding paper is attached by hook and loop or by a clamping system
- 4 m of durable rubber cable allows the user to move easily around his work piece



SPS 140	
Power input (W)	260
No load speed (rpm)	14,700
Oscillation rate (opm)	28,000
Oscillation diameter (mm)	1.6
Sanding pad size (mm)	113 x 105
Weight (kg)	1.6
Supplied in	No kitbox or bag supplied
Article Number 240V	4933447025
EAN Code	4002395005833

CS 85 SB | 235 MM CIRCULAR SAW (85 MM DOC)

- 2200 Watt motor allows smooth cutting at full depth of cut
- Soft start minimises the tripping of circuit breakers
- Dust extraction DEK26 compatible
- Integrated cable hatch, the cable can be replaced easily without the need to dismantle the whole saw
- Aluminium stamped base for strength and durability
- Spindle lock for easy and quick blade change



CS 85 SB	
Power input (W)	2200
No load speed (rpm)	4500
Blade diameter (mm)	235
Bevel capacity (°)	50
Max. cutting depth 45° (mm)	67
Max. cutting depth 90° (mm)	85
Bore size (mm)	30
Weight (kg)	6.6
Supplied in	No kitbox or bag supplied
Article Number 240 V	4933451129
EAN Code	4002395137985

RCS | REMOTE CONTROL SOCKET AND CONTROLLER KIT

- The MILWAUKEE® remote control socket and controller kit starts up AC devices with the push of a button
- It is possible to use it with any cordless tool that uses a corded vacuum for dust extraction to eliminate the need to walk back and forth to the vac
- Thanks to the Bluetooth® technology, the remote pairs to the socket in less then 3 seconds and it has a connection range of up to 30m
- The remote controller is equipped with an adjustable strap and removable belt clip, allowing it to be used in different orientations like on the wrist or at the end of the hose
- It can be used with any AC product such as AC vacuum cleaners, AC lights or AC compressors
- A standard 3V coin cell battery is included and allows a run time of more than one year
- With the option to pair multiple remote controllers to the same socket, it is suitable for shared working environments



RCS	
Max. current [A]	7.5
Max. power [W]	1800
Signal range [m]	30
Article number	4932478966
EAN code	4058546362485

CS 85 CBE | 235 MM CIRCULAR SAW (85 MM DOC)

- 2200 Watt motor allows smooth cutting at full depth of cut
- 60° bevel capacity gives the saw the ability to achieve a wide range of roofing cuts
- Sprung loaded riving knife allows the saw to be plunged into the material without the removal of the riving knife
- Guide rail compatible, the saw can be used in conjunction with a guide rail
- Soft start minimises the tripping of circuit breakers
- Brake stops the saw in 3.5 seconds
- Double fence is anchored at the front and the back of the saw allowing for greater accuracy
- Dust extraction DEK26 compatible
- Integrated cable hatch, the cable can be replaced easily without the need to dismantle the whole saw



CS 85 CBE	
Power input (W)	2200
No load speed (rpm)	4500
Blade diameter (mm)	235
Bevel capacity (°)	60
Max. cutting depth 45° (mm)	67
Max. cutting depth 90° (mm)	85
Bore size (mm)	30
Weight (kg)	7.7
Supplied in	Kitbox
Article Number 240V	4933459032
EAN Code	4002395281633

AS 2-250 ELCP

25 L L-CLASS DUST EXTRACTOR

- Large 25 litre tank capacity ideal for workshop use
- 1000 W motor power with over 210 mbar suction - 10% more efficient
- Power take off with auto switching for powertools
- 2600W power take off capacity allows for use with high wattage tools
- Clear press filter cleaning system maintains suction efficiency
- Washable PET filter provides longer filter life
- Dust class L. Standard MAK-factor > 1 mg/m³
- Wet and dry capability
- Hose and cable storage enables easy transportation
- Dust blower function
- 7.5 m rubber cable
- Supplied with 3.5 m hose with floor cleaning kit, PET filter, 2x powertool connection adaptor, 1x disposable bag, 1x fleece bag & 1x crevice nozzle

AS 2-250 ELCP	
Power input (W)	1000
Air volume (l/min)	3600
Max. vacuum (mbar)	210
Capacity (l)	25
Hose diameter (mm)	32
Weight (kg)	10.4
Supplied in	No kitbox or bag supplied
Article Number 240 V	4933447490
EAN Code	4002395006328



MS 216 | 8 1/2" (216 MM) SLIDING MITRE SAW

- 1800 Watt motor for high performance cutting in hard timber
- Durability - dual vertical steel rails with linear bearings deliver smooth sliding action
- Rail lock - the saw head locks in the back position automatically
- Adjustable laser - for perfect and quick alignment to cut line
- Steel detent plate with preset angles - gives repeatable accurate cuts
- Lock lever/handle over mold - allows the user to make repeated cuts comfortably and without fatigue
- Mitre release system - for quick and smooth change of cutting orientation
- Integral LED jobsite light
- Spindle lock - for quick and easy blade change
- Heavy duty cast base and fence ensures durability and accuracy
- 48°/-2° bevel capacity
- Supplied with saw blade (48 teeth), blade spanner and work clamp

MS 216 SB	
Power input (W)	1800
No load speed (rpm)	6000
Blade diameter (mm)	216
Bevel capacity left (°)	48
Bevel capacity right (°)	-2
Mitre capacity left (°)	50
Mitre capacity right (°)	50
Max. cutting capacity 45° mitre/45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre 90° bevel [mm]	270 x 60
Bore size (mm)	30
Weight (kg)	14.5
Supplied in	No kitbox or bag supplied
Article Number 240 V	4933471054
EAN Code	4058546286828



MSL 1000 | MITRE SAW STAND EXTENDABLE UP TO 2 M

- Light weight aluminium, easy to transport onto the job site
- 1.08 m total length, will fit into most small vans and cars
- Extendable each side - 2.08 m extended
- Will hold up to 180 kg
- One point leg adjustment for leveling on uneven ground
- Quick release brackets
- Height adjustable length stops
- Compact foldable design



MSL 1000	
Height (mm)	850
Base size (mm)	1065
Extendable up to (mm)	2125
Collapsed size (mm)	1065
Bearing force [kg]	180
Weight (kg)	17.0
Supplied in	No kitbox or bag supplied
Article Number	4933428970
EAN Code	4002395241729

MSL 2000 | MITRE SAW STAND EXTENDABLE UP TO 2.5 M

- Light weight aluminium, easy to transport onto the job site
- 1.09 m total length, will fit into most small vans and cars
- Extendable each side - 2.54 m extended
- Will hold up to 227 kg
- One point leg adjustment for leveling on uneven ground
- Quick release brackets
- Height adjustable length stops
- Compact foldable design with quick release latches




MSL 2000	
Height (mm)	860
Base size (mm)	1093
Extendable up to (mm)	2542
Collapsed size (mm)	1093
Bearing force [kg]	227
Weight (kg)	14.0
Supplied in	No kitbox or bag supplied
Article Number	4933459617
EAN Code	4058546027896

MSUV 280

MITRE SAW STAND EXTENDABLE UP TO 2.8 M

- Upright folding design for easy storage and transportation
- Easy one action foot pedal lock and single lift point allows the stand to be quickly setup with a mitre saw attached
- Universal quick release saw brackets compatible with all MILWAUKEE® mitre saws
- Extra wide work piece support rollers allows larger materials to be more easily handled
- 2.8 m extension width
- 136 kg maximum load capacity
- Integrated storage tray
- Large wheels for ease of transportation over uneven surfaces

MSUV 280	
Height (mm)	850
Base size (mm)	1160 x 650
Extendable up to (mm)	2800
Collapsed size (mm)	1320 x 650 x 630
Bearing force [kg]	136
Weight (kg)	27.0
Supplied in	No kitbox or bag supplied
Article Number	4933478992
EAN Code	4058546362744



ACCESSORIES, HAND TOOLS AND PPE



OVER 3000 ACCESSORY SOLUTIONS

DRILLING

4x

LIFE IN REBAR
COMPARED TO 2 CUTTER DRILL BITS

CHISELLING

FASTENING

SHOCKWAVE
IMPACT DUTY

DRIVING
PERFORMANCE FORWARD

SAWING & CUTTING

MATERIAL REMOVAL

OUTDOOR POWER EQUIPMENT

TOOL SPECIFIC ATTACHMENTS

SCAN

TO VIEW OUR EXTENSIVE RANGE OF ACCESSORIES

OVER 1000 HAND TOOLS

LEVELS



FASTENING



SCREWDRIVERS



MEASURING TOOLS



HAND GRIPPING TOOLS



KNIVES AND BLADES



HAMMERS & PRY BARS



SCAN

TO VIEW OUR EXTENSIVE RANGE OF HAND TOOLS

OVER 350 PPE SOLUTIONS



STAY **SAFE.**
STAY **PRODUCTIVE.**

**CUT
RESISTANT
GLOVES**



70%
OF WORKERS
WHO EXPERIENCED
HAND INJURIES
WERE NOT WEARING
THE CORRECT GLOVES

USING THE CORRECT
EYE PROTECTION
COULD REDUCE THE
SEVERITY OR PREVENT
90%
OF JOBSITE EYE INJURIES



**SAFETY
GLASSES**



LANYARDS



A FALLING OBJECT
IS THE **3RD**
HIGHEST CAUSE OF
FATALITY
ON A JOBSITE

AS MANY AS
95%
OF CONSTRUCTION
WORKERS ARE EXPOSED TO
**HIGH LEVELS
OF NOISE**
ON A DAILY BASIS.

**EAR
DEFENDERS**



SCAN

TO VIEW OUR EXTENSIVE RANGE OF PERSONAL PROTECTIVE EQUIPMENT

PACKOUT™

The MILWAUKEE® PACKOUT™ modular storage system revolutionises tool transportation, organisation and storage. Designed to provide users with the ability to interchnage and interlock a wide assortment of heavy duty tool boxes, organisers and storage totes in multiple different configurations.



**SCAN NOW TO
VIRTUALLY BUILD YOUR
PACKOUT™ SYSTEM**



SITE

TRANSIT

SHOP

**OVER
100 POSSIBLE
COMBINATIONS**

MX FUEL™ RANGE		
MX FUEL™ INTRODUCTION		4 - 5
CHOOSE YOUR CONCRETE VIBRATOR		7
CHOOSE YOUR CONCRETE VIBRATOR HEAD		7
CHOOSE YOUR CONCRETE VIBRATOR SHAFT		7
MXF C	MX FUEL™ CHARGER	11
MXF COS350	MX FUEL™ 350 MM CUT-OFF SAW	9
MXF COSC	MX FUEL™ CUT-OFF SAW CART	9
MXF CP203	MX FUEL™ REDLITHIUM™ 3.0 AH BATTERY	11
MXF CVBC	MX FUEL™ BRIEFCASE CONCRETE VIBRATOR	6
MXF CVBP	MX FUEL™ BACKPACK CONCRETE VIBRATOR	6
MXF DCD150	MX FUEL™ 150 MM DIAMOND CORE DRILL	8
MXF DH2528H	MX FUEL™ 25 KG CLASS 28 MM HEX DEMOLITION HAMMER	7
MXF DHT	BREAKER TROLLEY FOR MX FUEL™ DEMOLITION HAMMER	7
MXF DR255TV	PREMIUM DIAMOND DRILLING STAND FOR MX FUEL™ DIAMOND CORE DRILL	8
MXF LSDP	MX FUEL™ LARGE SEWER DRUM MACHINE WITH POWERTREDZ™	10, 132
MXF NRG	MX FUEL™ BATTERIES AND CHARGER KIT	11
MXF PS	MX FUEL™ POWER SUPPLY	9
MXF PSC	MX FUEL™ SCREED	6
MXF TL	MX FUEL™ TOWER LIGHT	9, 152
MXF XC406	MX FUEL™ REDLITHIUM™ 6.0 AH BATTERY	11
SYSTEM ATTACHMENTS FOR MXF DCD150		8
SYSTEM ATTACHMENTS FOR MXF LSDP		10

M18™ RANGE		
M18™ SUMMARY		12 - 13
M18 FUEL™ INTRODUCTION		14 - 15
ONE-KEY™ INTRODUCTION		16 - 17
REDLITHIUM™ BATTERY INTRODUCTION		18 - 19
C18 HZ	M18™ HACKZALL™	51
C18 PCG/310	M18™ CAULK GUN WITH 310 ML CANISTER	37
C18 PCG/400	M18™ CAULK GUN WITH 400 ML TUBE	37
C18 PCG/600	M18™ CAULK GUN WITH 600 ML TUBE	37
C18 RAD	M18™ COMPACT RIGHT ANGLE DRILL	28
GET THE RIGHT ANGLE GRINDER FOR THE JOB		38
GET THE RIGHT HAMMER FOR THE JOB		20
GET THE RIGHT IMPACT DRIVER FOR THE JOB		29
GET THE RIGHT IMPACT WRENCH FOR THE JOB		32
GET THE RIGHT MITRE SAW FOR THE JOB		45
GET THE RIGHT NAILER/STAPLER FOR THE JOB		54
GET THE RIGHT PERCUSSION DRILL FOR THE JOB		26
HD18 AG-115	M18™ 115 MM ANGLE GRINDER WITH PADDLE SWITCH	40
HD18 CS	M18™ 55 MM CIRCULAR SAW FOR WOOD AND PLASTIC	50
HD18 HX	M18™ 4-MODE SDS-PLUS HAMMER WITH FIXTEC™ CHUCK	24
M12-18 JSSP	M12™ - M18™ BLUETOOTH® SPEAKER	59, 85
M18 AF	M18™ AIR FAN	58
M18 BBL	M18™ BATTERY BLOWER	58
M18 BH	M18™ COMPACT 2-MODE SDS-PLUS HAMMER	23
M18 BHG	M18™ HEAT GUN	45
M18 BI	M18™ INFLATOR	58
M18 BIW12	M18™ 1/2" IMPACT WRENCH	35
M18 BJS	M18™ TOP HANDLE JIGSAW	52
M18 BLCS66	M18™ BRUSHLESS 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS	50
M18 BLID2	M18™ BRUSHLESS 1/4" HEX IMPACT DRIVER	31
M18 BLPD2	M18™ BRUSHLESS PERCUSSION DRILL	27
M18 BMS12	M18™ METAL SHEAR	45
M18 BMS20	M18™ METAL SHEAR	45
M18 BMT	M18™ MULTI-TOOL	53
M18 BOS125	M18™ 125 MM RANDOM ORBITAL SANDER	54
M18 BP	M18™ PLANER	53
M18 BQSS	M18™ QUARTER SHEET SANDER	54
M18 BRAID	M18™ RIGHT ANGLE IMPACT DRIVER	31
M18 BRAIW	M18™ 3/8" RIGHT ANGLE IMPACT WRENCH	36

M18 BSX	M18™ SAWZALL™	51
M18 CBS125	M18 FUEL™ DEEP CUT BAND SAW	42
M18 CCS55	M18 FUEL™ 55 MM CIRCULAR SAW FOR WOOD AND PLASTICS	49
M18 CDEX	M18 FUEL™ SDS-PLUS DUST EXTRACTOR	23
M18 CHM	M18 FUEL™ 5 KG SDS-MAX DRILLING AND BREAKING HAMMER	21
M18 CRAD2	M18 FUEL™ RIGHT ANGLE DRILL	28
M18 CV	M18™ HAND VAC	58
M18 FAC	M18 FUEL™ AIR COMPRESSOR	54
M18 FAP	M18 FUEL™ POLISHER	41
M18 FBJS	M18 FUEL™ BODY GRIP JIGSAW	52
M18 FBPV	M18 FUEL™ BACKPACK VACUUM	58
M18 FBS85	M18 FUEL™ COMPACT BAND SAW	42
M18 FBTS75	M18 FUEL™ 75 MM BELT SANDER	54
M18 FCDDXL	COMPACT DEDICATED DUST EXTRACTION FOR M18 FUEL™ 26 MM SDS-PLUS HAMMERS	23
M18 FCOS230	M18 FUEL™ CUT OFF SAW	24
M18 FCS66	M18 FUEL™ 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS	49
M18 FCSG66	M18 FUEL™ 66 MM CIRCULAR SAW FOR WOOD AND PLASTICS, GUIDE RAIL COMPATIBLE	49
M18 FCSRH66	M18 FUEL™ REAR HANDLE CIRCULAR SAW FOR WOOD	49
M18 FCVN	M18 FUEL™ NEEDLE CONCRETE VIBRATOR	25
M18 FDD2	M18 FUEL™ DRILL DRIVER	67
M18 FDDEXL	DEDICATED DUST EXTRACTION FOR M18 FUEL™26 MM SDSPLUS HAMMERS WITH AUTOPULSE™	23
M18 FDG	M18 FUEL™ DIE GRINDER	44
M18 FDGRB	M18 FUEL™ BRAKING DIE GRINDER WITH SLIDE SWITCH	44
M18 FDGROVB	M18 FUEL™ BRAKING DIE GRINDER WITH ONE-KEY™, VARIABLE SPEED AND SLIDE SWITCH	43
M18 FDGROVPDB	M18 FUEL™ BRAKING DIE GRINDER WITH ONE-KEY™, VARIABLE SPEED AND PADDLE SWITCH	43
M18 FFN	M18 FUEL™ 34° FRAMING NAILER	56
M18 FFN21	M18 FUEL™ 21° FRAMING NAILER	56
M18 FFUS	M18 FUEL™ FENCING UTILITY STAPLER	57
M18 FHM	M18 FUEL™ ONE-KEY™ 8 KG SDS-MAX DRILLING AND BREAKING HAMMER	21
M18 FHSAG125XPDB	M18 FUEL™ HIGH PERFORMANCE 125 MM BRAKING GRINDER WITH PADDLE SWITCH	39
M18 FHZ	M18 FUEL™ HACKZALL™	51
M18 FID3	M18 FUEL™ ¼" HEX IMPACT DRIVER	30
M18 FIW2F12	M18 FUEL™ 1/2" COMPACT IMPACT WRENCH WITH FRICTION RING	35
M18 FIW2F38	M18 FUEL™ 3/8" COMPACT IMPACT WRENCH WITH FRICTION RING	35
M18 FJS	M18 FUEL™ TOP HANDLE JIGSAW	52
M18 FLAG230XPDB	M18 FUEL™ 230 MM LARGE BRAKING GRINDER WITH PADDLE SWITCH	39
M18 FMCS	M18 FUEL™ 57 MM METAL CIRCULAR SAW	42
M18 FMCS66	M18 FUEL™ 66 MM METAL CIRCULAR SAW	42
M18 FMDP	M18 FUEL™ MAGNETIC DRILLING PRESS WITH PERMANENT MAGNET	44
M18 FMS190	M18 FUEL™ 190 MM MITRE SAW	48
M18 FMS254	M18 FUEL™ 254 MM MITRE SAW	47
M18 FMS305	M18 FUEL™ ONE-KEY™ 305 MM MITRE SAW	47
M18 FMT	M18 FUEL™ MULTI-TOOL	53
M18 FMTIW2F12	M18 FUEL™ 1/2" MID-TORQUE IMPACT WRENCH WITH FRICTION RING	34
M18 FMTIW2F38	M18 FUEL™ 3/8" MID TORQUE IMPACT WRENCH WITH FRICTION RING	34
M18 FN15GA	M18 FUEL™ 15 GA ANGLED NAIL FINISH NAILER	56
M18 FN16GA	M18 FUEL™ 16 GA ANGLED NAIL FINISH NAILER	56
M18 FN18GS	M18 FUEL™ 18 GS FINISH NAILER	57
M18 FNCS18GS	M18 FUEL™ NARROW CROWN STAPLER	57
M18 FPD3	M18 FUEL™ PERCUSSION DRILL	27
M18 FPDDXL	DEDICATED DUST EXTRACTION FOR M18 FUEL™ 32 MM SDSPLUS HAMMERS WITH AUTOPULSE™	22
M18 FPM	M18 FUEL™ PADDLE MIXER	24
M18 FPOVCL	M18 FUEL™ PACKOUT™ WET/ DRY VACUUM	58
M18 FPS55	M18 FUEL™ 55 MM PLUNGE SAW FOR WOOD AND PLASTICS, GUIDE RAIL COMPATIBLE	50
M18 FQID	M18 FUEL™ SURGE™ 1/4" HEX HYDRAULIC IMPACT DRIVER	30
M18 FRAD2	M18 FUEL™ SUPER HAWG® 2-SPEED RIGHT ANGLE DRILL DRIVER GEN II	28

M18™ RANGE		
M18 FROP15	M18 FUEL™ RANDOM ORBITAL POLISHER WITH 15 MM STROKE	41
M18 FROP21	M18 FUEL™ RANDOM ORBITAL POLISHER WITH 21 MM STROKE	41
M18 FSAGF125XPDB	M18 FUEL™ 125 MM FLATHEAD BRAKING ANGLE GRINDER WITH PADDLE SWITCH	40
M18 FSAGV115XPDB	M18 FUEL™ 125 MM VARIABLE SPEED & BRAKING ANGLE GRINDER WITH PADDLE SWITCH	40
M18 FSG	M18 FUEL™ SCREW GUN	31
M18 FSGC	M18 FUEL™ SCREW GUN WITH A COLLATED ATTACHMENT	31
M18 FSX	M18 FUEL™ SUPER SAWZALL™	51
M18 FSZ	M18 FUEL™ SAWZALL™	50
M18 FTR	M18 FUEL™ TRIM ROUTER	53
M18 FTS210	M18 FUEL™ ONE-KEY™ TABLE SAW	48
M18 F2VC23L	M18 FUEL™ 23L L-CLASS VACUUM	57
M18 GG	M18™ GREASE GUN	37
M18 JSR DAB+	M18™ JOBSITE RADIO DAB+	59
M18 ONEFHIWF1	M18 FUEL™ ONE-KEY™ 1" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING	33
M18 ONEFHIWF12	M18 FUEL™ ONE-KEY™ 1/2" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING	33
M18 ONEFHIWF1D	M18 FUEL™ ONE-KEY™ 1" HIGH TORQUE D-HANDLE IMPACT WRENCH WITH FRICTION RING AND EXTENDED ANVIL	33
M18 ONEFHIWF34	M18 FUEL™ ONE-KEY™ 3/4" HIGH TORQUE IMPACT WRENCH WITH FRICTION RING	33
M18 ONEFHIWH716	M18 FUEL™ 7/16" HEX UTILITY HIGH TORQUE IMPACT WRENCH WITH ONE-KEY™	34
M18 ONEFHPX	M18 FUEL™ HIGH PERFORMANCE 4-MODE 32 MM SDS-PLUS HAMMER WITH ONE-KEY™ AND FIXTEC™ CHUCK	21
M18 ONEFHX	M18 FUEL™ 4-MODE 26 MM SDS-PLUS HAMMER WITH FIXTEC™ CHUCK AND ONE-KEY™	22
M18 ONEFLAG230XPDB	M18 FUEL™ ONE-KEY™ 230 MM BRAKING ANGLE GRINDER WITH PADDLE SWITCH	39
M18 ONEFLT	M18 FUEL™ LOCKBOLT TOOL WITH ONE-KEY™	36
M18 ONEFPRT	M18 FUEL™ RIVET TOOL WITH ONE-KEY™	36
M18 ONEFSAG115XPDB	M18 FUEL™ ONE-KEY™ 115 MM BRAKING ANGLE GRINDER	40
M18 ONEFSZ	M18 FUEL™ ONE-KEY™ SAWZALL™	51
M18 ONEID2	M18 FUEL™ ONE-KEY™ 1/4" HEX IMPACT DRIVER	30
M18 ONEIWF12	M18 FUEL™ ONE-KEY™ 1/2" IMPACT WRENCH WITH FRICTION RING	34
M18 ONEIWP12	M18 FUEL™ ONE-KEY™ 1/2" IMPACT WRENCH WITH PIN DETENT	35
M18 ONEPD2	M18 FUEL™ ONE-KEY™ PERCUSSION DRILL	27
M18 PRCDAB+	M18™ PACKOUT™ RADIO CHARGER	59
M18 RC	M18™ JOBSITE RADIO CHARGER WITH BLUETOOTH®	59
M18 SMS216	M18™ 216 MM MITRE SAW	48
M18 VC2	M18™ WET/ DRY VACUUM	58
TSS 1000	TABLE SAW STAND	48

M18™ POWERPACKS		
M18 BLPP2A2	M18™ POWERPACK	61
M18 FPP2A3	M18 FUEL™ POWERPACK	61
M18 FPP7A3	M18 FUEL™ POWERPACK	60
M18 ONEPP2A2	M18 FUEL™ ONE-KEY™ POWERPACK	60

M12™ RANGE		
M12 FUEL™ SUMMARY		62 - 63
M12 FUEL™ INTRODUCTION		64 - 65
C12 HZ	M12™ SUB COMPACT HACKZALL™	83
C12 MT	M12™ SUB COMPACT MULTI-TOOL	82
C12 PN	M12™ SUB COMPACT PALM NAILER	83
C12 RAD	M12™ SUB COMPACT RIGHT ANGLE DRILL	68
C12 RT	M12™ SUB COMPACT ROTARY TOOL	79
GET THE RIGHT RATCHET FOR THE JOB		74
M12-18 JSSP	M12™ - M18™ BLUETOOTH® SPEAKER	59, 85
M12 AF	M12™ AIR FAN	85
M12 AUN	M12™ AIR-TIP™ UTILITY NOZZLE	84
M12 BBL	M12™ BLOWER	84
M12 BCST	M12™ SUB COMPACT CABLE STAPLER	81
M12 BD	M12™ SUB COMPACT DRIVER	69

M12 BDD	M12™ SUB COMPACT DRILL DRIVER	68
M12 BDDX	M12™ SUB COMPACT DRILL DRIVER WITH REMOVABLE CHUCK	68
M12 BI	M12™ SUB COMPACT INFLATOR	78
M12 BID	M12™ SUB COMPACT 1/4" HEX IMPACT DRIVER	70
M12 BIW12	M12™ SUB COMPACT 1/2" IMPACT WRENCH	71
M12 BIW38	M12™ SUB COMPACT 3/8" IMPACT WRENCH	72
M12 BPD	M12™ SUB COMPACT PERCUSSION DRILL	68
M12 BPRT	M12™ SUB COMPACT RIVET TOOL	72
M12 BPS	M12™ SUB COMPACT POLISHER / SANDER	80
M12 BRAID	M12™ SUB COMPACT RIGHT ANGLE IMPACT DRIVER	70
M12 BS	M12™ SUB COMPACT BANDSAW	79
M12 BST	M12™ SUB COMPACT STAPLER	83
M12 CCS44	M12 FUEL™ SUB COMPACT CIRCULAR SAW	82
M12 CD	M12 FUEL™ SUB COMPACT DRIVER	69
M12 CH	M12 FUEL™ SUB COMPACT SDS-PLUS HAMMER	66
M12 CHZ	M12 FUEL™ SUB COMPACT HACKZALL™	82
M12 FBFL10	M12 FUEL™ BAND FILE 10 MM	81
M12 FBFL13	M12 FUEL™ BAND FILE 13 MM	81
M12 FBS64	M12 FUEL™ SUB COMPACT BAND SAW WITH 64 MM CUTTING CAPACITY	79
M12 FCOT	M12 FUEL™ SUB COMPACT MULTI-MATERIAL CUT-OFF TOOL	79
M12 FDD2	M12 FUEL™ SUB COMPACT DRILL DRIVER	67
M12 FDDX	M12 FUEL™ INSTALLATION DRILL/DRIVER WITH INTERCHANGEABLE HEADS	67
M12 FDGA	M12 FUEL™ ANGLED DIE GRINDER	80
M12 FDGS	M12 FUEL™ STRAIGHT DIE GRINDER	80
M12 FDSS	M12 FUEL™ SUB COMPACT SPOT SANDER	81
M12 FHIR14	M12 FUEL™ 1/4" HIGH SPEED RATCHET	75
M12 FHIR14LR	M12 FUEL™ 1/4" EXTENDED REACH HIGH SPEED RATCHET	75
M12 FHIR38	M12 FUEL™ 3/8" HIGH SPEED RATCHET	76
M12 FHIR38LR	M12 FUEL™ 3/8" EXTENDED REACH HIGH SPEED RATCHET	75
M12 FID2	M12 FUEL™ SUB COMPACT 1/4" HEX IMPACT DRIVER	69
M12 FIR12	M12 FUEL™ SUB COMPACT 1/2" RATCHET	76
M12 FIR38	M12 FUEL™ SUB COMPACT 3/8" RATCHET	76
M12 FIR38LR	M12 FUEL™ 3/8" EXTENDED REACH RATCHET	75
M12 FIW14	M12 FUEL™ SUB COMPACT 1/4" IMPACT WRENCH	71
M12 FW38	M12 FUEL™ SUB COMPACT 3/8" IMPACT WRENCH	70
M12 FWF12	M12 FUEL™ SUB COMPACT 1/2" IMPACT WRENCH	71
M12 FMT	M12 FUEL™ MULTI-TOOL	82
M12 FNB16	M12 FUEL™ 1.6 MM NIBBLER	80
M12 FPD2	M12 FUEL™ SUB COMPACT PERCUSSION DRILL	67
M12 FPDX	M12 FUEL™ SUB COMPACT PERCUSSION DRILL WITH REMOVABLE CHUCK	67
M12 FQID	M12 FUEL™ SURGE™ 1/4" HEX HYDRAULIC IMPACT DRIVER	70
M12 FRAIWF12	M12 FUEL™ 1/2" RIGHT ANGLE IMPACT WRENCH WITH FRICTION RING	72
M12 FRAIWF38	M12 FUEL™ 3/8" RIGHT ANGLE IMPACT WRENCH WITH FRICTION RING	73
M12 FTB	M12 FUEL™ LOW SPEED TYRE BUFFER	78
M12 FVCL	M12 FUEL™ WET/ DRY VACUUM	58, 84
M12 GG	M12™ SUB COMPACT GREASE GUN	77
M12 H	M12™ SUB COMPACT SDS-PLUS HAMMER	66
M12 HV	M12™ SUB COMPACT STICK VAC	84
M12 IR	M12™ SUB COMPACT RATCHET	76
M12 JS	M12™ SUB COMPACT JIGSAW	83
M12 JSSP	M12™ JOBSITE BLUETOOTH® SPEAKER	85
M12 ONEFTR12	M12 FUEL™ ONE-KEY™ 1/2" DIGITAL TORQUE WRENCH	73
M12 ONEFTR38	M12 FUEL™ ONE-KEY™ 3/8" DIGITAL TORQUE WRENCH	73
M12 PCG/310	M12™ SUB COMPACT CAULK GUN WITH 310 ML CARTRIDGE HOLDER	77
M12 PCG/400	M12™ SUB COMPACT CAULK GUN WITH 400 ML TUBE	77
M12 PCG/600	M12™ SUB COMPACT CAULK GUN WITH 600 ML TUBE	77
M12 RCDAB+	M12™ RADIO CHARGER DAB+	85
M12 SI	M12™ SUB COMPACT SOLDERING IRON	78
M12 UDEL	M12™ UNIVERSAL DUST EXTRACTOR	66

M12™ POWERPACKS		
M12 BPP2B	M12™ POWERPACK	87
M12 FPP2A2	M12 FUEL™ POWERPACK	86

M12™ POWERPACKS		
L4 CLL	USB RECHARGEABLE GREEN CROSS LINE LASER	91
L4 CLLP	USB RECHARGEABLE GREEN CROSS LINE LASER WITH PLUMB POINTS	89
LASER ATTACHMENTS		
LDM 30	30 M LASER DISTANCE METER	91
LDM 50	50 M LASER DISTANCE METER	91
M12 3PL	M12™ GREEN 360° 3 PLANE LASER	89
M12 CLLP	M12™ GREEN CROSS LINE LASER WITH PLUMB POINTS	89
M12 CLL4P	M12™ CROSS LINE LASER WITH 4 POINTS	89

WORK GEAR		
HIGH-VISIBILITY VESTS		
L4 HBLB	USB RECHARGEABLE HEATED WORKSKIN™ BASE LAYER	95
M12 HH BL4	M12™ HEATED HOODIE - BLACK	95
M12 HH LBL1	M12™ HEATED HOODIE LADIES - BLACK	95
M12 HJ BL5	M12™ HEATED JACKET - BLACK	93
M12 HJ GREY5	M12™ HEATED JACKET - GREY	93
M12 HPJ BL2	M12™ HEATED HYBRID PUFFER JACKET - BLACK	94
M12 HPV BL2	M12™ HEATED PUFFER VEST - BLACK	94
M12 HV GREY1	M12™ HEATED VEST - GREY	94
MILWAUKEE® GLOVES GUIDE		98 - 99
MILWAUKEE® GLASSES GUIDE		100 - 101
NGFM	NECK GAITER & FACE MASK	97
PERFORMANCE FACE COVERINGS		
PREMIUM HIGH-VISIBILITY VESTS		
TOOL DROP PREVENTION		
WHB	WORK HOODIE BLACK	96
WTLSG	WORK T-SHIRT LONG SLEEVE - GREY	96
WTSSG	WORK T-SHIRT SHORT SLEEVE - GREY	96
WWLSG	WORKSKIN™ LIGHT WEIGHT PERFORMANCE LONG SLEEVE SHIRT - GREY	95
WWSSG	WORKSKIN™ LIGHT WEIGHT PERFORMANCE SHORT SLEEVE SHIRT - GREY	96

ELECTRICAL SPECIALIST		
2200-40	VOLTAGE DETECTOR	115
2212-20	AUTO VOLTAGE / CONTINUITY TESTER	114
2217-40	DIGITAL MULTIMETER	114
2235-40	LIGHT COMMERCIAL CLAMP METER	115
2267-40	10:1 INFRARED TEMP-GUN™	115, 127
CRIMPING DIES		
M12 CC	M12™ SUB COMPACT CABLE CUTTER	106
M18 FUEL™ FISH TAPE COMPATIBLE DRUMS		110
M18 HKP HYDRAULIC KNOCKOUT PUNCH ACCESSORIES		108
M18 HUP700 HYDRAULIC PUMP SYSTEM ATTACHMENTS		109
M18 ONEHCC HYDRAULIC CABLE CUTTER JAWS AND BLADES		107
M18 BLTRC	M18™ BRUSHLESS THREADED ROD CUTTER	111
M18 FPFT	M18 FUEL™ POWERED FISH TAPE	110
M18 HCC45	M18™ FORCE LOGIC™ HYDRAULIC 44 MM CABLE CUTTER	106
M18 HCC75R	M18™ FORCE LOGIC™ HYDRAULIC REMOTE UNDERGROUND CABLE CUTTER	106
M18 HCCT	M18™ FORCE LOGIC™ HYDRAULIC 53 KN CABLE CRIMPER	111
M18 HCCT109/42	M18™ FORCE LOGIC™ HYDRAULIC 109 KN CABLE CRIMPER	111
M18 HDCT	M18™ FORCE LOGIC™ HYDRAULIC DIELESS CRIMPER	110
M18 HKP	M18™ FORCE LOGIC™ HYDRAULIC KNOCKOUT PUNCH	108
M18 HUP700	M18™ HYDRAULIC UTILITY PUMP	109
M18 ONEHCC	M18™ FORCE LOGIC™ HYDRAULIC 35 MM CABLE CUTTER	107
M18 ONEHCCT60	M18™ FORCE LOGIC™ HYDRAULIC 60 KN CABLE CRIMPER	111
M18 UBL	M18™ LED UTILITY BUCKET LIGHT	114

PLUMBING SPECIALIST			
2267-40	10:1 INFRARED TEMP-GUN™		115, 127
C12 PC	M12™ SUB COMPACT COPPER PIPE CUTTER		126
C12 PPC	M12™ SUB COMPACT PEX CUTTER		126
C12 PXP	M12™ SUB COMPACT UPONOR™ Q&E EXPANSION TOOL		129
EXPANDER HEADS			
HD18 PXP	M18™ UPONOR™ Q&E EXPANSION TOOL		128
M12 BSWP	M12™ HYDROPASS™ BRUSHED STICK WATER PUMP		127
M12 FPXP	M12 FUEL™ SUB COMPACT UPONOR™ Q&E EXPANSION TOOL		128
M12 HPT	M12™ SUB COMPACT FORCE LOGIC™ HYDRAULIC PRESS TOOL		121
M12 PCSS	M12™ RAPTOR™ PIPE CUTTER STAINLESS STEEL		126
M18 BLHPT	M18™ FORCE LOGIC™ BRUSHLESS PRESSTOOL		119
M18 BLHPTXL	M18™ FORCE LOGIC™ BRUSHLESS XL PRESS TOOL		120
M18 BLTRC	M18™ BRUSHLESS THREADED ROD CUTTER		111
M18 BTP	M18™ COMPACT TRANSFER PUMP		127
M18 FPT114	M18 FUEL™ PIPE THREADER 1 1/4" WITH ONE-KEY™		124
M18 FPT2	M18 FUEL™ PIPE THREADER 2" WITH ONE-KEY™		124
M18 FPXP	M18 FUEL™ UPONOR™ Q&E EXPANSION TOOL		128
M18 ONEBLHPT	M18™ FORCE LOGIC™ BRUSHLESS PRESS TOOL WITH ONE-KEY™		118
M18 ONEBLPXPL	M18™ ONE-KEY™ FORCE LOGIC™ UPONOR™ Q&E HYDRAULIC PIPE EXPANDING TOOL		128
MPS	MILWAUKEE® PIPE STAND		124
PIPE STAND ATTACHMENTS			
PIPE THREADER DIES			
PIPE THREADER HEADS			
PRESS JAWS		122 - 123	
RAPID SEAL™ EXPANDER HEADS			

DRAIN CLEANING, DIAGNOSTICS AND INSPECTION			
AIC2	ALKALINE INSPECTION CAMERA		141
AUTO FEED SYSTEM ATTACHMENTS			
DRUM MACHINE ATTACHMENTS			
INSPECTION CAMERAS			
M12 BDC6	M12™ SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 6 MM		135
M12 BDC8	M12™ SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 8 MM		135
M12 IC	M12™ SUB COMPACT M-SPECTOR™ 360° CAMERA		137
M12 IC AV3	M12™ DIGITAL INSPECTION CAMERA		137
M12 PL	M12™ PLUMBING LOCATOR		137
M12 360IC12	M12™ 360° INSPECTION CAMERA 1 M		141
M12 360IC32	M12™ 360° INSPECTION CAMERA 3 M		141
M18 FCSSM	M18 FUEL™ COMPACT SECTIONAL SEWER MACHINE		135
M18 FDCPF10	M18 FUEL™ DRAIN CLEANER - POWER FEED 10 MM		133
M18 FDCPF8	M18 FUEL™ DRAIN CLEANER - POWER FEED 8 MM		133
M18 FFSDC10	M18 FUEL™ FREE STANDING DRAIN CLEANER 10 MM		133
M18 FFSDC16	M18 FUEL™ FREE STANDING DRAIN CLEANER 16 MM		132
M18 FSSM	M18 FUEL™ SECTIONAL SEWER MACHINE		135
M18 SIC36	M18™ SEWER INSPECTION CAMERA 36 M		139
M18 SIC60	M18™ SEWER INSPECTION CAMERA 60 M		139
M18 SIC60SC	M18™ SEWER INSPECTION SMALL CAMERA 60 M		139
M18 SIM	M18™ SEWER CAMERA MONITOR		140
M18 SISH	M18™ SEWER INSPECTION SMART HUB		140
MXF LSDP	MX FUEL™ LARGE SEWER DRUM MACHINE WITH POWERREDZ™	10, 132	
SECTIONAL SEWER MACHINE ATTACHMENTS			

OUTDOOR EQUIPMENT		
M12 BHCS3L	M12™ HANDHELD CHEMICAL SPRAYER 3.7 L	147
M12 FHS	M12 FUEL™ HATCHET™ PRUNING SAW	146
M12 FHT20	M12 FUEL™ HEDGE TRIMMER 20 CM	144
M18 BLT	M18™ BRUSHLESS LINE TRIMMER	143
M18 BPPFH	M18™ SWITCH TANK™	148
M18 CHT	M18 FUEL™ HEDGE TRIMMER 60 CM	144
M18 FBCU	M18 FUEL™ BRUSH CUTTER 23 CM	143

OUTDOOR EQUIPMENT		
M18 FBL	M18 FUEL™ BLOWER	147
M18 FCHS	M18 FUEL™ CHAINSAW WITH 40 CM BAR	144
M18 FCHS35	M18 FUEL™ CHAINSAW WITH 35 CM BAR	145
M18 FCHSC	M18 FUEL™ CHAINSAW WITH 30 CM BAR	145
M18 FHS20	M18 FUEL™ HATCHET™ PRUNING SAW 20 CM	145
M18 FHT45	M18 FUEL™ HEDGE TRIMMER 45 CM	144
M18 FOPH	M18 FUEL™ OUTDOOR POWER HEAD WITH QUIK-LOK™	149
M18 FTHCHS30	M18 FUEL™ TOP HANDLE CHAINSAW WITH 30 CM BAR	146
M18 FTHCHS35	M18 FUEL™ TOP HANDLE CHAINSAW WITH 35 CM BAR	146
M18 F2BL	M18 FUEL™ DUAL BATTERY BLOWER	147
M18 F2LM53	M18 FUEL™ DUAL BATTERY SELF-PROPELLED LAWN MOWER 53 CM	143

TRUEVIEW™ HIGH DEFINITION LIGHTING		
TRUEVIEW™ INTRODUCTION		
FL-LED	ALKALINE FLOOD LIGHT	159
HL2-LED	ALKALINE SLIM HEADLAMP	163
HL-SF	ALKALINE SPOT FLOOD HEADLAMP	163
HOBL 7000	HIGH OUTPUT BAY LIGHT	153
IPL-LED	ALKALINE PEN LIGHT	161
IR FL	INTERNAL USB RECHARGEABLE FLASHLIGHT 500 LUMENS	159
IR HL	INTERNAL USB RECHARGEABLE HEADLAMP 450 LUMENS	162
IR PL	INTERNAL USB RECHARGEABLE PEN LIGHT 250 LUMENS	161
ISHL-LED	ALKALINE INTRINSICALLY SAFE HEADLAMP	163
L4 BOLTHL	USB RECHARGEABLE BOLT HEADLAMP 600 LUMENS	164
L4 FFL	USB RECHARGEABLE FOLDING FLOOD LIGHT	160
L4 FL	USB RECHARGEABLE POCKET FLOOD LIGHT	159
L4 FL2000	USB RECHARGEABLE FLASHLIGHT 2000 LUMENS	160
L4 FMLED	USB RECHARGEABLE 800L FIXED FLASHLIGHT	160
L4 HL2	USB RECHARGEABLE HEADLAMP	162
L4 HLRP	USB RECHARGEABLE HARD HAT HEADLAMP	162
L4 HL-VIS	USB RECHARGEABLE HI-VIS HEADLAMP	162
L4 NL400	USB RECHARGEABLE NECK LIGHT 400 LUMENS	163
L4 PWL	USB RECHARGEABLE PIVOTING WORK LIGHT	160
L4 SL	USB RECHARGEABLE STICK LIGHT 550 LUMENS	159
L4™LED	USB RECHARGEABLE 1100L TWIST FOCUS FLASHLIGHT	161
M12 AL	M12™ LED AREA LIGHT	155
M12 CML	M12™ COLOUR MATCHING LIGHT	157
M12 LL	M12™ LED LANTERN LIGHT	158
M12 PAL	M12™ PIVOT AREA LIGHT	156
M12 POAL	M12™ PACKOUT™ AREA LIGHT 1400 LUMENS	154
M12 SAL	M12™ STAND LIGHT	154
M12 SL	M12™ LED STICK LIGHT	157
M12 SLED	M12™ LED SPOT LIGHT	156
M12 TLED	M12™ LED TORCH	158
M12 UCL	M12™ UNDERCARRIAGE LIGHT	157
M12 UHL	M12™ LED UNDERHOOD LIGHT	157
M18 AL	M18™ LED AREA LIGHT	155
M18 HOAL	M18™ HIGH OUTPUT AREA LIGHT	155
M18 HOSALC	M18™ HIGH OUTPUT STAND AREA LIGHT CHARGER	153
M18 IL	M18™ LED INSPECTION LIGHT	156
M18 LL	M18™ LED LANTERN LIGHT	158
M18 ONERSAL	M18™ ONE-KEY™ LED REMOTE STAND LIGHT	153
M18 ONESLDP	M18™ ONE-KEY™ LED COMPACT SITE LIGHT CHARGER	152
M18 ONESLSP	M18™ ONE-KEY™ LED COMPACT SITE LIGHT	152
M18 PAL	M18™ PIVOTING AREA LIGHT	155
M18 POALC	M18™ PACKOUT™ AREA LIGHT CHARGER	154
M18 SAL	M18™ LED STAND LIGHT BASIC	154
M18 SAL2	M18™ LED STAND LIGHT	153
M18 SLED	M18™ LED SEARCH LIGHT	156
M18 TAL	M18™ TRADESMAN AREA LIGHT	152
M18 TLED	M18™ LED TORCH	158
ML-LED	ALKALINE FLASHLIGHT	161
MXF TL	MX FUEL™ TOWER LIGHT	9, 152

BATTERIES AND CHARGERS	
BATTERIES	165
BATTERIES AND CHARGER KITS	167
CHARGERS	166
HIGH-OUTPUT BATTERIES AND CHARGER KITS	167

CONSTRUCTION		
BRT	BREAKER TROLLEY	170
DD 2-160 XE	2-SPEED DRY DIAMOND DRILL	173
DR 152 T	DIAMOND DRILL STAND FOR DD 3-152	173
FIXTEC™ SOLUTION WITH DUST EXTRACTION		175
FIXTEC™ SOLUTION WITHOUT DUST EXTRACTION		175
GUIDE RODS FOR DIAMOND CORE DRILLS		
K 1000 S	10 KG CLASS SDS-MAX BREAKING HAMMER	171
K 2628 H	25 KG CLASS 28 MM HEX BREAKING HAMMER	170
K 500 S	5 KG CLASS BREAKING HAMMER	173
K 500 ST	5 KG CLASS TRADESMAN BREAKING HAMMER	172
K 540 S	5 KG CLASS TRADESMAN BREAKING HAMMER	172
K 545 S	5 KG CLASS DRILLING AND BREAKING HAMMER	172
K 750 S	7 KG CLASS DRILLING AND BREAKING HAMMER	172
K 900	10 KG CLASS BREAKING HAMMER	171
K 950	10 KG CLASS DRILLING AND BREAKING HAMMER	171
SYSTEM ATTACHMENTS - WET DIAMOND DRILLING		

METALWORKING		
AG 800 E	800 W ANGLE GRINDER	179
AGV 10 EK	1000 W ANGLE GRINDER WITH AVS	178
AGV 13 XSPDE	1250 W ANGLE GRINDER WITH AVS AND SLIM PADDLE SWITCH	178
AGV 17	1750 W ANGLE GRINDER WITH AVS	178
AGV 22	2200 W ANGLE GRINDER WITH AVS	178
AP 12 E	1200 W POLISHER WITH ELECTRONIC VARIABLE SPEED	179
AP 14-2 200 E	1450 W POLISHER	179
BS 125	DEEP CUT BAND SAW	179

WOODWORKING		
AS 2-250 ELCP	25 L L-CLASS DUST EXTRACTOR	184
CS 85 SB	235 MM CIRCULAR SAW (85 MM DOC)	182
CS 85 CBE	235 MM CIRCULAR SAW (85 MM DOC)	182
CS 60	184 MM CIRCULAR SAW (61 MM DOC)	183
JSPE 135	HEAVY DUTY TOP HANDLE JIGSAW	182
MS 216	8 ½" (216 MM) SLIDING MITRE SAW	184
MSL 1000	MITRE SAW STAND EXTENDABLE UP TO 2 M	185
MSL 2000	MITRE SAW STAND EXTENDABLE UP TO 2.5 M	185
MSUV 280	MITRE SAW STAND EXTENDABLE UP TO 2.8 M	185
RCS	REMOTE SOCKET AND CONTROLLER KIT	183
SPS 140	1/4" SHEET SANDER	183
SSPE 1500 X	1500 W SUPER SAWZALL™	181
SSD 1100 X	1100 W SAWZALL™	181

ACCESSORIES, HAND TOOLS AND PPE	
ACCESSORIES	187
HAND TOOLS	188
PPE	189
PACKOUT™	190 - 191



NOTES

This image shows a full page of blank, lined paper. It features approximately 20 evenly spaced horizontal grey lines across the entire width of the page, providing a guide for writing. The background is a clean, solid white color. There are no margins, text, or other markings present.

NOTES

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.



Nothing but **HEAVY DUTY.**[™]

Distributed by:

Techtronic Industries UK Ltd

Suite A, Second Floor

Marlow International

Parkway

Marlow

Bucks

SL7 1YL

Tel: +44 (0)1628 894400

Fax: +44 (0)1628 894401