







CUT A GLOVES



FEATURES

- Designed to provide ultimate durability and all-day comfort, ideal for material handling or light construction duty.
- Reinforced palm due to a nitrile texture.
- Designed to provide dexterity when handling small objects.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut protection: EN ISO 21420 and EN388:2016 (4121A).

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):CUT LEVEL A (WHITE)

COLOR OF THE GLOVE:

RED

MATERIAL:

NYLON/LYCRA BLEND. COATING: NITRILE

GAUGE:

13

SIZE RANGE:

CUT A GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	H	IANG CARI)		12 PACK		GIFT BOX		
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)
7/S	4932479712	1	6/120	4932479713	12	12/144	4932479714	144	12/144
8 / M	4932471416	1	6/120	4932471614	12	12/144	4932479008	144	12/144
9/L	4932471417	1	6/120	4932471615	12	12/144	4932479009	144	12/144
10 / XL	4932471418	1	6/120	4932471616	12	12/144	4932479010	144	12/144
11 / XXL	4932471419	1	6/120	4932471617	12	12/144	4932479011	144	12/144



Disclaimer
Information present within this sheet was correct at the date of issue.









CUT A GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS





DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH 71364 Winnenden Germany













- Excellent grip performance, nitrile material performs better than other materials in wide range of temperatures and oily surfaces
- Designed to provide comfort and increased dexterity.
- Superior puncture resistance protects from sharp materials.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (4242B), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL B (BLUE)

COLOR OF THE GLOVE:

RED

MATERIAL:

PE FIBER, NYLON, POLYESTER, GLASS FIBER, SPANDEX. COATING: NITRILE. REINFORCEMENT: NITRILE

GAUGE:

15

SIZE RANGE:

CUT B GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	H	IANG CARI)		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479906	1	6/120		12	12/144		144	12/144	
8 / M	4932479907	1	6/120		12	12/144		144	12/144	
9/L	4932479908	1	6/120		12	12/144		144	12/144	
10 / XL	4932479909	1	6/120		12	12/144		144	12/144	
11 / XXL	4932479910	1	6/120		12	12/144		144	12/144	



Disclaimer
Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH 71364 Winnenden Germany









CUT B GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS



DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany









SMARTSWIPETM COMFORT

CUT C GLOVES



FEATURES

- Offers more resistance than a Cut Level 1, to cut and abrasion, ideal protection for stripping wire or pipe threading and cutting.
- Excellent grip performance, nitrile material performs better than other materials in wide range of temperatures and oily surfaces.
- Superior puncture resistance for sharp materials.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut protection: EN ISO 21420 and EN388:2016 (4343C).

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL C (BLACK)

COLOR OF THE GLOVE:

RED

MATERIAL:

NYLON, PE BLEND, GLASS FIBER, SPANDEX. COATING: NITRILE

GAUGE:

15

SIZE RANGE:

CUT C GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	H	HANG CARI)		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479715	1	6/120	4932479716	12	12/144	4932479717	144	12/144	
8 / M	4932471420	1	6/120	4932471618	12	12/144	4932479012	144	12/144	
9/L	4932471421	1	6/120	4932471619	12	12/144	4932479013	144	12/144	
10 / XL	4932471422	1	6/120	4932471620	12	12/144	4932479014	144	12/144	
11 / XXL	4932471423	1	6/120	4932471621	12	12/144	4932479015	144	12/144	



Disclaimer
Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH 71364 Winnenden Germany









CUT RESISTANCE

SMARTSWIPETM

CUT C GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS



DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany













- Excellent grip performance, nitrile material performs better than other materials in wide range of temperatures and oily surfaces.
- Reinforced nitrile coating between thumb and fingers and superior puncture resistance for more durability.
- Designed to provide comfort with a high breathable liner.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (4X43D), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL D (GREY)

COLOR OF THE GLOVE:

RED

MATERIAL:

PE BLEND, NYLON, GLASS FIBER. COATING: NITRILE.

REINFORCEMENT: NITRILE

GAUGE:

13

SIZE RANGE:

CUT D GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	H	HANG CARI)		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479911	1	6/120		12	12/144		144	12/144	
8 / M	4932479912	1	6/120		12	12/144		144	12/144	
9/L	4932479913	1	6/120		12	12/144		144	12/144	
10 / XL	4932479914	1	6/120		12	12/144		144	12/144	
11 / XXL	4932479915	1	6/120		12	12/144		144	12/144	



Disclaimer
Information present within this sheet was correct at the date of issue.









CUT D GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING





DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH 71364 Winnenden Germany









CUT RESISTANCE

COMFORT

CUT E GLOVES



- Double layer of nitrile for added durability and increased protection from sharp objects.
- Excellent grip performance, nitrile material performs better than other materials in wide range of temperatures and oily surfaces.
- Proprietary knitting process for all day comfort and high breathability while working all day.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut protection: EN ISO 21420 and EN388:2016 (4X44E).

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL E (RED)

COLOR OF THE GLOVE:

GREY

MATERIAL:

PE BLEND, GLASS FIBER, STEEL FIBER, SPANDEX. COATING: NITRILE, DOUBLE DIPPED

GAUGE:

13

SIZE RANGE:

CUT E GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	H	HANG CARI)		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479718	1	6/120	4932479719	12	12/144	4932479720	144	12/144	
8 / M	4932471424	1	6/120	4932471622	12	12/144	4932479016	144	12/144	
9 / L	4932471425	1	6/120	4932471623	12	12/144	4932479017	144	12/144	
10 / XL	4932471426	1	6/120	4932471624	12	12/144	4932479018	144	12/144	
11 / XXL	4932471427	1	6/120	4932471625	12	12/144	4932479019	144	12/144	



Disclaimer
Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH 71364 Winnenden Germany









CUT E GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS



DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany









WINTER

WINTER CUT A GLOVES



FEATURES

- Winter insulation will keep the hand warm while working in cold conditions.
- High dexterity while handling small objects.
- Warm and dual liner for excellent warmth in coolest condition and for high breathability all day.
- European Certified for cut and cold resistance protection: EN ISO 21420, EN388:2016 (1141A), EN511 (01X).

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL A (WHITE)

COLOR OF THE GLOVE:

RED

MATERIAL:

OUTER LINER: NYLON, ELASTIC FIBER; INNER LINER:

ACRYLIC TERRY. COATING: LATEX

GAUGE:

15,10

SIZE RANGE:

WINTER CUT A GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	ı	HANG CARI)		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479704	1	6/72	4932479705	12	12/72	4932479706	72	12/72	
8 / M	4932471343	1	6/72	4932471606	12	12/72	4932479000	72	12/72	
9/L	4932471344	1	6/72	4932471607	12	12/72	4932479001	72	12/72	
10 / XL	4932471345	1	6/72	4932471608	12	12/72	4932479002	72	12/72	
11 / XXL	4932471346	1	6/72	4932471609	12	12/72	4932479003	72	12/72	



Disclaimer Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH 71364 Winnenden Germany









WINTER CUT A GLOVES



CARE INSTRUCTIONS



NO CHEMICAL CLEANING



DO NOT BLEACH



NO TUMBLER



DO NOT IRON



NO WASHING

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany









WINTER

TER BREATHABILITY

WINTER CUT C GLOVES



FEATURES

- Winter insulation will keep the hand warm while working in cold conditions.
- Gloves fit comfortably after being worn for extended periods of time.
- Improved water resistance to keep hands from cold and wet environment due to a ³/₄ double dipped latex coverage.
- European Certified for cut and cold resistance protection: EN ISO 21420, EN388:2016 (2442C), EN511 (02X).

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL C (BLACK)

COLOR OF THE GLOVE:

RED

MATERIAL:

OUTER LINER: HPPE BLEND KNIT, POLYESTER, GLASS FIBER; INNER LINER: ACRYLIC TERRY. COATING: LATEX

GAUGE:

15,7

SIZE RANGE:

WINTER CUT C GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	ŀ	IANG CARE)		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479707	1	6/72	4932479708	12	12/72	4932479709	72	12/72	
8 / M	4932471347	1	6/72	4932471610	12	12/72	4932479004	72	12/72	
9/L	4932471348	1	6/72	4932471611	12	12/72	4932479005	72	12/72	
10 / XL	4932471349	1	6/72	4932471612	12	12/72	4932479006	72	12/72	
11 / XXL	4932471350	1	6/72	4932471613	12	12/72	4932479007	72	12/72	



Disclaimer
Information present within this sheet was correct at the date of issue.









WINTER CUT C GLOVES



CARE INSTRUCTIONS



NO CHEMICAL CLEANING



DO NOT BLEACH



NO TUMBLER



DO NOT IRON



NO WASHING

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany











WINTER CUT E GLOVES



FEATURES

- Winter insulation and dual acrylic liner will keep the hand warm while working in cold conditions.
- 13 Gauge in the outer liner and 10 gauge in the inner liner, allowing good mobility on fingers.
- Improved water resistance to keep hands from cold and wet environment due to a ³/₄ double dipped latex coverage.
- 2pc inner and outer liner adhered together for extended durability.
- European Certified for cut and cold resistance protection: EN ISO 21420, EN388:2016 (3X43E), EN511 (X1X), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL E (RED)

COLOR OF THE GLOVE:

GREY

MATERIAL:

OUTER LINER: HPPE BLEND KNIT, POLYESTER, GLASS FIBER; INNER LINER: ACRYLIC TERRY. COATING: LATEX

GAUGE:

13,10

SIZE RANGE:

WINTER CUT E GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	ŀ	IANG CARE)		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479710	1	6/72	4932479711	12	12/72		72	12/72	
8 / M	4932479558	1	6/72	4932479562	12	12/72		72	12/72	
9/L	4932479559	1	6/72	4932479563	12	12/72		72	12/72	
10 / XL	4932479560	1	6/72	4932479564	12	12/72		72	12/72	
11 / XXL	4932479561	1	6/72	4932479565	12	12/72		72	12/72	



Disclaimer
Information present within this sheet was correct at the date of issue.









WINTER CUT E GLOVES



CARE INSTRUCTIONS



NO CHEMICAL CLEANING



DO NOT BLEACH



NO TUMBLER



DO NOT IRON



NO WASHING

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany













- Fluorescent material provides high visibility in low light environment.
- Lightweight and thin gloves with polyurethane dipped palm.
- Designed to provide increased dexterity and all-day comfort, ideal for material Handling, Carpenter, Plumbing, remodeling, general contracting applications.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3121A), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):CUT LEVEL A (WHITE)

COLOR OF THE GLOVE:

RED

MATERIAL:

POLYESTER, HPPE, GLASS FIBER, COOPER FIBER. COATING: POLYURETHANE (PU)

GAUGE:

15

SIZE RANGE:

HI-VIS CUT A GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	H	IANG CARI	ס		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479916	1	6/120		12	12/144		144	12/144	
8 / M	4932479917	1	6/120		12	12/144		144	12/144	
9/L	4932479918	1	6/120		12	12/144		144	12/144	
10 / XL	4932479919	1	6/120		12	12/144		144	12/144	
11 / XXL	4932479920	1	6/120		12	12/144		144	12/144	



Disclaimer Information present within this sheet was correct at the date of issue.









HI-VIS CUT A GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS



DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany









HI-VIS CUT B GLOVES



- Fluorescent material provides high visibility in low light environment.
- Lightweight thin gloves with polyurethane dipped palm, allowing increased dexterity.
- Cut Level 2/B ideal for material handling, woodwork, dry wall, ceiling, painting.
- Reinforced nitrile coating with added protection between thumb and fingers.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3242B), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL B (BLUE)

COLOR OF THE GLOVE:

RED

MATERIAL:

POLYESTER, HPPE BLEND KNIT, GLASS FIBER, COOPER FIBER. COATING: POLYURETHANE (PU). REINFORCEMENT: NITRILE

GAUGE:

15

SIZE RANGE:

HI-VIS CUT LEVEL 2/B GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	· ·	HANG CARE	•	12 PACK			GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479921	1	6/120		12	12/144		144	12/144	
8 / M	4932479922	1	6/120		12	12/144		144	12/144	
9/L	4932479923	1	6/120		12	12/144		144	12/144	
10 / XL	4932479924	1	6/120		12	12/144		144	12/144	
11 / XXL	4932479925	1	6/120		12	12/144		144	12/144	



Disclaimer Information present within this sheet was correct at the date of issue.









HI-VIS CUT B GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS



NO CHEMICAL CLEANING



DO NOT IRON



DO NOT BLEACH



NO TUMBLER



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue.













- Fluorescent material provides high visibility in low light environment.
- Offers more resistance than a Cut Level A, to cut and abrasion, ideal protection for stripping wire or pipe threading and cutting.
- Lightweight thin gloves with polyurethane dipped palm, allowing good dexterity.
- Reinforced nitrile coating with added protection between thumb and fingers.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut resistance protection: EN ISO 21420 and EN388:2016 (4X42C).

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL C (BLACK)

COLOR OF THE GLOVE:

RED

MATERIAL:

POLYESTER, HPPE BLEND KNIT, STEEL FIBER, GLASS FIBER. COATING: POLYURETHANE (PU). REINFORCEMENT: NITRILE

GAUGE:

15

SIZE RANGE:

HI-VIS CUT C GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	ŀ	HANG CARE)	12 PACK			GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479721	1	6/120		12	12/144	4932479722	144	12/144	
8 / M	4932478131	1	6/120		12	12/144	4932479020	144	12/144	
9/L	4932478132	1	6/120		12	12/144	4932479021	144	12/144	
10 / XL	4932478133	1	6/120		12	12/144	4932479022	144	12/144	
11 / XXL	4932478134	1	6/120		12	12/144	4932479023	144	12/144	



Disclaimer
Information present within this sheet was correct at the date of issue.










HI-VIS CUT C GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING





DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH 71364 Winnenden Germany









HI-VIS CUT D GLOVES



FEATURES

- Fluorescent material provides high visibility in low light environment.
- Lightweight thin gloves with polyurethane dipped palm, allowing good dexterity.
- Cut Level D, ideal for wire stripping, pipe threading/cutting, light metal stamping.
- Reinforced nitrile coating with added protection between thumb and fingers.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (4X43D), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):CUT LEVEL D (GREY)

COLOR OF THE GLOVE:

RED

MATERIAL:

HPPE, POLYESTER, GLASS FIBER, STEEL FIBER. COATING: POLYURETHANE (PU). REINFORCEMENT: NITRILE

GAUGE:

13

SIZE RANGE:

HI-VIS CUT D GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	F.	IANG CARI)		12 PACK		GIFT BOX			
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	
7/S	4932479926	1	6/120		12	12/144		144	12/144	
8 / M	4932479927	1	6/120		12	12/144		144	12/144	
9/L	4932479928	1	6/120		12	12/144		144	12/144	
10 / XL	4932479929	1	6/120		12	12/144		144	12/144	
11 / XXL	4932479930	1	6/120		12	12/144		144	12/144	



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany










HI-VIS CUT D GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS





DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH 71364 Winnenden Germany









HI-VIS CUT E GLOVES



FEATURES

- Fluorescent material provides high visibility in low light environment.
- Cut Level E, ideal for sheet metal, glass handling, wire stripping, ducting.
- Lightweight thin gloves with polyurethane dipped palm, allowing good dexterity.
- Reinforced nitrile coating with added protection between thumb and fingers.
- SMARTSWIPE™ palm and fingertips allows the use of touch screen devices without removing gloves.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (4X43E), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):CUT LEVEL E (RED)

COLOR OF THE GLOVE:

GREY

MATERIAL:

HPPE, POLYESTER, GLASS FIBER, STEEL FIBER. COATING: POLYURETHANE (PU). REINFORCEMENT: NITRILE

GAUGE:

13

SIZE RANGE:

HI-VIS CUT E GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

	HANG CARD			12 PACK			GIFT BOX		
SIZE	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/ MASTER)
7/S	4932479931	1	6/120		12	12/144		144	12/144
8 / M	4932479932	1	6/120		12	12/144		144	12/144
9/L	4932479933	1	6/120		12	12/144		144	12/144
10 / XL	4932479934	1	6/120		12	12/144		144	12/144
11 / XXL	4932479935	1	6/120		12	12/144		144	12/144



Disclaimer
Information present within this sheet was correct at the date of issue.









HI-VIS CUT E GLOVES



CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS



DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer Information present within this sheet was correct at the date of issue. Techtronic Industries GmbH 71364 Winnenden Germany





CUT C SLEEVES

FEATURES

- High stretch nylon material with 4-way stretch points to fit
- Tapered design, wider on the bicep and tight on the wrist, to fit the natural arm form.
- Elastic band with non-slip dots on the bicep and stretch wrist cuff to keep the sleeves in place and prevent them from sagging.
- Breathable and lightweight material provides good dexterity and all-day comfort.
- Elastic thumb loop avoids pressure points when using gloves.
- European Certified for cut protection: EN ISO 21420, EN388:2016 (2342C), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE): CUT LEVEL C (BLACK)

COLOR OF THE GLOVE:

RFD

MATERIAL:

HPPE, POLYESTER, GLASS FIBER, NYLON, SPANDEX, ELASTIC YARN.

GAUGE:

15

SIZE RANGE: CUT C SLEEVES

UNIT GUIDE

DESCRIPTION	ARTICLE NUMBER	NO. OF PAIRS
CUT C SLEEVES - 40CM	4932478584	1
CUT C SLEEVES - 45CM	4932478585	1







CUT C SLEEVES

CARE INSTRUCTIONS



WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS



DO NOT IRON



NO TUMBLER



NO CHEMICAL CLEANING



DO NOT BLEACH



MAX. 5 WASHING CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer
Information present within this sheet was correct at the date of issue.